


UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY



SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Perry R. Bass

3. ADDRESS OF OPERATOR

Box 2760, Midland, Tx. 79702-2760

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FNL & 1980' FWL Unit Letter F

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Spud date & surface casing, & 7" csg.

5. LEASE

LC-061672-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Poker Lake Unit

8. FARM OR LEASE NAME

AUG 09 1983

9. WELL NO.

60

O. C. D.

10. FIELD OR WILDCAT NAME

Delaware

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 33, T25S, R31E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

14. API NO.

Unknown

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3297' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 12 1/4" hole @ 3:00 a.m., CST, 7-12-83.

Drld. 12 1/4" hole to 801' 7-13-83.

Ran 21 jts. 9 5/8" 36# K-55 ST&C csg. set @ 801'.

Cemented w/550sx Class "C" w/additives plug down @ 12:00 a.m. CDT, float held. Bumped to 1000 psi, ok - circ 200sx. Mr. Arlin Coke witnessed job. WOC & NU 14 1/2 hrs. drld. float collar, cement, & shoe.

Drld. 8 3/4" hole 7-14-83. Drld. 8 3/4" hole to 4100' 7-18-83, ran 64 jts. 7" 23# L-80 LT&C & 35 jts. 7" 23# K-55 LT&C csg., csg. set @ 4100' Western cemented w/2050sx pacesetter lite with additives, tailed w/200sx Class "C" w/additives. Bumped plug, float held ok. Plug down @ 5:30 p.m. MDST. circ 300sx cement. Mr. Pete Hines w/MMS witnessed job. WOC & NU 16 1/4 hrs. Test BOPE to 1000 psi, held ok. Drld. cement, float collar & shoe. Test csg. seat to 300 psi, held ok. Drld. 6 1/4" hole 7-19-83.

Subsurface Safety Valve: Manu. and Type

Set @

Ft.

18. I hereby certify that the foregoing is true and correct.

SIGNED

R.C. Houtchens

TITLE

Asst. Dir. Clark

DATE

July 20, 1983

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

AUG 8 1983

\*See Instructions on Reverse Side

## Instructions

**General:** This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

**Item 4:** If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

**Item 17:** Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.