

APPROVED

DEC 5 1963
Ronnie E. Shook
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Las Cruces**
Lease No. **064894**
Unit **Poker Lake**

copy to 54

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT..... X
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

..... **May 13**, 19**63**.

Continental Federal ✓
Well No. **2** is located **1980** ft. from **S** line and **660** ft. from **W** line of sec. **20**
SW 1/4 of Section 20 **T-25-S** **R-30-E** **N.M.P.M.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Undesignated **Eddy** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **3183** ft. **Elev. KDB (Measurement Datum) is 3184'. GL elev. 3176'.**

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Starting 8:00 a.m. 5-9-63, unseated packer, displaced oil in hole with water. Re-set retrievable retainer at 3425, Halliburton cemented with 50 sx. reg. neat cement. McCullough located free-point of 5 1/2" casing at 2890'. Cut off the casing at 2875, pulled and laid down 5 1/2" OD casing. Ran open-ended tubing to 2900', filled hole with gel mud. Spotted 50 sx. reg. neat cement at 2046'. Spotted 50 sx. reg. neat cement at 690'. Spotted 25 sx. reg. neat cement at 30', circulated cement to the top of the 8-5/8" OD surface casing. Installed 4" pipe marker with company name, well, location, etc. Job completed 2:50 p.m. May 10, 1963.

RECEIVED
1963

RECEIVED

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **PERRY R. BASS**
Address **Box 1178, Monahans, Texas**

MAY 14 1963
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO
By *Walter D. Powers*
Walter D. Powers
Title **Asst. Division Manager**