

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NM OIL CONS. COMMISS.
Drawer DD
Artesia, NM

Form Approved.
Budget Bureau No. 42-R1424

C/A

SUNDRY NOTICES AND REPORTS RECEIVED

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐ Drilling well **APR 19 1983**
2. NAME OF OPERATOR **O. C. D.**
BEL-DYN, INC. PROPERTIES **ARTESIA OFFICE**
3. ADDRESS OF OPERATOR
P. O. Box 136, Lovington, NM 88260
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2310' FSL & 990' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Use Rotary Tools

- ☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
APR 12 1983

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWell, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilling fluid will be as follows:

- 0 - 0680' Fresh water with gel and/or lime as needed for viscosity control.
- 680 - 3400' Brine conditioned as necessary for control of viscosity, pH, and water-loss.

BOP will consist of a 600-Series annular-type or double ram-type preventer.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED James S. Glass TITLE Agent DATE April 8, 1983

(ORIG. SGD.) **DAVID R. GLASS**

APPROVED BY _____
CONDITIONS OF APPROVAL IF ANY _____

APR 15 1983

For James A. Tillman

*See Instructions on Reverse Side

ATTENDING DISTRICT MANAGER