

DEC 28 1983

O. C. D.

ARTESIA, NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☒ Drilling Well.

2. NAME OF OPERATOR
J. Ray Stewart

3. ADDRESS OF OPERATOR
P.O. Box 451, Midland, Tx. 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 660' FWL of Sec.
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same @ depth 773' KB.

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Set & Cmt. Surface Casing.

5. LEASE

LC-064894-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT/AGREEMENT NAME

Poker Lake Unit

8. FARM OR LEASE NAME

9. WELL NO.

61

10. FIELD OR WILDCAT NAME

Corral Canyon Dela.-Oil

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 17, T25S-R30E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mex.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3195.6' GL; Est KB 3206'

(NOTE: Report results of mud log completion or zone change on Form 9-331-C)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 12-1/4" hole @ 11:00PM 12/03/83. TD 12-1/4" hole 5:00AM on 12/5/83 @ 773' KB. On 12/5/83, PU & ran 0.60' notched guide shoe and 19 jts 8-5/8" OD 23# J-55 STC new casing (Ft. Worth Pipe & Supply) and set @ 760.06' KB. String Length 764.06'. Installed flapper type insert float in collar of 1st. jt. Centralized bottom 3 jts. Lockwelded shoe to 1st jt., and 1st. jt. to 2nd. jt. Wstn. Co. cemented with 270 sx. C1 "C" Pacesetter Lite w/ 1.5# Hiseal/sx & 2% CaCl₂ (12.8 wt.) followed by 250 sx. C1 "C" w/ 1% CaCl₂ (14.8 wt). Displaced cmt & plug w/ 46 BFW, bumping plug w/net 300 psi. Plug held OK. Plug down at 1:00 PM 12/5/83. WOC 12-1/2 hrs. CO csg. in cellar. Welded on Series 600 starting head. Installed Series 900 double ram BOP. Tested BOP & casing with 1000 psi. surface pressure for 30 mins. Held OK. TOC 670' KB. Started drlg cmt @ 1:30AM

Subsurface Safety Valve: Manu. and Type

on 12/6/83.

Set @ ----- Ft. ---

18. I hereby certify that the foregoing is true and correct

NOTE: Circulated 120 sx cmt to Surf.

SIGNED

John A. Sheldon

TITLE Field Consultant

DATE

12-09-83

(ORIG. SGD.) DAVID R. GLASS

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL

TITLE

DATE

ROSWELL, NEW MEXICO

*See Instructions on Reverse Side