-

Oil Conservation Division 1220 South St. Francis Dr. Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

1220 S. St. Frar	icis Dr., Santa	a Fe, NM 87505		Sa	nta F	e, NM 875	05						
			Rele	ease Notific	atio	n and Co	orrective A	ction					
					OPERATOR			Initial Report			Final Report		
Name of Co	ompany: B	IYA Operate			Contact: Jubal Terry								
the second	and the second strends where the second	tleton Blvd.,		Telephone No. (303) 797-5417									
Facility Nat	me: Roads	ide flow line		Facility Type: Flow line									
Surface Owner: Ute Mountain Ute Tribe Mineral Owner						Ute Mountain Ute Tribe API N							
Surface Ow	ner. Ote iv	iountain Ote	THUE						AFINC).			
Unit Letter	Section	Township	Danas	LOCA Feet from the		N OF RE	LEASE Feet from the	Den et /W	Vest Line	County			
H	33	31N	Range 16W	reet nom me	2477		reet from the				uan County		
			La	titude <u>36.8551</u>	70 Lo	ongitude -1	08.499555 NA	D83					
				NAT	URE	OF REL	EASE						
Type of Rele							and the second se	ume Recovered					
Source of Re	elease			Date and Hour of Occurrence			Date and Hour of Discovery						
Flow Line Was Immedi	ate Notice (Given?				Unknown Unknown If YES, To Whom?				1			
was minear	are Notice (Yes 🗵	No 🗌 Not Re	equired		whom.						
By Whom?						Date and I	lour						
Was a Watercourse Reached?						If YES, Volume Impacting the Watercourse.							
			Yes 🗵	No		Unknown							
If a Waterco	urse was Im	pacted, Descr	ibe Fully.	*									
An unreporte unknown. A	ed release fr trench was	dug to remove	ne from th e contamin	e previous operate nated soils.	or. This	roadside leak	occurred due a p	boorly re	paired flov	vline. Origir	nal relea	ase date is	
The historica steep sandste a land farm. tank battery has not been pressure gas	al release is one ridge. A Samples we were flushe implemente line (8 ^{°°}) an	trench was dere taken from d and capped. ed due to the c	vest of the ag with a l the sides A work p langers th in the dire	main tank battery back hoe to detern of the trench to de lan was submitted is excavation wou ction of the sandst	nine dep etermine and ap Id creat	pth and extent e extent of com- proved by the e. The depth of	. All contaminate ntamination. All f BLM with input of the trench is ne	ed excava flow line from the early 20°	ated soils h s that came e Ute Mou deep and i	ave been re e through th ntain Ute Tr s in close pr	moved is ROW ibe and oximit;	and taken to V to the main I the BIA and y to a high	
regulations a public health should their or the enviro	all operators or the envi operations l onment. In a	are required to ronment. The nave failed to	o report a acceptan adequately OCD accept	e is true and comp nd/or file certain r ce of a C-141 repo y investigate and r ptance of a C-141	elease i ort by th emedia	notifications a ne NMOCD n te contaminat	nd perform corre- narked as "Final F ion that pose a the	ctive act Report" d reat to gi	ions for re loes not re ound wate	leases which lieve the ope er, surface w	n may e erator o ater, hu	ndanger f liability 1ma X health	
Signature: Malh. Jun Printed Name:: Jubal S. Terry						OIL CONSERVATION DIVISION Approved by Environmental Specialist:							
				\cup		Approved by Approval Da			t: C	Date:	n		
E-mail Add		diversifiedre	sourcesinc	com		Conditions c			слрнацоп				
Date: 7/27/2	2018			Phone: (303) 797-5417		S	EE ATTACHE	ED		Attache	d 🔀		
* Attach Add	itional She	ets If Neces	sary	(

NCS1725638943

SOIL REMEDIATION WORK PLAN

For

BIYA OPERATORS, INC. ROADSIDE LINE LEAK SECTION 33, T31N R16W, NMPM SAN JUAN COUNTY, NM



Prepared for: BIYA Operators, Inc. 1789 West Littleton Blvd. Littleton, CO 80120 Prepared by: Souder, Miller & Associates 401 W Broadway Farmington, NM 87401 505-325-7535

April 24, 2017 SMA Reference 5124920 BG12



Souder, Miller & Associates Engineering • Environmental • Surveying

401 W. Broadway ♦ Farmington, NM 87401 (505) 325-7535 ♦ fax (505) 326-0045 ♦ www.soudermiller.com

Table of Contents

1.0	Introduction	1
2.0	Site Ranking and Land Jurisdiction	1
3.0	Assessment and Initial Results	1
4.0	Soil Remediation Work Plan	1
5.0	Revegetation Plan	2
6.0	Conclusions and Recommendations	2

Figures:

Figure 1: Site Map

1.0 Introduction

Souder, Miller & Associates (SMA) is pleased to submit this work plan for excavation and remediation at the BIYA Operators, Inc., Roadside Line Leak release site. The site is located in Unit I (NE ¼ SE ¼), Section 33, Township 31 North, Range 16 West; GPS: 36.857086°, -108.521920°, in San Juan County, New Mexico on Ute Mountain Ute tribal lands.

2.0 Site Ranking and Land Jurisdiction

The Roadside Line Leak release is located on Ute Mountain Ute tribal land with an elevation of approximately 5,384 feet above sea level. After evaluation of the site using aerial photography and topographic maps and review of ground water information provided by Colin Larrick, Water Quality Program Manager, Ute Mountain Ute Tribe, depth to groundwater is estimated to be less than 50 feet below ground surface (bgs).

SMA searched the New Mexico State Engineer's Office online water well database for water wells in the vicinity of the release. No wells are located within a 1000 foot radius of the site. The physical location of this release is within the jurisdiction of Ute Mountain Ute tribal land.

This release location has been assigned soil remediation standards of 10 parts per million (ppm) benzene, 50 ppm combined benzene, toluene, ethyl-benzene, and total xylenes (BTEX), and 100 ppm total petroleum hydrocarbons (TPH).

3.0 Assessment and Initial Results

In 2016, BIYA Operators, Inc. attempted to excavate contaminated soil from the site. However, site conditions (nearby pipelines, road access) have limited the extent of excavation using standard heavy equipment. On June 9, 2016 BIYA Operators, Inc. personnel collected soil samples from the excavated area. The laboratory samples were sent under chain-of-custody protocols to Hall Environmental Analysis Laboratory for analysis for DRO and GRO by EPA Method 8015D.

Based on laboratory results of the samples collected by BIYA on June 9, 2016, further excavation is required. Per the Ute Mountain Ute Tribe, remediation and reclamation is to occur prior to June 30, 2017.

4.0 Soil Remediation Work Plan

Upon approval from the Ute Mountain Ute Tribe and with approval from area utilities owners via 811, SMA will guide the excavation activities utilizing hydrovac equipment to remove hydrocarbon impacted soil and rock. Excavation will continue to occur to sufficient to removal the impacted materials. Field screening will occur based on visual observation of stained soil and PetroFlag as needed. Affected soils will be removed from these areas before closure samples are collected at the final depth of excavation and sidewalls at which time SMA will conduct closure sampling.

Excavated material spoils are to be placed on a liner and within a bermed or fenced area. All excavated material is to be transported for disposal at an approved facility within 10 days of

excavation commencing. Excavated material is not to remain on location more than 10 consecutive days. The open excavated areas will remain fenced when excavation activities are not occurring to limit access by cattle and wildlife.

The Ute Mountain Ute Tribe has set a deadline of May 26, 2017 for closure sampling to occur.

5.0 Revegetation Plan

The Ute Mountain Ute Tribe has issued a deadline for reclamation to occur by June 30, 2017. Seed will be planted at one quarter to one-half-inch deep using a disc type or similar rangeland drill sufficient to accommodate variations in seed sizes. If broadcast, seeding rates should be doubled. Seeding can be accomplished as early as May given all dirt work for the location is stabilized. Soil in this area will be tilled to reduce compaction.

Seed-bed preparation will be performed to provide a hospitable environment for germinating seed by breaking up impermeable soil layers that have formed and increasing void spaces for air and water. Ground shall be roughed-up prior to planting by raking harrowing or other methods.

Seed shall be broadcast with a "cyclone" hand seeder or similar broadcast seeder to facilitate an even spread. After seed is broadcast, ground shall be raked or dragged, to help bury it and improve soil contact and provide texture.

Mulch will be placed to prevent loss of moisture and seed to wind.

Mulching shall be accomplished by using one of these following methods:

- a) weed free straw (2 tons/ac;kg/ha)
- b) wood residues (sawdust, wood chips, bar (2tons/ac;kg/ha)
- c) hydro-mulching (1,500 lb/ac;kg/ha)
- d) composted manure (5 tons/ac;kg/ha)
- e) excelsior blanket
- f) straw jute

Livestock will be temporarily fenced out of any seeded area, as they will otherwise greatly reduce possibility of successful revegetation. Probability of successful seeding will be considerably increased if fencing remains until reclamation is stable, and plant s have grown well enough to withstand grazing. Stabilization would occur after a minimum of two full summer growing seasons after planting.

6.0 Conclusions and Recommendations

This site has been assigned soil remediation standards of: 10 ppm (mg/kg) Benzene, 50 ppm total BTEX, and 100 ppm TPH. The release consisted of produced and associated petroleum found during the initial assessment and delineation.

After the soil remediation work plan is approved by the Ute Mountain Ute Tribe, SMA will begin the planned soil remediation activities on site.

Roadside Line Leak Work Plan SMA Ref 5124920 BG 12 4/24/2017 Page 3

If there are any questions regarding this report, please contact either Ashley Maxwell or Shawna Chubbuck at 505-325-7535.

Submitted by:

Reviewed by:

SOUDER, MILLER & ASSOCIATES

hauna Chubbuck

Shawna Chubbuck Senior Scientist

Ashley Maxwell Staff Scientist

FIGURE 1 SITE MAP

