UNITED STATES DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT OF THE PROPERTY OF T

d	Sundry Notice	ces and Re	ports on Wells	(IA WD 7	.)0						
			070 Fa	ming 's .n,	Lease Number 14-20-603-2034						
1. 1	Гуре of Well			6.	If Indian, All. or						
1.	WIW			0.	Tribe Name						
	N	, <u> </u>		7.	Unit Agreement Name						
2. I	Name of Operator Hart Oil & Gas, Inc.										
	nart Oil & Gas, IIIC.		ė.	8.	Well Name & Number						
3.	Address & Phone No. of Operator			0.	Navajo TI F #109						
•	PO Box 307, Farmington, NM 87499 (505)	326-1163		9.	API Well No . 30-045-10914						
Loca	ation of Well, Footage, Sec., T, R, M	, , , , , , , , , , , , , , , , , , ,		10.	Field and Pool Horseshoe Gallup						
	1980' FSL and 1980' FWL, Section 10, T-31-	-N. R-17-W	1.		1 1013631106 Gallup						
		.,	,	11.	County & State San Juan County, NM						
	CHECK APPROPRIATE BOX TO INDICATE		OF NOTICE, REPOR	Γ, OTHER D	ATA						
•	Type of Submission Type of A		Observe (D)								
	Notice of Intent X Abandor		Change of Pla								
	X Subsequent Report Plugging		New Construction								
	Casing I		Water Shut of								
	Final Abandonment Altering		Conversion to	Z-1.	The Man 2004 The						
	Other -				FOR THE PROPERTY OF THE PROPER						
			· · · · · · · · · · · · · · · · · · ·	3,100	10 10 10 10 10 10 10 10 10 10 10 10 10 1						
13 .	Describe Proposed or Completed Operation	ons		View (
1	Hart Oil & Gas plugged and abandone	ed this w	ell on January 26,	2004.	Carrier S. D.						
·	1/22/04 MOL & RU. Well flowing water and o	oil Work r	acker free TOH and	I D nacker	SDEN						
	•	•		•							
1/23/04 TIH with tubing and tag at 918' Circulate well clean. Plug #1 with 32 sxs cement with 2% CaCl ₂ from 918' to 297' to fill the Gallup perforations. TOH and LD tubing. WOC for 3.5 hours. Pressure test casing to 500#, held OK. Wireline tag cement at 380'. Perforate 2 squeeze holes at 99'. Establish circulation out bradenhead. Plug #2 with 50 sxs pumped down the casing from 99' to											
								_	· ·	the casing r	rom 99 to
						surface, circulate good cement out bradenhead. Shut in well.					
1/26/04 ND BOP and cut off wellhead. Found cement down 8' in 4" casing and at surface in 7"											
	annulus. Mix 24 sxs cement to fill casing and	d then insta	all P&A marker. RD a	nd MOL.							
14	I hereby certify that the foregoing is true a	nd correc	· · · · · · · · · · · · · · · · · · ·								
1-7.			•								
Sign	ed / fina M. Daild T	Γitle <u>V</u> io	e President		Date 2-28-04						
•	Gina M. Saied										
/TL:	V										
•	s space for Federal or State Office use)	Title			Da EAD BEAAD						
	ROVED BY	Title			DateOP PFCOR						
JU1,	TO THE TROPAL, II ally.				48						
					AR O O SONA						

AK 2 2 2004