Distribution:	O+4 (BLM); 1-Accounting; 1- Land; 1-File		
Form 3160-5 (June 1990)	UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT		FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993
	SUNDRY NOTICES AND REPORTS ON WELLS 2003 JAN 14 PM 1: 4	1/	e Designation and Serial No. - <b>080384-B</b>
Do r	use this form for proposals to drill or to deepen or reentry to a different reservoir.  Use "APPLICATION FOR PERMIT" for such proposals Farmington, NI		lian, Allottee or Tribe Name
	SUBMIT IN TRIPLICATE	7. If Un	it or CA, Agreement Designation
1. Type of W	Well Other		
2. Name of C	perator	1	Name and No.  CKMAN A No. 3R
	on Oil & Gas Corporation ad Telephone No.	9. API '	Well No. -045-30897
610 Re	tilly Avenue, Farmington, NM 87401-2634 (505) 327-9801		and Pool, or Exploratory Area
	SEL & 1690 FWL (NE SW)	<b></b>	ty or Parish, State
	10, T26N, R12W	SA! Nei	N JUAN COUNTY, w Mexico
12.	CHECK APPROPRIATE BOX (s) TO INDICATE NATURE OF NOTICE, REPO	RT, O	R OTHER DATA
<del></del>	TYPE OF SUBMISSION TYPE OF ACTION		
	Notice of Intent  Abandonment  Recompletion		Change of Plans  New Construction
	X Subsequent Report Plugging Back		Non-Routine Fracturing
	Casing Repair		Water Shut-Off
	Final Abandonment Notice Altering Casing		Conversion to Injection
	X Other Spud, Csg & TD Rpts	Note	Dispose Water  Report results of multiple completion on
13. Describe F	Tonosed or completed Operations (Clearly state all portinent details and give pertinent dates including estimated date of starting any	Comp	letion or Recompletion Report and Log form.)
13. Describe Proposed or completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*			
MIRU L&B Speed Drill. Spud surface hole at 1030 hrs 1/6/03 with bit #1 (8-3/4", STC, F2-RR). Drilled to 140' with spud mud. Circulated hole clean and TOH. Ran 4 joints (129.10') of 7", 20#, J-55, LT&C casing set at 134' KB. RU American Energy, cemented with 55 sx (65 cu.ft.) of Class "B" with 3% CaCl <sub>2</sub> and ¼ #/sk celloflake. Displaced cement with 4.0 bbls of water. Job completed at 1445 hrs 1/6/03. Circulated 4.0 bbls of good cement to surface. Hole was staying full. SDON to WOC.			
1/7//03	Drilling at 702' made 562'.		
1/8/03	Drilling at 1208' made 506'.		
1/9/03	TD well at 1515'. Circulate hole clean, TOH, LDDP &DC's. RU casing crew. Ran 34 joints (150 casing landed at 1512' KB. Insert float at 1467' KB. Circulate casing on bottom. RU American E 10 bbls of water. Mix and pump 120 sxs (247 cu.ft) of Class "B" with 2% SMS, 3#/sx of gilsonite sxs (71 cu.ft) of Class "B" with ½#/sx of celloflake. Displace with 22.8 bbls of water. Circulated 1 16:45 hrs 1/9/03. Float held OK. Set slips. Will RDMOL in AM 9/11/03. Note: used starch to comwoct.	nergy So and 1/4#/ 2 bbls o	ervices. Precede cement with sx of celloflake. Tail with 60 of cement to surface. PD at
Signed	Title Drlg & Prod Manager	Date	ACCEPTED 202
	e for Federal or State office use)		TO FUR RECOR
Approved	By Title	Date	JAN 1 6 2002
	of approval, if any: Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United	States	FARMING OF RELADIOF FINEment
or representations as to any matter within its jurisdiction.			
	Minos		<del> </del>