Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals. FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

5. Lease Serial No. NMSF078426

	NIVISEU / 6420	
6.	If Indian, Allottee or Tribe Name	

SUBMIT IN TRIE	PLICATE - Other instruc	ctions on reverse side		NMNM78416E	neity realite allow or rec-			
1. Type of Well	8. Well Name and No. SJ 29-6 240A							
Oil Well Gas Well Oth								
2. Name of Operator CONOCOPHILLIPS COMPANY Contact: PATSY CLUG E-Mail: plclugs(
3a. Address 3b. Phone No 5525 HIGHWAY 64 Ph: 505.59 FARMINGTON, NM 87401 Fx: 505-599			ea code)	10. Field and Pool, or Exploratory BASIN FRUITLAND COAL				
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description	n)	 	11. County or Parish, and State				
Sec 18 T29N R6W NESE 139 36.72228 N Lat, 107.49802 W				RIO ARRIBA COUNTY, NM				
12. CHECK APPR	OPRIATE BOX(ES) TO	O INDICATE NATUR	E OF NOTICE, R	EPORT, OR OTHER	DATA			
TYPE OF SUBMISSION TYPE OF ACTION								
□ Notice of Intent	□ Acidize	Deepen	□ Produc	tion (Start/Resume)	☐ Water Shut-Off			
_	☐ Alter Casing	☐ Fracture Treat	☐ Reclam	ation	☐ Well Integrity			
Subsequent Report	Casing Repair	□ New Construc	ion Recom	plete	Other Well Spud			
☐ Final Abandonment Notice	☐ Change Plans	Plug and Abar	don Tempo	rarily Abandon	Well Spud			
	Convert to Injection	Plug Back	☐ Water I	Disposal				
1/8/04 MIRU Key #49. Spud 12-1/4" hole @ 2030 hrs 1/8/04. Drilled to 244'. Circ. hole. RIH w/9-5/8", 32.3# H-40 casing and set @ 234'. RU Schlumberger to cement. Pumped a preflush of 30 bbls FW w/dye in last 10 bbls. Pumped 17.5 bbls cement. Ran out of cement. Circulated out cement with rig pump. Wait on cement bulk truck. Pumped another 15 bbls FW w/dye in last 10 bbls. Pumped 180 sx (208.8 cf - 37.2 bbls slurry) 150% excess - Class G cement w/2% CaCl2, .25#/sx Cello-phane, 2#/bbl cemnet. Released wiper plug and displaced plug w/15 bbls FW. Bumped plug w/420 psi. Circulated 7 bbls (39.3 cf) good cement to surface. RD Schlumberger. WOC. NU WH & NU BOP. PT - OK. WOC. PT blind rams, choke line valve, & casing to 300 psi for 3 minutes and 1000 psi for 30 minutes. Good test.								
14. Thereby certify that the foregoing is	Electronic Submission	#26774 verified by the B HILLIPS COMPANY, ser ssing by ADR ENNE GA	t to the Farmingtor	1 *				
Name (Printed/Typed) PATSY C	LUGSTON	Title /	AUTHORIZED REI	PRESENTATIVE				
Signature (Electronic S	Submission)	Date (01/12/2004					
	THIS SPACE F	OR FEDERAL OR S	TATE OFFICE U	SE				
Approved By ACCEPTED			RIENNE GARCIA TROLEUM ENGIN	EER	Date 01/15/2004			
Conditions of approval, if any, are attache certify that the applicant holds legal or eq which would entitle the applicant to cond	uitable title to those rights in that the contract operations thereon.	ne subject lease Office F	Office Farmington					
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it statements or representations a	a crime for any person know s to any matter within its jur	ingly and willfully to r isdiction.	nake to any department or	agency of the United			