Form 3160-5

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVE

	BUREAU OF LAND MANAGEMENT		5
	BUREAU OF LAND MAIN	AGEMENT 23	Expires Merch 31, 1993 5. Lease Designation and Serial No.
	SUNDRY NOTICES AND REPO	RTS ON WELKS Solver Land 19 5	
	Do not use this form for proposals to drill or to deeper	or months to folifforent recognistr	6. If Indian, Allotte or Tribe Name
	Use "APPLICATION FOR PERMIT"	for such proposals. NOV 2002	Jicarilla Apache Tribe
	SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
1. Type of Well	000000000000000000000000000000000000000	CA CONS. DIV.	₱ N/A
Oil V	Well X Gas Well Other:		all j
2. Name of Operator		12.	8. Well Name and No.
	Mallon Oil Company		Jicarilla 29-02-30 No. 1
Address and Telephone	[№] . P.O. Box 2797 Durango, CO 80213	(970) 38 2-910 0	9. Well API No. 30-039-27246
			10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 640' FNL and 2165' FEL (NW NE) Unit B			E. Blanco, Pictured Cliffs
Sec. 30, T29N-R02W			11. County or Parish, State Rio Arriba County, New Mexico
3ec. 30, 12314-10	7 v 4		Trio Arriba Codinty, New Mexico
12.	CHECK APPROPRIATE BOX(S) TO INI	DICATE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
	TYPE OF SUBMISSION		OF ACTION
	Notice of Intent	Abandonment	Change of Plans
		Recompletion	New Construction
	X Subsequent Report	Plugging Back	Non-Routine Fracturing
,		Casing Repair	Water Shut-Off
•	Final Abandonment Notice	Altering Casing	Conversion to Injection
•		X Other:	Dispose Water
•		spud and surface casing	(Note: Report results of multiple completion on Well
	2.2	well on 0/25/2002 at 9:45 mm. I	nrs. Drilled
at 12	Oil Company spud the above referenced 4/4" hole, 8 5/8", 24.0 lb/ft. Surface casing ype III cement, circulated 18 bbls cmt to p	y was set at 266.11'. Cemented	
at 12	1/4" hole, 8 5/8", 24.0 lb/ft. Surface casing type llf cement, circulated 18 bbls cmt to p	y was set at 266.11'. Cemented vit.	Date 10/6/02
at 12 sxs T	1/4" hole, 8 5/8", 24.0 lb/ft. Surface casing type III cement, circulated 18 bbls cmt to p	y was set at 266.11'. Cemented v	Date 10/6/62
at 12 SXS T 14. I hereby settify that the Signed (THIS SPACE FOR FEDERAL OR ST	1/4" hole, 8 5/8", 24.0 lb/ft. Surface casing ype III cement, circulated 18 bbls cmt to p	title Production Technician Lands and Minera	Date 10/6/02 al Resources OCT 3 0 200
at 12 SXS T SXS T 14. I heraby sertify that the Signed (THIS SPACE FOR FEDERAL OR S' Approved B	1/4" hole, 8 5/8", 24.0 lb/ft. Surface casing ype III cement, circulated 18 bbls cmt to p	title Production Technician Lands and Minera	Date 10/6/02 al Resources OCT 3 0 200
at 12 SXS T SXS T 14. I heraby sertify that the Signed (THIS SPACE FOR FEDERAL OR S' Approved B	1/4" hole, 8 5/8", 24.0 lb/ft. Surface casing ype III cement, circulated 18 bbls cmt to p	title Production Technician Lands and Minera	Date 10/6/62 al Resources OCT 3 0 200