30-039-25566

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator B	BURLINGTON RESOURCES OIL & GAS CO.					SAN JUAN 29	-7 UNIT		Well No. 90A	
Location										
of Well:	Unit I	Sect 05	Twp.	029N	Rge.	007W	County	RIO ARRIBA		
	NA	ME OF RESE	RVOIR OR POO	L	TY	TE OF PROD.	METH	OD OF PROD.	PR	OD. MEDIUM
						(Oil or Gas)	(Flov	v or Art. Lift)	(1	bg. or Csg.)
Upper Completion	MESAVERDE					Gas	Flow		Tubing	
Lower Completion	DAKOTA					Gas	Flow			Tubing
			PRE-F	LOW SHUT-IN	PRESS	URE DATA				
Upper	Hour, date shut-in	ı L	ength of time shut-	-in	SI pı	ess. psig		Stabilized? (Yo	es or No)	1
Completion	5/3/2004		168 Ho	urs		201				
Lower Completion	5/3/2004		120 Ho	urs		315				
	1	1	. –	FLOW TES	ST NO. 1					
Commenced	at (hour,date)*		5/8/2004			Zone producing (Upper or Lower) LOWER				
TIME	LAPSED TIME		PRESSURE			PROD. ZONE	ì			
(hour,date)	SINCE*		Upper Completion Lower Compl		etion	TEMP	REMARKS			
5/9/2004	144 Hours	•	201	124			well IS for 5 days			
5/10/2004	168 Hours		202	126			well flowing when I arrived to test			
							well fl	owing when I ar	rived to	test. Line psi u
									15.50 MAY 200	VI.
Production rate	during test								·	
Oil BOPD based on			Bbls. in			Hours. G		1202 ST 1802 S	GOR	•
Gas:		MC.	FPD; Tested thru (Orifice or Meter	·):				403	
			1400	PPOT OLITITE ST	DDFCC	IDE DATA				-
Upper Completion	Hour, date shut-in	ı L	MID-TEST SHUT-IN F Length of time shut-in			SI press. psig		Stabilized? (Yes or No)		
Lower Completion	Hour, date shut-in	ı L	Length of time shut-in			ess. psig		Stabilized? (Yes or No)		
2579504 202										

(Continue on reverse side)

FLOW TEST NO. 2

Commenced at (hour, da	te)**		Z	Zone producing (Upper or Lower):					
TIME (hour, date)	LAPSED TIME SINCE **		SURE Lower Completion		PROD. ZONE TEMP.	REMARKS			
()		Upper Completion							
		۸							

					<u> </u>				
Production rate dur	ring test								
Oil:	BC	OPD based on	Bbls. ir	n	Hours	Grav	GOR		
Gas:		MCFPI	D: Tested thru (0	Orific	ce or Meter):				
Remarks:									
			and complete to	o the	best of my knowled	ge.			
Approved	MAY 26 20	<u>04</u> 19	9	C	Operator Burling	ton Resources			
New Mexico Oi	l Conservation Divis	- 4			ΩL	Prince			
	1-1			В	By Aldrin	acong i			
By Chal, To Title Operations Associate									
Title									

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test
 No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).