

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Avenue, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural ResourcesOil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.

30-045-31024

5. Indicate Type of Lease

STATE ☒ FEE ☐

State Oil & Gas Lease No.

SF-079045

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:

OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER ☐

b. Type of Completion:

NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF.
WELL OVER BACK RESVR. ☐ OTHER ☐

2. Name of Operator

Devon Energy Corporation L.P.

3. Address of Operator

1751 Highway 511 Navajo Dam, New Mexico 87419

4. Well Location

Unit Letter D: 660' Feet From The North Line and 660' Feet From The West LineSection 21 Township 31N Range 7W NMPM County San Juan

10. Date Spudded

11/24/2002

11. Date T.D. Reached

12/5/2002

12. Date Compl. (Ready to Prod.)

1/28/2003

13. Elevations (DF& RKB, RT, GR, etc.)

6490' GL

14. Elev. Casinghead

15. Total Depth

8130'

16. Plug Back T.D.

8120'

17. If Multiple Compl. How Many
Zones? 318. Intervals
Drilled By

Rotary Tools

Cable Tools

19. Producing Interval(s), of this completion - Top, Bottom, Name

Point Lookout- 5605'-5867' Cliffhouse- 5014'-5564' Lewis- 4434'-4706'

20. Was Directional Survey Made

Yes

21. Type Electric and Other Logs Run

HRI-SDL-DSN-GR SDL-DSN-GR GR-CCL-CBL

22. Was Well Cored

No

23.

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9-5/8"	32.3 #	279'	12-1/4"	200 sx Class "B"	
7"	23#	3625'	8-3/4"	Lead-500 sx foamed 50/50 Poz Tail- 75 sx nonfoamed 50/50 Poz	
4-1/2"	11.6#	8086' 8/30	6-1/4"	500 SX 50/50 Poz	

24.

LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN

25.

TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2-3/8"	7962'	5927'

26. Perforation record (interval, size, and number)

5605'-5867' 0.37" 24 holes

5014'-5564' 0.33" 24 holes

4434'-4706' 0.33" 24 holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
5605'-5867'	1300 gals 15% HCL, 95,340 gals 2% KCL, 101,070 # 20/40 Brady sand
5014'-5564'	1300 gals 15% HCL, 101,185 # 20/40 Brady sand, 93,534 gals 2% KCL
4434'-4706'	300 gals 15% HCL, 180,000 # 20/40 Brady sand, 34,482 gals gelled 2% KCL

28

PRODUCTION

Date First Production		Production Method (Flowing, gas lift, pumping - Size and type pump)			Well Status (Prod. or Shut-in)		
2/17/2003		Flowing			Producing		
Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl	Gas - MCF	Water - Bbl.	Gas - Oil Ratio
1/23/2003	4	2"		0	286 MMCF	5 BBLS	
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)	
260			0	1716 MCFD	30 BBLS/day		

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Vented

Test Witnessed By

30. List Attachments

Signature

Printed

Name Kenny Rhoades Title Company Representative Date 3-12-03

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE**Southeastern New Mexico**

T. Anhy	T. Canyon
T. Salt	T. Strawn
B. Salt	T. Atoka
T. Yates	T. Miss
T. 7 Rivers	T. Devonian
T. Queen	T. Silurian
T. Grayburg	T. Montoya
T. San Andres	T. Simpson
T. Glorieta	T. McKee
T. Paddock	T. Ellenburger
T. Blinbry	T. Gr. Wash
T. Tubb	T. Delaware Sand
T. Drinkard	T. Bone Springs
T. Abo	T.
T. Wolfcamp	T.
T. Penn	T.
T. Cisco (Bough C)	T.

Northwestern New Mexico

T. Ojo Alamo	Not Logged	T. Penn. "B"
T. Kirtland-Fruitland	Not Logged	T. Penn. "C"
T. Pictured Cliffs	Not Logged	T. Penn. "D"
T. Cliff House	5320'	T. Leadville
T. Menefee	5366'	T. Madison
T. Point Lookout	5656'	T. Elbert
T. Mancos	6038'	T. McCracken
T. Gallup	7012'	T. Ignacio Otzte
Base Greenhorn	7765'	T. Granite
T. Dakota	7888'	T.
T. Morrison	8078'	T.
T. Todilto		T.
T. Entrada		T.
T. Wingate		T.
T. Chinle		T.
T. Permian		T.
T. Penn "A"		T.

**OIL OR GAS
SANDS OR ZONES**

No. 1, from.....to.....

No. 3, from.....to.....

No. 2, from.....to.....

No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....

No. 2, from.....to.....feet.....

No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
------	----	----------------------	-----------	------	----	----------------------	-----------