

RECEIVED

FORM APPROVED
OMB NO. 1004-0136
Expires: November 30, 2000

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

2003 JAN 16 AM 11:26
070 Farmington, NM SF-078615

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of Work ☒ DRILL ☐ REENTER
1b. Type of Well ☐ Oil Well ☒ Gas Well ☐ Other ☐ Single Zone ☐ Multiple Zone

5. Lease Serial No.
6. If Indian, Allottee or Tribe Name
N/A
7. If Unit or CA Agreement, Name and No.
NORTHEAST BLANCO UNIT
8. Lease Name and Well No.
NEBU 443A

2. Name of Operator
Attn: Diane Busch Devon Energy Production Company, L.P.

9. API Well No.
30045 31354

3a. Address
20 N. Broadway Oklahoma City, OK 73102

3b. Phone No. (include area code)
(405) 228-4362

10. Field and Pool, or Exploratory
Basin Fruitland Coal

4. Location of well (Report location clearly and in accordance with any State requirements. *)
At surface 1780' FNL & 750' FWL SW NW Unit E
At bottom hole Same
At proposed prod. zone Same

11. Sec., T., R., M., or Blk. And Survey or Area
Sec. 24, T. 30N, R. 8W
E

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*
Approximately 26 miles east of Aztec, New Mexico

12. County or Parish
San Juan
13. State
NM

15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drlg unit line, if any) 750'	16. No. of Acres in lease 1323	17. Spacing Unit dedicated to this well 320 w/2
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft.	19. Proposed Depth 3215'	20. BLM/ BIA Bond No. on file CO-1104
21. Elevations (Show whether DF, RT, GR, etc.) 6345' GL	22. Approximate date work will start* Upon Approval	23. Estimated Duration 20 Days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1 shall be attached to this form:

- | | |
|---|---|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by existing bond on file (see item 20 above). |
| 2. A Drilling Plan. | 5. Operator certification. |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, SUPO shall be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/ or plans as may be required by the authorized officer. |

25. Signature Diane Busch	Name (Printed/ Typed) Diane Busch	Date 1-14-03
------------------------------	--------------------------------------	-----------------

Title Sr. Operations Technician

Approved By (Signature) David J. Mankiewicz	Name (Printed/ Typed)	Date APR 29 2003
--	-----------------------	---------------------

Title	Office
-------	--------

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to operations thereon.

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*(Instructions on reverse)

This action is subject to technical and procedural review pursuant to 43 CFR 3165.3 and appeal pursuant to 43 CFR 3165.4

DRILLING OPERATIONS AUTHORIZED ARE
SUBJECT TO COMPLIANCE WITH ATTACHED
"GENERAL REQUIREMENTS".

NMOCD

District I
PO Box 1980, Hobbs NM 88241-1980
District II
PO Drawer KK, Artesia, NM 87211-0719
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

Form C-102
Revised February 21, 1994

Instructions on back
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

1 API Number 30-045-31354		2 Pool Code 71629		3 Pool Name Basin Fruitland COAL		
4 Property Code 19641		5 Property Name NEBU			6 Well Number # 443A	
7 OGRID No. 6137		8 Operator Name Devon Energy Production Company, L.P.			9 Elevation 6345	

10 Surface Location

UL or Lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
E	24	30 N	8 W		1780	NORTH	750	WEST	SAN JUAN

11 Bottom Hole Location If Different From Surface

7 UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
12 Dedicated Acres FC-W/320		13 Joint or Infill		14 Consolidation Code		15 Order No.			

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

	<p>17 OPERATOR CERTIFICATION</p> <p>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.</p> <p>Signature: <u>Diane Busch</u></p> <p>Printed Name: <u>DIANE BUSCH</u></p> <p>Title: <u>SR. OPERATIONS TECH</u></p> <p>Date: <u>1-14-03</u></p>
	<p>18 SURVEYOR CERTIFICATION</p> <p>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</p> <p>Date of Survey: <u>December 5, 2002</u></p> <p>Signature and Seal of Professional Surveyor: </p> <p>Certificate Number: <u>7016</u></p>

**NEBU 443A
Unit E 24-30N-8W
San Juan Co., NM**

DRILLING PLAN

1. ESTIMATED TOPS OF IMPORTANT GEOLOGIC MARKERS & ANTICIPATED WATER, OIL, GAS OR MINERAL FORMATIONS:

Formation	Depth (ft)	Hydrocarbon/Water Bearing Zones
San Jose	Surface	
Ojo Alamo	2045	Aquifer
Kirtland	2255	
Fruitland	2690	Gas
Pictured Cliffs	3210	Gas
TD	3215	

All shows of fresh water and minerals will be adequately protected and reported.

2. PRESSURE CONTROL EQUIPMENT:

All well control equipment shall be in accordance with Onshore Order #2 for 2M systems.

The minimum specifications for pressure control equipment that will be provided are included on the attached schematic diagram which shows the size and pressure ratings.

2000# BOP With Pipe Rams
2000# BOP With Blind Rams

The anticipated bottom hole pressure is 300 psi.

Auxiliary equipment to be used:

- Upper kelly cock with handle available.

The manifold includes appropriate valves and adjustable chokes. The kill line will have one check valve. Ram type preventers will be pressure tested to full working pressure (utilizing a test plug) or 70% of the internal yield pressure (without a test plug) at:

- Initial installation
- Whenever any seal subject to test pressure is broken
- Following related repairs
- At 30 day intervals

Pipe and blind rams shall be activated each trip.

A BOPE pit level drill will be conducted weekly for each drilling crew.

All tests and drills will be recorded in the drilling log.

The accumulator will have sufficient capacity to close all rams and retain 200 psi above pre-charge pressure without the use of closing unit pumps.

Master controls will be at the accumulator.

3. CASING & CEMENTING PROGRAM:

A. The proposed casing program will be as follows:

Depth	Hole Size	Size	Grade	Weight	Thread	Condition
0-250'	12-1/4"	9-5/8"	H-40	32#	STC	New
0-2690'	8-3/4"	7"	K-55	23#	LTC	New
2640'-TD	6-1/4"	5-1/2"	K-55	15.5 #	LTC	New

All casing strings below the conductor shall be pressure tested to 0.22 psi/ft. of casing string length or 1500 psi, whichever is greater, but not to exceed 70% minimum internal yield.

Surface: The bottom three joints of the surface casing will have a minimum of one centralizer per joint and one centralizer every joint thereafter (Total 5 centralizers estimated)

7" Casing: The bottom three joints of the 7" casing will have a minimum of one centralizer per joint and one centralizer every fifth joint thereafter to above Ojo Alamo with one turbolizer above and below the Ojo Alamo. (Total 12 centralizers estimated).

B. The proposed casing and cementing program will be as follows:

Surface String: 9-5/8" Surface cemented in a 12-1/4" hole at 250'.
32.3# H-40 ST&C 8 Rnd
Saw tooth guide shoe
Cemented with 200 sacks Class B mixed at 15.6 ppg w/.25 pps celloflake, 2% calcium chloride. Yield 1.19 ft³/sx, cement designed to circulate to surface.

Production String: 7" Intermediate cemented in an 8-3/4" hole.
23# J-55 LT&C 8 Rnd
Float Collar
Joint
Float Shoe
Cement with 450 sacks Class B 50/50 POZ, 3% gel, 5# gilsonite, 1/4"# Flocele, .1% CFR 3, .2% Halad 344, yield 1.47 ft³/sx.
Cement designed to circulate to surface.
Pending hole conditions cement baskets may be installed above TD.

Liner: 5-1/2" Liner
15.5# J-55 LT&C 8 Rnd
Shoe
Not cemented

Actual volumes will be calculated and adjusted with caliper log prior to cementing.

4. DRILLING FLUIDS PROGRAM:

Interval	Type	Weight (ppg)	Viscosity	pH	Water Loss	Remarks
0-250'	Spud	8.4-9.0	29-70	8.0	NC	FW gel
250-2690'	LSND	8.4-9.0	29-70	8.0	10-12	LCM as needed
2690-TD	Air					Foam as needed

NC = no control

Sufficient quantities of mud material will be maintained on site or be readily accessible for the purpose of assuring well control. Slow pump rates will be recorded on daily drilling report after mudding up. Visual mud monitoring will be conducted during operations.

5. EVALUATION PROGRAM:

Wire Line Logs: None