NEW MEXICO ENERGY, MINERALS and NATURAL RESOURCES DEPARTMENT

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Production rate during test

Page 1 Revised 11/16/98 NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST Operator Williams Production Lease Name Rosa Well No 80 Location of Well: Unit Letter K Sec 8 Twp 31N Rge 5 W API # 30-0 392253700 TYPE OF PROD. NAME OF RESERVOIR OR POOL METHOD OF PROD. PROD.MEDIUM (Oil or Gas) (Flow or Art. Lift) (Tbg. or Csg.) Upper Completion MesA Verde TRG Lower Completion DAKOTA PRE-FLOW SHUT-IN PRESSURE DATA Hour, date shut-in Length of time shut-in SI press. Psig Upper Stabilized? (Yes or No) Completion 9.50 4-11-03 Hour, date shut-in Length of time shut-in St press. Psig Stabilized? (Yes or No) Lower Completion 9:60 4-11-03 1400 412 FLOW TEST NO. 1 Commenced at (hour, date)* 950 Zone producing (Upper or Lower): Lower 4-13-03 TIME LAPSED TIME **PRESSURE** PROD. ZONE REMARKS (hour,date) SINCE: TEMP. Upper Completion Lower Completion 10:50 AM 155 412 4-14-07 73/142 Turen Later jon 10:50 97 Hes 4-16-03 120 pre 128 155 155 144 HW

Oil:_ BOPD based on Bbls. in __Hours____ Grav. 210 MCFPD; Tested thru (Orifice or Meter): MID-TEST SHUT-IN PRESSURE DATA Upper Hour, date shut-in Length of time shut-in SI press psig Stabilized? (Yes or No) Completion Hour, date shut-in Lower Length of time shut-in SI press. psig Stabilized (Yes or No) Completion

115

your gone on

FLOW TEST NO. 2

Commenced at (hour, date)**				Zone producing (Upper or Lowr):	
TIME (hour,date)	LAPSED TIME Since**	PRESS Upper Completion		PROD. ZONE	REMARKS
Production ra	te during test				
Oil:	BOPD based on			ols. inHo	oursGravGOR
Oil:BOPD based onBbls. inHoursGravGOR Gas:MCFPD:Tested thru (Orfice or Meter):					
Remarks:					
I hereby certify that the information herein contained is true and complete to the bes of my knowledge.					
Approved MAY - 7 2003 20 Operator William Production & Exp New Mexico Oil Conservation Division By Michael Durule					
					Durule
TO THE FORM THE SE AS AN A SECRETARY PROPERTY OF THE SECRETARY AND ASSAULT.				tich 3	
DEPUTY OIL & GAS IMSTECTOR, DIST, 63 Dat				4-17-03	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial

packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

- 5. Following completion of Flow Test No. 1, the well shall again be strut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at filteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The result s of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).