This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

NEW MEXICO OIL CONSERVATION DIVISION

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Page 1 Revised 11/16/98

Well CONOCOPHILLIPS COMPANY 217817 Lease Name HELEN JACKSON No. 2A Operator Location Of Well: Unit Letter O Sec 33 Twp 29N Range 9W API# 30-045-23294 Name of Reservoir or Pool Type of Prod. Method of Prod. Prod. Medium (Oil or Gas) (Flow or Art. Lift) (Tbg. Or Csg.) Upper GAS **FLOWING** Completion **MESAVERDE** TUBING Lower Completion DAKOTA GAS **FLOWING** TUBING **Pre-Flow Shut-In Pressure Data** Length of Time Shut-In Hour, Date, Shut-In SI Press. Psig Stabilized? (Yes or No) Upper Completion 10:00 am 12/04/2004 48 hrs 223# yes Hour, Date, Shut-In Length of Time Shut-In SI Press. Psig Lower Stabilized? (Yes or No) 10:00 am 12/04/2004 Completion 48 hrs 284# Flow Test No. 1 Commenced at (hour, date)* 12:20 pm 12/06/2004 Zone producing (Upper or Lower): Upper Lapsed Time Prod. Zone Time Pressure Remarks (Hour, Date) Since* Upper Compl. Lower Compl. Temp. 12:25 pm 12/07/2004 24 hrs 146# 284# 60 degrees 1:20 pm 12/08/2004 140# 284# 59 degrees 48 hrs 10:50 am 12/09/2004 140# 284# 60 degrees 72 hrs 11:00 am 140# 284# 58 degrees 12/10/2004 96 hrs Production rate during test Oil: 2 BOPD based on Bbls. In 24 Hrs. Grav. GOR Gas: 120 MCFPD; Test thru (Orifice or Meter): _____meter___ Mid-Test Shut-In Pressure Data Hour, Date, Shut-In Upper Length of Time Shut-In SI Press. Psig Stabilized? (Yes or No) Completion 11:15 am 12/10/2004 48 hrs 223# ves Lower Hour, Date, Shut-In Length of Time Shut-In SI Press. Psig Stabilized? (Yes or No) Completion 11:15 am 12/10/2004 48 hrs 284# yes

(Continue on reverse side)

Flow Test No. 2

			LIOM I CO	L 110. 2	
Commenced a	t (hour, date)**	10:45 am 12/12/2	:45 am 12/12/2004 Zone producing (U		pper or Lower): lower
Time	Lapsed Time	Pressure		Prod. Zone	Remarks
(Hour, Date)	Since**	Upper Compl.	Lower Compl.	Temp.	
10:50 am					
12/13/2004	24 hrs	223#	163#	63 degrees	
11:00 am					
12/14/2004	48 hrs	223#	155#	63 degrees	
11:05 am					
12/15/2004	72 hrs	223#	155#	63 degrees	
ĺ,					
Production rate	during test				_
Oil:2	BOPD based	onI	3bls. In24	Hrs	Grav GOR
Oil:2 BOPD based on Bbls. In24 Gas:122 MCFPD; Test thru (Orifice or Meter):				meter	
Remarks:					
I hereby certify	that the informat	tion herein contain	ned is true and co	emplete to the best	of my knowledge.
	DFC	27 2004		_	
Approvedzozo				Operator	CONOCOPHILLIPS COMPANY
	il Conservation I	Division		_	
By Chalit				Ву	Mike Pena
- Philipp					
By Chair				Iitle	MSO
Title Hote	MA SUPER	VISOR DISTRICT	#3	D 4	10/15/0004
11tle /10/10	V			Date	12/15/2004

Northwest New Mexico Packer Leakage Test Instructions

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98,