Submit 3 Copies To Appropriate District State of New Mexico Form C-103 Energy, Minerals and Natural Resources Revised March 25, 1999 District I WELL API NO. 1625 N. French Dr., Hobbs, NM 87240 District II 30-039-27263 OIL CONSERVATION DIVISION 811 South First, Artesia, NM 87210 5. Indicate Type of Lease 2040 South Pacheco District III 1000 Rio Brazos Rd., Aztec, NM 87410 STATE | FEE X Santa Fe, NM 87505 District IV 6. State Oil & Gas Lease No. 2040 South Pacheco, Santa Fe, NM 87505 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name: (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG-BACK-TO, A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH. PROPOSALS.) San Juan 32-5 Unit 1. Type of Well: Oil Well Gas Well X Other MAY 2003 2. Name of Operator 8. Well No. Energen Resources Corporation <101S 3. Address of Operator 9. Pool name or Wildcat 2198 Bloomfield Highway, Farmington, NM 87401 <u> ^ブBasin Fruitland Coal</u> 4. Well Location 710 feet from the 780 South East line and feet from the line Section **Township** 32N Range 06W **NMPM** County Rio Arriba 10. Elevation (Show whether DR, RKB, RT, GR, etc.) 6331' GL 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON **REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS** COMMENCE DRILLING OPNS. **PLUG AND ABANDONMENT** PULL OR ALTER CASING **MULTIPLE** CASING TEST AND COMPLETION **CEMENT JOB** OTHER: OTHER: set casing \square 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation. 05/20/03 Ran 67 jts. 7" 20# J-55 LT&C casing, set @ 2931'. RU BJ Services. Cement with 435 sks 65/35 Class C poz, 6% gel, 10#/sk gilsonite, 1/4#/sk flocele, 2% CaCl2 followed by 100 sks Class C, 10#/sk gilsonite, 1/4#/sk flocele, 2% CaCl2 (1004 cu.ft.). Plug down @ 2:30 pm on 05/20/3. Circulate 225 sks cement to surface. WOC. RD BJ Services. NU BOP. Test casing & BOP to 1200 psi-ok.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNATURE VILLE DOMOGRAY	TITLE Production Assistant	DATE	05/21/03
Type or print name Vicki Donaghey		Telephone No.	505-325-6800
APPROVED BY Conditions of approval, if any:	DEPUTY OIL & GAS INSPECTOR	EST EAPR	2 2 2003