

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**


FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

03 MAR 31 PM 1:57
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals

SUBMIT IN TRIPLICATE



5. Lease Designation and Serial No.
NM 105189

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Byrne Federal 24-1

9. API Well No.

30-039-27262

10. Field and Pool, or Exploratory Area

West Lindreth Gallup / Blanco MV

11. County or Parish, State

Rio Arriba County, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- Notice of Intent
- Subsequent Report
- Final Abandonment Notice

- Abandonment
- Recompletion
- Plugging Back
- Casing Repair
- Altering Casing
- Other Drilling Operations

- Change of Plans
- New Construction
- Non-Routine Fracturing
- Water Shut-Off
- Conversion to Injection
- Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depth for all markers and zones pertinent to this work.)*

3/9/03: MIRU Aztec 124. Spud 12 1/4" surface hole. Drilling to 2892'.
 3/10/03: Reamed out 12 1/4" hole to 17 1/2". Drilled 17 1/2" hole to 292'. Ran 6 jts of 13 3/8", 48"ppf, H40 casing w/ saw tooth guide shoe on bottom and insert float one joint from the bottom. Landed casing at 274'. Insert float at 230'. Cement with 200sks Class "G" + 2% CaCl2 + 1/4 #/sk flocele (blended bulk) followed by 20 sks Class 'G' + 2% CaCl2. Circulated cement to surface. Float did not hold. NU 13 3/8", 3000psi x 13 5/8" 3000psi casing head.
 3/11/03: Completed NU of BOP and choke manifold. Pressure test blind rams, wellhead, pipe rams, choke manifold, kill line valves and casing to 600 psi. Drill cement, insert float, and cement. Drill 12 1/4" hole to 1436'

14. I hereby certify that the foregoing is true and correct

Signed Robert R. Griffec Title Operations Manager

Date: 03/13/03

(This space for Federal or State office use)

Approved by [Signature]
Conditions of approval, if any:

Division of Multi-Resources

Title _____ Date APR 17 2003

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side