

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0136
Expires November 30, 2000

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of Work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. SF-078282
1b. Type of Well: <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/> Single Zone <input checked="" type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name
2. Name of Operator CONOCOPHILLIPS COMPANY		7. If Unit or CA Agreement, Name and No.
Contact: VICKI WESTBY E-Mail: VICKI.R.WESTBY@CONOCOPHILLIPS.COM		8. Lease Name and Well No. SAN JUAN 29-5 UNIT 52G
3a. Address 4001 PENBROOK ODESSA, TX 79762	3b. Phone No. (include area code) Ph: 915-368-1352	9. API Well No. 3003929333
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface NWNE 350FNL 1980FEL At proposed prod. zone NWNE 350FNL 1980FEL		10. Field and Pool, or Exploratory MESAVARDE / DAKOTA
14. Distance in miles and direction from nearest town or post office*		11. Sec., T., R., M., or Blk. and Survey or Area Sec 29 T29N R5W Mer NMP B
15. Distance from proposed location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any)	16. No. of Acres in Lease 147.56	12. County or Parish RIO ARRIBA
18. Distance from proposed location to nearest well, drilling, completed, applied for, on this lease, ft.	19. Proposed Depth 8173 MD	13. State NM
21. Elevations (Show whether DF, KB, RT, GL, etc.) 6740	22. Approximate date work will start	17. Spacing Unit dedicated to this well E/2 320
20. BLM/BIA Bond No. on file		23. Estimated duration

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

1. Well plat certified by a registered surveyor.
2. A Drilling Plan.
3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).
4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
5. Operator certification
6. Such other site specific information and/or plans as may be required by the authorized officer.

25. Signature (Electronic Submission)	Name (Printed/Typed) VICKI WESTBY Ph: 915-368-1352	Date 11/03/2004
Title AGENT		
Approved by (Signature) <i>Wayne Townsend</i>	Name (Printed/Typed) Wayne Townsend	Date 1-26-05
Title Acting AFM	Office FFO	

Application approval does not warrant or certify the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Additional Operator Remarks (see next page)

Electronic Submission #50661 verified by the BLM Well Information System
For CONOCOPHILLIPS COMPANY, sent to the Farmington

✓
DRILLING OPERATIONS AUTHORIZED ARE
SUBJECT TO COMPLIANCE WITH ATTACHED
"GENERAL REQUIREMENTS".

This action is subject to technical and
procedural review pursuant to 43 CFR 3165.3
and appeal pursuant to 43 CFR 3165.4

** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED **

SUT
"GENERAL REQUIREMENTS". NMOCB

District I
PO Box 1980, Hobbs, NM 88241-1980

District II
PO Drawer DD, Artesia, NM 88211-0719

District III
1000 Rio Brazos Rd., Aztec, NM 87410

District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

Form C-102
Revised February 21, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

*API Number 30039-29333	*Pool Code 72319 \ 71599	*Pool Name BLANCO MESAVERDE \ BASIN DAKOTA
*Property Code 31325	*Property Name SAN JUAN 29-5 UNIT	*Well Number 52G
*OGRID No. 217817	*Operator Name CONOCOPHILLIPS COMPANY	*Elevation 6740'


¹⁰ Surface Location

UL or lot no. B	Section 29	Township 29N	Range 5W	Lot Ion	Feet from the 350	North/South line NORTH	Feet from the 1980	East/West line EAST	County RIO ARriba
--------------------	---------------	-----------------	-------------	---------	----------------------	---------------------------	-----------------------	------------------------	----------------------

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Ion	Feet from the	North/South line	Feet from the	East/West line	County
¹² Dedicated Acres 320.0 Acres - E/2 (MV) 320.0 Acres - E/2 (DK)					¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.		

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



¹⁷ OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief

Vicki Westby (pj)
Signature

Vicki R. Westby

Printed Name
Staff Agent

Title


Date
11/3/04

¹⁸ SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief

Survey Date: SEPTEMBER 13, 2004

Signature and Seal of Professional Surveyor



JASON C. EDWARDS
Certificate Number 15269

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-103

May 27, 2004

WELL API NO.

5. Indicate Type of Lease

STATE ☐

FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

SAN JUAN 29-5 UNIT

8. Well Number

52G

9. OGRID Number

217817

10. Pool name or Wildcat

BLANCO MESAVERDE / BASIN DAKOTA

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

ConocoPhillips Company

3. Address of Operator

4001 Penbrook, Odessa, TX 79762

4. Well Location

Unit Letter B 350 feet from the NORTH line and 1980 feet from the EAST line
Section 29 Township 29N Range 5W NMPM RIO ARRIBA County

1. Elevation (Show whether DR, RKB, RT, GR, etc.)
6740 GL

Pit or Below-grade Tank Application ☒ Closure ☐

Pit type DRILL Depth to Groundwater 40' Distance from nearest fresh water well 0.5 MILE Distance from nearest surface water 500'

Liner Thickness:

mil

Below-Grade Tank: Volume

bb1s; Construction Material

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 11.03. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

ConocoPhillips' Generic Pit Plan is on file at the NMOCDD in Aztec, NM. See the attached diagram that details the location of the pit in reference to the proposed wellhead. The drill pit will be lined. The drill pit will be closed after the well has been completed. The solids left after the water has been disposed of will be sampled and NMOCDD approval will be obtained prior to closure of this pit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCDD guidelines ☐ a general permit ☐ or an (attached) alternative OCD-approved plan ☐

SIGNATURE Vicki Westby

TITLE Staff Agent

DATE 11/03/04

Type or print name

E-mail address:

Telephone No.

For State Use Only

DEPUTY OIL & GAS INSPECTOR, DIST. 28

APPROVED BY: [Signature]


TITLE

DATE



Conditions of Approval (if any):

JAN 28 2005

LATITUDE: 36.70290° N
LONGITUDE: 107.37789° W



****SURFACE OWNER***
Bureau of Land
Management

A-A'						
6752'						
6742'						
6732'						
B-B'						
6752'						
6742'						
6732'						
C-C'						
6752'						
6742'						
6732'						

PROJECT PROPOSAL - New Drill / Sidetrack

SAN JUAN 29-5 52G

Lease:		AFE #:		AFE \$:	
Field Name: hPHILLIPS 29-5	Rig:	State: NM	County: RIO ARRIBA	API #:	
Geoscientist: Glaser, Terry J	Phone: (832)486-2332	Prod. Engineer: Moody, Craig E.		Phone: 486-2334	
Res. Engineer: Johnson, Tom B.	Phone: (832)-486-2347	Proj. Field Lead: Fransen, Eric E.		Phone:	

Primary Objective (Zones):

Zone	Zone Name
FRR	BASIN DAKOTA (PRORATED GAS)
RON	BLANCO MESAVERDE (PRORATED GAS)

Location: Surface

Straight Hole

Latitude: 36.70	Longitude: -107.38	X:	Y:	Section: 29	Range: 5W
Footage X: 1980 FEL	Footage Y: 350 FNL	Elevation: 6740 (FT)	Township: 29N		

Tolerance:

Location Type: Year Round	Start Date (Est.):	Completion Date:	Date In Operation:
---------------------------	--------------------	------------------	--------------------

Formation Data: Assume KB = 6753 Units = FT

Formation Call & Casing Points	Depth (TVD in Ft)	SS (Ft)	Depletion (Yes/No)	BHP (PSIG)	BHT	Remarks
SURFACE CSG	213	6540	<input type="checkbox"/>			12-1/4 hole. 9 5/8" 32.3 ppf, H-40, STC casing. Circulate cement to surface.
NCMT	1510	5243	<input type="checkbox"/>			
OJAM	2893	3860	<input type="checkbox"/>			Possible water flows.
KRLD	3053	3700	<input type="checkbox"/>			
FRLD	3373	3380	<input type="checkbox"/>			Possible gas.
PCCF	3673	3080	<input type="checkbox"/>			
LEWS	3873	2880	<input type="checkbox"/>			
Intermediate Casing	3973	2780	<input type="checkbox"/>			8 3/4" Hole. 7", 20 ppf, J-55, STC Casing. Circulate cement to surface.
CHRA	4683	2070	<input type="checkbox"/>			
CLFH	5503	1250	<input type="checkbox"/>	575		Gas; possibly wet
MENF	5603	1150	<input type="checkbox"/>			Gas.
PTLK	5853	900	<input type="checkbox"/>			Gas.
MNCS	6153	600	<input type="checkbox"/>			
GLLP	7113	-360	<input type="checkbox"/>			Gas. Possibly wet.
GRHN	7823	-1070	<input type="checkbox"/>	750		Gas possible, highly fractured
CBBO	7983	-1230	<input type="checkbox"/>			Gas
Total Depth	8173	-1420	<input type="checkbox"/>			6-1/4" Hole. 4-1/2", 11.6 ppf, N-80, LTC casing. Circulate cement a minimum of 100' inside the previous casing string. No open hole logs. Cased hole TDT with GR to surface.

Reference Wells:

Reference Type	Well Name	Comments
----------------	-----------	----------

Logging Program:

Intermediate Logs:	<input type="checkbox"/> Log only if show	<input type="checkbox"/> GR/ILD	<input type="checkbox"/> Triple Combo
TD Logs:	<input type="checkbox"/> Triple Combo	<input type="checkbox"/> Dipmeter	<input type="checkbox"/> RFT <input type="checkbox"/> Sonic <input type="checkbox"/> VSP <input checked="" type="checkbox"/> TDT

Additional Information:

Comments: General/Work Description -
Drilling Mud Program:

Printed on: 11/3/2004 9:47:46 AM

San Juan 29-5 # 52G

SURFACE CASING :

Drill Bit Diameter	12.25"	
Casing Outside Diameter	9.625"	Casing Inside Diam. 9.001"
Casing Weight	32.3	ppf
Casing Grade	H-40	
Shoe Depth	230'	
Cement Yield	12.1	cuft/sk
Excess Cement	125	%
Cement Required	149	sx

SHOE 230', 9.625", 32.3 ppf, H-40 STC

INTERMEDIATE CASING :

Drill Bit Diameter	8.75"	
Casing Outside Diameter	7"	Casing Inside Diam. 6.456"
Casing Weight	20	ppf
Casing Grade	J-55	
Shoe Depth	3973'	
Lead Cement Yield	2.88	cuft/sk
Lead Cement Excess	150	%
Tail Cement Length	794.6'	
Tail Cement Yield	1.33	cuft/sk
Tail Cement Excess	150	%
Lead Cement Required	398	sx
Tail Cement Required	232	sx

SHOE 3973', 7", 20 ppf, J-55 STC

PRODUCTION CASING :

Drill Bit Diameter	6.25"	
Casing Outside Diameter	4.5"	Casing Inside Diam. 4.000"
Casing Weight	11.6	ppf
Casing Grade	N-80	
Top of Cement	3773'	200' inside intermediate casing
Shoe Depth	8173'	
Cement Yield	1.45	cuft/sk
Cement Excess	50	%
Cement Required	462	sx

SHOE 8173', 4.5", 11.6 ppf, N-80 LTC

9-5/8 Surface Casing	
Cement Recipe	Class C Standard Cement
	+ 3% Calcium Chloride
	+0.25 lb/sx Flocele
Cement Volume	149 sx
Cement Yield	1.21 cuft/sx
Slurry Volume	179.8 cuft
	32.0 bbls
Cement Density	15.6 ppg
Water Required	5.29 gal/sx

7" Intermediate Casing	
Lead Slurry	
Cement Recipe	Standard Cement
	+ 3% Econolite (extender)
	+ 10 lb/sx Pheno Seal
Cement Required	398 sx
Cement Yield	2.88 cuft/sx
Slurry Volume	1146.9 cuft
	204.3 bbls
Cement Density	11.5 ppg
Water Required	16.91 gal/sx

7" Intermediate Casing	
Tail Slurry	
Cement Slurry	50 / 50 POZ:Standard Cement
	+ 2% Bentonite
	+ 6 lb/sx Pheno Seal
Cement Required	232 sx
Cement Yield	1.33 cuft/sx
Slurry Volume	308.2 cuft
	54.9 bbls
Cement Density	13.5 ppg
Water Required	5.52 gal/sx

4-1/2" Production Casing	
Cement Recipe	50 / 50 POZ:Standard Cement
	+ 3% Bentonite
	+ 3.5 lb/sx PhenoSeal
	+ 0.2% CFR-3 Friction Reducer
	+ 0.1% HR-5 Retarder
	+ 0.8% Halad-9 Fluid Loss Additive
Cement Quantity	462 sx
Cement Yield	1.45 cuft/sx
Cement Volume	670.1 cuft
	119.3
Cement Density	13.1 ppg
Water Required	6.47 gal/sx

9-5/8 Surface Casing	
Cement Recipe	Class G Standard Cement
	+ 2% S001 Calcium Chloride
	+0.25 lb/sx D029 Cellophane Flakes
Cement Volume	148 sx
Cement Yield	1.16 cuft/sx
Cement Volume	171.5 cuft
Cement Density	15.8 ppg
Water Required	4.983 gal/sx


7" Intermediate Casing	
Lead Slurry	
Cement Recipe	Class G Standard Cement
	+0.25 lb/sx D029 Cellophane Flakes
	+ 3% D079 Extender
	+ 0.20% D046 Antifoam
	+ 10 lb/sx Pheno Seal
Cement Required	422 sx
Cement Yield	2.72 cuft/sx
Slurry Volume	1148.2 cuft
	204.5 bbls
Cement Density	11.7 ppg
Water Required	15.74 gal/sx

7" Intermediate Casing	
Tail Slurry	
Cement Slurry	50 / 50 POZ:Standard Cement
	+0.25 lb/sx D029 Cellophane Flakes
	+ 2% D020 Bentonite
	+ 1.5 lb/sx D024 Gilsonite Extender
	+ 2% S001 Calcium Chloride
	+ 0.10% D046 Antifoam
	+ 6 lb/sx Pheno Seal
Cement Required	235 sx
Cement Yield	1.31 cuft/sx
Slurry Volume	308.2 cuft
	54.9 bbls
Cement Density	13.5 ppg
Water Required	5.317 gal/sx


4-1/2" Production Casing	
Cement Recipe	50 / 50 POZ:Class G Standard Cement
	+0.25 lb/sx D029 Cellophane Flakes
	+ 3% D020 Bentonite
	+ 1.0 lb/sx D024 Gilsonite Extender
	+ 0.25% D167 Fluid Loss
	+ 0.15% D065 Dispersant
	+ 0.1% D800 Retarder
	+ 0.1% D046 Antifoamer
	+ 3.5 lb/sx PhenoSeal
Cement Quantity	465 sx
Cement Yield	1.44 cuft/sx
Cement Volume	669.8 cuft
	119.3
Cement Density	13 ppg
Water Required	6.43 gal/sx

BLOWOUT PREVENTER ARRANGEMENT & PROGRAM

For Drilling to Intermediate Casing Point & Setting 7" Intermediate Casing



1. Rotating Head
- 2A. Fill-up Line & valve
- 2B. Flowline
3. Spacer Spool
4. Double Ram BOP (11", 3000 psi)
5. Pipe Rams
6. Blind Rams
7. Kill Line
8. Kill Line Check Valve
9. Kill Line Valve
10. Inner Choke Line Valve (3")
11. Outer Choke Line Valve (3")
12. Choke Line (3")
13. Variable Choke
14. Choke Line Valve (2")
15. Panic Line Valve (3")
16. Choke Manifold Pressure Gauge
17. Choke Line (2")
18. Mud Cross Spacer Spool
19. Casing Head "A" Section
20. Casing Head "A" Section 2" Valve
21. 9 5/8" Casing Collar



A 12-1/4" hole will be drilled to approximately 220' and the 9-5/8" surface casing will be run and cemented. The Casing Head "A" Section will be screwed onto the 9-5/8" surface casing stub. The BOP will be installed on the Casing Head "A" Section. A test plug will be set in the wellhead and the pipe rams and choke manifold will be tested to 200 psi to 300 psi (low pressure test) for 10 minutes and to 1000 psi (high pressure test) for 10 minutes. Then the test plug will be removed, and the **9-5/8" casing will be pressure tested** against closed blind rams to 200 psi to 300 psi for 10 minutes and to **1000 psi for 30 minutes** (this value is one 44% of the minimum internal yield pressure of the 9-5/8" casing). (Note: per regulatory requirements we will wait on cement at least 8 hrs after placement before testing the 9-5/8" surface casing). Then an 8-3/4" hole will be drilled to intermediate casing point and 7" intermediate casing will be run and cemented.


In addition to the equipment in the above diagram the following equipment will comprise the BOP system:

1. Upper Kelly cock Valve with handle
2. Stab-in TIW valve for all drillstrings in use


Revision Date: September 1, 2004

BLOWOUT PREVENTER ARRANGEMENT & PROGRAM

For Drilling to TD and Setting 4.5 inch Casing



1. Rotating Head
- 2A. Fill-up Line & valve
- 2B. Bloopie Line (for Air Drilling)
3. Spacer Spool
4. Double Ram BOP (11", 3000 psi)
5. Pipe Rams
6. Blind Rams
7. Kill Line
8. Kill Line Check Valve
9. Kill Line Valve
10. Inner Choke Line Valve (3")
11. Outer Choke Line Valve (3")
12. Choke Line (3")
13. Variable Choke
14. Choke Line Valve (2")
15. Panic Line Valve (3")
16. Choke Manifold Pressure Gauge
17. Choke Line (2")
18. Mud Cross Spacer Spool
- 19A Csg Spool "B" Section (11", 3M)
- 19B "B" Section Csg Valve (2", 3M)
- 20A Csg Head "A" Section (11", 3M)
- 20B "A" Section Csg Valve (2", 3M)
21. 9 5/8" Casing Collar



After the 7" intermediate casing has been run and cemented, the Casing Spool ("B" Section) will be installed on the wellhead ("A" Section) and the BOP will be installed on the Casing Spool. A test plug will be set in the wellhead and the pipe rams, blind rams, and choke manifold will be tested to 200 psi to 300 psi (low pressure test) for 10 minutes and to 3000 psi (high pressure test) for 10 minutes. Then the test plug will be removed and the 7" casing will be pressure tested against closed blind rams to 200 psi to 300 psi for 10 minutes and to 1800 psi for 30 minutes - this test pressure is 48% of the minimum internal yield strength of 3740 psi for the 7", 20#, J-55, STC casing. Then we will air drill the 6-1/4" hole to TD and run and cement the 4-1/2" casing.

In addition to the equipment in the above diagram the following equipment will comprise the BOP system:

1. Upper Kelly cock Valve with handle
2. Stab-in TIW valve for all drillstrings in use

Revision Date: September 1, 2004