

Submit 1 Copy To Appropriate District  
Office  
District I  
1625 N French Dr, Hobbs, NM 88240  
District II  
1301 W Grand Ave, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd, Aztec, NM 87410  
District IV  
1220 S St Francis Dr, Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
October 13, 2009

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-045-35235
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. OG 959-6
7. Lease Name or Unit Agreement Name Moncrief Com
8. Well Number # 100
9. OGRID Number 006515
10. Pool name or Wildcat Basin Fruitland Coal (71629)

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator  
Dugan Production Corp. (505) 325-1821

3. Address of Operator  
P.O. Box 420, Farmington, NM 87499-0420

4. Well Location

Unit Letter A : 990 feet from the FNL line and 680 feet from the FEL line

Section 02 Township 30N Range 13W NMPM County San Juan

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
5946' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: TD, production casing  
☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date  
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of  
proposed completion or recompletion.

Drilled to TD @ 2237' on 06/11/2011. Run 5-1/2" 15.5# J-55 LT&C casing in 7-7/8" hole. Land @ 2227', float collar @ 2184'.  
Cement w/240 sx Premium Life FM w/3% CaCl<sub>2</sub>, 1/4# Celloflake, 5#/sm LCM, 0.4% FI-52, 8%Bentonite & 0.4% Sodium Metasilicate.  
Tail w/65 sx Type III cement w/1# sx CaCl<sub>2</sub>, 1/4# celloflake/sx, 0.2% FL-52 (601 cu ft total slurry). Displace w/52.5 bbls water.  
Circulate 3 bbls cement. BJ Services released on 06/12/2011. *AV*

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*John C. Alexander*

TITLE: Vice President

DATE: 06/14/2011

Type or print name John C. Alexander E-mail address: johncalexander@duganproduction.com PHONE: 505-325-1821

For State Use Only

APPROVED BY:

*Brook Bell*

TITLE

Deputy Oil & Gas Inspector,  
District #3

DATE

6-24-11

Conditions of Approval (if any):

*AV*

