Form 3160-5 (April 2004)

(Instructions on page 2)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT JUL 05 2011 FORM APPROVED

OM B N	No 1004	⊦0137
Expires	March	31, <b>2</b> 00

5 Lease Senal No SUNDRY NOTICES AND REPORTS ON MEIGHS Field Office NMNM 104609

Do not use this form for proposals to drill or Utoaresénter an anagem 116. If Indian. Allottee or Tribe Name NMNM 104609

SUBMIT IN TR	RIPLICATE- Other ins	tructions on reverse	side.	7 If Unit or CA/Agreement, Name and/or No
Type of Well Oil Well	✓ Gas Well Other			8 Well Name and No.
				Juniper West 24 #44
Name of Operator Coleman Oil	l & Gas, Inc.			9 API Well No
a. Address P.O. Drawer 3337		3b Phone No (include area 505-327-0356	a code)	30-045-33595  10 Field and Pool, or Exploratory Area
Location of Well (Footage, Sec.,	.T.R.M. or Survey Description)	)		Basin Fruitland Coal
1100' FSL, 700' FEL P, Sect			07.948138°	11 County or Parish, State
,	, ,	, <b>,</b>		San Juan, New Mexico
12. CHECK A	APPROPRIATE BOX(ES) TO	O INDICATE NATURE (	OF NOTICE, RE	PORT, OR OTHER DATA
TYPE OF SUBMISSION		ТҮРЕ С	OF ACTION	
	Acidize	Deepen	Production (Start	(Resume) Water Shut-Off
Notice of Intent	Alter Casing	Fracture Treat	Reclamation	Well Integrity
Subsequent Report	Casing Repair	New Construction	Recomplete.	Other
Subsequent Report	Change Plans	Plug and Abandon	Tèmporarily Abai	
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal	
testing has been completed. F determined that the site is read	Final Abandonment Notices shall be dy for final inspection )	pe filed only after all requirement	ts, including reclamat	a new interval, a Form 3160-4 shall be filed once ion, have been completed, and the operator has
testing has been completed. F determined that the site is read SPUD WELL JUNE 20, CASING. RAN A TOTA CALCIUM CHLORIDE NIPPLED UP BOP AND DRILLED 7 7/8" HOLE 15.50#/FT LT&C J-55. I GILSONITE AND 1/4# I	inal Abandonment Notices shall be dy for final inspection )  2011 @ 11:45 AM. DRILLEI AL FOOTAGE OF 126.60 FT AND 1/4# PER SACK POLY D MANIFOLD. PRESSURE TO 1160 FT. KB. TD WELL LANDED CASING @ 1152.6 PER SACK POLY-E-FLAKE E-FLAKE CIRCULATED 1	D 12 1/4" HOLE TO 136 FT  AND LANDED @ 131.60 I  Y-E-FLAKE. CIRCULATE TESTED BOP, MANIFOLE  @ 1160 FT. KB @ 2:15 PM  0 FT. KB. CEMENTED W/  C. TAILED W/ 90 SACKS O	S, including reclamate  KB AND RAN 3  FT. KB. CEMENT  D 10 BARRELS CO  AND CASING TO  I ON JUNE 26, 20  120 SACKS CLA  LASS G 50/50 PO	JTS OF 8 5/8" 24# J-55 ST&C NEW TED W/150 SACKS CLASS B W/2% DF CEMENT TO RESERVE PIT: O LOW 250 PSIG AND HIGH 750 PSIG. 11. RAN A TOTAL OF 28 JTS 5 1/2". SS G W/3% ECONOLITE, 5# PER SACK IZ W/5# PER SACK GILSONITE AND LUG DOWN AT 9:34 AM JUNE 27, 2011
testing has been completed. F determined that the site is read  SPUD WELL JUNE 20, CASING. RAN A TOTA CALCIUM CHLORIDE NIPPLED UP BOP AND DRILLED 7.7/8" HOLE 15.50#/F LT&C J-55. 1 GILSONITE AND 1/4# I 1/4# PER SACK POLY-I BUMPED PLUG TO 806  SPUD WELL JUNE 20, RELEASED ROTARY 1	imal Abandonment Notices shall be dy for final inspection )  2011 @ 11:45 AM. DRILLEI AL FOOTAGE OF 126.60 FT. AND 1/4# PER SACK POLY D MANIFOLD. PRESSURE TO 1160 FT. KB. TD WELL LANDED CASING @ 1152.60 PER SACK POLY-E-FLAKE E-FLAKE CIRCULATED 10 PSIG. PLUG HELD.  2011 FOOLS JUNE 22. 2011	D 12 1/4" HOLE TO 136 FT. AND LANDED @ 131.60 IY-E-FLAKE. CIRCULATE TESTED BOP, MANIFOLE @ 1160 FT. KB @ 2:15 PM OFT. KB. CEMENTED W/ E. TAILED W/ 90 SACKS C6 BARRELS OF CEMENT	S, including reclamate  KB AND RAN 3  FT. KB. CEMENT  D 10 BARRELS CO  AND CASING TO  I ON JUNE 26, 20  120 SACKS CLA  LASS G 50/50 PO	JTS OF 8 5/8" 24# J-55 ST&C NEW TED W/150 SACKS CLASS B W/2% OF CEMENT TO RESERVE PITY O LOW 250 PSIG AND HIGH 750 PSIG. 11. RAN A TOTAL OF 28 JTS 5 1/2". SS G W/3% ECONOLITE, 5# PER SACK Z W/5# PER SACK GILSONITE AND LUG DOWN AT 9:34 AM JUNE 27, 2011
testing has been completed. F determined that the site is read SPUD WELL JUNE 20, CASING. RAN A TOTA CALCIUM CHLORIDE NIPPLED UP BOP AND DRILLED 7 7/8" HOLE 15.50#/FT LT&C J-55. I GILSONITE AND 1/4# I 1/4# PER SACK POLY-I BUMPED PLUG TO 800 SPUD WELL JUNE 20, RELEASED ROTARY T	inal Abandonment Notices shall be dy for final inspection )  2011 @ 11:45 AM. DRILLEI AL FOOTAGE OF 126.60 FT. AND 1/4# PER SACK POLY D MANIFOLD. PRESSURE TO 1160 FT. KB. TD WELL LANDED CASING @ 1152.60 PER SACK POLY-E-FLAKE E-FLAKE CIRCULATED 100 PSIG. PLUG HELD.  2011 FOOLS JUNE 22. 2011	D 12 1/4" HOLE TO 136 FT. AND LANDED @ 131.60 IY-E-FLAKE. CIRCULATE TESTED BOP, MANIFOLE @ 1160 FT. KB @ 2:15 PM OFT. KB. CEMENTED W/ E. TAILED W/ 90 SACKS C6 BARRELS OF CEMENT	S, including reclamate  KB AND RAN 3  FT. KB. CEMENT  D 10 BARRELS CO  AND CASING TO  I ON JUNE 26, 20  120 SACKS CLA  LASS G 50/50 PO	JTS OF 8 5/8" 24# J-55 ST&C NEW FED W/150 SACKS CLASS B W/2% OF CEMENT TO RESERVE PIT: O LOW 250 PSIG AND HIGH 750 PSIG: 11. RAN A TOTAL OF 28 JTS 5 1/2" SS G W/3% ECONOLITE, 5# PER SACK VZ W/5# PER SACK GILSONITE AND LUG DOWN AT 9:34 AM JUNE 27, 2011
testing has been completed. F determined that the site is read  SPUD WELL JUNE 20, CASING. RAN A TOTA CALCIUM CHLORIDE NIPPLED UP BOP AND DRILLED 7.7/8" HOLE 15.50#/FT LT&C J-55. I GILSONITE AND 1/4# I 1/4# PER SACK POLY-I BUMPED PLUG TO 800  SPUD WELL JUNE 20, RELEASED ROTARY TO A CASING AND TO SELECT SECTION OF THE SE	inal Abandonment Notices shall be dy for final inspection )  2011 @ 11:45 AM. DRILLEI AL FOOTAGE OF 126.60 FT. AND 1/4# PER SACK POLYD MANIFOLD. PRESSURE TO 1160 FT. KB. TD WELL LANDED CASING @ 1152.60 PER SACK POLY-E-FLAKE E-FLAKE CIRCULATED 10 PSIG. PLUG HELD.  2011 1000LS JUNE 22. 2011	D 12 1/4" HOLE TO 136 FT AND LANDED @ 131.60 I Y-E-FLAKE. CIRCULATE TESTED BOP, MANIFOLE @ 1160 FT. KB @ 2:15 PM 0 FT. KB. CEMENTED W/ E. TAILED W/90 SACKS C 6 BARRELS OF CEMENT	IS, including reclamates, including reclamates.  IS KB AND RAN 3 IST. KB. CEMENT ID 10 BARRELS CO O AND CASING TO O 10 SUNE 26, 20 I 120 SACKS CLA ILASS G 50/50 PO TO SURFACE. P	JTS OF 8 5/8" 24# J-55 ST&C NEW TED W/150 SACKS CLASS B W/2% OF CEMENT TO RESERVE PITY O LOW 250 PSIG AND HIGH 750 PSIG. 11. RAN A TOTAL OF 28 JTS 5 1/2" SS G W/3% ECONOLITE, 5# PER SACK Z W/5# PER SACK GILSONITE AND LUG DOWN AT 9:34 AM JUNE 27, 2011
testing has been completed. F determined that the site is read  SPUD WELL JUNE 20, CASING. RAN A TOTA CALCIUM CHLORIDE NIPPLED UP BOP AND DRILLED 7.7/8" HOLE 15.50#/FT LT&C J-55. I GILSONITE AND 1/4# I 1/4# PER SACK POLY-I BUMPED PLUG TO 800  SPUD WELL JUNE 20, RELEASED ROTARY T	inal Abandonment Notices shall be dy for final inspection )  2011 @ 11:45 AM. DRILLEI AL FOOTAGE OF 126.60 FT. AND 1/4# PER SACK POLYD MANIFOLD. PRESSURE TO 1160 FT. KB. TD WELL LANDED CASING @ 1152.60 PER SACK POLY-E-FLAKE E-FLAKE CIRCULATED 10 PSIG. PLUG HELD.  2011 1000LS JUNE 22. 2011	D 12 1/4" HOLE TO 136 FT AND LANDED @ 131.60 I Y-E-FLAKE. CIRCULATE TESTED BOP, MANIFOLE @ 1160 FT. KB @ 2:15 PM 0 FT. KB. CEMENTED W/ E. TAILED W/90 SACKS C 6 BARRELS OF CEMENT	S, including reclamate  KB AND RAN 3  FT. KB. CEMENT  D 10 BARRELS CO  AND CASING TO  I ON JUNE 26, 20  120 SACKS CLA  LASS G 50/50 PO	JTS OF 8 5/8" 24# J-55 ST&C NEW FED W/150 SACKS CLASS B W/2% OF CEMENT TO RESERVE PIT: O LOW 250 PSIG AND HIGH 750 PSIG. 11. RAN A TOTAL OF 28 JTS 5 1/2" SS G W/3% ECONOLITE, 5# PER SACK DZ W/5# PER SACK GILSONITE AND LUG DOWN AT 9:34 AM JUNE 27, 2011
testing has been completed F determined that the site is read  SPUD WELL JUNE 20, CASING. RAN A TOTA CALCIUM CHLORIDE NIPPLED UP BOP AND DRILLED 7.7/8" HOLE 15.50#/FT LT&C J-55. I GILSONITE AND 1/4# I 1/4# PER SACK POLY-I BUMPED PLUG TO 800  SPUD WELL JUNE 20, RELEASED ROTARY TO A CASC MARCH 14 I hereby certify that the for Name (Printed/Typed)	inal Abandonment Notices shall be dy for final inspection )  2011 @ 11:45 AM. DRILLEI AL FOOTAGE OF 126.60 FT. AND 1/4# PER SACK POLYD MANIFOLD. PRESSURE TO 1160 FT. KB. TD WELL LANDED CASING @ 1152.60 PER SACK POLY-E-FLAKE E-FLAKE CIRCULATED 10 PSIG. PLUG HELD.  2011 1000LS JUNE 22. 2011	D 12 1/4" HOLE TO 136 FT AND LANDED @ 131.60 I Y-E-FLAKE. CIRCULATE TESTED BOP, MANIFOLE @ 1160 FT. KB @ 2:15 PM 0 FT. KB. CEMENTED W/ E. TAILED W/90 SACKS C 6 BARRELS OF CEMENT	IS, including reclamates, including reclamates.  IS KB AND RAN 3 IST. KB. CEMENT ID 10 BARRELS CO O AND CASING TO O 10 SUNE 26, 20 I 120 SACKS CLA ILASS G 50/50 PO TO SURFACE. P	JTS OF 8 5/8" 24# J-55 ST&C NEW FED W/150 SACKS CLASS B W/2% DF CEMENT TO RESERVE PIT. O LOW 250 PSIG AND HIGH 750 PSIG. 11. RAN A TOTAL OF 28 JTS 5 1/2". SS G W/3% ECONOLITE, 5# PER SACK IZ W/5# PER SACK GILSONITE AND LUG DOWN AT 9:34 AM JUNE 27, 2011
testing has been completed. F determined that the site is read  SPUD WELL JUNE 20, CASING. RAN A TOTA CALCIUM CHLORIDE NIPPLED UP BOP AND DRILLED 7.7/8" HOLE 15.50#/FT LT&C J-55. I GILSONITE AND 1/4# I 1/4# PER SACK POLY-I BUMPED PLUG TO 800  SPUD WELL JUNE 20, RELEASED ROTARY TO  A PROBLEM OF THE PROBLEM	inal Abandonment Notices shall be dy for final inspection )  2011 @ 11:45 AM. DRILLEI AL FOOTAGE OF 126.60 FT. AND 1/4# PER SACK POLY OMANIFOLD. PRESSURE TO 1160 FT. KB. TD WELL LANDED CASING @ 1152.60 PER SACK POLY-E-FLAKE E-FLAKE CIRCULATED 10 PSIG. PLUG HELD.  2011 FOOLS JUNE 22. 2011  Color of the c	D 12 1/4" HOLE TO 136 FT. AND LANDED @ 131.60 IY-E-FLAKE. CIRCULATE TESTED BOP, MANIFOLD. @ 1160 FT. KB @ 2:15 PM OFT. KB. CEMENTED W/S. TAILED W/90 SACKS COEMENT	KB AND RAN 3 FT. KB. CEMENT TO 10 BARRELS CO AND CASING TO 10 10 JUNE 26, 20 120 SACKS CLA CLASS G 50/50 PO TO SURFACE. P	JTS OF 8 5/8" 24# J-55 ST&C NEW TED W/150 SACKS CLASS B W/2% DF CEMENT TO RESERVE PIT: O LOW 250 PSIG AND HIGH 750 PSIG. 11. RAN A TOTAL OF 28 JTS 5 1/2". SS G W/3% ECONOLITE, 5# PER SACK DZ W/5# PER SACK GILSONITE AND LUG DOWN AT 9:34 AM JUNE 27, 2011
spud Well June 20, Casing. Ran a Tota Calcium Chloride Nippled up Bop and Drilled 7.7/8" Hole 15.50#/FT LT&C J-55. I GILSONITE AND 1/4# I 1/4# PER SACK POLY-I BUMPED PLUG TO 806  Spud Well June 20, Released Rotary To Released Rotary To Name (Printed/Typed)  Michael T. 1  Signature	inal Abandonment Notices shall be dy for final inspection )  2011 @ 11:45 AM. DRILLEI AL FOOTAGE OF 126.60 FT. AND 1/4# PER SACK POLY OMANIFOLD. PRESSURE TO 1160 FT. KB. TD WELL LANDED CASING @ 1152.60 PER SACK POLY-E-FLAKE E-FLAKE CIRCULATED 10 PSIG. PLUG HELD.  2011 FOOLS JUNE 22. 2011  Color of the c	D 12 1/4" HOLE TO 136 FT AND LANDED @ 131.60 I Y-E-FLAKE. CIRCULATE TESTED BOP, MANIFOLE @ 1160 FT. KB @ 2:15 PM 0 FT. KB. CEMENTED W/ E. TAILED W/90 SACKS C 6 BARRELS OF CEMENT  Title OPE  Date  R FEDERAL OR STA	KB AND RAN 3 FT. KB. CEMENT TD 10 BARRELS CO AND CASING TO 1 ON JUNE 26, 20 1 120 SACKS CLA LASS G 50/50 P.O TO SURFACE. P	JTS OF 8 5/8" 24# J-55 ST&C NEW FED W/150 SACKS CLASS B W/2% OF CEMENT TO RESERVE PIT: O LOW 250 PSIG AND HIGH 750 PSIG: 11. RAN A TOTAL OF 28 JTS 5 1/2" SS G W/3% ECONOLITE, 5# PER SACK IZ W/ 5# PER SACK GILSONITE AND LUG DOWN AT 9:34 AM JUNE 27, 2011  15 G CONS DIV DIC
testing has been completed. F determined that the site is read  SPUD WELL JUNE 20, CASING. RAN A TOTA CALCIUM CHLORIDE NIPPLED UP BOP AND DRILLED 7 7/8" HOLE 15.50#/FT LT&C J-55. I GILSONITE AND 1/4# I 1/4# PER SACK POLY-I BUMPED PLUG TO 806  SPUD WELL JUNE 20, RELEASED ROTARY T  APPROVED WELL TO SIGNATURE OF Name (Printed/Typed) MICHAEL T. I  Signature  Approved by	inal Abandonment Notices shall be dy for final inspection )  2011 @ 11:45 AM. DRILLEI AL FOOTAGE OF 126.60 FT. AND 1/4# PER SACK POLY D MANIFOLD. PRESSURE TO 1160 FT. KB. TD WELL LANDED CASING @ 1152.60 PER SACK POLY-E-FLAKE E-FLAKE CIRCULATED 10 PSIG. PLUG HELD.  2011 FOOLS JUNE 22. 2011  TOOLS JUNE 22. 2011  THE SPACE FOR	D 12 1/4" HOLE TO 136 FT AND LANDED @ 131.60 I Y-E-FLAKE. CIRCULATE TESTED BOP, MANIFOLE @ 1160 FT. KB @ 2:15 PM 0 FT. KB. CEMENTED W/ E. TAILED W/90 SACKS C 6 BARRELS OF CEMENT  Title OPE  Date  Title Title	KB AND RAN 3 FT. KB. CEMENT TD 10 BARRELS CO AND CASING TO 1 ON JUNE 26, 20 1 120 SACKS CLA LASS G 50/50 P.O TO SURFACE. P	JTS OF 8 5/8" 24# J-55 ST&C NEW TED W/150 SACKS CLASS B W/2% DF CEMENT TO RESERVE PIT: O LOW 250 PSIG AND HIGH 750 PSIG. 11. RAN A TOTAL OF 28 JTS 5 1/2". SS G W/3% ECONOLITE, 5# PER SACK DZ W/5# PER SACK GILSONITE AND LUG DOWN AT 9:34 AM JUNE 27, 2011
testing has been completed. F determined that the site is read  SPUD WELL JUNE 20, CASING. RAN A TOTA CALCIUM CHLORIDE NIPPLED UP BOP AND DRILLED 7.7/8" HOLE 15.50#/FT LT&C J-55. I GILSONITE AND 1/4# I 1/4# PER SACK POLY-I BUMPED PLUG TO 800  SPUD WELL JUNE 20, RELEASED ROTARY TO  A PROBLEM OF THE PROBLEM	inal Abandonment Notices shall be dy for final inspection )  2011 @ 11:45 AM. DRILLEI AL FOOTAGE OF 126.60 FT. AND 1/4# PER SACK POLY. D MANIFOLD. PRESSURE TO 1160 FT. KB. TD WELL LANDED CASING @ 1152.60 PER SACK POLY-E-FLAKE E-FLAKE CIRCULATED 100 PSIG. PLUG HELD.  2011 FOOLS JUNE 22. 2011  TOOLS JUNE 22. 2011  THE SPACE FOR	D 12 1/4" HOLE TO 136 FT AND LANDED @ 131.60 I Y-E-FLAKE. CIRCULATE TESTED BOP, MANIFOLE @ 1160 FT. KB @ 2:15 PM 0 FT. KB. CEMENTED W/ E. TAILED W/90 SACKS C 6 BARRELS OF CEMENT  Title OPE  Date  Title COPE  Ti	KB AND RAN 3 FT. KB. CEMENT TO 10 BARRELS CO AND CASING TO 10 ON JUNE 26, 20 120 SACKS CLA CLASS G 50/50 PO TO SURFACE. P	JTS OF 8 5/8" 24# J-55 ST&C NEW FED W/150 SACKS CLASS B W/2% OF CEMENT TO RESERVE PIT: O LOW 250 PSIG AND HIGH 750 PSIG: 11. RAN A TOTAL OF 28 JTS 5 1/2" SS G W/3% ECONOLITE, 5# PER SACK IZ W/ 5# PER SACK GILSONITE AND LUG DOWN AT 9:34 AM JUNE 27, 2011  15 G CONS DIV DIC

**FARMINGTON FIELD OFFICE** 

JUL 0 6 2011