Form 3160-5 (August 2007)

entitle the applicant to conduct operations thereon

fictitious or fraudulent statements or representations as to any matter within its jurisdiction

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an

RECEIVED

FORM APPROVED OMB NO 1004-0137 Expires July 31, 2010

IIII 13 201L

3 2011 5. Lease Serial No.

)L	13	ZU	I	USA	SF	080

USA SF 080245
6. If Indian, Allottee or Tribe Name

abandoned well. Use Form 3160	(APD) for such proposals. Familigion field united			
SUBMIT IN TRIPLICATE - O	r instructions on page 2 7. If Unit or CA/Agree	eement, Name and/or N		
1. Type of Well Oil Well X Gas Well Other  2. Name of Operator	8. Well Name and No Federal. 29-9-2			
ENERGEN RESOURCES CORPORATION	9 API Well No	9 API Well No		
3a. Address	3b. Phone No. ( <i>include area code</i> ) 30–045–34995			
2010 Afton Place, Farmington, NM 87401 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	505-325-6800 10. Field and Pool, o	•		
2111' FSL, 1598' FWL, Sec.28, T29N,		a Coat		
NE/SW (K)	11. County or Parish	ı. State		
12,5,1 (14)	San Juan	NM		
12. CHECK APPROPRIATE BOX	S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DA			
TYPE OF SUBMISSION	TYPE OF ACTION	-		
Notice of Intent		Water Shut-Off Well Integrity		
X Subsequent Report		Other <u>production</u>		
Final Abandonment Notice	nge Plans Plug and Abandon Temporarily Abandon <u>cas</u>	ing		
BO	vert to Injection Plug Back Water Disposal			
determined that the final site is ready for final inspection.) 6/29/11 TD 2402'. PBID 2378'. Drill set at 2402' KB. Cement with 275 sks. flocele, tailed with 150 sks. Type G, down at 7:30 pm on 7/2/11. Pressure j	I be filed only after all requirements, including reclamation, have been completed as 5.50" hole to 2402'. Run 56 jts. 5.50" 15.5# J-55 LT 6.56/35 Poz with 6% gel, 2% CaCl2, 10#/sk gilsonite, sk gilsonite, 1/4#/sk of flocele (761 cf total). Pit before plug hit 1280 psi - increase pressure to 175 ld ok. Curculate .5 bbls cement to surface. WCC. No	6C casing, 1/4#/sk lugged 50 psi - held		
	JUL 1 4 2011  FARMINGTON FIELD OFFICE  BY  STATUTE OF THE STATE OF THE	ECEIVED 1. 2011  ENS. DIV. DIST. 3  L— LE 0E 61-81		
14. I hereby certify that the foregoing is true and correct Name ( <i>Printed/Typed</i> )		12.00		
Anna Stotts Signature	Title Regulatory Analyst	10900001 1200700		
Thurs 101	Date 7/5/11	<del></del>		
	FOR FEDERAL OR STATE OFFICE USE  Title Date	<u> </u>		
Approved by	Title			
Conditions of approval, if any, are attached Approval of this notice does the applicant holds legal or equitable title to those rights in the subject lear				

Title 18 U S C Section 1001, and Title 43 U.S C Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false,