District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

		Santa Fe, NIVI 8/303	to the appropriate NMO	CD District Office.
12769 45-06623	· ·	, Below-Grade Tank, or Method Permit or Closure l	Plan Application	RECEIVED By OCD 3-4-15
	Closure of a pit, b Modification to a	registration proposed alternative method pelow-grade tank, or proposed alternat n existing permit/or registration submitted for an existing permitted o		ow-grade tank,
	Instructions: Please submit one application	on (Form C-144) per individual pit, below	-grade tank or alternative	request
environment. Nor	hat approval of this request does not relieve the does approval relieve the operator of its respons			
	ington Resources			
	PO BOX 4289, Farmington, NM 87499			
5	name:Charles Et Al 1			
	004506623			
	J (NWSE) Section 12 Townsh	V		
523	sed Design: Latitude <u>36.58636000 N</u>		_ NAD: ⊠1927 ∐ 1983	
Surface Owner:	☐ Federal ☐ State ☐ Private ☒ Tribal Tru	ist or Indian Allotment		
2				
Pit: Subsec	ction F, G or J of 19.15.17.11 NMAC			
Temporary:	Drilling Workover	Closed Prior to	Closure Plan App	roval
Permanent	☐ Emergency ☐ Cavitation ☐ P&A ☐ M	ulti-Well Fluid Management I	Low Chloride Drilling Flui	d □ yes □ no
Lined U	nlined Liner type: Thicknessm	il □LLDPE□ HDPE□ PVC□ C	Other	
String-Reinf	orced			
Liner Seams:	Welded Factory Other	Volume:bl	ol Dimensions: L	« W x D
3. Relow-grade	e tank: Subsection I of 19.15.17.11 NMAC			
Volume:	120 bbl Type of fluid:			
	on material: Metal			
	containment with leak detection Visible s	sidewalls, liner, 6-inch lift and automatic of	overflow shut-off	
	ewalls and liner Visible sidewalls only			
	ckness <u>45</u> mil HI			
	200000			
Alternative Submittal of an	Method: exception request is required. Exceptions ma	ust be submitted to the Santa Fe Environm	nental Bureau office for cor	nsideration of approval.
5.	2 2	9281 V	2 2 3	
	ection D of 19.15.17.11 NMAC (Applies to pe			
Chain link, s institution or ch	six feet in height, two strands of barbed wire a wrch)	at top (Required if located within 1000 feet	of a permanent residence,	school, hospital,
The state of the s	ight, four strands of barbed wire evenly space	ed between one and four feet		

A

Alternate. Please specify_

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)			
☐ Screen ☐ Netting ☐ Other			
☐ Monthly inspections (If netting or screening is not physically feasible)			
7.			
Signs: Subsection C of 19.15.17.11 NMAC			
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers			
☐ Signed in compliance with 19.15.16.8 NMAC			
8.			
<u>Variances and Exceptions:</u> Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.			
Please check a box if one or more of the following is requested, if not leave blank:			
☐ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.			
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.			
9.			
Siting Criteria (regarding permitting): 19.15.17.10 NMAC	. **		
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accept material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	table source		
General siting			
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.	☐ Yes ☒ No		
- ☐ NM Office of the State Engineer - iWATERS database search; ☐ USGS; ☒ Data obtained from nearby wells	☐ NA ☐ Yes ☐ No		
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells			
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ Yes ☐ No		
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality			
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No		
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	☐ Yes ☐ No		
Society; Topographic map Within a 100-year floodplain. (Does not apply to below grade tanks)			
- FEMA map			
Below Grade Tanks			
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured	☐ Yes ☒ No		
from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site			
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.	☐ Yes ☒ No		
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site			
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)			
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)	☐ Yes ☐ No		
- Topographic map; Visual inspection (certification) of the proposed site			
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No		
 Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 			
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock	20000		
watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No		

Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Temporary Pit Non-low chloride drilling fluid						
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No					
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site						
Permanent Pit or Multi-Well Fluid Management Pit						
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No					
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site						
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:						
11. Mult: Wall Fluid Management Dit Cheekligt: Subsection D of 10 15 17 0 NMAC						
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:						
	- Tromosof Approved Society of accessing a secondary					

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the distached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	ocuments are			
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Fluid Management Pit Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method				
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC				
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC for guidance.				
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA			
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Yes Yes NA NA NA NA NA NA NA N				
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Yes NA				
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site				
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No			
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No			
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes \sum No				
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance				

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No			
ithin the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Yes No				
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological				
Society; Topographic map				
/ithin a 100-year floodplain. FEMA map Yes □ No				
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC				
17. Operator Application Certification:				
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and be	elief.			
Name (Print): Title:	<u> </u>			
Signature: Date:				
e-mail address: Telephone:				
18. OCD Approval: Permit Application (including closure plan) Closure Plan (enly) OCD Conditions (see attachment)				
OCD Representative Signature: Apr 24, 2015				
Title: Environmental Specialst OCD Permit Number:				
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed.				
☐ Closure Completion Date: 10/19/09				
20. Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-loop systems only) If different from approved plan, please explain.				
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please mark in the box, that the documents are attached. □ Proof of Closure Notice (surface owner and division) □ Proof of Deed Notice (required for on-site closure for private land only) □ Plot Plan (for on-site closures and temporary pits) □ Confirmation Sampling Analytical Results (if applicable) □ Waste Material Sampling Analytical Results (required for on-site closure) □ Disposal Facility Name and Permit Number □ Soil Backfilling and Cover Installation □ Re-vegetation Application Rates and Seeding Technique □ Site Reclamation (Photo Documentation)				
On-site Closure Location: Latitude Longitude NAD: 19	41 1703			

Page 5 of 6

22. Onerster Cleaner Cartification	
Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure	report is true accurate and complete to the heat of my knowledge and
belief. I also certify that the closure complies with all applicable closure requirer	
Name (Print): Kenny Davis	Title: Staff Regulatory Technician
Signature:	Date: <u>12/3/14</u>
e-mail address: kenny.r.davis@conocophillips.com	Telephone: 505-599-4045

Burlington Resources Oil Gas Company, LP San Juan Basin Below Grade Tank Closure Report

Lease Name: Charles Et Al 1

API No.: 3004506623

In accordance with Rule 19.15.17.13 NMAC the following information describes the closure of the below-grade tank referenced above. All proper documentation regarding closure activities is being included with the C-144.

General Plan:

- 1. BR shall close a below-grade tank within 60 days of cessation of operations per Subsection G.4 of 19.15.17.13 NMAC. This will include a) below-grade tanks that do not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC within five years, if not retrofitted to comply with Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC; b) an earlier date that the division requires because of imminent danger to fresh water, public health or the environment. For any closure, BR will file the C144 Closure Report as required.
- 2. The below-grade tank referenced above was permitted and closed within 60 days of cessation of the below-grade tanks operation.
- 3. BR shall remove liquids and sludge from a below-grade tank prior to implementing a closure method and shall dispose of the liquids and sludge in a division-approved facility. The facilities to be used will be Basin Disposal (Permit #NM-01-005), JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B) and Envirotech Land Farm (Permit #NM-01-011). The liner after being cleaned well (Subsection D, Paragraph 1, Subparagraph (m) of 19.15.9.712 NMAC) will be disposed of at the San Juan County Regional Landfill located on CR 3100.

All recovered liquids were disposed of at Basin Disposal (Permit #NM-01-005) and any sludge or soil required to be removed to facilitate closure was hauled to Envirotech Land Farm (Permit #NM-01-011) and JFJ Landfarm % IEI (Permit #NM-01-0010B). The liner was cleaned per Subsection D, Paragraph 1, Subparagraph (m) of 19.15.9.712 NMAC was disposed of at the San Juan County Regional Landfill located on CR 3100.

4. BR Will receive prior approval to remove the below-grade tank and dispose of it in a division-approved facility or recycle, reuse, or reclaim it in a manner that the appropriate division district office approves.

The below-grade tank was disposed of in a division-approved manner.

5. If there is any on-site equipment associated with a below-grade tank, then BR shall remove the equipment, unless the equipment is required for some other purpose.

All on-site equipment associated with the below-grade tank was removed.

6. BR will test the soils beneath the below-grade tank to determine whether a release has occurred. COPC shall collect, at a minimum, a five point, composite sample; collect individual grab samples from any area that is wet, discolored or showing other evidence of a release; and analyzed for the constituents listed in Table I of 19.15.17.13 NMAC. COPC shall notify the division of its results on form C-141.



7. A five point composite sample was taken of the below-grade tank using sampling tools and all samples tested per Subsection B of 19.15.17.1 3(B)(1)(b). (Sample results attached).

Components	Tests Method	Limit (mg/kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	100
Chlorides	EPA 300.1	250

8. If BR or the division determines that a release has occurred, then BR shall comply with 19.15.3.116 NMAC and 19.15.1.19 NMAC, as appropriate.

A release was not determined for the above referenced well.

9. If the sampling program demonstrates that a release has not occurred or that any release does not exceed the concentrations specified in Table I of 19.15.17.13 NMAC, then BR shall backfill the excavation with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover; recontour and re-vegetate the site

The below-grade tank area passed all requirements of Paragraph (4) of Subsection E of 19.15.17.13 NMAC and was backfilled with compacted, non-waste containing, earthen material.

- 10. Notice of Closure will be given prior to closure to the Aztec Division office between 72 hours and one week via email or verbally. The notification of closure will include the following:
 - i. Operator's name
 - ii. Location by Unit Letter, Section, Township, and Range. Well name and API number.

Notification is missing due to employee turnovers. ConocoPhillips has reviewed our internal processes and has updated them to include the required 72 hour notification.

11. The surface owner shall be notified of BR's closing of the below-grade tank 72 hours, but not more than one week, prior to closure as per the approved closure plan via certified mail, return receipt requested.

The closure process notification to the landowner not found. COPC was not aware that the original notification sent at the time of Permitting was not the only closure notification required.

ConocoPhillips has reviewed our internal processes and has updated them to include the required 72 hour notification.

12. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.

The below-grade tank area was re-contoured to match fit, shape, line, form and texture of the surrounding area. Re-shaping, including drainage control, to prevent ponding and erosion. Natural drainages were unimpeded and water bars and/or silt traps were placed in areas where needed to prevent erosion on a large scale. Final recontour has a uniform appearance with smooth surface, fitting the natural landscape.

13. BR Shall seed the disturbed areas the first favorable growing season following closure of a below-grade tank. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved

methods. BLM stipulated seed mixes will used on federally regulated lands and division-approved seed mixtures (administratively approved if required) will be utilized on all State or private lands. A uniform vegetative cover has been established that reflects a life-form ratio of plus or minus fifty percent (50%) of pre- disturbance levels and a total percent plant cover of at least seventy percent (70%) of pre-disturbance levels, excluding noxious weeds. If alternate seed mix is required by the state, private owner or tribe, it will be implemented with administrative approval if needed. COPC will repeat seeding or planting will be continued until successful vegetative growth occurs.

Provision 13 was accomplished through complying with BLM seeding requirements as allowed by the BLM/OCD MOU.

14. A minimum of four feet of cover shall be achieved and the cover shall include one foot of suitable material, with chloride concentrations less than 600 mg/kg as analyzed by EPA Method 300.0, to establish vegetation at the site, or the background thickness of topsoil, whichever is greater.

The below-grade tank area was backfilled and more than four feet of cover was achieved and the cover included one foot of suitable material to establish vegetation at the site.

- 15. All closure activities will include proper documentation and be available for review upon request and will be submitted to OCD within 60 days of closure of the below-grade tank. Closure report will be filed on C-144 and incorporate the following:
 - Soil Backfilling and Cover Installation (See Report)
 - Re-vegetation application rates and seeding techniques (See Report)
 - Photo documentation of the site reclamation (Included as an attachment)
 - Confirmation Sampling Results (Included as an attachment)
 - Proof of closure notice (Included as an attachment)

Closure Documentation was not submitted within the 60 day requirement due to employee turnovers. ConocoPhillips has reviewed our internal processes and has updated them to ensure closure documentation is submitted with the 60 day time frame.



November 18, 2009

Project No. 92115-1129

Ms. Kelsi Gurvitz Conoco Phillips 3401 E 30th St. Farmington, NM 87401

Phone: (505) 320-2461 Fax: (505) 599-4005

RE: BELOW GRADE TANK CLOSURE DOCUMENTATION CHARLES ET AL #001, SAN JUAN COUNTY, NEW MEXICO

Dear Ms. Gurvitz,

Enclosed please find the field notes and analytical results for below-grade tank (BGT) closure activities performed at the Charles Et Al #001 well site located in Section 12, Township 27N, Range 9W, San Juan County, New Mexico. One (1) five (5)-point composite sample was collected from below the BGT and analyzed in the field for total petroleum hydrocarbons (TPH) using USEPA Method 418.1, for organic vapors using a Photo Ionization Detector (PID), and for chlorides. The sample returned results below the regulatory limits of 100 ppm TPH, 100 ppm organic vapors (OV), and 250 ppm chlorides. Additionally, the five (5)-point composite sample was collected into a four (4)-ounce glass jar, capped headspace free and transported on ice under chain of custody to Envirotech's laboratory to be analyzed for benzene, toluene, ethyl-benzene and total xylenes (BTEX) using USEPA Method 8021 and for total chlorides using USEPA Method 4500B. The sample returned results below the regulatory limits of 0.2 ppm benzene, 50 ppm BTEX, and 250 ppm total chlorides. These results confirmed a release had not occurred; therefore no excavation was required. Envirotech, Inc. recommends no further action in regards to this incident.

We appreciate the opportunity to be of service. If you have any questions or require additional information, please contact our office at (505) 632-0615.

Respectfully Submitted, ENVIROTECH, INC.

Rene Garcia Reyes Environmental Technician

rgarcia@envirotech-inc.com

Enclosures: Field Notes

Analytical Results

Cc: Client File No. 92115

PAGE NO:
TEMP PIT: PERMANENT PIT: BGT:
DECATION: NAME:
LEGAL ADD: UNIT: SEC: /7 TWP: 27 N RNG: 9 W PM:
ST:
EXCAVATION APPROX: FT. X FT. X FT. DEEP CUBIC YARDAGE: DISPOSAL FACILITY: REMEDIATION METHOD: LAND OWNER: API:30-095-06623 BGT / PIT VOLUME: CONSTRUCTION MATERIAL: DOUBLE-WALLED, WITH LEAK DETECTION: LOCATION APPROXIMATELY: FT. FROM WELLHEAD DEPTH TO GROUNDWATER: TEMPORARY PIT - GROUNDWATER 50-100 FEET DEEP BENZENE < 0.2 mg/kg, BTEX < 50 mg/kg, GRO & DRO FRACTION (8015) < 500 mg/kg, TPH (418.1) < 2500 mg/kg, CHLORIDES < 500 mg/kg TEMPORARY PIT - GROUNDWATER > 100 FEET DEEP BENZENE < 0.2 mg/kg, BTEX < 50 mg/kg, GRO & DRO FRACTION (8015) < 500 mg/kg, TPH (418.1) < 2500 mg/kg, CHLORIDES < 1000 mg/kg PERMANENT PIT OR BGT BENZENE < 0.2 mg/kg, BTEX < 50 mg/kg, TPH (418.1) < 100 mg/kg, CHLORIDES < 250 mg/kg FIELD 418,1 ANALYSIS TIME SAMPLE 1D. LAB NO. WEIGHT (g mL FREON DILUTION READING CALC. (mg/kg) 1/15 50 200 STD 260 1/2 5/0 5pi (sym) 1 9 20 STD 260 1/3 3 4 5 5 6 5 6 6 6 7 5 6 6 7 5 6 7 6 7 6 7 6
DISPOSAL FACILITY: REMEDIATION METHOD: API:30→045-06623 BGT/PIT VOLUME: CONSTRUCTION MATERIAL: DOUBLE-WALLED, WITH LEAK DETECTION: LOCATION APPROXIMATELY: FT. FROM WELLHEAD DEPTH TO GROUNDWATER: TEMPORARY PIT - GROUNDWATER 50-100 FEET DEEP BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, GRO & DRO FRACTION (8015) ≤ 500 mg/kg, TPH (418.1) ≤ 2500 mg/kg, CHLORIDES ≤ 500 mg/kg TEMPORARY PIT - GROUNDWATER ≥100 FEET DEEP BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, GRO & DRO FRACTION (8015) ≤ 500 mg/kg, TPH (418.1) ≤ 2500 mg/kg, CHLORIDES ≤ 1000 mg/kg PERMANENT PIT OR BGT BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, TPH (418.1) ≤ 100 mg/kg, CHLORIDES ≤ 250 mg/kg FEELD 418.1 ANALYSIS TIME SAMPLE ID. LAB NO. WEIGHT (g) mL FREON DILUTION READING CALC. (mg/kg) 1/2 50 200 STD - 260 1/2 50 200 STD - 260 1/3 50 300 STD - 260 1/4 4 4 5 5 6 500 STD - 260 1/5 50 500
LAND OWNER: API:30 -04 5 - 0 66 2 3 BGT / PIT VOLUME; CONSTRUCTION MATERIAL: DOUBLE-WALLED, WITH LEAK DETECTION: LOCATION APPROXIMATELY: FT. FROM WELLHEAD DEPTH TO GROUNDWATER: TEMPORARY PIT - GROUNDWATER 50-100 FEET DEEP BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, GRO & DRO FRACTION (8015) ≤ 500 mg/kg, TPH (418.1) ≤ 2500 mg/kg, CHLORIDES ≤ 500 mg/kg TEMPORARY PIT - GROUNDWATER ≥100 FEET DEEP BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, GRO & DRO FRACTION (8015) ≤ 500 mg/kg, TPH (418.1) ≤ 2500 mg/kg, CHLORIDES ≤ 1000 mg/kg PERMANENT PIT OR BGT BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, TPH (418.1) ≤ 100 mg/kg, CHLORIDES ≤ 250 mg/kg FELD 418.1 ANALYSIS TIME SAMPLE ID. LAB NO. WEIGHT (g) mL FREON DILUTION READING CALC. (mg/kg) 1
CONSTRUCTION MATERIAL: DOUBLE-WALLED, WITH LEAK DETECTION: LOCATION APPROXIMATELY: FT. FROM WELLHEAD DEPTH TO GROUNDWATER: TEMPORARY PIT - GROUNDWATER 50-100 FEET DEEP BENZENE \(\leq 0.2 \) mg/kg, BTEX \(\leq 50 \) mg/kg, GRO & DRO FRACTION (8015) \(\leq 500 \) mg/kg, TPH (418.1) \(\leq 2500 \) mg/kg, CHLORIDES \(\leq 500 \) mg/kg TEMPORARY PIT - GROUNDWATER \(\leq 100 \) FEET DEEP BENZENE \(\leq 0.2 \) mg/kg, BTEX \(\leq 50 \) mg/kg, GRO & DRO FRACTION (8015) \(\leq 500 \) mg/kg, TPH (418.1) \(\leq 2500 \) mg/kg, CHLORIDES \(\leq 1000 \) mg/kg PERMANENT PIT OR BGT BENZENE \(\leq 0.2 \) mg/kg, BTEX \(\leq 50 \) mg/kg, TPH (418.1) \(\leq 100 \) mg/kg, CHLORIDES \(\leq 250 \) mg/kg FIELD 418.1 ANALYSIS TIME SAMPLE ID LAB NO WEIGHT (g mL FREON DILUTION READING CALC (mg/kg) // \(\leq \leq 50 \) 200 STD
LOCATION APPROXIMATELY: FT. FROM WELLHEAD DEPTH TO GROUNDWATER: TEMPORARY PIT - GROUNDWATER 50-100 FEET DEEP BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, GRO & DRO FRACTION (8015) ≤ 500 mg/kg, TPH (418.1) ≤ 2500 mg/kg, CHLORIDES ≤ 500 mg/kg TEMPORARY PIT - GROUNDWATER ≥100 FEET DEEP BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, GRO & DRO FRACTION (8015) ≤ 500 mg/kg, TPH (418.1) ≤ 2500 mg/kg, CHLORIDES ≤ 1000 mg/kg PERMANENT PIT OR BGT BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, TPH (418.1) ≤ 100 mg/kg, CHLORIDES ≤ 250 mg/kg FIELD 418.1 ANALYSIS TIME SAMPLE I.D. LAB NO. WEIGHT (g) mL FREON DILUTION READING CALC. (mg/kg) // 5 50 200 STD -
TEMPORARY PIT - GROUNDWATER 50-100 FEET DEEP
TEMPORARY PIT - GROUNDWATER 50-100 FEET DEEP BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, GRO & DRO FRACTION (8015) ≤ 500 mg/kg, TPH (418.1) ≤ 2500 mg/kg, CHLORIDES ≤ 500 mg/kg TEMPORARY PIT - GROUNDWATER ≥100 FEET DEEP BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, GRO & DRO FRACTION (8015) ≤ 500 mg/kg, TPH (418.1) ≤ 2500 mg/kg, CHLORIDES ≤ 1000 mg/kg PERMANENT PIT OR BGT BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, TPH (418.1) ≤ 100 mg/kg, CHLORIDES ≤ 250 mg/kg FELD 418.1 ANALYSIS TIME SAMPLE I.D. LAB NO. WEIGHT (g) mL FREON DILUTION READING CALC. (mg/kg) 1/5 50
BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, GRO & DRO FRACTION (8015) ≤ 500 mg/kg, TPH (418.1) ≤ 2500 mg/kg, CHLORIDES ≤ 500 mg/kg TEMPORARY PIT - GROUNDWATER ≥100 FEBT DEEP BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, GRO & DRO FRACTION (8015) ≤ 500 mg/kg, TPH (418.1) ≤ 2500 mg/kg, CHLORIDES ≤ 1000 mg/kg PERMANENT PIT OR BGT BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, TPH (418.1) ≤ 100 mg/kg, CHLORIDES ≤ 250 mg/kg FELD 418.1 ANALYSIS TIME SAMPLE 1D. LAB NO. WEIGHT (g) mL FREON DILUTION READING CALC. (mg/kg) 1
TEMPORARY PIT - GROUNDWATER ≥100 FEET DEEP BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, GRO & DRO FRACTION (8015) ≤ 500 mg/kg, TPH (418.1) ≤ 2500 mg/kg, CHLORIDES ≤ 1000 mg/kg PERMANENT PIT OR BGT BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, TPH (418.1) ≤ 100 mg/kg, CHLORIDES ≤ 250 mg/kg FELD 418,1 ANALYSIS TIME SAMPLE ID. LAB NO. WEIGHT (g) mL FREON DILUTION READING CALC. (mg/kg) // 5 50 200 STD Z60 // 7 7 0 5 pt (544) 1 5 20 × 4 5 20 3 4 5 50 4 5 6 5 6 6
BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, GRO & DRO FRACTION (8015) ≤ 500 mg/kg, TPH (418.1) ≤ 2500 mg/kg, CHLORIDES ≤ 1000 mg/kg PERMANENT PIT OR BGT BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, TPH (418.1) ≤ 100 mg/kg, CHLORIDES ≤ 250 mg/kg FIELD 418.1 ANALYSIS TIME SAMPLE I.D. LAB NO. WEIGHT (g mL FREON DILUTION READING CALC. (mg/kg)
BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, GRO & DRO FRACTION (8015) ≤ 500 mg/kg, TPH (418.1) ≤ 2500 mg/kg, CHLORIDES ≤ 1000 mg/kg PERMANENT PIT OR BGT BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, TPH (418.1) ≤ 100 mg/kg, CHLORIDES ≤ 250 mg/kg FIELD 418.1 ANALYSIS TIME SAMPLE I.D. LAB NO. WEIGHT (g mL FREON DILUTION READING CALC. (mg/kg)
PERMANENT PIT OR BGT BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, TPH (418.1) ≤ 100 mg/kg, CHLORIDES ≤ 250 mg/kg FIELD 418,1 ANALYSIS TIME SAMPLE ID. LAB NO. WEIGHT (g mL FREON DILUTION READING CALC. (mg/kg) // 5 50 200 STD - - - Z40 // 7 7 / 0 5 pi (3144) 1 3 20 3 4 5 20 4
BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/kg, TPH (418.1) ≤ 100 mg/kg, CHLORIDES ≤ 250 mg/kg FIELD 418.1 ANALYSIS TIME SAMPLE I.D. LAB NO. WEIGHT (g) mL FREON DILUTION READING CALC. (mg/kg) // 5 50 200 STD - - - - - - - // 5 50 200 STD - - - - - - - // 5 50 200 STD 2 - - - - - - - - // 5 50 2 00 STD 2 - - - - - - - - // 5 50 2 00 STD 3 - - - - - - - - // 5 50 2 00 STD 2 - - - - - - - // 5 50 2 00 STD 3 - - - - - - - // 5 50 2 00 STD 3 - - - - - - - // 5 50 2 00 STD 3 - - - - - - // 5 50 2 00 STD 3 - - - - - // 5 50 2 00 STD 4 5 5 5 // 5 50 5 0 STD 5 5 5 5 // 5 50 5 0 STD 5 5 5 // 5 50 5 0 STD 5 5 5 // 5 50 5 0 STD 5 5 5 // 5 50 5 0 STD 5 5 // 5 50 5 0 STD 5 5 // 5 50 5 0 STD 5
TIME SAMPLE ID. LAB NO. WEIGHT (g mL FREON DILUTION READING CALC. (mg/kg) 1/5 50 200 STD - - - 260
TIME SAMPLE ID. LAB NO. WEIGHT (g) mL FREON DILUTION READING CALC. (mg/kg) // 5 50
1/5 50 200 STD 260 17 = 10 50 (Stal) 1 5 20 × 4 5 20 1
17=10 505 (stup) 1 5 20 × 4 5 20 3 3 5 5 6
2 3 4 5 6
3 4 5 6
4 5 6
6
PERIMETER FIELD CHI ODIDES RESULTS PROFILE
SAMPLE READING CALC. 16'
ID (mg/kg)
SNIMUN Ook
(BUT)
CVM PRO RESULTS
SAMPLE ID RESULTS
SAMPLE ID RESULTS (ppm)
SAMPLE ID RESULTS (ppm) Spi comp X samples points
SAMPLE ID RESULTS (ppm) Spi (ppm) X So up (op point) LAB SAMPLES NOTES:
SAMPLE ID RESULTS (ppm) Spi comp X samples points
LAB SAMPLES NOTES: SAMPLE ID RESULTS (ppm) X So wp (cp point) BENZENE BTEX
LAB SAMPLES NOTES: SAMPLE ID RESULTS (ppm) X Sample points BENZENE BTEX GRO & DRO
SAMPLE ID RESULTS (ppm) Spi (ppm) Spi (ppm) X So wplow points EAB SAMPLES NOTES: SAMPLE ID ANALYSIS RESULTS BENZENE BTEX



EPA METHOD 418.1 TOTAL PETROLEUM **HYDROCARBONS**

Client:

Burlington Resources

Sample No.:

Sample ID:

5 point Comp

Sample Matrix:

Soil

Preservative: Condition:

Cool

Cool and Intact

Project #:

92115-1129

Date Reported:

10/28/2009

Date Sampled:

10/19/2009

Date Analyzed:

10/19/2009

Analysis Needed: TPH-418.1

700		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons

20

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis

of Water and Waste, USEPA Storet No. 4551, 1978.

Comments:

Charles Et Al #001

Instrument calibrated to 200 ppm standard. Zeroed before each sample

Analyst

Review

Rene Garcia Reyes

Printed

James McDaniel

Printed



CONTINUOUS CALIBRATION EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Cal	Date:

19-Oct-09

Parameter	Standard Concentration mg/L	Concentration Reading mg/L	i i
ТРН	100		
IFN	200	200	
	500	200	
	1000		

The accepted percent relative deviation (%RSD) of the calibration factor is less than 20% over the working range.

X Sta	10/28/09
Analyst	Date
Rene Garcia Reyes	
Print Name	10/28/09 Date
James McDaniel	Date

Print Name



Field Chloride

Client:

Burlington

Sample No.:

1

Sample ID:

BGT Comp

Sample Matrix:

Soil

Preservative:

Cool

Condition:

Cool and Intact

Project #:

92115-1129

Date Reported:

10/28/2009

Date Sampled: Date Analyzed: 10/19/2009

Date Allalyzed.

10/19/2009

Analysis Needed:

Chloride

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Field Chloride

ND

27.0

ND = Parameter not detected at the stated detection limit.

References:

"Standard Methods for the Examination of Water and Wastewater", 18th ed., 1992

Hach Company Quantab Titrators for Chloride

Comments:

Charles Et Al #001

Analyst

Rene Garcia Reyes

Printed

Heriem

James McDaniel

Printed



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client: Sample ID: Laboratory Number: Chain of Custody:	Burlington 5pt Comp 52173 8231	Project #: Date Reported: Date Sampled: Date Received:	92115-1129 10-25-09 10-19-09 10-19-09 10-21-09
Sample Matrix: Preservative: Condition:	Soil Cool Intact	Date Analyzed: Date Extracted: Analysis Requested:	10-21-09 10-20-09 BTEX
Condition.	made		

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	ND	0.9
Toluene	ND	1.0
Ethylbenzene	ND	1.0
p,m-Xylene	ND	1.2
o-Xylene	ND	0.9
Total BTEX	ND	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	99.0 %
	1,4-difluorobenzene	99.0 %
	Bromochlorobenzene	99.0 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Charles Et. Al. #1.

Analyst

Ahrestin on Weetles
Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	N/A	Project #: Date Reported:	N/A 10-25-09
Sample ID:	10-21-BT QA/QC	이번 보겠다면 하시다 하시는 맛이 있었다.	*.**
Laboratory Number:	52161	Date Sampled:	N/A
Sample Matrix:	Soil	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	10-21-09
Condition:	N/A	Analysis:	BTEX

Calibration and Detection Limits (ug/L)	I Cal RF	G-Gal RF: Accept. Rang	%Diff 19.0 - 15%	Blank Conc	Detect. Limit
	2 750 45 4 205	8.7760E+005	0.2%	ND	0.1
Benzene	8.7584E+005			ND	0.1
Toluene	8.0092E+005	8.0253E+005	0.2%		7.5
Ethylbenzene	7.2781E+005	7,2927E+005	0.2%	ND	0.1
p,m-Xylene	1.7982E+006	1.8018E+006	0.2%	ND	0.1
o-Xylene	6.8304E+005	6.8441E+005	0.2%	ND	0.1

Duplicate Conc. (ug/Kg)	Sample	Duplicate	%Diff.	Accept Range	Detect, Limit
Benzene	6.1	6.0	1.6%	0 - 30%	0.9
Toluene	24.2	23.8	1.7%	0 - 30%	1.0
Ethylbenzene	21.8	21.7	0.5%	0 - 30%	1.0
p,m-Xylene	69.5	68.2	1.9%	0 - 30%	1.2
o-Xylene	26.3	26.0	1.1%	0 - 30%	0.9

Spike Conc. (ug/Kg)	Sample	Amount Spiked	Spiked Sample	% Recovery	Accept Range
Benzene	6.1	50.0	57.3	102%	39 - 150
Toluene	24.2	50.0	75.2	101%	46 - 148
Ethylbenzene	21.8	50.0	72.8	101%	32 - 160
p,m-Xylene	69.5	100	168	99.1%	46 - 148
o-Xylene	26.3	50.0	78.8	103%	46 - 148

ND - Parameter not detected at the stated detection limit.

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using

Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments:

QA/QC for Samples 52110, 52161- 52164, 52173, and 52180 - 52183.

Analyst



Chloride

Client: Sample ID: Lab ID#:

Sample Matrix:

Preservative:

Condition:

Burlington 5pt Comp 52173 Soil

Cool

Intact

Date Reported: Date Sampled: Date Received: Date Analyzed: Chain of Custody:

Project #:

10-26-09 10-19-09 10-19-09 10-26-09 8231

92115-1129

Parameter

Concentration (mg/Kg)

Total Chloride

33

Reference:

U.S.E.P.A., 4500B, "Methods for Chemical Analysis of Water and Wastes", 1983. Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments:

Charles Et Al #1

CHAIN OF CUSTODY RECORD

Project Name / Location: ANALYSIS / PARAMETERS	7	25 de (havies El Ah II	Sampler Name:	(Certice (Coac) 100 100 100 100 100 100 100 100 100 10	ne No.: (Methoday Nethoday Net	Sample Sample No.Volume Preservative H TX OC PA TECT COLD TO NO. No. OC PRESERVATIVE TO COLD TO TAKE T	Date Time Matrix Containers Wolf Roll Time > CT Co. L. T. C.	10/19/69 11:30 52/73 Solid Aqueous 452 X X			Soil Studge Solid Aqueous		Soil Sludge Soild Aqueous	Soil Sludge	Sindge	Solid Aqueous Time Received by: (Signature)	A C. 1/2 1/2 14:15	4	hed by: (Signature)	envirotech Analytical taboratory
	Cilent:	Burtanste	Client Address: /		Client Phone No.:	Sample No./	Identification		المراجعة الم								Relinquished by: (Signature)	Relinquished by: (Signature)	Relinquished by: (Signature)	

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Form C-141 Revised October 10, 2003

Submit 2 Copies to appropriate District Office in accordance with Rule 116 on back side of form

Release Notification and Corrective Action OPERATOR ☐ Initial Report Final Report Contact Kenny Davis Name of Company Burlington Resources Address 3401 East 30th St, Farmington, NM Telephone No.(505) 599-4045 Facility Name: Charles Et Al 1 Facility Type: Gas Well Mineral Owner Tribal Lease No. I-149-IND-8465 Surface Owner Federal LOCATION OF RELEASE Unit Letter Section Township Range Feet from the North/South Line Feet from the East/West Line County 1450 V J 12 / 27N 9W 1450 🗸 South V East V San Juan Latitude36.58636000 / Longitude-107.73525000 / NATURE OF RELEASE Type of Release BGT Closure Summary Volume of Release N/A Volume Recovered N/A Source of Release: NONE Date and Hour of Occurrence N/A Date and Hour of Discovery N/A Was Immediate Notice Given? If YES, To Whom? ☐ Yes ☐ No ☒ Not Required N/A By Whom? N/A Date and Hour N/A Was a Watercourse Reached? If YES, Volume Impacting the Watercourse. ☐ Yes ☒ No N/A N/A If a Watercourse was Impacted, Describe Fully.* N/A Describe Cause of Problem and Remedial Action Taken.* N/A Describe Area Affected and Cleanup Action Taken.* BGT Closure: NO RELEASE FOUND UPON REMOVAL I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations. OIL CONSERVATION DIVISION Signature: Approved by District Supervisor: Printed Name: Kenny Davis **Expiration Date:** Approval Date: Title: Staff Regulatory Technician E-mail Address: Kenny.r.davis@conocophillips.com Conditions of Approval: Attached

Date: 12/10/14 Phone: (505) 599-4045

* Attach Additional Sheets If Necessary





