District I 1625 N. French Dr., Hobbs, NM 88240 District II
811 S. First St., Artesia, NM 88210
District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit Relow-Grade Tank or

Santa Fe, NM 87505

Proposed Alternative Method Permit or (
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or propo Modification to an existing permit/or registration	od od By Rvillalobos at 9:37 am, Dec 30, 2015 osed alternative method
Instructions: Please submit one application (Form C-144) per individu	
Please be advised that approval of this request does not relieve the operator of liability should oper environment. Nor does approval relieve the operator of its responsibility to comply with any other	
I. Operator:ConocoPhillips CompanyOGRID #:217817 Address:PO BOX 4289, Farmington, NM 87499 Facility or well name: _BLANCO WASH FEDERAL 1 (Tank 2) API Number:30-045-07099OCD Permit Number:UL or Qtr/QtrNSection26Township28NRange9W Center of Proposed Design: Latitude36.628172 aNLongitude107.761258 aW Surface Owner:FederalStatePrivateTribal Trust or Indian Allotment	County: San Juan BGT Closed Prior
2.	, ipp. oran
□ Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: □ Drilling □ Workover □ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Managemen □ Lined □ Unlined Liner type: Thickness mil □ LLDPE □ HDPE □ PV □ String-Reinforced Liner Seams: □ Welded □ Factory □ Other	C Other
3. ☐ Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: Max 120 bbl Type of fluid: Produced Water	This location has two Below Grade Tanks. This report is for Tank 2.
Tank Construction material: Metal	
□ Secondary containment with leak detection □ Visible sidewalls, liner, 6-inch lift ar □ Visible sidewalls and liner □ Visible sidewalls only □ Other □ Liner type: Thicknessmil □ HDPE □ PVC ☒ Other	nd automatic overflow shut-off
4. Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa	a Fe Environmental Bureau office for consideration of approval.
5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits. Chain link, six feet in height, two strands of barbed wire at top (Required if located wiinstitution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	ithin 1000 feet of a permanent residence, school, hospital,

Serious Netting Other	6.	
Monthly inspections (If netting or screening is not physically feasible)	Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Tark 247 2" Intering, providing Operator's name, site location, and emergency telephone numbers	☐ Screen ☐ Netting ☐ Other	
Signed in compliance with 19.15.16.8 NMAC Ta's 24°, 2" lettering, providing Operator's name, site location, and emergency telephone numbers	☐ Monthly inspections (If netting or screening is not physically feasible)	
Signed in compliance with 19.15.16.8 NMAC Ta's 24°, 2" lettering, providing Operator's name, site location, and emergency telephone numbers	7	
Disp's 24", 2" lettering, providing. Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC Variances and Exceptions: Dustifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a back join or mare of the following is requested, if not leave blank: Carpitolon(5): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Exception(5): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Exception(6): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Siting Criterin (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each string criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.		
Signed in compliance with 19.15.16.8 NMAC		
Variances and Exceptions:		
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NNAC for guidance. Pleme check to bot flow or more of the following is requested, if not tense blank: Straception(s): Requests must be submitted to the appropriate division district for consideration of approval. Straception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Straception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Straception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Straception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Straception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Straception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Straception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Straception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration. Recommendations of acceptable source material approval can be submitted to the Santa Fe Environmental Bureau of Bureau of Santa Fe Environmental Bureau of Bureau	Signed in compniance with 19.15.16.8 NMAC	
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NNAC for guidance. Pleme check to bot flow or more of the following is requested, if not tense blank: Straception(s): Requests must be submitted to the appropriate division district for consideration of approval. Straception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Straception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Straception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Straception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Straception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Straception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Straception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Straception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration. Recommendations of acceptable source material approval can be submitted to the Santa Fe Environmental Bureau of Bureau of Santa Fe Environmental Bureau of Bureau	8.	
Please check a box if one or more of the following is requested. If not feave blanks:		
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks. General siting Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. Yes No	Please check a box if one or more of the following is requested, if not leave blank:	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks. General siting Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tanks. Yes No NM Office of the State Engineer - itwATERS database search; USGS; Data obtained from nearby wells NA Yes NO NM Office of the State Engineer - itwATERS database search; USGS; Data obtained from nearby wells Yes No NM Office of the State Engineer - itwATERS database search; USGS; Data obtained from nearby wells Yes No NM Office of the State Engineer - itwATERS database search; USGS; Data obtained from nearby wells Yes No NM Office of the State Engineer - itwATERS database search; USGS; Data obtained from nearby wells Yes No NM Office of the State Engineer - itwATERS database search; USGS; Data obtained from nearby wells Yes No NM Office of the State Engineer - itwATERS database search; USGS; Data obtained from nearby wells Yes No Written confirmation or verification from the municipality. Written approval obtained from the municipality Yes No Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Yes No Yes No Society, Topographic map Written and Indiana Yes No Yes Yes No Yes No Yes No Yes No Yes No Yes		
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant unate demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks. General siting Ground water is less than 25 feet below the hottom of a low chloride temporary pit or below-grade tank. Yes No NA No Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Yes No NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Yes No NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Yes No NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Yes No NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Yes No NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Yes No Yes No Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978; Section 3-27-3, as amended. (Does not apply to below grade tanks) Yes No Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Yes No Yes No Society; Topographic map Within a Uno-year floodplain. (Does not apply to below grade tanks) Yes No	Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant unate demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks. General siting Ground water is less than 25 feet below the hottom of a low chloride temporary pit or below-grade tank. Yes No NA No Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Yes No NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Yes No NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Yes No NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Yes No NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Yes No NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Yes No Yes No Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978; Section 3-27-3, as amended. (Does not apply to below grade tanks) Yes No Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Yes No Yes No Society; Topographic map Within a Uno-year floodplain. (Does not apply to below grade tanks) Yes No		
Ceneral siting Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tanks. Yes No NA NO NA NO NO NA NA	Siting Criteria (regarding permitting): 19.15.17.10 NMAC	
General siting Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. NM Office of the State Engineer - IWATERS database search; USGS; Data obtained from nearby wells NA NA NA NA NA NO flice of the State Engineer - IWATERS database search; USGS; Data obtained from nearby wells NA NA NO flice of the State Engineer - IWATERS database search; USGS; Data obtained from nearby wells NA NA NO flice of the State Engineer - IWATERS database search; USGS; Data obtained from nearby wells NA NA NO flice of the State Engineer - IWATERS database search; USGS; Data obtained from nearby wells NA NA NA NA NO flice of the State Engineer - IWATERS database search; USGS; Data obtained from nearby wells NA		otable source
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Vest No No No No No No No N	material are provided below. Sitting criteria does not apply to drying pads of above-grade tanks.	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Vest No No No No No No No N	General siting	
Graund water is less than 50 feet below the hottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Within an unstable area. (Does not apply to below grade tanks) Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map. Within a 100-year floodplain. (Does not apply to below grade tanks) FEMA map Below Grade Tanks Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.	Concrat Stang	
Cround water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Witten confirmation or verification from the municipality; Written approval obtained from the municipality Witten confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map Within a 100-year floodplain. (Does not apply to below grade tanks) FEMA map Below Grade Tanks Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Yes	Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. Within 300 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.	- MM Office of the State Engineer - TWATERS database search, _ OSOS, _ Data obtained from hearby wens	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society, Topographic map Within a 100-year floodplain. (Does not apply to below grade tanks) - FEEMA map Below Grade Tanks Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for d		
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map Within a 100-year floodplain. (Does not apply to below grade tanks) FEMA map Below Grade Tanks Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; NM Office of the State Engineer - iWATERS database scarch; Visual inspection (certification) of the proposed site Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well used by less than five households for domestic or stock watering purpos	NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	
Written confirmation or verification from the municipality; Written approval obtained from the municipality Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map Below Grade Tanks Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark) Topographic map; Visual inspection (certification) of the proposed site Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well used by less than five households for domes		☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map Within a 100-year floodplain. (Does not apply to below grade tanks) FEMA map Below Grade Tanks Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300fect of any other fresh water well or spring, in existence at the time of the initial application.	adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)	V
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map Below Grade Tanks Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300 feet of any other fresh water well used by less than five households for domestic or stock watering purposes, or 300 feet of any other fresh water well used by less than five households for domestic or stock watering purposes, or 300 feet of any other fresh water well used by less than five households for domestic or stock watering purposes, or 300 feet of any other fresh water well used by less than five households for domestic or stock watering purposes, or 300 feet o	- Written confirmation or verification from the municipality; written approval obtained from the municipality	
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map Below Grade Tanks Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark) Topographic map; Visual inspection (certification) of the proposed site Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300fect of any other fresh water well used by less than five households for domestic or stock watering purposes, or 300fect of any other fresh water well used by less than five households for domestic or stock watering purposes, or 300fect of any other fresh water well used by less than five households for domestic or stock watering purposes, or 300fect of any other fresh water well or spring, in existence at the time of the initial application.		☐ Yes ☐ No
- Engineering measures incorporated into the design; NM Burcau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image		
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map Below Grade Tanks Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark) Topographic map; Visual inspection (certification) of the proposed site Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. No		☐ Yes ☐ No
Below Grade Tanks Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. ¬ Visual inspection (certification) of the proposed site; Aerial photo; Satellite image		
Below Grade Tanks Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300fect of any other fresh water well or spring, in existence at the time of the initial application. ¬ Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Within a 100-year floodplain. (Does not apply to below grade tanks)	☐ Yes ☐ No
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. No		
From the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. Yes \Boxed No	Below Grade Tanks	
From the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. Yes \Boxed No	Within 100 feet of a centing only flewing watercourse significant watercourse lake had sinkhole wetland or playa lake (measured	
- Topographic map; Visual inspection (certification) of the proposed site Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. □ Yes □ No		☐ Yes ☒ No
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.	- Topographic map; Visual inspection (certification) of the proposed site	
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. ¬ Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption:	☐ Yes ☑ No
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.		
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.	Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15 000 mg/liter)	
or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.	Temporary Tit using now omorrow briming Trate (maximum emorroe content 15,000 mg morg	
- Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.		☐ Yes ☐ No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. Yes \Boxed{No} Yes \Boxed{No}		
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. Yes No		
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. □ Yes □ No		Yes No
watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.		
watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.	Within 200 houizontal fact of a apping on a private domestic fresh water well used by less than five households for domestic or steely	
NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site		☐ Yes ☐ No
	NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	

Treviously Approved Design (attach copy of design) Art Number.	
 ☐ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Previously Approved Design (attach copy of design) API Number: or Permit Number: 	
□ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC	.15.17.9 NMAC
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached.	cuments are
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site IO. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 Natructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	ouments are
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	☐ Yes ☐ No
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

12.	
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the o	locuments are
Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Erosion Control Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
13. <u>Proposed Closure</u> : 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Fl Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems)	uid Management Pit
In-place Burial On-site Trench Burial Alternative Closure Method	
14.	CONTACTOR OF THE CONTAC
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached. ☐ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC ☐ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC ☐ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) ☐ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC ☐ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC ☐ Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	macnea to the
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland.	
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes No
Within a 100-year floodplain FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC .15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and bel	ief.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) S OCD Representative Signature: Compliance Officer OCD Permit Number:	_
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 1/29/14	
20. Closure Method: Waste Excavation and Removal □ On-Site Closure Method □ Alternative Closure Method □ Waste Removal (Closed-le □ If different from approved plan, please explain.	oop systems only)
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please in mark in the box, that the documents are attached. □ Proof of Closure Notice (surface owner and division) □ Proof of Deed Notice (required for on-site closure for private land only) □ Plot Plan (for on-site closures and temporary pits) □ Confirmation Sampling Analytical Results (if applicable)	ndicate, by a check

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure report is belief. I also certify that the closure complies with all applicable closure requirements ar	s true, accurate and complete to the best of my knowledge and and conditions specified in the approved closure plan.
Name (Print): Kelly G. Roberts Title: Regulatory Technician	
Signature: 204 G. Poll	Date: 12/21/15
e-mail address: <u>Kelly.Roberts@cop.com</u> Telephone: (505) 326-9775	

ConocoPhillips Company San Juan Basin Below Grade Tank Closure Report

Lease Name: Blanco Wash Federal 1 (South Tank #2)

API No.: 30-045-07099

In accordance with Rule 19.15.17.13 NMAC the following information describes the closure of the below-grade tank referenced above. All proper documentation regarding closure activities is being included with the C-144.

General Plan:

COPC shall close a below-grade tank within 60 days of cessation of operations per Subsection G.4 of 19.15.17.13
 NMAC. This will include a) below-grade tanks that do not meet the requirements of Paragraphs (1) through (4) of
 Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five
 years, if not retrofitted to comply with Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC; b) an earlier
 date that the division requires because of imminent danger to fresh water, public health or the environment. For any
 closure, COPC will file the C144 Closure Report as required.

The below-grade tank referenced above was permitted and closed within 60 days of cessation of the below-grade tanks operation.

COPC shall remove liquids and sludge from a below-grade tank prior to implementing a closure method and shall
dispose of the liquids and sludge in a division-approved facility. The facilities to be used will be Basin Disposal
(Permit #NM-01-005), JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) and Envirotech Land Farm
(Permit #NM-01-011). The liner after being cleaned well (Subsection D, Paragraph 1, Subparagraph (m) of
19.15.9.712 NMAC) will be disposed of at the San Juan County Regional Landfill located on CR 3100.

All recovered liquids were disposed of at Basin Disposal (Permit #NM-01-005) and any sludge or soil required to be removed to facilitate closure was hauled to Envirotech Land Farm (Permit #NM-01-011) and JFJ Landfarm % IEI (Permit #NM-01-0010B). The liner was cleaned per Subsection D, Paragraph 1, Subparagraph (m) of 19.15.9.712 NMAC was disposed of at the San Juan County Regional Landfill located on CR 3100.

3. COPC will receive prior approval to remove the below-grade tank and dispose of it in a division-approved facility or recycle, reuse, or reclaim it in a manner that the appropriate division district office approves.

The below-grade tank was disposed of in a division-approved manner.

4. If there is any on-site equipment associated with a below-grade tank, then COPC shall remove the equipment, unless the equipment is required for some other purpose.

All on-site equipment associated with the below-grade tank was removed.

5. COPC will test the soils beneath the below-grade tank to determine whether a release has occurred. COPC shall collect, at a minimum, a five point, composite sample; collect individual grab samples from any area that is wet, discolored or showing other evidence of a release; and analyzed for the constituents listed in Table I of 19.15.17.13 NMAC. COPC shall notify the division of its results on form C-141.

A five point composite sample was taken of the below-grade tank using sampling tools and all samples tested per Subsection B of 19.15.17.1 3(B)(1)(b). (Sample results attached). Form C-141 is attached.

Components	Tests Method	Limit (mg/kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	100
Chlorides	EPA 300.0	250

6. If COPC or the division determines that a release has occurred, then COPC shall comply with 19.15.3.116 NMAC and 19.15.1.19 NMAC, as appropriate.

A release was determined for the above referenced well.

7. If the sampling program demonstrates that a release has not occurred or that any release does not exceed the concentrations specified in Table I of 19.15.17.13 NMAC, then COPC shall backfill the excavation with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover; recontour and re-vegetate the site.

The below-grade tank area passed all requirements of Paragraph (4) of Subsection E of 19.15.17.13 NMAC and was backfilled with compacted, non-waste containing, earthen material.

- 8. Notice of Closure will be given prior to closure to the Aztec Division office between 72 hours and one week via email or verbally. The notification of closure will include the following:
 - i. Operator's name
 - ii. Location by Unit Letter, Section, Township, and Range. Well name and API number.

Notification of closure was not provided to the Aztec Division office between 72 hours and one week prior to closure.

9. The surface owner shall be notified of COPC's closing of the below-grade tank 72 hours, but not more than one week, prior to closure as per the approved closure plan via certified mail, return receipt requested.

The closure process notification to the landowner was not found

10. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.

The below-grade tank area was re-contoured to match fit, shape, line, form and texture of the surrounding area. Re-shaping including drainage control, to prevent ponding and erosion. Natural drainages were unimpeded and water bars and/or silt traps were placed in areas where needed to prevent erosion on a large scale. Final recontour has a uniform appearance with smooth surface, fitting the natural landscape.

11. COPC shall seed the disturbed areas the first favorable growing season following closure of a below-grade tank. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM stipulated seed mixes will used on federally regulated lands and division-approved seed mixtures (administratively approved if required) will be utilized on all State or private lands. A uniform vegetative cover has been established that reflects a life-form ratio of plus or minus fifty percent (50%) of pre- disturbance levels and a total percent plant cover of at least seventy percent (70%) of pre-disturbance levels, excluding noxious weeds. If alternate seed mix is required by the state, private owner or tribe, it will be implemented with administrative approval if needed. COPC will repeat seeding or planting will be continued until successful vegetative growth occurs.

Provision 13 was accomplished through complying with BLM seeding requirements as allowed by the BLM/OCD MOU.

12. A minimum of four feet of cover shall be achieved and the cover shall include one foot of suitable material, with chloride concentrations less than 600 mg/kg as analyzed by EPA Method 300.0, to establish vegetation at the site, or the background thickness of topsoil, whichever is greater.

The below-grade tank area was backfilled and more than four feet of cover was achieved and the cover included one foot of suitable material to establish vegetation at the site.

- 13. All closure activities will include proper documentation and be available for review upon request and will be submitted to OCD within 60 days of closure of the below-grade tank. Closure report will be filed on C-144 and incorporate the following:
 - Soil Backfilling and Cover Installation (See Report)
 - Re-vegetation application rates and seeding techniques (See Report)
 - Photo documentation of the site reclamation (Included as an attachment)
 - Confirmation Sampling Results (Included as an attachment)
 - Proof of closure notice (Included as an attachment)

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office to accordance with 19.15.29 NMAC.

			Rele	ase Notific	atio	n and Co	rrective A	ction	ľ			
						OPERA'	ГOR		☐ Initia	al Report	\boxtimes	Final Report
		onocoPhillips				Contact Lis						
)th St, Farm		IM		Telephone No. (505) 326-9786						
Facility Na	ne: Blanc	o Wash Fed	leral #1			Facility Typ	e: Gas Well					
Surface Ow	ner Fede	ral		Mineral O	wner	Federal			API No	. 3004507	099	
				LOCA	TIO	N OF RE	LEASE					
Unit Letter	Section	Township	Range	Feet from the		/South Line	Feet from the	East/	West Line	County		
N	26	28N	09W	790		South	1700		West	San Juan		
				8		L Longitud	e - <u>107.76122</u> EASE					
Type of Rele	ase Hvd	rocarbon		11281	CILL	Volume of		nown	Volume I	Recovered	Non	ie
Source of Re	lease Belo		nk (BGT)	- South BGT		100011100000011100000000000000000000000	Iour of Occurrenc	e		Hour of Dis	covery	N.
*** * ***		21 0				If YES, To			January	28, 2014		
Was Immedi	ate Notice (Yes] No 🛛 Not Re	quired	N/A	wnom?					
By Whom? N/A Was a Watercourse Reached?						Date and I		W 5554				
Was a Water	course Read		Yes 🛛 1	No		If YES, Vo	olume Impacting t	the Wat	ercourse.			
If a Waterco	urse was Im	pacted, Descr	ibe Fully.*	ŧ								
N/A		[
Describe Car Below-Grad	ase of Probl e Tank Clo	em and Reme sure activitie	dial Actions with fie	n Taken.* Id samples taken	result	ing in constit	uents exceeded st	tandaro	ls outlined	by 19.15.17	7.13 NN	MAC.
NMOCD ac	tion levels t Samples w	ere collected	re specifie	cen.* ed in NMOCD's (rtical results are	Guidel below	ines for Leak applicable N	s, Spills and Rele MOCD action lev	eases ar vels. No	d the relea o further w	ise was assi ork will be	gned a perfor	ranking med. The
regulations a public health should their or the enviro	Il operators or the envi operations h nment. In a	are required to ronment. The nave failed to	o report and acceptant adequately OCD accept	e is true and completed in the certain rece of a C-141 report investigate and received and certain control of a C-141	elease of ort by the emedia	notifications a ne NMOCD m te contaminat	nd perform correct parked as "Final R ion that pose a thr	ctive act eport" of reat to g	ions for rel loes not rel round wate	eases which ieve the ope r, surface wa	may en rator of ater, hu	ndanger f liability man health
							OIL CON	SERV	ATION	DIVISIO	<u>NC</u>	
Signature:	fel	- HA										
Printed Nam	e: Lisa Hu	nter				Approved by	Environmental S	pecialis	st:			
		ental Specialis	st			Approval Da	te:		Expiration	Date:		
		unter@cop.co				Conditions o				Attached		
Date: Decei	nber 21, 20	15	Phone: (505) 326-9786								

^{*} Attach Additional Sheets If Necessary



February 27, 2014

Lindsay Dumas ConocoPhillips San Juan Business Unit Office 214-07 5525 Hwy 64 Farmington, New Mexico 87401 www.animasenvironmental.com

624 E. Comanche Farmington, NM 87401 505-564-2281

> Durango, Colorado 970-403-3084

Via electronic mail to: SJBUE-Team@ConocoPhillips.com

RE: Below Grade Tank Closure Report

Blanco Wash Federal #1

San Juan County, New Mexico

Dear Ms. Dumas:

Animas Environmental Services, LLC (AES) is pleased to provide the final report associated with two below grade tank (BGT) closures at ConocoPhillips (CoP) Blanco Wash Federal #1, located in San Juan County, New Mexico. Removal of tanks had been completed by CoP contractors prior to AES' arrival at the location.

1.0 Site Information

1.1 Location

Site Name – Blanco Wash Federal #1

Legal Description – SE¼ SW¼, Section 26, T28N, R9W, San Juan County, New Mexico Well Latitude/Longitude – N36.62799 and W107.76091, respectively

North BGT Latitude/Longitude – N36.62814 and W107.76122, respectively

South BGT Latitude/Longitude – N36.62791 and W107.76122, respectively

Land Jurisdiction – Bureau of Land Management (BLM)

Figure 1. Topographic Site Location Map

Figure 2. Aerial Site Map, January 2014

1.2 NMOCD Ranking

In accordance with the New Mexico Oil Conservation Division (NMOCD) *Guidelines for Remediation of Leaks, Spills, and Releases* (August 1993), the location was given a ranking score of 20 based on the following factors:

- Depth to Groundwater: A cathodic protection report form dated December 1991 for the Lackey H #709, located 235 feet west and at the same elevation, reported the depth to groundwater as 110 feet below ground surface (bgs). (0 points)
- Wellhead Protection Area: The tank locations are not within a wellhead protection area. (0 points)
- Distance to Surface Water Body: Blanco Wash is located approximately 190 feet northeast of the location. (20 points)

1.3 BGT Closure Assessment

AES was initially contacted by Dan Rudder, CoP representative, on January 28, 2014, and on January 29, 2014, Deborah Watson and Jesse Sprague of AES mobilized to the location. AES personnel collected six soil samples from below the BGT liner of each BGT. Four samples were collected from the perimeter of each BGT footprint, one sample was collected from the center of each BGT footprint, and one sample was composited from the four perimeter samples and one center sample of each BGT.

2.0 Soil Sampling

On January 29, 2014, AES personnel conducted field screening and collected ten soil samples (S-1 through S-10) and two 5-point composites (SC-1 and SC-2) from below the BGTs. Soil samples were collected from approximately 0.5 feet below the former BGTs for field screening of volatile organic compounds (VOCs) and total petroleum hydrocarbon (TPH). Soil samples SC-1 and SC-2 were field screened for VOCs and chlorides and submitted for confirmation laboratory analysis. Soil sample locations are included on Figure 2.

2.1 Field Screening

2.1.1 Volatile Organic Compounds

A portion of each sample was utilized for field screening of VOC vapors with a photo-ionization detector (PID) organic vapor meter (OVM). Before beginning field screening, the PID-OVM was first calibrated with 100 parts per million (ppm) isobutylene gas.

2.1.2 Total Petroleum Hydrocarbons

Soil samples were also analyzed in the field for TPH per USEPA Method 418.1 using a Buck Scientific Model HC-404 Total Hydrocarbon Analyzer Infrared Spectrometer (Buck). A 3-point calibration was completed prior to conducting soil analyses. Field analytical protocol followed AES's Standard Operating Procedure: Field Analysis Total Petroleum Hydrocarbons per EPA Method 418.1.

2.1.3 Chlorides

Soil samples SC-1 and SC-2 were field screened for chlorides using Chloride Drop Count Titration with silver nitrate. Sampling and analysis methods followed procedures provided by Hach Company.

2.2 Laboratory Analyses

The composite soil samples collected for laboratory analysis were placed into new, clean, laboratory-supplied containers, which were then labeled, placed on ice, and logged onto a sample chain of custody record. The samples were maintained on ice until delivery to the analytical laboratory, Hall Environmental Analysis Laboratory (Hall), in Albuquerque, New Mexico. Soil samples SC-1 and SC-2 were laboratory analyzed for:

- Benzene, toluene, ethylbenzene, and xylene (BTEX) per U.S. Environmental Protection Agency (USEPA) Method 8021B; and
- Chloride per USEPA Method 300.0.

In addition, sample SC-2 was laboratory analyzed for:

 TPH for gasoline range organics (GRO) and diesel range organics (DRO) per USEPA Method 8015D.

2.3 Field and Laboratory Analytical Results

North BGT field screening readings for VOCs via OVM ranged from 0.4 ppm in S-2 and SC-1 up to 1.0 ppm in S-3. Field TPH concentrations ranged from less than 20.0 mg/kg in S-1 and S-3 up to 69.4 mg/kg in S-2. The field chloride concentration in SC-1 was 80 mg/kg.

South BGT field screening readings for VOCs via OVM ranged from 0.7 ppm in S-6 and S-8 through S-10, up to 3.8 ppm in S-7. Field TPH concentrations ranged from 141 mg/kg in S-9 up to 2,440 mg/kg in S-7. The field chloride concentration in SC-1 was 80 mg/kg. Field screening results are summarized in Table 1 and presented on Figure 2. The AES Field Screening Reports are attached.

Table 1. Soil Field Screening VOCs, TPH, and Chloride Results Blanco Wash Federal #1 BGT Closure, January 2014

Sample ID	Date Sampled	Depth below BGT (ft)	VOCs OVM Reading (ppm)	Field TPH (mg/kg)	Field Chlorides (mg/kg)
NMOCD Action L	evel (NMAC 19.	15.17.13E)	22	100	250
S-1 (North)	1/29/14	0.5	0.8	<20.0	NA
S-2 (North)	1/29/14	0.5	0.4	69.4	NA
S-3 (North)	1/29/14	0.5	1.0	<20.0	NA
S-4 (North)	1/29/14	0.5	0.5	30.3	NA
S-5 (North)	1/29/14	0.5	0.6	22.5	NA
SC-1 (North)	1/29/14	0.5	0.4	NA	80
S-6 (South)	1/29/14	0.5	0.7	636	NA
S-7 (South)	1/29/14	0.5	3.8	2,440	NA
S-8 (South)	1/29/14	0.5	0.7	512	NA
S-9 (South)	1/29/14	0.5	0.7	141	NA
S-10 (South)	1/29/14	0.5	0.7	388	NA
SC-2 (South)	1/29/14	0.5	1.2	NA	80

NA - not analyzed

For SC-1, laboratory analytical results reported benzene and total BTEX concentrations as less than 0.036 mg/kg and 0.179 mg/kg, respectively. The laboratory chloride concentration was reported below the laboratory detection limit of 30 mg/kg. In SC-2, laboratory analytical results reported benzene and total BTEX concentrations as less than 0.030 mg/kg and 0.151 mg/kg, respectively. TPH concentrations as GRO and DRO were reported at less than 3.0 mg/kg and 74 mg/kg, respectively. The laboratory chloride concentration in SC-2 was less than the laboratory detection limit of 30 mg/kg. Laboratory analytical results are summarized in Table 2 and included on Figure 2. The laboratory analytical reports are attached.

Table 2. Soil Laboratory Analytical Results
Blanco Wash Federal #1 BGT Closure, January 2014

Sample ID	Date Sampled	Depth (ft)	Benzene (mg/kg)	Total BTEX (mg/kg)	TPH- GRO (mg/kg)	TPH- DRO (mg/kg)	Chlorides (mg/kg)
NMOCD Action Level (NMAC 19.15.17.13E)		0.2	50		00	250	
SC-1 (North)	1/29/14	0.5	<0.036	<0.179	NA	NA	<30
SC-2 (South)	1/29/14	0.5	<0.030	<0.151	<3.0	74	<30

NA - not analyzed

3.0 Conclusions and Recommendations

NMOCD action levels for BGT closures are specified in New Mexico Administrative Code (NMAC) 19.15.17.13E. For the north BGT, field TPH concentrations were below the NMOCD action level, with the highest concentration reported in S-2 with 69.4 mg/kg. For the south BGT, field TPH concentrations were reported above the NMOCD action level of 100 mg/kg, with the highest concentration reported in S-7 with 2,440 mg/kg. However, laboratory analytical results for TPH (as GRO/DRO) in SC-2 were reported below the NMOCD action level of 100 mg/kg. Benzene and total BTEX concentrations in SC-1 and SC-2 were below the NMOCD action levels of 0.2 mg/kg and 50 mg/kg, respectively. Chloride concentrations in SC-1 and SC-2 were also below the NMOCD action level of 250 mg/kg. Based on field screening and laboratory analytical results for benzene, total BTEX, TPH, and chlorides, no further work is recommended at Blanco Wash Federal #1.

If you have any questions about this report or site conditions, please do not hesitate to contact Deborah Watson at (505) 564-2281.

Sincerely,

David J. Reese

Environmental Scientist

Elizabeth V McNolly

David of Rem


Elizabeth McNally, P.E.


Lindsay Dumas Blanco Wash Federal #1 BGT Closure Report February 27, 2014 Page 6 of 6

Attachments:

Figure 1. Topographic Site Location Map Figure 2. Aerial Site Map, January 2014 AES Field Screening Report 012914 Hall Analytical Report 1401B76 Hall Analytical Report 1401B77

R:\Animas 2000\Dropbox\0000 Animas Server Dropbox EM\2014 Projects\ConocoPhillips\Blanco Wash Federal #1\Blanco Wash Federal #1 BGT Closure Report 022714.docx





AES Field Screening Report



Animas Environmental Services, LLC

624 E. Comanche Farmington, NM 87401 505-564-2281 www.animasenvironmental.com

Durango, Colorado 970-403-3084

Date: 1/29/2014

Project Location: Blanco Wash Federal #1

Client: ConocoPhillips

Matrix: Soil

		Time of			Field	Field TPH				ТРН
Sample ID	Collection Date	Sample Collection	Sample Location	(mdd)	Chloride (mg/kg)	Analysis Time	Field TPH* (mg/kg)	TPH PQL (mg/kg)	DF	Analysts Initials
S-1 (North)	1/29/2014	10:30	North	0.8	NA	11:19	9.48	20.0	H	DAW
S-2 (North)	1/29/2014	10:32	South	0.4	NA	11:22	69.4	20.0	1	DAW
S-3 (North)	1/29/2014	10:34	East	1.0	NA	11:25	14.7	20.0	Н	DAW
S-4 (North)	1/29/2014	10:36	West	0.5	NA	11:27	30.3	20.0	Н	DAW
S-5 (North)	1/29/2014	10:38	Center	9.0	NA	11:30	22.5	20.0	1	DAW
SC-1 (North)	1/29/2014	10:45	Composite	0.4	80		Not	Not Analyzed for TPH	Н	
S-6 (South)	1/29/2014	12:01	North	0.7	NA	12:29	989	20.0	ч	DAW
S-7 (South)	1/29/2014	12:02	South	3.8	NA	12:33	2,440	20.0	Н	DAW
S-8 (South)	1/29/2014	12:03	East	0.7	NA	12:36	512	20.0	П	DAW
S-9 (South)	1/29/2014	12:04	West	0.7	NA	12:40	141	20.0	1	DAW
S-10 (South)	1/29/2014	12:05	Center	0.7	NA	12:44	388	20.0	1	DAW
SC-2 (South) 1/29/2014	1/29/2014	12:10	Composite	1.2	80		Not	Not Analyzed for TPH	PH	

Report Finalized: 1/29/14

Field Chloride - Quantab Chloride Titrators or Drop Count Titration with Silver Nitrate

Total Petroleum Hydrocarbons - USEPA 418.1

Analyst:

*Field TPH concentrations recorded may be below PQL.

Practical Quantitation Limit

PQL ND NA A

Not Detected at the Reporting Limit

Dilution Factor Not Analyzed



Hall Environmental Analysis Laboratory
4901 Hawkins NE
Albuquerque, NM 87109
TEL: 505-345-3975 FAX: 505-345-4107
Website: www.hallenvironmental.com

February 04, 2014

Debbie Watson Animas Environmental 624 East Comanche Farmington, NM 87401 TEL: (505) 486-4071

FAX

RE: CoP Blanco Wash Federal #1 South BGT

OrderNo.: 1401B76

Dear Debbie Watson:

Hall Environmental Analysis Laboratory received 1 sample(s) on 1/30/2014 for the analyses presented in the following report.

These were analyzed according to EPA procedures or equivalent. To access our accredited tests please go to www.hallenvironmental.com or the state specific web sites. In order to properly interpret your results it is imperative that you review this report in its entirety. See the sample checklist and/or the Chain of Custody for information regarding the sample receipt temperature and preservation. Data qualifiers or a narrative will be provided if the sample analysis or analytical quality control parameters require a flag. When necessary, data qualifers are provided on both the sample analysis report and the QC summary report, both sections should be reviewed. All samples are reported, as received, unless otherwise indicated. Lab measurement of analytes considered field parameters that require analysis within 15 minutes of sampling such as pH and residual chlorine are qualified as being analyzed outside of the recommended holding time.

Please don't hesitate to contact HEAL for any additional information or clarifications.

ADHS Cert #AZ0682 -- NMED-DWB Cert #NM9425 -- NMED-Micro Cert #NM0190

Sincerely,

Andy Freeman

Laboratory Manager

Only

4901 Hawkins NE

Albuquerque, NM 87109

Analytical Report Lab Order 1401B76

Date Reported: 2/4/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Animas Environmental

Client Sample ID: SC-1 SC-2 South DAW

CoP Blanco Wash Federal #1 South BGT Project:

Collection Date: 1/29/2014 12:10:00 PM

1401B76-001 Lab ID:

Matrix: MEOH (SOIL) Received Date: 1/30/2014 10:00:00 AM

Analyses	Result	RL Q	ual Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANG	E ORGANICS				Analys	: BCN
Diesel Range Organics (DRO)	74	10	mg/Kg	1	1/30/2014 3:49:43 PM	11455
Surr: DNOP	83.2	66-131	%REC	1	1/30/2014 3:49:43 PM	11455
EPA METHOD 8015D: GASOLINE RA	NGE				Analys	:: JMP
Gasoline Range Organics (GRO)	ND	3.0	mg/Kg	1	1/30/2014 11:31:59 AM	R16396
Surr: BFB	90.8	74.5-129	%REC	1	1/30/2014 11:31:59 AM	R16396
EPA METHOD 8021B: VOLATILES					Analys	: JMP
Benzene	ND	0.030	mg/Kg	1	1/30/2014 11:31:59 AM	R16396
Toluene	ND	0.030	mg/Kg	1	1/30/2014 11:31:59 AM	R16396
Ethylbenzene	ND	0.030	mg/Kg	1	1/30/2014 11:31:59 AM	R16396
Xylenes, Total	ND	0.061	mg/Kg	1	1/30/2014 11:31:59 AM	R16396
Surr: 4-Bromofluorobenzene	102	80-120	%REC	1	1/30/2014 11:31:59 AM	R16396
EPA METHOD 300.0: ANIONS					Analys	: JRR
Chloride	ND	30	mg/Kg	20	1/30/2014 12:41:54 PM	11489

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- Analyte detected below quantitation limits J
- O RSD is greater than RSDlimit
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit Sample pH greater than 2 for VOA and TOC only.
- P
- Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1401B76

04-Feb-14

Client:

Animas Environmental

Project:

CoP Blanco Wash Federal #1 South BGT

Sample ID MB-11489

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 11489

RunNo: 16422

Prep Date:

1/30/2014

Analysis Date: 1/30/2014

SeqNo: 473554

Units: mg/Kg HighLimit

RPDLimit

%RPD

%RPD

Qual

Analyte Chloride

Result PQL ND 1.5

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: LCSS

Batch ID: 11489

RunNo: 16422

Prep Date: 1/30/2014

Sample ID LCS-11489

SeqNo: 473555

Units: mg/Kg

Analysis Date: 1/30/2014

SPK value SPK Ref Val %REC LowLimit

HighLimit

RPDLimit

Qual

Analyte

Result 14

15.00

91.9

90

Chloride

PQL 1.5

SPK value SPK Ref Val %REC LowLimit

110

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range E
- Analyte detected below quantitation limits J
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits
- В Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 2 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#: 1401B76

04-Feb-14

Client:

Animas Environmental

	CoP Blanco Wash Federal #1 South BGT														
Sample ID LCS-11455	SampType: LCS	TestCode: EPA Method	8015D: Diesel Range C	rganics											
Client ID: LCSS	Batch ID: 11455	RunNo: 16383													
Prep Date: 1/29/2014	Analysis Date: 1/30/2014	SeqNo: 473042	Units: mg/Kg												
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual											
Diesel Range Organics (DRO)	40 10 50.00	0 79.4 60.8	145												
Surr: DNOP	4.2 5.000	84.4 66	131												
Sample ID MB-11441															
Client ID: PBS															
Prep Date: 1/28/2014															
Analyte	rte Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Q														
Surr: DNOP	ayte Rooth Fac of Read														
Sample ID LCS-11441	SampType: LCS	TestCode: EPA Method	8015D: Diesel Range C	Organics											
Client ID: LCSS	Batch ID: 11441	RunNo: 16383													
Prep Date: 1/28/2014	Analysis Date: 1/30/2014	SeqNo: 473351	Units: %REC												
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual											
Surr: DNOP	3.9 5.000	78.6 66	131												
Sample ID MB-11455	SampType: MBLK	TestCode: EPA Method	8015D: Diesel Range C	Organics											
Client ID: PBS	Batch ID: 11455	RunNo: 16383		8											
Prep Date: 1/29/2014	Analysis Date: 1/30/2014	SeqNo: 473541	Units: mg/Kg												
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual											
Diesel Range Organics (DRO)		80.3 66	131												
Surr: DNOP	8.0 10.00	00.3	101												

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range E
- Analyte detected below quantitation limits
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- Sample pH greater than 2 for VOA and TOC only. P
- RLReporting Detection Limit

Page 3 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#: 1401B76

04-Feb-14

Client:

Animas Environmental

Project:

CoP Blanco Wash Federal #1 South BGT

TestCode: EPA Method 8015D: Gasoline Range Sample ID MB-11468 MK SampType: MBLK Batch ID: R16396 RunNo: 16396 Client ID: **PBS** SeqNo: 473261 Units: mg/Kg Prep Date: Analysis Date: 1/30/2014 Qual HighLimit %RPD **RPDLimit** SPK value SPK Ref Val %REC LowLimit Analyte Result PQL Gasoline Range Organics (GRO) ND 5.0 129 90.4 74.5 Surr: BFB 900 1000 Sample ID LCS-11468 MK SampType: LCS TestCode: EPA Method 8015D: Gasoline Range

Client ID: LCSS	Batcl	n ID: R1	6396	F	RunNo: 1	6396							
Prep Date:	Analysis D	ate: 1/	30/2014	S	SeqNo: 4	73262	Units: mg/Kg						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Gasoline Range Organics (GRO)	26	5.0	25.00	0	103	74.5	126						
Surr: BFB	970		1000		97.4	74.5	129						

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 4 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1401B76

04-Feb-14

Client:

Animas Environmental

Project:

CoP Blanco Wash Federal #1 South BGT

Sample ID MB-11468 MK	SampT	ype: ME	зьк	Tes	14.					
Client ID: PBS	Batcl	1 ID: R1	6396	R	tunNo: 1	6396				
Prep Date:	Analysis E	ate: 1/	30/2014	S	SeqNo: 4	73287	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.0		1.000		102	80	120			

Sample ID LCS-11468 MK	Samp	Гуре: LC	s	Tes										
Client ID: LCSS	Batc	h ID: R1	6396	RunNo: 16396										
Prep Date:	Analysis I	Date: 1/	30/2014	8	SeqNo: 4	73288	Units: mg/Kg							
Analyte	Result PQL SPK value			SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Benzene	1.0	0.050	1.000	0	104	80	120							
Toluene	1.1	0.050	1.000	0	105	80	120							
Ethylbenzene	1.1	0.050	1.000	0	107	80	120							
Xylenes, Total	3.2	0.10	3.000	0	106	80	120							
Surr: 4-Bromofluorobenzene	1.1		1.000		111	80								

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 5 of 5



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

RoptNo: 1 Work Order Number: 1401B76 Client Name: Animas Environmental Received by/date: Muhille Garriso 1/30/2014 10:00:00 AM Michelle Garcia Logged By: 1/30/2014 10:26:34 AM Completed By: Michelle Garcia Reviewed By: Chain of Custody No [] Not Present V Yes [1. Custody seals intact on sample bottles? Yes V No 🗔 Not Present 2. Is Chain of Custody complete? Courier 3. How was the sample delivered? Log In No ! NA 4. Was an attempt made to cool the samples? No 🗌 NA [5. Were all samples received at a temperature of >0° C to 6.0°C Yes V Yes 🗸 No \Box 6. Sample(s) in proper container(s)? No 🗔 Yes 🗸 7. Sufficient sample volume for indicated test(s)? Yes V 8. Are samples (except VOA and ONG) properly preserved? Yes ! NA i No V 9. Was preservative added to bottles? Yes | | No VOA Vials . No 10.VOA vials have zero headspace? No V Yes 11. Were any sample containers received broken? # of preserved bottles checked Yes 🗸 No ... for pH: 12. Does paperwork match bottle labels? (<2 or >12 unless noted) (Note discrepancies on chain of custody) Adjusted? No 🗌 Yes 🗸 13. Are matrices correctly identified on Chain of Custody? No 🗔 Yes V 14. Is it clear what analyses were requested? Checked by: No : Yes V: 15. Were all holding times able to be met? (If no, notify customer for authorization.) Special Handling (if applicable) Yes [NA V No 🗌 16. Was client notified of all discrepancies with this order? Person Notified: Date: Via: eMail Phone Fax In Person By Whom: Regarding: Client Instructions: 17. Additional remarks: 18. Cooler Information Seal Intact | Seal No Seal Date Cooler No Temp °C Condition

	.>							(1)	.10	٧)	Air Bubbles	<u> </u>										-	5	
	HALL ENVIKONMENTAL ANALYSIS LABORATORY																						p. 22	ort.
	Ē		_			0	VAL.	10.42	_	_,													<u> </u>	ical rep
L.	E 55		4901 Hawkins NE - Albuquerque, NM 87109	. 70		50	1/10	17	ر 	ب	, COE	+	•		 							2	A -	analyt
	B	mo	8 M	5-41(76				(A(imə2) 0728										_ :	1	3	on the
C	Z S	ntal.o	ue, l	505-345-4107	Request		200	7000			8260B (VO	-									-	D ~	为	otated
		nme	luerq	500			2000				O,4) snoinA oitseq 1808											200	84	early n
d	HALL ENVI ANALYSIS	www.hallenvironmental.com	\lpuq	Fax	Analysis	(.0	5 Od	·OIV			RCRA 8 Me										_	Guaco	0	Il be cl
	Ė	halle	7 - 3	72	An		(SMI	S 04			168) s'HA9				•								Tho phyllo	data wi
1	Z	WWW.	S NE	Tel. 505-345-3975	-						EDB (Wetho											23	4	acted
1		>	awkir	5-34			100	(1	81	t po	TPH (Metho											Remarks: Bill to 10356623	01/7	p-confr
			Z Z	. 50		(84	## (0)	Ha)(95	(E	83108 H9T	X										Remarks: Bill 103566	1- ia	Any su
			490	Te		(ƙju	ල පළ	Hd.			TM + X3T8											mark	Sob Soc	Delity.
	_					(1	. (802		B +	1	BTEX + 🕅	×										<u>8</u> 3	% हैं।	s poss
		↑	17	į).e.				0	٠									me 13i	ime 1D0 D	whis serves as notice of this possibility. Any sub-contracted data will be clearly notated on the analytical report
	3	<i>ا</i> کا	7-7	27							HEAL No	ļ	25									Time	H	as not
	. 0	6	S &									1										Date 30/1/	0ate 38 14	serves
	3	4	7.						ON I	n	2	}		9			1					0 73	Date Da	
	hsh	45.	5	^			Sov		No.		<u>ه</u> ک	Neo!		-					 200 200)]	atories
85	X Rush Same	-	Danco Wash Take	分	,	*	Z,		SS	10.18	Preservative Type	/S	•									4	(accredited laboratories.
ומוויבאטשות ווווק.		22	3	Š	1	Jer:	3	. ,	. √ Yes	Sample Temperature	Pres	$ 1\rangle$							3.5			च्)J	credite
2	lard	Project Name:		:	The state of the s	Project Manager:	~			Lemp	d#	13										L by:	1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	ther ac
2	□ Standard	ಶ ಕೃ /	20	Project #:	M	ect №	A	Sampler:	On lee	ple	Container Type and #	402 JONE	1 00			ŕ						Med by:	Received by:	ed to o
5		Pog.	ٽ	Proje		Proj		San	On	Sarr	ა ₹	40										S. C.	F 7	ontract
			J				(nc				Q													e subc
D			4		60		idatic		1	ı	est													тау Б
000	7	Ĭ	ome.		228		II Val				edu											M		menta
Y	3		Ì				t (Fu				Sample Request ID			6								N	13	Environ
g	2	()	-	2	564		vel 4				amp	1,70)									101	19	Hall E
Sto	72		East	ZZ		1	□ Level 4 (Full Validation)				Ö	\ \										od by:	ed by:	nitted to
3	11	۸,		\$	30.5				□ Other		Matrix	(COLUMN)										Relinguished by:	Relinquished by:	uqns sa
ģ	3	į	624	ATON	-						Ma	ŝ.										Relin	Relin	semple
Chain-of-Custody Record	17.	Senices	dress	Farmina		1X#:	kage: n	LG LG		ype)	Time	021	i i									Time:	Time:	If necessary, samples submitted to Hall Environmental may be subcontracted to other
5	A	V	ig Ad	13	#	or F	3 Pac	ditati	ELAP.	T) Q(-		-						-	╁	1		# nec
	Client: Arimas Emiliamust		Mailing Address:	4	Phone #:	email or Fax#:	QA/QC Package: \(\text{\text{Standard}}\)	Accreditation	□ NELAP	□ EDD (Type)	Date	41-12						1.				Date:	Sol/	<u>.</u>



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

OrderNo.: 1401B77

February 03, 2014

Debbie Watson Animas Environmental 624 East Comanche Farmington, NM 87401 TEL: (505) 486-4071

FAX

RE: CoP Blanco Wash Federal #1 North BGT

Dear Debbie Watson:

Hall Environmental Analysis Laboratory received 1 sample(s) on 1/30/2014 for the analyses presented in the following report.

These were analyzed according to EPA procedures or equivalent. To access our accredited tests please go to www.hallenvironmental.com or the state specific web sites. In order to properly interpret your results it is imperative that you review this report in its entirety. See the sample checklist and/or the Chain of Custody for information regarding the sample receipt temperature and preservation. Data qualifiers or a narrative will be provided if the sample analysis or analytical quality control parameters require a flag. When necessary, data qualifers are provided on both the sample analysis report and the QC summary report, both sections should be reviewed. All samples are reported, as received, unless otherwise indicated. Lab measurement of analytes considered field parameters that require analysis within 15 minutes of sampling such as pH and residual chlorine are qualified as being analyzed outside of the recommended holding time.

Please don't hesitate to contact HEAL for any additional information or clarifications.

ADHS Cert #AZ0682 -- NMED-DWB Cert #NM9425 -- NMED-Micro Cert #NM0190

Sincerely,

Andy Freeman

Laboratory Manager

Only

4901 Hawkins NE

Albuquerque, NM 87109

Analytical Report

Lab Order 1401B77

Date Reported: 2/3/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Animas Environmental

Client Sample ID: SC-1

CoP Blanco Wash Federal #1 North BGT Project:

Collection Date: 1/29/2014 10:45:00 AM

Lab ID:

1401B77-001

Matrix: MEOH (SOIL)

Received Date: 1/30/2014 10:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8021B: VOLATILES					Analyst	: JMP
Benzene	ND	0.036	mg/Kg	1	1/30/2014 12:00:34 PM	R16396
Toluene	ND	0.036	mg/Kg	1	1/30/2014 12:00:34 PM	R16396
Ethylbenzene	ND	0.036	mg/Kg	1	1/30/2014 12:00:34 PM	I R16396
Xylenes, Total	ND	0.071	mg/Kg	1	1/30/2014 12:00:34 PM	R16396
Surr: 4-Bromofluorobenzene	103	80-120	%REC	1	1/30/2014 12:00:34 PM	1 R16396
EPA METHOD 300.0: ANIONS		*			Analyst	: JRR
Chloride	ND	30	mg/Kg	20	1/30/2014 12:54:18 PM	1 11489

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range E
- Analyte detected below quantitation limits J
- RSD is greater than RSDlimit 0
- R RPD outside accepted recovery limits
- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank В
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit Sample pH greater than 2 for VOA and TOC only.
- P
- Reporting Detection Limit RL

Hall Environmental Analysis Laboratory, Inc.

WO#:

1401B77

03-Feb-14

Client:

Animas Environmental

Project:

CoP Blanco Wash Federal #1 North BGT

Sample ID MB-11489

Sample ID LCS-11489

LCSS

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

Prep Date:

PBS

1/30/2014

Batch ID: 11489

RunNo: 16422

Analysis Date: 1/30/2014

SeqNo: 473554

Units: mg/Kg

HighLimit

Qual

Analyte Chloride

PQL Result ND

RPDLimit %RPD

Batch ID: 11489

Analysis Date: 1/30/2014

SampType: LCS

RunNo: 16422

TestCode: EPA Method 300.0: Anions

SeqNo: 473555

Units: mg/Kg

HighLimit

Analyte

Result

Chloride

14

RPDLimit

1/30/2014

15.00

SPK value SPK Ref Val %REC

Client ID:

Prep Date:

Qual

91.9

90

110

SPK value SPK Ref Val %REC LowLimit

LowLimit

%RPD

E

- Value exceeds Maximum Contaminant Level.
- Analyte detected below quantitation limits J
- 0 RSD is greater than RSDlimit RPD outside accepted recovery limits R

Value above quantitation range

- Spike Recovery outside accepted recovery limits S
- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Η
- ND Not Detected at the Reporting Limit Sample pH greater than 2 for VOA and TOC only. P
- Reporting Detection Limit

Page 2 of 3

Hall Environmental Analysis Laboratory, Inc.

WO#:

1401B77

03-Feb-14

Client:

Animas Environmental

Project:

CoP Blanco Wash Federal #1 North BGT

Sample ID MB-11468 MK	SampT	ype: ME	BLK	Test						
Client ID: PBS	Batcl	h ID: R1	6396	R	tunNo: 1	6396				
Prep Date:	Analysis D	Date: 1/	30/2014	S	eqNo: 4	73287	Units: mg/K	(g		
Analyte	Result PQL SPK value			SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.0		1.000		102	80	120			

Sample ID LCS-11468 MK	Samp	ype: LC	S	TestCode: EPA Method 8021B: Volatiles											
Client ID: LCSS	Batc	n ID: R1	6396	F	RunNo: 1	6396									
Prep Date:	Analysis I	Date: 1/	30/2014	8	SeqNo: 4	73288	Units: mg/K	ı/Kg							
Analyte	Result PQL SPK value			SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Benzene	1.0	0.050	1.000	0	104	80	120								
Toluene	1.1	0.050	1.000	0	105	80	120								
Ethylbenzene	1.1	0.050	1.000	0	107	80	120								
Xylenes, Total	3.2	0.10	3.000	0	106	80	120								
Surr: 4-Bromofluorobenzene	1.1		1.000		111	80	120								

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 3 of 3



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

RcptNo: 1 Work Order Number: 1401B77 Animas Environmental Client Name: Received by/date: Michelle Garcia Michelle Garcia 1/30/2014 10:00:00 AM : Logged By: 1/30/2014 10:33:03 AM Completed By: Michelle Garcia Reviewed By: Chain of Custody Not Present V No ... Yes 1 Custody seals intact on sample bottles? No [Not Present Yes V 2. Is Chain of Custody complete? Courler 3. How was the sample delivered? Log In No ! NA ! Yes V 4. Was an attempt made to cool the samples? NA [5. Were all samples received at a temperature of >0° C to 6.0°C No 🗌 Yes 🗸 6. Sample(s) in proper container(s)? No [7. Sufficient sample volume for indicated test(s)? No ! 8. Are samples (except VOA and ONG) properly preserved? No V NA 1 Yes [1] 9. Was preservative added to bottles? Yes | No i . No VOA Vials IV 10.VOA vials have zero headspace? Yes 1.__ No V 11. Were any sample containers received broken? # of preserved bottles checked No 🗌 for pH: Yes V 12. Does paperwork match bottle labels? (<2 or >12 unless noted) (Note discrepancies on chain of custody) Adjusted? No i 13. Are matrices correctly identified on Chain of Custody? V No !! 14, is it clear what analyses were requested? No I Checked by: Yes 15. Were all holding times able to be met? (If no, notify customer for authorization.) Special Handling (if applicable) No [7 NA M Yes ... 16. Was client notified of all discrepancies with this order? Date: Person Notified: eMail Phone Fax In Person By Whom: Regarding: Client Instructions: 17. Additional remarks: 18. Cooler Information Seal Date . Cooler No Temp ºC Condition Seal Intact Seal No

4	ĨŘ Ž					# E *		((N no	(Y)	səlddu8 riA							_					r		
I ATMENTED IN THE	ANALYSIS LABORATORY													\dashv	_		\dashv	\dashv	+	\dashv		-	and a		accredited laboratories. This serves as notice of this possibility. Any sub-contracted data will be clearly notated on the analytical report.
	N		109	2				لأوه	2YV (n m	30.008	X				X .							25	_	nalytica
	0	E	M 87	Fax 505-345-4107	مند				(A	ΟΛ-	imə2) 07S8												30	· —	n the a
Ç	} ₹	tal.cc	e, N	-345	nest					(∀	OV) 80928											$ \bot $	(Z)	Very	ated o
		men	erqu	505	Red		STATE OF STA				oltse9 1808								_			_	18 J	Area?	ırly not
	SI	viron	nbnq	Fax	Analysis Request	([†] O	S'*O	О ₂ ,Р			⊃,국) anoinA						_		_	4		_	\$ -	P 4"	be clea
U	֓֞֞֓֓֓֞֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֡֓֓֡֓֡֓֡֓֓֡֓֡֓֡֓֡֡֝֡֡֡֡֝֡֓֡֡֡֝֡֡֡֡֡֓֓֡֡֡֡֡֡	www.hallenvironmental.com	4901 Hawkins NE - Albuquerque, NM 87109		Ana		/014				RCRA 8 Me			_		_		\dashv	-	4	_	┩`	Surfature Line	٥	ta will
	15	ww.h	N N	3975			(SN				EDB (Methors (831						\dashv	-	-	+	_	_		, 35°	sted da
		\ 	vkins	345							TPH (Metho			-	-	-	\dashv	-	\dashv	\dashv	_	_	50	1/2	contrac
F = 3)	1 F		Hav	Tel. 505-345-3975		(0)-	INI / C				88108 H9T		 		-		-	-	+		+	-	POST E	Super, Sasho Trugullo	ry sub-
			4901	<u> 1</u>							BTEX + MT						\dashv	_		1	\dashv	-	25 52 F	. 5	ity. An
	JL										EXE+ X3T8	\times							\dashv	1	\top	-	We 1635 6623	र्डेड	lidissoc
¥——	11		1.	·					杨													Ī		B	of this p
	art	Z on N	28-1								TEMBRIST (CARS)	9						1					1630		nofice
	Z .											Ī											7	<u>" 100</u>	res as
	Char	- -	t ว						9	5													7		nis sen
	So		ger						oN 🖂		and the second					_			_	_			-5	T	ies. T
	No Rush SCHAM	(Cop Planco Wash Federal "I					V)		Preservative Type	Mest											-7	4	rotation
<u>i</u>	7	ķ '	Na4		3	١	9		Z SS	aterie	eserva	1/2											-3		lited lai
ן ועווד אוטטואם ווווק.	р	.e.	3	2	を自むると	Project Manager:	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	3 -	3	Sample Temperatur		1 1							-	-	-	-		, 3	асство
2007	□ Standard	Project Name:	De	# 1	香	Man		2 2] - 	Ter	Container Type and #	돌										1	= +1	ا برگزار درگزیار	offher
<u> </u>	Sta	oject	C	Project #:	多	oject	6		On Ice	ill lost	Container	1204-1											Const	Seiver Seiver	acted to
		Ę.	<u>ئ</u>	<u>P</u>	Γ	4		0	5 6	S	——————————————————————————————————————			_	\dashv	-		\dashv	+	\dashv	\dashv	- 6		§) Scontra
_			3				(1)	(lon)	¥		Ω								c						ns aq /
500	tal		3				3.	alida			nest			ĺ									1		tal may
ec	§		SAN ACTOR				7	□ Level 4 (rull validation)			Sample Request ID												13	n.	nemec
Y	7 7		3	5	278		7	4 -			ple	-											B	B	l Enviro
od	5	~	10	2	5		[eve.			Sam	SC											\leq	\$	to Hal
IST	N.V.(7	(1)	2	South		[5	<u>₽</u>										_	_	_	_			mitted
ゔ	(1)	કુ		3	20				□ Other		Matrix	1							1			ŀ	Madusined by	Make by $\mathcal{M}_{\mathcal{L}}$	les sut
Ö	Mais	5	20	3	5			į			Ž	50,	 								\dashv	- 1			, salonip
ain	Animais Environmental	25/25	dress	Farmuch	200	#	kage:	p 5	5	ype)	Time	部											ESC.	LYP	If necessary, semples submitted to Hall Environmental may be subcontracted to ether
Chain-or-Custody Record	A3350	7	g Ad	(J)	#:	일	3 Pac	difati	IAP	0		9 4		-					+	-	+	ļ			lf nec
	Client:		Mailing Address: 624		Phone #:	email or Fax#:	QA/QC Package:	Accreditation	□ NELAP	□ EDD (Type)	Date	-29-14												30 L	
	~	ı	1	L		, ΨΙ	J).	_1 _		1				1				ı	į	1		ā,			•

