District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

		Dit Dalaw	Cuada Taula	24	RECEIVED
	Duore	•	Grade Tank, o		By kcollins at 8:34 am, Apr 05, 201
14682	3 12 · 1	sed Alternative Method F ☐ Below grade tank registration ☐ Permit of a pit or proposed alt ☐ Closure of a pit, below-grade ☐ ☐ Modification to an existing pe	ernative method tank, or proposed a	Iternative method	
	or proposed alter	Closure plan only submitted for			low-grade tank,
	Instructions: Plea	se submit one application (Form C-14	44) per individual pit	, below-grade tank or alternativ	ve request
		quest does not relieve the operator of liab the operator of its responsibility to comp			
Address: _	Burlington Resources C PO BOX 4289, Farmin vell name: <u>HUERFAN</u> 0		4538	Constituents Exceed by 19.15.17.13 NMA separate C-141 unde	C. Please submit a
U/L or Qtr/0 Center of Pr	OtrD (NWNW)_ roposed Design: Latitud	OCD Permit Numb Section 28 Townshi de 36.46374167 N Longitude e Private Tribal Trust or Indian	ip <u>26N</u> Ra 107.8000279	nge 9W County: San J	fuan CLOSED
Temporary: Permane Lined [String-R	Unlined Liner type		HDPE ☐ PVC ☐	Other	
Volume: Tank Consti	MAX 120 ruction material: ary containment with leasidewalls and liner	n I of 19.15.17.11 NMAC bbl Type of fluid:P Metal ak detection	er, 6-inch lift and auto	5 New 1975 12 Sept 5 New 19	
N	tive Method:	required. Exceptions must be submit	ted to the Santa Fe Er	nvironmental Bureau office for c	onsideration of approval.
☐ Chain lir institution o	nk, six feet in height, tw r church)	1.11 NMAC (Applies to permanent pits, o strands of barbed wire at top (Require barbed wire evenly spaced between on	ed if located within 1	and the same and t	ce, school, hospital,

6. Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
☐ Screen ☐ Netting ☐ Other	
☐ Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
8.	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank:	
☐ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. ☐ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
Exception(s). Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC	
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acce	ptable source
material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☑ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured	
from the ordinary high-water mark).	☐ Yes ☑ No
- Topographic map; Visual inspection (certification) of the proposed site	
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☑ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

	- 55/
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	NMAC 15.17.9 NMAC
Within 500 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	☐ Yes ☐ No

10	
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	nuu management Fit
14.	attendend to the
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. ☐ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC ☐ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC ☐ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) ☐ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC ☐ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC ☐ Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

	200
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	
Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	☐ Yes ☐ No
16.	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe	
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: ☐ Permit Application (including closure plan) ☐ Closure Plan (enly) ☐ OCD Conditions (see attachment)	See Front Page
OCD Representative Signature: Spath . Kelly Approval Date: 7/12/2	016
Title: Compliance Officer OCD Permit Number:	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 1/17/2011	
20. Closure Method: Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-lo ☐ If different from approved plan, please explain.	op systems only)
 Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please incommark in the box, that the documents are attached. ☑ Proof of Closure Notice (surface owner and division) ☐ Proof of Deed Notice (required for on-site closure for private land only) 	dicate, by a check

22.
Operator Closure Certification:
I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.
Name (Print) Crystal Walker Title: Regulatory Coordinator
Signature: Stal Walker Date: 4/1/16
e-mail address: <u>crystal.walker@cop.com</u> Telephone: <u>(505)</u> <u>326-9837</u>

Burlington Resources Oil & Gas Company San Juan Basin: New Mexico Assets

Below Grade Tank Closure Report

Lease Name: Huerfano Unit 182

API No.: 30-045-20309

In accordance with Rule 19.15.17.13 NMAC, the following information describes the closure of the below-grade tank referenced above. All proper documentation regarding closure activities is being included with the C-144.

General Plan Requirements:

1. Prior to initiating any BGT closure, except in the case of an emergency, BR will notify the surface owner of the intent to close the BGT by certified mail no later than 72 hours or one week before closure and a copy of this notification will be included in the closure report. In the case of an emergency, the surface owner will be notified as soon as practical.

The surface owner notification was not found.

- 2. Notice of closure will be given to the District Division office between 72 hours and one week of the scheduled closure via email or phone. The notification of closure will include the following:
 - a. Operators Name
 - b. Well Name and API Number
 - c. Location

Notification was not found.

3. All liquids will be removed from the BGT following cessation of operation. Produced water will be disposed of at one of COP's approved Salt Water Disposal facilities or at a District Division approved facility.

All recovered liquids were disposed of at an approved SWD facility or an approved District Division facility within 60 days of cessation of operation.

4. Solids and sludge's will be shoveled and/or vacuumed out for disposal at one of the District Division approved facilities, depending on the proximity of the BGT site: Envirotech Land Farm (Permit #NM-01-011), JFJ Land Farm % Industrial Ecosystems Inc. (Permit #NM-01-0010B), and Basin Disposal (Permit #NM-01-005).

Any sludge or soil required to be removed to facilitate closure was transported to Envirotech Land Farm (Permit # NM-01-011) and/or JFJ Landfarm % IEI (Permit# NM-01-0010B).

5. BR will obtain prior approval from District Division to dispose, recycle, reuse, or reclaim the BGT and provide documentation of the disposition of the BGT in the closure report. Steel materials will be recycled or reused as approved by the District Division. Fiberglass tanks will be empty, cut up or shredded, and EPA cleaned for disposal as solid waste. Liner materials will be cleaned without soils or contaminated material for disposal as solid waste. Fiberglass tanks and liner materials will meet the conditions of 19.15.35 NMAC. Disposal

will be at a licensed disposal facility, presently San Juan County Landfill operated by Waste Management under NMED Permit SWM-052426.

The below-grade tank was disposed of in a division-approved manner. The liner was cleaned per 19.15.35.8.C(1)(m) NMAC and disposed of at the San Juan County Regional Landfill located on CR 3100.

6. Any equipment associated with the BGT that is no longer required for some other purpose, following the closure, will be removed.

All on-site equipment associated with the below-grade tank was removed.

- 7. Following removal of the tank and any liner material, BR will test the soils beneath the BGT as follows:
 - a. At a minimum, a five-point composite sample will be taken to include any obvious stained or wet soils or any other evidence of contamination.
 - b. The laboratory sample shall be analyzed for the constituents listed in Table I of 19.15.17.13.

A five point composite sample was taken of the below-grade tank using sampling tools and all samples tested per Table I of 19.15.17.13 and the results are attached.

8. If the District Division and/or BR determine there is a release, BR will comply with 19.15.17.13.C.3b.

A release was not determined for the above referenced well.

9. Upon completion of the tank removal, pursuant to 19.15.17.13.C.3c, if all contaminant concentrations are less than or equal to the parameters listed in Table I of 19.15.17.13 NMAC, the excavation will be backfilled with non-waste earthen material compacted and covered with a minimum of one foot top soil or background thickness whichever is greater and to existing grade. The surface will be re-contoured to match the native grade and to prevent ponding.

The tank removal area passed all requirements of Table I of 19.15.17.13 NMAC and was backfilled with compacted, non-waste containing, earthen material which included at least one foot of suitable material to establish vegetation at the site.

10. For those portions of the former BGT area no longer required for production activities, BR will seed the disturbed area the first favorable growing season after the BGT is covered. Seeding will be accomplished via drilling on the contour whenever practical, or by other District Division-approved methods. BR will notify the District Division when reclamation and re-vegetation is complete.

Reclamation of the BGT shall be considered complete when:

- Vegetative cover reflects a life form ratio of +/- 50% of pre disturbance levels.
- Total percent plant cover of at least 70% of pre-disturbance levels (Excluding noxious weeds) OR
- Pursuant to 19.15.17.13.H.5d BR will comply with obligations imposed by other applicable federal or tribal agencies in which there re-vegetation and reclamation

requirements provide equal or better protection of fresh water, human health and the environment.

Provision 10 will be accomplished pursuant to 19.15.17.H.5d and notification will be submitted upon completion.

11. For those portions of the former BGT area required for production activities, reseeding will be done at well abandonment, and following the procedure noted above.

The former BGT area is not required for production activities and reseeding was completed on 4/19/12 per the procedure noted above.

Closure Report:

All closure activities will include proper documentation and will be submitted to OCD within 60 days of the BGT closure on a Closure Report using District Division Form C-144. The Report will include the following:

- Proof of Closure Notice (surface owner and District Division) (Not Attached)
- Backfilling & cover installation (See Report)
- Confirmation Sampling Analytical Results (Attached)
- Application Rate & Seeding techniques (See Report)
- Photo Documentation of Reclamation (Attached)

District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Form C-141 Revised October 10, 2003

Final Report

Submit 2 Copies to appropriate District Office in accordance with Rule 116 on back side of form

Initial Report

Release Notification and Corrective Action

OPERATOR

	Name of Company Burlington Resources, a Wholly Owned Subsidiary of ConocoPhillips Company					Contact Shelly Cook-Cowden				
				NM 87402	Telephone No. 505-324-5140					
		ano Unit #1		<u> </u>		pe Gas Well A		20309		
Surface Ow	ner Feder	ral		Mineral Own	er Federal			_ease N	lo. NMSF-078060A	
			17		ON OF RE	CLEASE				
Unit Letter D	Section 28	Township 026N	Range 009W	Feet from the 990'	rth/South Line North	Feet from the 890'	East/West Wes	300-001 (SIGNA) - 100	County San Juan County	
			La	atitude 36.46365 °		ude <u>107.79941</u>	° W			
3				NATUR	E OF REI	25 270 1900 0 7			(4)	
Type of Rele						f Release - Unkno			Recovered -	
Source of Re	lease – Belo	ow Grade Ta	nk		Unknow	Hour of Occurrenc	ce – Da	ate and	Hour of Discovery – 1/17/11	
Was Immedi	ate Notice (Yes [] No 🛛 Not Requir		o Whom?				
By Whom?			3400		Date and	Hour -				
Was a Water	course Read		Vec V	1 No.		olume Impacting t	the Waterco	ourse.		
☐ Yes ⊠ No						-				
If a Watercou	ırse was Im	pacted, Descr	ibe Fully.	K						
Describe Co.	as of Duckl	em and Reme	dial Astio	n Tokon *			43-14-411-5		40-5-40-	
		osure Activiti		ii Takeii.						
					•					
Describe Are	a Affected	and Cleanup A	Action Tal	cen.*						
The below g	rade tank	sample resul	ts were ab	ove the regulatory st					ssment was then conducted	
							w the regula	atory st	andards set forth in the	
NMOCD Gi	idelines fo	e Remediatio	n of Leak	s, Spills and Releases	no further ac	tion is required.				
	0 1 1				1 1	1 1 1 1	1 (1 (1	1 1	11 NR/OOD 1 1	
									uant to NMOCD rules and eases which may endanger	
public health	or the envi	ronment. The	acceptano	ce of a C-141 report by	the NMOCD	narked as "Final R	eport" does	not reli	eve the operator of liability	
should their	perations h	ave failed to	adequately	investigate and remed	liate contamina	tion that pose a thr	eat to groun	nd water	, surface water, human health	
		iddition, NMC ws and/or regi		otance of a C-141 repo	rt does not relie	ve the operator of	responsibili	ty for co	ompliance with any other	
rederal, state,	or local lav	ws and/or regu	nations.			OIL CON	SERVAT	ΓΙΟΝ	DIVISION	
		V-240				OIL COIV	DLACTA	11011	DIVIDIOIV	
Signature:	Shelley	Cook-Ca	o Da		- 10					
-8	Approved by District Supervisor:									
Printed Name	: Shelly Co	ook-Cowden					ſ			
Title: Enviro	nmental T	echnician			Approval D	ate:	Exp	iration l	Date:	
F-mail Addre	ege Shally	g Cook-Cow	den@Con	ocoPhillips.com	Conditions	of Approval:				
E-man Addro	os. blichy.	g.Cook-Cow			Conditions	ar approvar.			Attached	
Date: March	1, 2011		Ph	one: 505-324-5140		_				



February 3, 2011

Project Number 92115-1559

Phone: (505) 599-3403

Ms. Kelsi Harrington ConocoPhillips 3401 East 30th Street Farmington, New Mexico 87401

RE: BELOW GRADE TANK CLOSURE DOCUMENTATION FOR THE HUERFANO #182 (HBR)

WELL SITE, SAN JUAN COUNTY, NEW MEXICO

Dear Ms. Harrington:

Enclosed please find the field notes and analytical results for below grade tank (BGT) closure activities performed at the Huerfano #182 (hBr) well site located in Section 28, Township 26 North, Range 9 West, San Juan County, New Mexico. Upon Envirotech personnel's arrival on January 17, 2011 one (1) five (5)-point composite sample was collected from beneath the former BGT. The sample was analyzed in the field for TPH using USEPA Method 418.1, for organic vapors using a photoionization detector (PID) and for chlorides. The sample returned results above the BGT closure standard of 100 ppm for TPH confirming a release had occurred.

A brief site assessment was conducted and the regulatory standards were determined to be 1000 parts per million (ppm) total petroleum hydrocarbons (TPH) and 100 ppm organic vapors due to horizontal distance to surface water being between 200 and 1000 feet, pursuant to New Mexico Oil Conservation Division (NMOCD) Guidelines for Remediation of Spills, Leaks, and Releases. The sample was placed into a four (4)-ounce glass jar, capped headspace free, and transported on ice, under chain of custody, to Envirotech's Analytical Laboratory to be analyzed for benzene and BTEX using USEPA Method 8021 and for total chlorides using USEPA Method 4500. The sample returned results below the regulatory standards for all constituents analyzed; see attached *Analytical Results*. Envirotech, Inc. recommends no further action in regards to this incident.

ConocoPhillips Huerfano #182 BGT Closure Documentation Project Number 92115-1559 Page 2

We appreciate the opportunity to be of service. If you have any questions or require additional information, please contact our office at (505) 632-0615.

Respectfully Submitted, ENVIROTECH, INC.

Crystal Delgai

Environmental Field Technician cdelgai@envirotech-inc.com

Enclosures: Field Notes

Analytical Results

Cc: Client File 92115

PAGE NO: OF 2 DATE STARTED: /- /7-// DATE FINISHED: /- /7-//		RONMENT 5796 U. FARMING	AL SCIENT S. HIGHWA	CH INC FISTS & ENG AY 64 - 3014 MEXICO 874		SPECIAL LAT: 3	6.46374167
the second secon	D DEDORT	-					107.8000279
	D REPORT:						
LOCATION: NAME: HUEYA	SEC: 2 8	WELL #:		TEMP PIT:		NENT PIT:	BGT: X
QTR/FOOTAGE: 890W 990/		CNTY:	TWP: 2 San Jua	6/V	RNG: q		PM:
		-		" , /			AND A CE
DISPOSAL FACILITY:	γ) FT. X Δ/4	20	FT. X REMEDIA	TION METH		CUBIC YA	ARDAGE:
LAND OWNER:		API: 3 o	045203	04	BGT / PIT	VOLUME:	120 barrel
	Steel	DOUBLE	-WALLED,	WITH LEAK	9.44	N:	
LOCATION APPROXIMATELY: DEPTH TO GROUNDWATER:	100	FT. 2	SU "	FROM WEL	LHEAD		
TEMPORARY PIT - GROUN	フ(O & ' DWATER 50-100 1	FEET DEEP	,				
BENZENE ≤ 0.2 mg/kg, BTEX ≤ 5				00 mg/kg, TPH	(418.1) ≤ 250	0 mg/kg, CH	LORIDES ≤ 500 mg/kg
TEMPORARY PIT - GROUN							
BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50			N (8015) ≤ 50	00 mg/kg, TPH	(418.1) ≤ 2500	mg/kg, CHL	ORIDES ≤ 1000 mg/kg
X PERMANENT PIT OR BGT							
BENZENE ≤ 0.2 mg/kg, BTEX ≤	50 mg/kg, TPH (418	.1) ≤ 100 mg/	/kg, CHLORI	DES ≤ 250 mg/	'kg		
				D 418.1 ANAI	WAR THE TAX TO SELECT THE TAX		
	ME SAMPLE I.D	LAB NO.	WEIGHT (g	mL FREON	DILUTION	READING 190	CALC. (mg/kg)
105	20 Sut Britan	1	5	20	4	92	36.8
-10-	20 BGT	3	}				
		4				-	
		5	-				

PERIMETER	,		HLORIDE	S RESULTS		PRO	FILE
1		SAMPLE	READING	CALC. (mg/kg)			
IN The said	mp		0.9	C 23			
/ R	\	<u> </u>					
						9	·
					-	10	1
(A) 1 (n)		Ī	PID RESUI	TS	1		
		SAME	LEID	RESULTS	1 1		i
TEST	1			(mg/kg)	4'		
7	ar X				(ال	-	2 28
	Ĺ l				W.	\$	2 8
X	hugher						
LAB SAMPLES	NOTES:						
SAMPLE ID ANALYSIS RESU BENZENE	LTS Sam	ple to	Lab	for:			
BTEX GRO & DRO	- 8031	4 C1	_				
CHLORIDES	Surface	victer 20	00-10001				
	WORKORDE	R#		WHO ORDER	ED		

Client: OPC				05) 632-0615 U.S. Hwy 64, Far			Location N	No: o: 92115-1557
FIELD REPORT	: SPILL CL	OSURE V	/ERIFIC	CATION			PAGE NO	o:
LOCATION: NAME	Hyertano		WELL #:	182			DATE FIN	
QUAD/UNIT:	SEC: 2 X	TWP: 26N		PM: NM	CNTY:SJ	ST: NM	ENVIRON	the state of the s
QTR/FOOTAGE:			CONTRAC				SPECIALI	
EXCAVATION APPRO DISPOSAL FACILITY:	X: <u>20</u>	FT. X	20	FT. X REMEDIAT	4 ON METU	FT. DEEP	CUBIC Y	ARDAGE:
LAND USE:			LEASE:	REMEDIATI	ON WETH	LAND OW	NED.	
CAUSE OF RELEASE:			LLX IOLX	MATERIAL	RELEASED	***************************************	IVEIC.	
SPILL LOCATED APPR	OXIMATELY:	100%	FT. 2	5700		Where		
DEPTH TO GROUNDW					TROM (A)			WATER: 200 -10007
NMOCD RANKING SC			STREET, SQUARE,	PH CLOSUR	ESTD: /		PPM	
	s. 1	18					***************************************	
SAMPLE DESCRIPITION	N TIME 7:5%	SAMPLE I.D.	LAB NO.	WEIGHT (g)	mL FREON	DILUTION	READING 190	CALC. ppm
30+ BGT	10:20	1		5	2.0	4	92	368
-						L		
SPILL I	PERIMETER			OVM RESULTS			SPILL P	PROFILE
A (AS) 1	purp soil		ID I	AB SAMPLI	n) 3	12		* * * * * * * * * * * * * * * * * * *
TRAVEL NOTES:	CALLED OL	Miess Road	SAMPLE ID	ANALYSIS	TIME ONSITE:	4		



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:

ConocoPhillips

Project #:

92115-1559

Sample No.:

1

Date Reported:

2/3/2011

Sample ID:

BGT

Date Sampled:

1/17/2011

Sample Matrix:

Soil Cool Date Analyzed: Analysis Needed: 1/17/2011 TPH-418.1

Preservative: Condition:

Cool and Intact

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons

368

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis

of Water and Waste, USEPA Storet No. 4551, 1978.

Comments:

Huerfano #182 (hBr)

Instrument calibrated to 200 ppm standard. Zeroed before each sample

Analyst

Review

Crystal Delgai

Printed

Toni McKnight, EIT

Printed



CONTINUOUS CALIBRATION EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

\$60mm(0)	2	-			
Ca				1 -	-
·	20		a	TΩ	•

17-Jan-11

Parameter	Standard Concentration mg/L	Concentration Reading mg/L	
TPH	100		
	200	190	
	500		
	1000		

The accepted percent relative deviation (%RSD) of the calibration factor is less than 20% over the working range.

Constal Qui	1/20/2011
Analyst /	Date
Crystal Delgai Print Name	
Toni Midnight	1/20/2011
Review	Date

Toni McKnight, EIT

Print Name



Field Chloride

Client

ConocoPhillips

Project #:

92115-1559

Sample No.:

1

Date Reported:

2/3/2011

Sample ID:

BGT Sample

Date Sampled:

1/17/2011

Sample Matrix:

Soil

Date Analyzed:

1/17/2011

Preservative:

Cool

Analysis Needed:

Chloride

Condition:

Cool and Intact

3 12 10		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Field Chloride

ND

33.0

ND = Parameter not detected at the stated detection limit.

References:

"Standard Methods for the Examination of Water and Wastewater", 18th ed., 1992

Hach Company Quantab Titrators for Chloride

Comments:

Huerfano #182 (hBr)

Crystal Delgai

Printed

Toni McKnight, EIT



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	ConocoPhillips	Project #:	92115-1559
Sample ID:	BGT	Date Reported:	01-18-11
Laboratory Number:	57015	Date Sampled:	01-17-11
Chain of Custody:	11020	Date Received:	01-17-11
Sample Matrix:	Soil	Date Analyzed:	01-18-11
Preservative:	Cool	Date Extracted:	01-17-11
Condition: Intact	Intact	Analysis Requested:	BTEX
		Dilution:	10

	Dilution.	10		
Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)		
Benzene	ND	0.9		
Toluene	ND	1.0		
Ethylbenzene	ND	1.0		
p,m-Xylene	ND	1.2		
o-Xylene	ND	0.9		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	88.9 %
	1,4-difluorobenzene	93.6 %
	Bromochlorobenzene	83.3 %

References:

Total BTEX

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

ND

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Huerfano #182

Analyst



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

ND

ND

ND

0.1

0.1

0.1

Client: Sample ID: Laboratory Number:	N/A 0118BBLK QA/QC 57015		Project #: Date Reported: Date Sampled:		N/A 01-18-11 N/A		
Sample Matrix:		Date Received:		N/A			
Preservative:	N/A		Date Analyzed:		01-18-11		
Condition:	N/A		Analysis:		BTEX		
			Dilution:		10		
Calibration and	I-Cal RF:	C-Cal RF:	%Diff,	Blank	Detect,		
Detection Limits (ug/L)		Accept, Range 0		Conc	Limit		
Benzene	1.5723E+005	1.5755E+005	0.2%	ND	0.1		
Toluene	1.7592E+005	1.7627E+005	0.2%	ND	0.1		

1.5371E+005

3.4196E+005

1.4000E+005

0.2%

0.2%

0.2%

Duplicate Conc. (ug/Kg)	Sample	Duplicate	%Diff.	Accept Range	Detect. Limit
Benzene	ND	ND	0.0%	0 - 30%	0,9
Toluene	ND	ND	0.0%	0 - 30%	1.0
Ethylbenzene	ND	ND	0.0%	0 - 30%	1.0
p,m-Xylene	ND	ND	0.0%	0 - 30%	1.2
o-Xylene	ND	ND	0.0%	0 - 30%	0.9

Spike Conc. (ug/Kg)	Sample	Amount Spiked	Spiked Sample	% Recovery	Accept Range
Benzene	ND	500	488	97.5%	39 - 150
Toluene	ND	500	467	93.4%	46 - 148
Ethylbenzene	ND	500	456	91.2%	32 - 160
p,m-Xylene	ND	1000	938	93.8%	46 - 148
o-Xylene	ND	500	462	92.4%	46 - 148

ND - Parameter not detected at the stated detection limit.

1

Dilution: Spike and spiked sample concentration represent a dilution proportional to sample dilution.

1.5340E+005

3.4128E+005

1.3972E+005

References:

Ethylbenzene

p,m-Xylene

o-Xylene

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using

Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments:

QA/QC for Samples 57015-57016

Analyst

Review



Chloride

Client: ConocoPhillips Project #: 92115-1559 Sample ID: **BGT** Date Reported: 01/18/11 Lab ID#: 57015 Date Sampled: 01/17/11 Sample Matrix: Soil Date Received: 01/17/11 Preservative: Cool 01/18/11 Date Analyzed: Condition: Intact Chain of Custody: 11020

Parameter Concentration (mg/Kg)

Total Chloride

10

Reference:

U.S.E.P.A., 4500B, "Methods for Chemical Analysis of Water and Wastes", 1983. Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992

Comments:

Huerfano #182

Analyst

Review

CHAIN OF CUSTODY RECORD

			looD e		 										Date Time //17/11 11:45				
	ANALTOIS / PARAMETERS	j	418.1) 3019	онго	-										4				
1 0	7 7 7			НАЧ											7				
	LY 313														2				
3	A		noinA \	RCI	-										X				ic.com
			8 Meta		-										7				otech-ir
		8560)	Method) DOV											natrure)	ature)	ature)	Tory Itory	@envir
	,	1808 t	(Methoc	хэта												(Signa	(Signa	boro	15 • lab
-		(3108	hortel												Received by: (Signature	Received by: (Signature)	Received by: (Signature)		632-06
				No./Volume Preservative of Hgd, Hg A											Recei	Recei	Recei	envirotech Analytical Laboratory	1 • 505-
				Iume Plass	iņ										Time //:45			And	M 8740
				No./Volume of Containers	1-403.										± "/			0	gton, NI
	るとは		1559	Sample Matrix	Sludge Aqueous	Date /-//-//			(11)	5796 US Highway 64 • Farmington, NM 87401 • 505-632-0615 • lab@envirotech-inc.com									
cation	T Q	13	5	S	Solid	Soil					Highwa								
oject Name / Lo	Furtano #18%	Sampler Name:	Client No.: 0	Lab No.	51015					•									5796 US
			30	Sample Time	1-17-1 10:20										· \$				
	thill bs			Sample Date	1-1-1											tture)	tture)	50	
Cjient:	Conoco 4	Olient Address:	Client Phone No.:	Sample No./ Identification	BGT										Rejinduished by: (Signature	Relinguished by: (Signature)	Relinquished by: (Signature)	A USH	**

ACCENT Printing • Form 28-0807



