For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

		<u>P</u>	it, Below-Grade Tar	<u>nk, or</u>		RECEIVED By kcollins at 9:10 am, Jun 17, 2016
	Prope	osed Alternative	Method Permit or C	Closure Plan	Application	Direction and a second and a second and a second
14979		Closure of a pit, Modification to	k registration or proposed alternative methor below-grade tank, or propo an existing permit/or registr ly submitted for an existing	sed alternative m ation		pelow-grade tank,
	or proposed alte	ernative method				
environment. No	l that approval of this r	equest does not relieve th	tion (Form C-144) per individu e operator of liability should oper asibility to comply with any other	rations result in pol	lution of surface w	ater, ground water or the
1. Operator: B	urlington Resources (Dil & Gas Company, LP	OGRID # 14538			
-		gton, New Mexico 8749				
			OCD Permit Number:			
U/L or Qtr/Qtr	D Section	n <u>14</u> Township	28N Range 6W	<u>/</u> County: <u>R</u>	tio Arriba	
Center of Prop	osed Design: Latitud	e <u>36.665406</u> °N	Longitude107.445066_	°W	NAD: 1927 [1983 🖂
Surface Owner	r: 🛛 Federal 🗌 State	e 🗌 Private 🗌 Tribal T	rust or Indian Allotment			
 2. Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other						
Volume:		1 of 19.15.17.11 NMA				
Secondary containment with leak detection 🗌 Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off						
Visible sidewalls and liner 🗌 Visible sidewalls only 🗌 Other						
Liner type: Thicknessmil HDPE PVC OtherUnspecified						
4. <u>Alternativ</u> Submittal of an	= =3	required. Exceptions n	nust be submitted to the Santa F	e Environmental I	Bureau office for	consideration of approval.
☐ Chain link, <i>institution or c</i> ☐ Four foot h	six feet in height, two hurch)	o strands of barbed wire	permanent pits, temporary pits, at top (Required if located with ed between one and four feet			ce, school, hospital,

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen Netting Other

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

7.

8.

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

□ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.

Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting			
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank			
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells			
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 			
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No		
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No		
 Within a 100-year floodplain. (Does not apply to below grade tanks) FEMA map 	🗌 Yes 🗌 No		
Below Grade Tanks			
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 			
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 			
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)			
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No		
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.			
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image			
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site			

 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No		
Temporary Pit Non-low chloride drilling fluid			
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 			
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 			
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 			
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No		
Permanent Pit or Multi-Well Fluid Management Pit			
 Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No		
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No		
 Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No		
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No		
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:			
11.			
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.10 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number:			

affactual consequences and a sequence of the sequences of the appropriate requirements of 19.15.17.9 NMAC by Confide Comparison Com	^{12.} <u>Permanent Pits Permit Application Checklist</u> : Subsection B of 19.15.17.9 NMAC <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are</i>				
Instructions: Please complete the applicable boxes, Boxes J 4 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Multi-well Fluid Management Pit Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) Do-site Closure Method Do-site Closure Method Waste Removal (Closed-loop systems only) Do-site Closure Method Do-site Closure Method Do-site Closure Method Waste Removal (Closed-loop systems only) Do-site Closure Method Do-site Closure Method Do-site Closure Method Waste Removal (Dosure Plan Checklist: (9.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Plane Checklist: (9.15.17.13 NMAC) Dosubsection A or 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for Eiguids, drilling fluids and drill cuttings) Soil Backlin ad Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Issiste Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Issiste Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Issiste Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Issiste Reclamation Plan - based upon the appropriate requirem	attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Muisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of 19.15.17.9 NMAC and 19.15.17.13 NMAC				
Alternative					
Proposed Closure Method Waste Excavation and Removal Waste Removal (Closure Opsystems only) Implace Burial On-site Tenneh Burial Implace Burial Atternative Closure Method (Closure Opsystems) Implace Burial Implace Burial Maste Excavation and Removal Closure Plan Checklist; (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please Indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Pane (Tapplicable) - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Biting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siling criteria requirements of Subsection H of 19.15.17.13 NMAC Instructions: Each siling criteria requirements of Subsection H of 19.15.17.13 NMAC Instructions: Each siling criteria requirements of Subsection H of 19.15.17.13 NMAC Instructions: Each siling criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Regnesst regarding changes to certain sting criteria require pustifications and/or demonstrations of equivalency. Plans erfer to 19.15.17.10 NMAC Instructions: Each siling criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Regnesst regarding changes to certain sting criteria require pustifications and/or demonstrations of equival		luid Management Pit			
On-site Closure Method (Only for temporary pits and closed-loop systems) In place Burial Alternative Closure Method On-site Trench Burial Alternative Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please Burial to be appropriate requirements of 19.15.17.13 NMAC On-site Trench Burial Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Disposal Facility Name and Permi Number (for fliquk, drilling fuldis and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Sting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each sling criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding clamages to certain sling criteria require justifications and/or demonstrations of equivalency. Flase refer to 19.13.17.10 NMAC for guidance. word of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells On shill for the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells NA NA NA NA NA NA See (no a continuous) flowing watercourse, alaebed, sinkhole, or playa lake (measured from the ordinary high-water mark). NA	Proposed Closure Method: 🛛 Waste Excavation and Removal				
Image: Contract Network in the box, that the documents are attached. Image: Confirmation S and Preact Numk in the box, that the documents are attached. Image: Protocols and Preact Numk in the box, that the documents are attached. Image: Protocols and Preact Numk in the box, that the documents are attached. Image: Protocols and Preact Numk in the box, that the documents are attached. Image: Protocols and Preact Number (For liquids, diffing fulsa and drill cuttings) Image: Protocols and Preact Number (For liquids, diffing fulsa and drill cuttings) Image: Protocols and Preact Number (For liquids, diffing fulsa and drill cuttings) Image: Protocols and Preact Number (For liquids, diffing fulsa and drill cuttings) Image: Protocols and Preact Number (For liquids, diffing fulsa and drill cuttings) Image: Protocols and Preact Number (For liquids, diffing fulsa and drill cuttings) Image: Protocols and Preact Number (For liquids, diffing fulsa and drill cuttings) Image: Protocols and Preact Number (For liquids, diffing fulsa and drill cuttings) Image: Protocols and Preact Number (For liquids, diffing fulsa and drill cuttings) Image: Protocols and Preact Number (For liquids, diffing fulsa and preact Number (For liquids, diffing fulsa and diffic cuttings) Image: Protocols and Preact Number (For liquids, diffing fulsa and preact Number (For liquids, diffing fulsa and diffic cuttings) Image: Protocols and Preact Number (For liquids, diffing fulsa and preact Prea	On-site Closure Method (Only for temporary pits and closed-loop systems)				
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box; that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Confirmation Sampling Plan (fi applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Bis Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Revegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Its Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 25 feet below the bottom of the buried waste. Pscs NA NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells NA NA Ground water is between 25-50 feet below the bottom of the buried waste. NA NA NA NM Office of the State Engi					
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 25 feet below the bottom of the buried waste.	 closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 				
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells NA Ground water is between 25-50 feet below the bottom of the buried waste NA - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells NA Ground water is more than 100 feet below the bottom of the buried waste. NA - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells NA Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa Yes lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Yes Within 300 feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence Yes No - NM Office of the State Engincer - iWATERS database; Visual inspection (certification) of the proposed site Yes No Within 300 feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence Yes No - NM Office of the State Engincer - iWATERS database; Visual inspection (certification) of the proposed site Yes No Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence Yes No	Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to				
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells NA Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Yes NA Yes NA Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Yes No No Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes No Yes No Yes No Yes No 					
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells NA Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Yes No Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes No Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance 					
lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - No - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Yes No Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes No Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance Yes No					
 Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Yes No Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes No Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance 	lake (measured from the ordinary high-water mark).				
at the time of initial application NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance		🗌 Yes 🗌 No			
Written confirmation or verification from the municipality; Written approval obtained from the municipality Yes No Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes No Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance Yes No	at the time of initial application.				
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance					
	US Fish and Wildlife Wetland Identification man: Topographic man: Visual inspection (certification) of the proposed site				

Oil Conservation Division

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality				
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 				
Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 				
Within a 100-year floodplain. - FEMA map				
- TEWA map	Yes No			
 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 				
17. Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.				
Name (Print): Crystal Walker Title: Regulatory Coordinator Signature: Stal Walker Date: 5'-3/-/6				
Signature: Date:				
e-mail address: <u>crystal.walker@conocophillip.com</u> Telephone: <u>505- 326-9837</u>				
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)				
OCD Representative Signature: For at D. Kelly Approval Date: 8/10/2	2016			
Title:Compliance Officer OCD Permit Number:				
19. <u>Closure Report (required within 60 days of closure completion)</u> : 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:				
20. Closure Method: Waste Excavation and Removal On-Site Closure Method If different from approved plan, please explain.	op systems only)			
21. Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please intermark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique	dicate, by a check			

22. Operator Closure Certification:

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.			
Name (Print):	Title:		
Signature:	Date:		
e-mail address:	Telephone:		

Burlington Resources Oil & Gas Company, LP BGT Modification

Burlington Resources is requesting to modify the below-grade tank permit for SAN JUAN 28-6 UNIT 137M.

Burlington Resources found that the SAN JUAN 28-6 UNIT 137M shares a BGT with the SAN JUAN 28-6 UNIT 121N and would like to modify the existing permit.