District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources
Department

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy the the grape prints of NMOCD District of Office.

Revised June 6, 2013

RECEIVEDRECEIVED

Strict Office.

Pit, Below-Grade Tank By OCD; Dr. Oberding at 2:36 pm, Jun 07, 2016

OGRID #:	Proposed Alternative Method Permit of Closure Plan Application
acity and that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the irronnent. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances. Perator: BP America Production Company OGRID #:	 ☐ Permit of a pit or proposed alternative method ☐ Closure of a pit, below-grade tank, or proposed alternative method ☐ Modification to an existing permit/or registration ☐ Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,
perator: BP America Production Company OGRID #:	Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
acility or well name:Gallegos Canyon Unit 219E	lease be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the nvironment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
acility or well name: Gallegos Canyon Unit 219E PI Number: 3004525449	Operator: BP America Production Company OGRID #: 778
PI Number: 3004525449 OCD Permit Number:	Address: 200 Energy Court, Farmington, NM 87401
Pit: Subsection F, G or J of 19.15.17.11 NMAC County: Sam Juan County: Subsection F, G or J of 19.15.17.11 NMAC County: Subsection F, G or J of 19.15.17.11 NMAC County: Subsection F, G or J of 19.15.17.11 NMAC County: Subsection F, G or J of 19.15.17.11 NMAC County: Subsection F, G or J of 19.15.17.11 NMAC County: String-Reinforced Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced New Yolume: bbl Dimensions: L x W x D Dimensions: L Description X W X D Dimensions: L Steel Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other Single walled/double bottom; no visible sidewalls iner type: Thickness mil HDPE PVC Other Description Descriptio	Facility or well name: Gallegos Canyon Unit 219E
Pit: Subsection F, G or J of 19.15.17.11 NMAC County: Sam Juan County: Subsection F, G or J of 19.15.17.11 NMAC County: Subsection F, G or J of 19.15.17.11 NMAC County: Subsection F, G or J of 19.15.17.11 NMAC County: Subsection F, G or J of 19.15.17.11 NMAC County: Subsection F, G or J of 19.15.17.11 NMAC County: String-Reinforced Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced New Yolume: bbl Dimensions: L x W x D Dimensions: L Description X W X D Dimensions: L Steel Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other Single walled/double bottom; no visible sidewalls iner type: Thickness mil HDPE PVC Other Description Descriptio	API Number: 3004525449 OCD Permit Number:
urface Owner: State	U/L or Qtr/Qtr D Section 23 Township 28N Range 12W County: San Juan
Pit: Subsection F, G or J of 19.15.17.11 NMAC Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced iner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other Dimensions: L x W x D Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Liner type: Thickness mil HDPE PVC Other Other Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Low Chloride Drilling Fluid yes no Low Chloride Drilling Fluid yes no Lined Nother Low Chloride Drilling Fluid yes no Lined Nother Low Chloride Drilling Fluid yes no Low Chloride	Center of Proposed Design: Latitude <u>36.65305</u> Longitude <u>-108.08733</u> NAD: □1927 ☑ 1983
emporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced String-Reinforced Welded Factory Other Volume: bbl Dimensions: L x W x D Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK A olume: 95 bbl Type of fluid: Produced water ank Construction material: Steel Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other Single walled/double bottom; no visible sidewalls alternative Method:	Surface Owner: ☑ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment
Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK A olume: 95	Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: □ Drilling □ Workover □ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management Low Chloride Drilling Fluid □ yes □ no □ Lined □ Unlined Liner type: Thickness mil □ LLDPE □ HDPE □ PVC □ Other □ String-Reinforced □ String-Reinforced
Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK A olume: 95	Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other Single walled/double bottom; no visible sidewalls iner type: Thicknessmil HDPE PVC Other	3. ■ Below-grade tank: Subsection I of 19.15.17.11 NMAC TANK A Wolume: 95bbl Type of fluid: Produced water
Visible sidewalls and liner Visible sidewalls only Other <u>Single walled/double bottom; no visible sidewalls</u> iner type: Thickness mil HDPE PVC Other	
iner type: Thicknessmil	
Alternative Method:	
	Liner type: Thicknessmil
	Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	l, hospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
7. Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	eptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa	
lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
 initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.	
and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	cuments are
 □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. 	
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	15.17.9 NMAC
 ☐ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
 attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment 	
 ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC 	
☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan	
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan	
Emergency Response Plan Oil Field Waste Stream Characterization	
☐ Monitoring and Inspection Plan ☐ Erosion Control Plan	
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	72.17
<u>Proposed Closure</u> : 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative	luid Management Pit
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only)	
☐ On-site Closure Method (Only for temporary pits and closed-loop systems) ☐ In-place Burial ☐ On-site Trench Burial ☐ Alternative Closure Method	
14. Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be	attached to the
closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	rce material are Please refer to
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain.	Yes No
- FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC 15.17.11 NMAC
Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ief.
Name (Print): Title:	and the second s
Signature: Date:	
e-mail address:	
e-mail address:	
e-mail address:	
e-mail address: Telephone:	the closure report.
e-mail address: Telephone:	the closure report.
e-mail address: Telephone:	the closure report. complete this

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure report belief. I also certify that the closure complies with all applicable closure requirement	
Name (Print): Steve Moskal	Title: Field Environmental Coordinator
Signature: Mun)	Date:April 29, 2016
e-mail address: steven.moskal@bp.com	Telephone: (505) 326-9497

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Gallegos Canyon Unit #219E <u>API No. 3004525449</u> Unit Letter H, Section 21, T28N, R12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

 Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice was provided and documented in the attached email.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported for recycling.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	< 0.041
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	< 0.083
TPH	US EPA Method SW-846 418.1 or 8015 extended	100	<u><50</u>
Chlorides	US EPA Method 300.0 or 4500B	250 or background	<30

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled for TPH, BTEX and chloride. BTEX, TPH and chloride concentrations were below the stated limits. The field report and laboratory reports are attached.

7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.

- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

 Sampling results indicate no significant release has occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

Sampling results determine no significant release has occurred. Area was backfilled with clean, earthen material and is within the active well pad.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

The area has been backfilled and will be reclaimed once the well has been plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included including photos of reclamation completion.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District III

1000 Rio Brazos Road, Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rei	ease Notino	catio	n and Co	orrective A	cuon	1			
						OPERA	ГOR		☐ Initia	al Report	\boxtimes	Final Report
Name of Co	ompany: B	P				Contact: Ste	eve Moskal			•		
						Telephone No.: 505-326-9497						
Facility Na	me: Galleg	os Canyon U	nit 219E	3		Facility Type: Natural gas well						
Surface Ow	ner: State			Mineral C)wner:	State			API No	. 30045254	149	
				LOCA	ATIO	N OF REI	LEASE					
Unit Letter	Section	Township	Range	Feet from the			Feet from the	East/V	West Line	County: Sa	an Juan	L ₁
D	23	28N	12W	870	North	1	800	West				
		Latit	ude3	6.65305		_ Longitude	-108.08733					
				NAT	URE	OF REL	EASE					
Type of Rele	ase: none					Volume of	Release: unknow	vn .				
Source of Release: below grade tank – 95 bbl						The second secon	Iour of Occurrence	e:	Date and	Hour of Dis	covery:	none
Was Immediate Notice Given? ☐ Yes ☒ No ☐ Not Red						If YES, To	Whom?		<u> </u>			
			Yes 🗵	No Not Re	equired							
By Whom? Was a Watercourse Reached?								the Wate	preource			
was a water	course Reac		Yes 🗵] No		II IES, VC	nume impacting (ine wate	acourse.			
If a Watercon	ırse was Im	nacted. Descri	be Fully.*	k								
			,									
Dogovilho Cox	an of Dunhl	om and Damad	ial Aatio	n Takan * Campli	na of th	a goil banaath	the DGT was do	ne durin	a removal	Soil analys	ic recul	ted for
BTEX, TPH	and chlorid	e below standa	rds. Fiel	ld reports and lab	oratory	results are atta	iched.	ne durin	g removai.	Son anarys	is resur	icu ioi
Describe Are	a Affected	and Cleanup A	ction Tak	cen.* No action no	ecessary	. Final labora	tory analysis supp	orted cl	losure of th	e BGT locat	ion.	
T1 1 1	C 11 - 1 11 - 1	· C · · · · · · · · · · · · · · · ·	1	latura and same	1040 40 4	ha haat af my	Imaveladas and u	ndorator	ad that nura	uent to NIM	2CD ***	log and
regulations a	ry that the i Il operators	ntormation giv are required to	report ar	dor file certain r	elease r	ne best of my notifications ar	id perform correc	tive acti	ions for rele	eases which	may en	danger
public health	or the envir	onment. The	acceptanc	ce of a C-141 repo	rt by th	e NMOCD m	arked as "Final R	eport" d	oes not reli	eve the oper	ator of	liability
should their	perations h	ave failed to a	dequately	investigate and re	emediat	te contaminati	on that pose a thr	eat to gr	ound water	, surface wa	ter, hur	nan health
or the environ	nment. In a	ddition, NMO vs and/or regul	CD accep	tance of a C-141	report o	loes not reliev	e the operator of	responsi	bility for co	omphance w	iin any	otner
rederal, state,	or rocar ray	vs and/or regul	attions.				OIL CON	SERV	ATION	DIVISIO	N	
	01	m.						2000000				
Printed Name	e: Steve Mo	skal				Approved by	Environmental S	pecialist	:			
Title: Field E	nvironment	al Coordinator				Approval Dat	e:	I	Expiration I	Date:		
						Conditions of	Арргочаг.			Attached		
Date: April 2	urface Owner: State Mineral Owner: State Mineral Owner: State API No. 3004525449											

^{*} Attach Additional Sheets If Necessary

bp



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

March 4, 2016

Bureau of Land Management Katherina Diemer 6251 College Suite A Farmington, NM 87402

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank

Well Name: GALLEGOS CANYON UNIT 219E

API#: 3004525449

Dear Mrs. Diemer,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about March 7, 2016. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

If witnessing of the tank removal is required please contact me for a specific time (505)-326-9497.

Sincerely,

Steven Moskal

BP America Production Company

Moskal, Steven

From:

Railsback, Farrah (CH2M HILL)

Sent:

Friday, March 04, 2016 10:39 AM

To:

'Smith, Cory, EMNRD'; 'Fields, Vanessa, EMNRD (Vanessa.Fields@state.nm.us)'

Cc:

'jeffcblagg@aol.com'; 'blagg_njv@yahoo.com'; Moskal, Steven

Subject:

BP Pit Close Notification - GALLEGOS CANYON UNIT 219E

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US; VANESSA.FIELDS@STATE.NM.US

March 4, 2016

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 219E API 30-045-25449 (D) Section 23 – T28N – R12W San Juan County, New Mexico

Dear Mr. Cory Smith and Mrs. Vanessa Fields,

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around March 7, 2016.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Steven Moskal BP Field Environmental Coordinator

(505) 326-9497

Farrah Railsback
BGT Project Support
970-946-9199 -cell

This email and any attachments are intended only for the addressee(s) listed above and may contain confidential, proprietary, and/or privileged information. If you are not an intended recipient, please immediately advise the sender by return email, delete this email and any attachments, and destroy any copies of same. Any unauthorized review, use, copying disclosure or distribution of this email and any attachments is prohibited.

CHENT: BP	BLAGG EN P.O. BOX 87, BL	GINEERING, IN		API#: 3004	525449				
CLIENT:) 632-1199	107413	TANK ID (if applicble):	Α				
FIELD REPORT:	REPORT: (circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER:								
SITE INFORMATION	I: SITE NAME: GCU # 2	19E		DATE STARTED: (03/07/16				
QUAD/UNIT: D SEC: 23 TWP:	28N RNG: 12W PM:	NM CNTY: SJ	st: NM	DATE FINISHED:					
1/4-1/4/F00TAGE: 870'N / 800'\ LEASE #: SF078828	NW/NW LEASE TYPE PROD. FORMATION: DK CON	PE: FEDERAL STATE / STRIKE ITRACTOR: MBF - B. S		ENVIRONMENTAL SPECIALIST(S):	NJV				
REFERENCE POINT				GL ELEV.:	5,768'				
1) 95 BGT (SW/DB)	GPS COORD.: 36.6			The same of the sa	The second secon				
2)									
3)	GPS COORD.:		DISTANCE/BEA	ARING FROM W.H.:					
4)	GPS COORD.:		DISTANCE/BEA	ARING FROM W.H.:	1 2022				
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR I	LAB USED: HALL			OVM READING (ppm)				
1) SAMPLE ID: 5PC - TB @ 5	(95) SAMPLE DATE: 03/07/16	SAMPLE TIME: 1300	LAB ANALYSIS: 801	5B/8021B/300.0 (C	I) NA				
2) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:						
3) SAMPLEID:									
4) SAMPLEID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:						
SOIL DESCRIPTION	SOIL TYPE: SAND SILTY SAND SILT	T / SILTY CLAY / CLAY / GRAVE	EL/OTHER						
SOIL COLOR: DARK YELL		LASTICITY (CLAYS): NON PLASTIC							
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC		ENSITY (COHESIVE CLAYS & CODOR DETECTED: YES NO							
MOISTURE: DRY SLIGHTLY MOIST MOIST / W		CODON BETECTED. TESTINO	LAI LAVAIION -						
SAMPLE TYPE: GRAB (COMPOSITE) #		NY AREAS DISPLAYING WETNES	SS: YES NO EXPLAN	NATION -					
DISCOLORATION/STAINING OBSERVED: YES N									
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE									
EQUIPMENT SET OVER RECLAIMED AREA:			ABOVE-GRADE TAI	NK TO BE SET ATOP B	GT POSITION.				
OTHER:									
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. X NA f	n. X NA ft.	EXCAVATION EST	TIMATION (Cubic Yards)	:NA				
DEPTH TO GROUNDWATER: <50' N	EAREST WATER SOURCE: >1,000'	NEAREST SURFACE WATER:	<1,000' NMOC	CD TPH CLOSURE STD:	100 ppm				
SITE SKETCH	BGT Located: off on site	PLOT PLAN circ	cle: attached OVM	CALIB. READ. = NA	ppm RF =0,52				
	BERM		♠ ovm	CALIB. GAS = NA	ppm 14 0.02				
	\		N TIME	:: <u>NA</u> am/pm DATE:	NA				
FEN	PBGTL T.B. ~ 5		1	MISCELL. N	OTES				
, _,	X X X B.G.		l w	IO:					
			R	EF#: P-474					
BERM			<u>v</u>	ID: VHIXONEV	B2				
\\	WOODEN R.W.	Î	<u>P</u> .	J#:					
\\		SEPARATOR		ermit date(s):	0 				
_	()		O	CD Appr. date(s): ?	or Meter				
PROD	ТО		<u> IC</u>	ppm = parts per mil BGT Sidewalls Visible:					
TANK	√ W.H.	V	, epp ⊩	BGT Sidewalls Visible:	<u> </u>				
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO	N DEPRESSION: B.G. = RELOW GRADE: R = RELO	577.7	K - S.P.D.	BGT Sidewalls Visible:	Y / N				
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL	OW-GRADE TANK LOCATION; SPD = SAMPLE POIN	IT DESIGNATION; R.W. = RETAINING	WALL; NA - NOT N	lagnetic declination:	10°E				
APPLICABLE OR NOT AVAILABLE; SW-SINGLE NOTES: GOOGLE EARTH IMAGE	EWALL; DW - DOUBLE WALL; SB - SINGLE BOTTON ERV DATE: 3/15/2015	/i; DB - DOUBLE BOTTOM. ONSITE:O3/07/1							
NOIES. COUCLE LAIVITINAGE	ALTE MATERIAL OF TOTAL TO	ONSITE. USIOTI	10						

Analytical Report

Lab Order 1603345

Date Reported: 3/9/2016

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

GCU #219E

gg Engineering

Lab ID: 1603345-001

Project:

Client Sample ID: 5PC-TB@5'(95)

Collection Date: 3/7/2016 1:00:00 PM

Matrix: MEOH (SOIL) Received Date: 3/8/2016 7:45:00 AM

Analyses	Result	PQL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 300.0: ANIONS					Analyst	: LGT
Chloride	ND	30	mg/Kg	20	3/8/2016 11:31:19 AM	24145
EPA METHOD 8015M/D: DIESEL RAN	GE ORGANIC	S			Analyst	: KJH
Diesel Range Organics (DRO)	ND	9.9	mg/Kg	1	3/8/2016 11:39:09 AM	24125
Motor Oil Range Organics (MRO)	ND	50	mg/Kg	1	3/8/2016 11:39:09 AM	24125
Surr: DNOP	104	70-130	%Rec	1	3/8/2016 11:39:09 AM	24125
EPA METHOD 8015D: GASOLINE RAM	IGE				Analyst	: NSB
Gasoline Range Organics (GRO)	ND	4.1	mg/Kg	1	3/8/2016 10:32:54 AM	24107
Surr: BFB	104	66.2-112	%Rec	1	3/8/2016 10:32:54 AM	24107
EPA METHOD 8021B: VOLATILES					Analyst	: NSB
Benzene	ND	0.041	mg/Kg	1	3/8/2016 10:32:54 AM	24107
Toluene	ND	0.041	mg/Kg	1	3/8/2016 10:32:54 AM	24107
Ethylbenzene	ND	0.041	mg/Kg	1	3/8/2016 10:32:54 AM	24107
Xylenes, Total	ND	0.083	mg/Kg	1	3/8/2016 10:32:54 AM	24107
Surr: 4-Bromofluorobenzene	106	80-120	%Rec	1	3/8/2016 10:32:54 AM	24107

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits Page 1 of 5
- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified

(M to Y) solddu8 TiA ANALYSIS LABORATORY 5 pt. composite sample This serves as notice of this possibility. Any sub-contracted data will be clearly notared on the analytical report HALL ENVIRONMENTAL John Ritchie VRITCHFEC elqmes derð CORRESPONDING VID & REFERENCE # WHEN APPLICABLE; BILL DIRECTLY TO BP USING THE CIRCLED CONTACT WITH 4901 Hawkins NE - Albuquerque, NM 87109 Chloride (soil - 300.0 / water - 300.1) Fax 505-345-4107 www.hallenvirormental.com (AOV-imas) 0158 VMOSEHQFEC Steve Moskal Analysis Request SSEOB (NOV) 8081 Pesticides / 8082 PCB's Anions (F, Cl, NO₃, NO₂, PO₄, SO₄) Vance Hixon RCRA 8 Metals Tel. 505-345-3975 P-474 (ZMI20758 10 01 E8) HA9 EDB (Method 504.1) (F.81A bortsoM) H91 dis ハプント | Reference # грн вот5в (бко / рко / мко) Remarks: (VIOSED) HTT + 38TM + X3T8 (81508) 24MT + 281M + X3T8 > 106 1603345 HEAL No. Time SAME DAY 100splic **%**□ **NELSON VELEZ NELSON VELEZ** GCU # 219E may be subcontrasted to other accredited laboratories. Preservative N Rush Type Cool Sample Temperature: 以Yes Turn-Around Time: Project Manager. Project Name: ☐ Standard Type and # Container JEN NA 1-707 Received by: Project #: Received by Sampler On Ice: Level 4 (Full Validation) Sample Request ID (36) Chain-of-Custody Record W BLOOMFIELD, NM 87413 BLAGG ENGR. / BP AMERICA SPC - TB @ (505) 632-1199 Relanguished by: P.O. BOX 87 □ Other Watrix SOIL 200 Time $\frac{1}{\omega}$ lailing Address: A/GC Package EDD (Type) mail or Fax#; ccreditation: 2 Standard NELAP 1/2 hone #: 3/7/16 Date Tent.

Hall Environmental Analysis Laboratory, Inc.

WO#:

1603345

09-Mar-16

Client:

Blagg Engineering

Project:

GCU #219E

Sample ID MB-24145

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 24145

PQL

1.5

RunNo: 32667

Prep Date:

HighLimit

3/8/2016

Analysis Date: 3/8/2016

SeqNo: 999588

Units: mg/Kg

%RPD

Qual

Analyte Chloride

Result ND

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: LCSS Batch ID: 24145

RunNo: 32667

Prep Date: 3/8/2016

Sample ID LCS-24145

Analysis Date: 3/8/2016

SegNo: 999589

Units: mg/Kg

HighLimit %RPD LowLimit

Analyte

PQL

15.00

%REC 92.0

Qual

Chloride

14

110

RPDLimit

SPK value SPK Ref Val %REC LowLimit

RPDLimit

1.5

SPK value SPK Ref Val

Value exceeds Maximum Contaminant Level. D Sample Diluted Due to Matrix

Oualifiers:

Holding times for preparation or analysis exceeded Η

ND Not Detected at the Reporting Limit R RPD outside accepted recovery limits В Analyte detected in the associated Method Blank

E Value above quantitation range

Analyte detected below quantitation limits

Page 2 of 5

P Sample pH Not In Range

Reporting Detection Limit RL

% Recovery outside of range due to dilution or matrix S

Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#:

1603345

09-Mar-16

Client:

Blagg Engineering

Project:

GCU #219E

Sample ID LCS-24125	SampType: LCS			TestCode: EPA Method 8015M/D: Diesel Range Organics						
Client ID: LCSS	Batch ID: 24125			RunNo: 32636						
Prep Date: 3/8/2016	Analysis Date: 3/8/2016			SeqNo: 998600			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	50	10	50.00	0	99.9	65.8	136			
Surr: DNOP	4.1		5.000		82.5	70	130			

Sample ID MB-24125 SampType: MBLK			Tes	TestCode: EPA Method 8015M/D: Diesel Range Organics						
Client ID: PBS	Batch ID: 24125			RunNo: 32636						
Prep Date: 3/8/2016	Analysis D	Analysis Date: 3/8/2016			SeqNo: 998602			Units: mg/Kg		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Motor Oil Range Organics (MRO)	ND	50								
Surr: DNOP	8.7		10.00		87.5	70	130			

Qualifiers:

* Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

Page 3 of 5

P Sample pH Not In Range

RL Reporting Detection Limit
W Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

WO#:

1603345

09-Mar-16

Client:

Blagg Engineering

Project:

GCU #219E

Sample ID MB-24107	SampType: MBLK Batch ID: 24107 Analysis Date: 3/8/2016			TestCode: EPA Method 8015D: Gasoline Range						
Client ID: PBS				RunNo: 32632						
Prep Date: 3/7/2016				SeqNo: 999108			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	ND	5.0								
Surr: BFB	1000		1000		105	66.2	112			
Sample ID LCS-24107	SampType: LCS			Tes	TestCode: EPA Method 8015D: Gasoline Range					

Sample ID LCS-24107	s	TestCode: EPA Method 8015D: Gasoline Range									
Client ID: LCSS	Batch ID: 24107 Analysis Date: 3/8/2016			E	RunNo: 3	2632					
Prep Date: 3/7/2016				SeqNo: 999109			Units: mg/Kg				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Gasoline Range Organics (GRO)	26	5.0	25.00	0	103	80	120				
Surr: BFB	1100		1000		113	66.2	112			S	

Qualifiers:

* Value exceeds Maximum Contaminant Level.

D Sample Diluted Due to Matrix

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

S % Recovery outside of range due to dilution or matrix

B Analyte detected in the associated Method Blank

E Value above quantitation range

J Analyte detected below quantitation limits

Page 4 of 5

P Sample pH Not In Range

RL Reporting Detection Limit
W Sample container temperature is out of limit as specified

Hall Environmental Analysis Laboratory, Inc.

1.1

3.2

1.2

0.050

0.10

1.000

3.000

1.000

WO#:

1603345

09-Mar-16

Client:

Blagg Engineering

Project:

Ethylbenzene

Xylenes, Total

Surr: 4-Bromofluorobenzene

GCU #219E

Sample ID MB-24107	SampType: MBLK			Tes	tCode: El					
Client ID: PBS	Batch ID: 24107			RunNo: 32632						
Prep Date: 3/7/2016	Analysis Date: 3/8/2016			8	SeqNo: 9	99122	Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.1		1.000		109	80	120			
Sample ID LCS-24107	SampType: LCS			TestCode: EPA Method 8021B: Volatiles						
Client ID: LCSS	Batch ID: 24107			RunNo: 32632						
Prep Date: 3/7/2016	Analysis Date: 3/8/2016			SeqNo: 999123			Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.1	0.050	1.000	0	107	80	120			
	1.1	0.050	1,000	0	107	80	120			

0

0

106

106

118

80

80

80

120

120

120

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S % Recovery outside of range due to dilution or matrix
- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits

Page 5 of 5

- P Sample pH Not In Range
- RL Reporting Detection Limit
- W Sample container temperature is out of limit as specified



Hall Environmental Analysis Laboratory 1901 Hawkins NL Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107

Sample Log-In Check List

Website: www.hallenvironmental.com ReplNo: 1 Work Order Number, 1603345 BLAGG Olient Name: Received by/date: Joe Archuleta 3/8/2016 7:45:00 AM Logged By: 3/8/2016 8:05:13 AM Completed By: Joe Archuleta Reviewed By: 03/08/1L 70 Chain of Custody No L Not Present V Yes | 1 Custody seals intact on sample bottles? Yes V No 🗌 Not Present 2. Is Chain of Custody complete? 3. How was the sample delivered? Counter Log In No 🗌 NA 🔲 Yes V 4. Was an attempt made to cool the samples? NA 🗍 No . Were all samples received at a temperature of >0° C to 6,0°C Yes V No _ Yes V Sample(s) in proper container(s)? No I Yes V Sufficient sample volume for indicated test(s)? No L Yes V 8 Are samples (except VOA and ONG) properly preserved? No V NA 🗌 Yes 9. Was preservative added to bottles? Yes I No [No VOA Vials V 10. VOA viets have zero headspace? Yes L No Y 11. Were any sample containers received broken? # of preserved battles checked for pH: No L Yes Y 12. Does paperwork match bottle labels? (<2 or >12 unless noted) (Note discrepancies on chain of custody) Adjusted? No _ 13. Are matrices correctly identified on Chain of Custody? Yes V Yes V No _ 14, is it clear what analyses were requested? Checked by No -Yes V 15. Were all holding times able to be met? (If no, notify customer for authorization.) Special Handling (if applicable) 16. Was client notified of all discrepancies with this order? Yes No L NA W Person Notified: Date Phone Fax In Person Vin' | eMail By Whom! Regarding Client Instructions: 17. Additional remarks. 18. Cooler Information Condition | Seal Intact | Seal No Seal Date Signed By Cooler No Temp C

1.6

Yes

Good



