For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

	RECEIVED			
Pit, Below-Grade Tank, or	By kcollins at 2:45 pm, May 23, 2016			
Proposed Alternative Method Permit or Closure Plan Application	<u>on</u>			
15259 Type of action: Below grade tank registration Dermit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure of a pit, below-grade tank, or proposed alternative method	alum en la trala			
Closure plan only submitted for an existing permitted or non-permitted pit, b or proposed alternative method	below-grade tank,			
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alterna	tive reauest			
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface w environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's	ater, ground water or the			
1. Operator: <u>ConocoPhillips Company</u> OGRID # <u>217817</u>				
Address: P.O. Box 4289, Farmington, New Mexico 87499				
Facility or well name:				
API Number:				
U/L or Qtr/Qtr _ D Section _33 Township _31N Range _11W County: San Juan				
Center of Proposed Design: Latitude <u>36.860866</u> °N Longitude <u>- 108.018483</u> °W NAD: 1927 [□ 1983 ⊠			
Surface Owner: X Federal State Private Tribal Trust or Indian Allotment				
2				
<u>Pit:</u> Subsection F, G or J of 19.15.17.11 NMAC				
Temporary: Drilling Workover				
Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling F	luid 🗌 yes 🗌 no			
Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other	0.			
String-Reinforced	-			
Liner Seams: 🗌 Welded 🗍 Factory 🗋 Other Volume:bbl Dimensions: L	x Wx D			
3. Below-grade tank: Subsection I of 19.15.17.11 NMAC				
Volume: <u>Max 120 bbl</u> Type of fluid: <u>Produced Water</u>				
Tank Construction material: <u>Metal</u>				
Secondary containment with leak detection 🗌 Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off				
Visible sidewalls and liner Visible sidewalls only Other				
Liner type: Thickness mil HDPE PVC Other Unspecified				
4.				
Alternative Method:				
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.				
5.				
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)				
Chain link, six feet in height, two strands of barbed wire at top (<i>Required if located within 1000 feet of a permanent residence, school, hospital, institution or church</i>)				
Four foot height, four strands of barbed wire evenly spaced between one and four feet				
Alternate. Please specify				

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible) Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks. **General siting** Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. Yes No NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 🗌 NA TYes No Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit . 🗌 NA NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance Yes No adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Yes No Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Within an unstable area. (Does not apply to below grade tanks) Yes No Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map Yes No Within a 100-year floodplain. (Does not apply to below grade tanks) FEMA map **Below Grade Tanks** Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured Yes No from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site □ Yes □ No Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, Yes No or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial Yes No application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock Yes No watering purposes, or 300 feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site

6.

 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No		
Temporary Pit Non-low chloride drilling fluid			
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No		
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No		
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No		
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No		
Permanent Pit or Multi-Well Fluid Management Pit			
 Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No		
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No		
 Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No		
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No		
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.10 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC nd 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:			
II. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.			

^{12.} <u>Permanent Pits Permit Application Checklist</u> : Subsection B of 19.15.17.9 NMAC <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the</i>	locuments are			
attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC				
 Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC 				
 Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC 				
 Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan 				
 Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC 				
 Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan 				
 Oil Field Waste Stream Characterization Monitoring and Inspection Plan 				
 Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC 				
^{13.} Proposed Closure: 19.15.17.13 NMAC				
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.				
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	uid Management Pit			
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only)				
On-site Closure Method (Only for temporary pits and closed-loop systems)				
Alternative Closure Method				
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.				
 Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC 				
 Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 				
 Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 				
15.				
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are				
provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	lease rejer to			
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA			
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA			
 Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	☐ Yes ☐ No ☐ NA			
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	🗌 Yes 🗌 No			
- Topographic map; Visual inspection (certification) of the proposed site				
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No			
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No			
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No			
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No			
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance				
Form C-144 Oil Conservation Division Page 4 o	f 6			

 adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality 	🗌 Yes 🗌 No			
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Image: Confirmation or verification or map from the NM EMNRD-Mining and Mineral Division				
Within an unstable area.				
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 				
Within a 100-year floodplain. - FEMA map	🗌 Yes 🗌 No			
 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Stil Reclamation Plan - based upon the appropriate requirements of 19.15.17.13 NMAC 				
17. Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.				
Name (Print): Crystal Walker Title: Regulatory Coordinator				
Signature: Date: 5/12/2016				
e-mail address:crystal.walker@conocophillip.comTelephone:505326-9837				
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)				
OCD Representative Signature: Vanessa Fields Approval Date: 12-21	-2016			
Environmental Specialist				
Title: OCD Permit Number:				
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed. □ Closure Completion Date:				
20.				
 20. Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-logonal of the formation of the second of the second	oop systems only)			

22. Operator Closure Certification:

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.		
Name (Print):	Title:	
Signature:	Date:	
e-mail address:	Telephone:	

ConocoPhillips Company BGT Modification

ConocoPhillips Company is requesting to modify the below-grade tank permit for HEATON 101S.

ConocoPhillips Company found that the HEATON 101S shares a BGT with the HEATON LS 6A and would like to modify the existing permit.