Form 3160-5 (June 2015)

## UNITED STATES

FORM APPROVED
OMB NO. 1004-0137
Expires: January 31, 201

BUREAU OF LAND MANAGEMENT  SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.					Expires: January 31, 2018		
					5. Lease Serial No. NMSF078860		
					6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE - Other instructions on page 2					7. If Unit or CA/Agreement, Name and/or No. NMNM132981A		
Type of Well     Oil Well	8. Well Name and No. NAGEEZI UNIT 627H						
Name of Operator     DJR OPERATING LLC	9. API Well No. 30-045-35649-00-X1						
3a. Address 1 ROAD 3263 AZTEC, NM 87410	3b. Phone No Ph: 505-63	(include area code 2-3476	)	10. Field and Pool or E BASIN MANCO			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				11. County or Parish, State			
Sec 30 T24N R8W SWSW 1133FSL 0447FWL					SAN JUAN COUNTY, NM		
12. CHECK THE AI	PPROPRIATE BOX(ES)	TO INDICA	ΓE NATURE C	F NOTICE,	REPORT, OR OTH	ER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION						
☐ Notice of Intent	☐ Acidize	☐ Deepen ☐ Pr		☐ Producti	on (Start/Resume)	■ Water Shut-Off	
☐ Alter Casing		☐ Hydraulic Fracturing		☐ Reclama	tion	□ Well Integrity	
Subsequent Report	☐ Casing Repair	□ New	Construction	☐ Recomp	lete	Other	
☐ Final Abandonment Notice	☐ Change Plans	Plug and Abandon		☐ Tempora	rily Abandon	Drilling Operations	
BP	☐ Convert to Injection ☐ Plug Back ☐ Water I			isposal			
13. Describe Proposed or Completed Ope If the proposal is to deepen direction. Attach the Bond under which the wor following completion of the involved testing has been completed. Final Al determined that the site is ready for for	ally or recomplete horizontally, rk will be performed or provide operations. If the operation re- pandonment Notices must be file	give subsurface the Bond No. or sults in a multipl	locations and measurable with BLM/BI/ completion or rec	ured and true ver A. Required sub ompletion in a n	tical depths of all pertine sequent reports must be ew interval, a Form 3160	ent markers and zones. filed within 30 days 0-4 must be filed once	
AMENDED Intermediate Casiper the NMOCD. 11/26/19: MIRU ad 920. NU 1 inch 5K Cameron wellhead. P pipe rams, kill valves, check v valve and inside BOP valve 25 casing to 1500 high 30 min. P Drill 8.75 inch hole to 443 ft. 11/27/19: Drill 8.75 inch hole to 11/28/19: Drill 8.75 inch hole to 11/29/19: Drill 8.75 inch hole to 11/30/19: Run 139 jts of 7 inch	1 inch 3K BOP on pre-set T annular and TIW 250 lo alve, lower Kelly, choke n 50 low 5 min, 3000 high fo all tested good & recorded to 3591 ft. o 4666 ft. o 5864 ft.	t 9.625 36# Jt w 5 min. 1500 nanifold and v or 10 min. PT d on chart (3rd	55 surface casin ) high 10 min. F alves, full openi pre-set 9.625 ir I party Wilson S	g with install T blind rams ing safety ach surface Services)	11		
14. I hereby certify that the foregoing is	Electronic Submission #				System		
For DJR OPERATING LL¢, sent to the Farmington Committed to AFMSS for processing by JOE KILLINS on 03/13/2020 (20JK0166SE)							
Name (Printed/Typed) SHAW-MA	ARIE FORD		Title REGUL	ATORY SPE	CIALIST		
Signature (Electronic S	Submission)		Date 03/13/2	2020			
	THIS SPACE FO	R FEDERA	L OR STATE	OFFICE US	SE .		
Approved By ACCEPTED			JOE KILLINS <sub>Title</sub> PETROLEUM ENGINEER		Date 03/13/2020		
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			Office Farming	iton			

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

## Additional data for EC transaction #507089 that would not fit on the form

## 32. Additional remarks, continued

cement crew. PT 5000 psi on lines. Test good. Cement with 50% excess on both lead and tail. 10 bbls 7% KCL water spacer at 8.3 lb. Followed by 50 bbls (74 sx) 11 ppg, 3.82 yield, 25.75 gps IntegraGaurd EZ II spacer. LEAD: 168 bbls (404 sx) 12.3 ppg, 2.34 yield, 13.4 gps. TAIL: 62 bbls (233 sx) 13.5 ppg, 1.5 yield, 7.24 gps. Displace with 222 bbls FW. Bump plug. Check floats. Floats held. 10 bbls good cement back to surface.