Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an

5. Lease Serial No. NMNM6681 6 If Indian, Allottee or Tribe Name

abandoned well. Use form 3160-3 (APD) for such proposals.					EASTERN NAVAJO			
SUBMIT IN TRIPLICATE - Other instructions on page 2					7. If Unit or CA/Agreement, Name and/or No. NMNM135229A			
1. Type of Well ☑ Oil Well ☐ Gas Well ☐ Other					8. Well Name and No. NORTH ALAMITO UNIT 335H			
Name of Operator DJR OPERATING LLC SHAW-MARIE FORD E-Mail: sford@djrllc.com					9. API Well No. 30-043-21340-00-X1			
3a. Address 1 ROAD 3263 AZTEC, NM 87410			nclude area code 3476)	10. Field and Pool or Exploratory Area WILDCAT BASIN MANCOS			
4. Location of Well (Footage, Sec., T		11. County or Parish, SANDOVAL CO			or Parish, St	r Parish, State		
Sec 31 T23N R7W NWSW 20 36.181531 N Lat, 107.621937					OVAL COL	JNTY, NM		
12. CHECK THE AF	PPROPRIATE BOX(ES) TO) INDICAT	E NATURE O	F NOTICE,	REPORT,	OR OTHE	ER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION							
☐ Notice of Intent	☐ Acidize ☐ I		pen 🔲 Produc		etion (Start/Resume)		☐ Water Shut-Off	
_	☐ Alter Casing	☐ Hydra	ulic Fracturing	□ Reclams	□ Reclamation		■ Well Integrity	
■ Subsequent Report	□ Casing Repair	☐ New Construction		☐ Recomplete			⊘ Other	
☐ Final Abandonment Notice	☐ Change Plans	Change Plans Plug and Abandon Tempor		arily Aband	on	Drilling Operations		
BP	□ Convert to Injection	☐ Plug I	Back	■ Water Disposal				
If the proposal is to deepen directions Attach the Bond under which the wor following completion of the involved testing has been completed. Final At determined that the site is ready for fill Intermediate Casing & Cemer 3/14/20: MIRU ad 920. NU 11 inch 5K Cameron wellhead. Pippe rams, kill valves, check vivalve and inside BOP valve 25 casing to 1500 high 30 min. A regulatory agencies onsite to Drill 8.75 inch hole to 4296 ftk 3/15/20: Drill 8.75 inch hole to 3/16/20: RU casing crew. Run at 5456 ftKB. RU BJ cement co 55% excess on both lead & ta	k will be performed or provide the operations. If the operation results bandonment Notices must be filed of inal inspection. It inch 3K BOP on pre-set 9.6; T annular and TIW 250 low 5 alve, lower Kelly, choke man 50 low 5 min, 3000 high for 1 ll tested good & recorded on witness. B. 5511 ftKB. TOH. 130 jts of 7 inch 26 lb J55 L rew. PT 5000 psi on lines. Til as follows: pump 10 FW sp	Bond No. on f s in a multiple only after all re- 25 36# J55 5 min. 1500 nifold and va 10 min. PT p a chart (3rd p	surface casing high 10 min. Pives, full openiarty Wilson Set at 5501 ftKE ecorded on ch	A. Required sultering reclamation with install of the control of t	r with	rts must be fi a Form 3160-	led within 30 days 4 must be filed once d the operator has	
	true and correct. Electronic Submission #507 For DJR OPER Committed to AFMSS for proce	ATING LLC, essing by JO	sent to the Far E KILLINS on 0	mington	JK0177SE)			
•								
Signature (Electronic S	Submission)	1	Date 03/18/2	020				
	THIS SPACE FOR	FEDERAL	OR STATE	OFFICE U	SE			
Approved By ACCEPTED			JOE KILLI _{Title} PETROLE		EER		Date 03/18/2020	
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			Office Farming	jton				

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Additional data for EC transaction #507493 that would not fit on the form

32. Additional remarks, continued

LEAD: 161 bbls (386 sx), 12.3 ppg, 2.34 yield, 13.4 gps. TAIL: 61 bbls (230 sx) at 13.5 ppg, 1.49 yield, 7.24 gps. Displaced with 208 bbls FW. Drop plug. Bump plug at 2650 psi & hold for 5 min. Check floats. Floats held. 5 bbls good cement back to surface. TOC: surface BOC: 5501 ftKB. Skid rig to N. Alamito Unit 334H at 13:00.