

RECEIVED

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FEB 23 2012

Sundry Notices and Reports on Wells

Farmington Field Office
Bureau of Land Management

1. Type of Well
GAS

5. Lease Number
NM-019410

6. If Indian, All. or
Tribe Name

2. Name of Operator

7. Unit Agreement Name

ConocoPhillips

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

8. Well Name & Number
BRUINGTON 15G

9. API Well No.

30-045-35115

4. Location of Well, Footage, Sec., T, R, M

Surface: Unit L (NW/SW), 1795' FSL & 905' FWL, Section 15, T30N, R11W, NMPM

10. Field and Pool

BLANCO MV / BASIN DK

11. County and State
San Juan, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Other - Casing Report

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Plugging

☐ Non-Routine Fracturing

☐ Final Abandonment

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

RCVD MAR 5 '12
OIL CONS. DIV.
DIST. 3

13. Describe Proposed or Completed Operations

02/05/12 MIRU AWS 673. NU BOPE. PT csg to 600#/30min @ 09.15hrs on 02/07/12 Test - OK. PU & TIH w/ 8 3/4" bit. Tagged @ 192' & DO cmt to 232'. Drilled ahead to 4204' - Inter TD reached 02/10/12. Circ. hole & RIH w/ 7", J-55 (87jts, 20# ST&C, 12jts, 23# LT & C) csg set @ 4189' w/ ST @ 1781'. 1st Stage: Pre-flushed w/ 10bbls GW, 2bbls FW. Pumped scavenger w/ 19sx(57cf-10bbls=3.02yld) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Lead w/ 243sx(518cf-92bbls=2.13yld) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Tail w/ 97sx(134cf-24bbls=1.38yld) Type III cmt w/ 1% CaCl, .025 pps celloflake, & 0.2% FL-52. Shut dwn. Dropped plug & displaced w/ 105bbls FW, w/ 63bbls of MW. Bumped plug @ 00 27hrs 02/11/11. Open ST & circ. 1bbl cmt to surface WOC. 2nd Stage: Preflushed w/ 10bbls of FW, w/ 10bbls of GW & 10bbls of FW. Pumped scavenger w/ 19sx(57cf-10bbls=3.02yld) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Lead w/ 174sx(371cf-66bbls=2.13yld) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Shut dwn. Dropped plug & displaced w/ 72bbls of FW. Bumped plug & Close ST. Plug down @ 05:53hrs 02/11/12. Circ. 20bbls cmt to surface. WOC. TIH, & tagged 1775' & DO ST @ 1781'. PT 7" csg to 1500#/30min @ 16:00hrs on 02/12/12 Test - OK. Drilled w/ 6 1/4", tagged @ 4130' & DO cmt to 4204'. TD reached @ 6848' on 02/13/12. Circ. hole & RIH w/ 164jts, L-80, 4 1/2", 11 6#, LT&C csg set @ 6847'. RU to cmt Pre-flushed w/ 10bbls GW, 2bbls of FW. Pumped scavenger 9sx(28cf-5bbls=3.10yld) Premium lite HS FM, 0.25pps celloflake, 0.3% CD-32, 6.25pps LCM-1, & 1% FL-52 Tail w/ 208sx(412cf-73bbls=1.98yld) Premium lite HS FM, 0.25 pps celloflake, 0.3% CD-32, 6.25pps LCM-1 & 1% FL-52 Dropped plug & displaced w/ 106bbls FW. Bumped plug. Plug down @ 18:11hrs on 02/14/12. RD-cmt. WOC. ND BOPE NU WH. RD RR @ 00:15hrs on 02/15/12

PT will be conducted by Completion Rig. Results & TOC will appear on next report.

14. I hereby certify that the foregoing is true and correct.

Signed

Marie E. Jaramillo

Title Staff Regulatory Tech.

Date 02/22/12

(This space for Federal or State Office use)

APPROVED BY

Title

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

ADATED FOR RECORD
MAR 05 2012
FARMINGTON FIELD OFFICE
BY T. S. JAMES

Amend Sundry to include correct dates of 7" PT +