District I 1625 N. French Dr. Hobbs, NM 88240 District II 1301 W. Grand Avenue. Artesia. NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fc, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office

Pit, Closed-Loop System, Below-Grade Tank, or						
Proposed Alternative Method Permit or Closure Plan Applie	cation					
I ype of action. Permit of a pit, closed-loop system, below-grade tank, or proposed alto Closure of a pit, closed-loop system, below-grade tank, or proposed al Modification to an existing permit Closure plan only submitted for an existing permitted system, below-grade tank, or proposed alternative method	ternative method					
Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank, or alternative request						
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations, or ordinances						
Operator XTO Energy, Inc OGRID # 5380						
Address. 382 Road 3100, Azicc, New Mexico 87410						
Facility or well name: Florance LS #4						
API Number 30-045-0472 OCD Permit Number						
U/L or Qtr/Qtr K Section 18 Fownship 27N Range 8W County San Juan						
Center of Proposed Design Latitude 36 56972 Longitude -108 00250 NAD □1927 ⋈ 1983						
Surface Owner 🔲 Federal 🗌 State 🔲 Private 🔲 Tribal Trust or Indian Allotment						
Pit: Subsection I' or G of 19 15 17 11 NMAC						
Temporary Drilling Workover	RCVD MAR 13'12					
OIL VOITS: DIV.						
Permanent ☐ Linergency ☐ Cavitation ☐ P&A DIST. 3 ☐ Lined ☐ Unlined Liner type Thickness mil ☐ LLDPE ☐ HDPL ☐ PVC ☐ Other						
String-Reinforced						
	LxWxD					
3						
Closed-loop System: Subsection H of 19 15 17 11 NMAC						
Type of Operation P&A Drilling a new well Workover or Drilling (Applies to activities which require prior intent)	r approval of a permit or notice of					
Drying Pad Above Ground Steel Tanks Haul-off Bins Other						
☐ Lined ☐ Unlined I iner type Thickness mil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other						
Liner Seams						
4						
Below-grade tank: Subsection I of 19 15 17 11 NMAC						
Volume 21bbi Type of fluid Produced Water						
Tank Construction material <u>Steel</u>						
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off						
☐ Visible sidewalls and liner ☑ Visible sidewalls only ☐ Not labeled						
I mer type: Thicknessmil						
5						
Alternative Method:						

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19 15 17 11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate Please specify—Four foot height, steel mesh field fence (hogwire) with pipe top railing				
Netting: Subsection E of 19 15 17 11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Expanded Metal or Solid Vaulted Top Monthly inspections (If netting or screening is not physically feasible)				
Signs: Subsection C of 19 15.17 11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19 15 3 103 NMAC				
Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s). Requests must be submitted to the appropriate division district or the Santa l'e Environmental Bureau office for consideration of approval. Exception(s). Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.				
Siting Criteria (regarding permitting): 19.15.17 10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above-grade tanks associated with a closed-loop system.				
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search, USGS, Data obtained from nearby wells	☐ Yes ⊠ No			
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map: Visual inspection (certification) of the proposed site				
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application (Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo: Satellite image				
Within 1000 feet from a permanent residence, school hospital, institution or church in existence at the time of initial application.				
(Applies to permanent pits) - Visual inspection (certification) of the proposed site: Aerial photo, Satellite image	☐ Yes ☐ No 図 NA			
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application - NM Office of the State I ngineer - iWATLRS database search. Visual inspection (certification) of the proposed site				
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978. Section 3-27-3, as amended				
Within 500 feet of a wetland	☐ Yes 🖾 No			
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ⊠ No			
Within an unstable area - Engineering measures incorporated into the design, NM Bureau of Geology & Mineral Resources, USGS, NM Geological Society, Topographic map	☐ Yes ☒ No			
Within a 100-year floodplain	☐ Yes ⊠ No			

compact of the property of the

Femporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19 15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are ittached. ☐ Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19 15 17.9 NMAC ☐ Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19 15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 10 NMAC ☐ Design Plan - based upon the appropriate requirements of 19 15 17.12 NMAC ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19 15 17.12 NMAC ☐ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 15 17.9 NMAC ☐ Previously Approved Design (attach copy of design) API Number					
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15 17 9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19 15.17 9 Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19 15 17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15 17 11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19 15 17 12 NMAC Closure Plan (Please complete Boxes 14 through 18. if applicable) - based upon the appropriate requirements of Subsection C of 19.15 17 9 NMAC and 19 15 17 13 NMAC					
Previously Approved Design (attach copy of design) API Number					
Previously Approved Operating and Maintenance Plan API Number(Applies only to closed-loop system that use above ground steel tanks or haul-off bins and propose to implement waste removal for closure)					
Permanent Pits Permit Application Checklist: Subsection B of 19 15 17 9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19 15.17 9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19 15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19 15 17 11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15 17 11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19 15 17 12 NMAC I reeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19 15 17 11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19 15 17 9 NMAC and 19 15 17 13 NMAC					
Proposed Closure: 19 15 17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Lype Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Closed-loop System Alternative Proposed Closure Method Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method (Exceptions must be submitted to the Santa Γε Environmental Bureau for consideration)					
Waste Excavation and Removal Closure Plan Checklist: (19 15 17 13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17 13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection Γ of 19.15 17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15 17 13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19 15.17 13 NMAC					

Ton Carrier December 1997 Page 3105

Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: (19 15.17 13 Districtions: Please indentify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings. Use attachment if no control of the disposal of liquids and drill cuttings.					
facilities are required.					
Disposal Facility Name Disposal Facility Permit Number					
Disposal Facility Name Disposal Facility Permit Number:					
Will any of the proposed closed-loop system operations and associated activities occur on or in areas that will not be used for future service and operations? Yes (If yes, please provide the information below) No					
Required for impacted areas which will not be used for fidure service and operations: Soil Backfill and Cover Design Specifications based upon the appropriate requirements of Subsection II of 19 15 17 13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19 15 17 13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19 15.17 13 NMAC					
Siting Criteria (regarding on-site closure methods only): 19.15 17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.					
Ground water is less than 50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search, USGS, Data obtained from nearby wells	☐ Yes ☐ No ☐ NA				
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search, USGS. Data obtained from nearby wells					
Ground water is more than 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search, USGS, Data obtained from nearby wells					
Within 300 feet of a continuously flowing watercourse or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark) - Topographic map, Visual inspection (certification) of the proposed site					
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application - Visual inspection (certification) of the proposed site. Acrial photo: Satellite image					
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application - NM Office of the State Engineer - (WATERS database, Visual inspection (certification) of the proposed site					
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978. Section 3-27-3, as amended. - Written confirmation or verification from the municipality: Written approval obtained from the municipality					
Within 500 feet of a wetland - US Fish and Wildlife Wetland Identification map, Fopographic map, Visual inspection (certification) of the proposed site	☐ Yes ☐ No				
Within the area overlying a subsurface mine - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division					
 Within an unstable area. Figureering measures incorporated into the design, NM Bureau of Geology & Mineral Resources, USGS, NM Geological Society, Topographic map 					
Within a 100-year floodplain - FEMA map	☐ Yes ☐ No				
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plants as the common of the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC. Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection Γ of 19.15.17.13 NMAC. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC. Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC. Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC. Disposal Facility Name and Permit Number (for liquids drilling fluids and drill cuttings or in case on-site closure standards cann. Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC. Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC. Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC.	15 17.11 NMAC				

Page 6-144 On Seiserum in Deiste Page 9-315

Operator Application Certification: I hereby certify that the information submitted with this application is true accurate and complete to the best of my knowledge and belief.					
Name (Print) Logan Hixon TitleEnvironmental Technician					
Signature					
E-mail address: Logan Hixon'a)xtoenergy com Telephone (505)333-3683					
20. OCD Approval: ☐ Permit Application (including closure plan) ☑ Closure Plan (only) ☐ OCD Conditions (see attachment)					
OCD Representative Signature:					
Title: Compliance Office OCD Permit Number:					
Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17 13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed.					
Closure Completion Date:					
Closure Method: Waste Fxcavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-loop systems only) If different from approved plan, please explain					
Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: Instructions: Please indentify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities were utilized.					
Disposal Facility Permit Number					
Disposal Facility Name Disposal Facility Permit Number					
Yes (II yes, please demonstrate compliance to the items below) No					
Required for impacted areas which will not be used for future service and operations Site Reclamation (Photo Documentation)					
Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique					
24 Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check					
mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division)					
Proof of Deed Notice (required for on-site closure) Plot Plan (for on-site closures and temporary pits)					
Confirmation Sampling Analytical Results (if applicable)					
 ☐ Waste Material Sampling Analytical Results (required for on-site closure) ☐ Disposal I acility Name and Permit Number 					
Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique					
Site Reclamation (Photo Documentation)					
On-site Closure Location Latitude Longitude NAD 1927 1983					
Operator Closure Certification:					
I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.					
Name (Print) Title:					
Signature Date.					
E-mail address Telephone					

XTO Energy Inc. San Juan Basin Below Grade Tank Closure Plan

Lease Name: Florance LS #4 API No.: 30-045-06472

Description: Unit K, Section 18, Township 27N, Range 8W, San Juan County

In accordance with Rule 19.15.17.13 NMAC the following information describes the closure requirements of below-grade tanks on XTO Energy Inc. (XTO) locations. This is XTO's standard procedure for all below-grade tanks. A separate plan will be submitted for any below-grade tank which does not conform to this plan.

General Plan

- 1. XTO will close below-grade tanks within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the division requires because of imminent danger to fresh water, public health or the environment
- 2. XTO will close a below-grade tank that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofitted to comply with Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC.
- 3. XTO will close a permitted below-grade tank within 60 days of cessation of the below-grade tank's operation or as required by the transitional provisions of Subsection B of 19.15.17.17 NMAC in accordance with a closure plan that the appropriate division district office approves The closure report will be filed on form C-144.
- 4. XTO will remove liquids and sludge from below-grade tanks prior to implementing a closure method and will dispose of the liquids and sludge in a division-approved facility. Approved facilities and waste streams include:

Envirotech Permit No. NM01-0011 and IEI Permit No. NM 01-0010B

Soil contaminated by exempt petroleum hydrocarbons

Produced sand, pit sludge and contaminated bottoms from storage of exempt wastes

Basin Disposal Permit No. NM01-005 Produced water

- 5. X1O will remove the below-grade tank and dispose of it in a division approved facility or recycle, reuse, or reclaim it in a manner that the appropriate division district office approves.
- 6. XTO will remove any on-site equipment associated with a below-grade tank unless the equipment is required for some other purpose.

7. XTO will test the soils beneath the below-grade tank to determine whether a release has occurred. At a minimum 5 point composite sample will be collected along with individual grab samples from any area that is wet, discolored or showing other evidence of a release. Samples will be analyzed for BTEX, TPH and chlorides to demonstrate that the benzene concentration, as determined by EPA SW-846 methods 8021B or 8260B or EPA method that the division approves, does not exceed 0.2 mg/kg; total BTEX concentration, as determined by EPA SW-846 methods 8021B or 8260B or other EPA method that the division approves, does not exceed 50 mg/kg, the TPH concentration, as determined by EPA method 418 1 or other EPA method that the division approves, does not exceed 100mg/kg; and the chloride concentration, as determined by EPA method 300.1 or other EPA method that the division approves, does not exceed 250 mg/kg, or the background concentration, whichever is greater. XTO will notify the division of its results on form C-141.

Components	Test Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BIEX	EPA SW-846 8021B or 8260B	50
ТРН	EPA SW-846 418.1	100
Chlorides	EPA 300.1	250 or background

- If XTO or the division determines that a release has occurred, XTO will comply with 19.15.3.116 NMAC and 19.15 1.19NMAC as appropriate.
- If the sampling program demonstrates that a release has not occurred or that any release does not exceed the concentrations specified in Paragraph (4) of Subsection E of 19.15.17.13 NMAC, XTO will backfill the excavation with compacted, non-waste containing, earthen material; construct a division prescribed soil cover; recontour and re-vegetate the site
- 10. Notice of Closure operations will be given to the Aztec Division District III office between 72 hours and one week prior to the start of closure activities via email or verbally.

 The notification will include the following:
 - i. Operator's name
 - ii. Well Name and API Number
 - iii Location by Unit Letter, Section, Township, and Range

The surface owner shall be notified of XTO's proposal to close the BGT as per the approved closure plan using certified mail, return receipt requested

- 11. Re-contouring of location will match fit, shape, line, form and texture of the surrounding area. Re-shaping will include drainage control, prevent ponding, and prevent crosion. Natural drainages will be unimpeded and water bars and/or silt traps will be placed in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape
- 12. A minimum of 4 feet of cover shall be achieved and the cover shall include 1 foot of suitable material to establish vegetation at the site, or the background thickness of topsoil, whichever is greater
- 13. XTO will seed the disturbed areas the first growing season after the operator closes the pit. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will be used on federal lands.

Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

- 14. All closure activities will include proper documentation and be available for review upon request and will be submitted in closure report form to OCD within 60 days of closure of the below-grade tank. Closure report will be filed on form C-144 and incorporate the following:
 - i. Proof of closure notice to division and surface owner;
 - ii Details on capping and covering, where applicable;
 - iii. Inspection reports,
 - iv. Confirmation sampling analytical results;
 - v. Disposal facility name(s) and permit number(s);
 - vi. Soil backfilling and cover installation;
 - vii. Re-vegetation application rates and seeding techniques, (or approved alternative to re-vegetation requirements if applicable);
 - viii. Photo documentation of the site reclamation