

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N French Dr, Hobbs, NM 88240
District II - (575) 748-1283
811 S First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd, Aztec, NM 87410
District IV - (505) 476-3460
1220 S St Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.	30-045-35313
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>	
6. State Oil & Gas Lease No. V079180000, V089410000, B-10889	
7. Lease Name or Unit Agreement Name Escrito P16-2409	
8. Well Number 01H	
9. OGRID Number 282327	
10. Pool name or Wildcat Bisti-Lower Gallup	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6827 GR	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Encana Oil & Gas (USA) Inc.

3. Address of Operator
370 17th Street, Suite 1700 Denver, CO 80202

4. Well Location
SHL: Unit Letter P : 700 feet from the S line and 330 feet from the E line
BHL: Unit Letter M : 700 feet from the S line and 330 feet from the W line
Section 16 Township 24N Range 9W NMPM San Juan County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Utilized synthetic oil-based mud system, kicked off 3908' lateral at 4660' TVD/MD KOP on 3/27/12. TD reached 04/08/12. TD at 9585' MD/4471' TVD. Set production liner and installed external swellable casing packers on 04/10/12.

Lateral hole diameter: 8.5", production string diameter: 5.5", production string weight and grade 17 ppf I/L80 LTC. Depth of 8.5" hole from 4500' to 9585' MD. Float shoe set at 9522' MD and float collar set at 9507' MD. Production liner set from 4295' to 9522' MD.

Set 18 external swellable casing packers for isolation of production string at: (1) 9276' (2) 9042' (3) 8809' (4) 8575' (5) 8340 (6) 8106' (7) 7871' (8) 7638' (9) 7638' (10) 7169' (11) 6935' (12) 6703' (13) 6469' (14) 6235' (15) 6000' (16) 5768' (17) 5530' (18) 4484'.

Rig released 04/11/12.

RCVD APR 25 '12
OIL CONS. DIV.

DIST. 3

Spud Date: 03/03/12

Rig Release Date: 04/11/12

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Brenda R. Linster TITLE Regulatory Advisor
Type or print name: Brenda R. Linster E-mail address: brenda.linster@encana.com

DATE 04/23/12
PHONE: 720-876-3989

For State Use Only

APPROVED BY: BRL TITLE Deputy Oil & Gas Inspector, District #3 DATE 4/30/12
Conditions of Approval (if any):

A