Form 3160-5 (November 1994)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0135
Expires July 31, 1996

5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS				BIA # 11		
Do not use this form for proposals to drill or reenter an				6. If Indian, Allottee or Tribe Name		
abandoned well.	Use Form 3160-3 (APD)	for such proposals	i.			
SUBMIT IN TRIPLICATE – Other instructions on reverse side				7. If Unit or CA/Agreement, Name and/or No.		
1. Oil Well X Gas Well	Other			8. Well Name	and No.	
2. Name of Operator		E A	769 on 1	Jicarilla Apache B-11-E		
Elm Ridge Resources, Inc.			1.6	9 API Well N		
		3b. Phone No. (include	A 3 44	30-039-27720 10. Field and Pool, or Exploratory Area		
		505-632-3476	<u> </u>			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		/c-i			Otero Gallup & Basin Dakota	
Sec.19-T24N-R5W 1075 FNL X 1065 FWL			5 m 5 3 m	11. County or Parish, State Rio Arriba County, NM		
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATUR	E OF NOTICE, REPO	ORT, OR OTHER I	DATA		
TYPE OF SUBMISSION	TYPE OF ACTION					
Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	Production (S	tart/Resume)	Water Shut-Off Well Integrity	
X Subsequent Report	Casing Repair	New Construction	Recomplete		X Other Casing	
	Change Plans	Plug and Abandon	Temporarily A			
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposa	al 		
Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days Following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once Testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) Elm Ridge Resources, Inc. reached a TD of 6920' on 2-6-05. Ran 4 1/2" 10.5# J55 csg to 6914'. Pumped 727 sks of 50/50/POZ cement with 10 bbls of cement to surface. Tailed in with 950 sks 65/35/POZ cement with 70 bbls e cement to surface. Pressure tested to 1500 PSI.						
					070 FEB	
14. I hereby certify that the foregoing is	irue and correct	Lorent			22.7	
Name (Printel/Typed) Amy N	nackey	Title	Producti	on Assista	nt 32	
Signature Mus Au	h	Date		ary 8, 2005		
	THIS SPACE I	FOR FEDERAL OR ST	ATE USE	8.66	FORTH EAD BEAABA	
Approved by		Title		DAG	ENTED FOR BECORD	
Conditions of approval, if any, are attached certify that the applicant holds legal or equi which would entitle the applicant to conduct	table title to those rights in the sub t operations thereon.	ject lease			APR 1 1 2005	
Title 18 U.S.C. Section 1001, makes it a c	rime for any person knowingly an	d willfully to make to any	department or agency	of the United	MING LOW PARTY NATIVE	