

(SUBMIT IN TRIPLICATE)

U. S. Land Office

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLease or permit No. **Tocito**
I-149-1nd 5852

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		
Testing cement job, surface casing		X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 31

1943

Center NW $\frac{1}{4}$ SW $\frac{1}{4}$ (Unsurveyed)

Well No. 1 is located ft. from N line and ft. from E line of sec. 17

Center NW $\frac{1}{4}$ SW $\frac{1}{4}$ Sec 17 26N 18W

NMPM

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

Tocito

San Juan

New Mexico

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

1-23-43: Ran 321.28 feet of 13 3/8" 48# 8 thd. smls casing; set at 336' from rotary table and at 321' from ground, with 200 sacks of slo-set cement.

1-31-43 Tested cement plug with 850 lbs pressure for 30 minutes; no drop in pressure.

Rigged up blow-out preventer, tested with 600 lbs pressure for 30 minutes; pressure dropped to 550 lbs.

HAJ

2-1-43

USGS-IOI-File

This plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Shiprock, New Mexico

By

Title District Foreman