

(SUBMIT IN TRIPLICATE)

U. S. Land Office

ToolitoUNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

L. 1-149-1nd 3852

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	X
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 27, 1944

Well No. **1** is located _____ ft. from **N** line and _____ ft. from **E** line of sec. **17**
Con. NW 1/4 SW 1/4 17 **26N** **18E** **N.M.P.M. (Unsurveyed)**
(4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Toolito **San Juan** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.)

Killed well January 21, 1944, with water. Flugged back from 6680 to 6190 feet with 100 sac cement pumped through tubing with Halliburton Oil Well Cementing Company. Mixed 300 sac Baroid to fill hole. Pulled 213 joints of tubing, or 6675 feet. Run 30 foot plug in top of 7" casing with 6 sac cement. Pumped 24 sac cement between 7" casing and 13 3/8" and set marker. Work completed January 23, 1944

OCE

1-27-44

USGS(2)-JCT(2)-SOC(3)-STC(3)-File

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Continental Oil Company**Address **Shiprock, New Mexico**

By

Title

Artesia, New Mexico**District Foreman**