BASIN FRUITLAND COAL

Location:

990' FNL and 970' FWL NW/4 NW/4 Sec 23D, T31N R4W

Rio Arriba, New Mexico Elevation: 6844' GR

Top Depth
Ojo Alamo 3058'
Kirtland 3276'

3540'

Fruitland

Spud 9/6/99 Completed 7/6/00

12 jts 8-5/8", 24#, K-55, ST&C csg @ 527'. Cemented with 350 sx cmt

117 jts 2-3/8", 4:7#, J-55, 8rd EUE tbg with 1/2" mule shoe on bottom and seating nipple one jt up. Landed @ 3652'

Top of liner @ 3522'

87 jts 5-1/2", 15.5#, K-55, LT&C csg @ 3591'. Float @ 3546'. Cemented with 535 sx cmt.

90238

RCVD AUG 8'12 DIL CONS. DIV.

4 jts 4", 10.5#, J-55, 8rd, @ 3522'-3703'. Did not cement

DIST. 3

PBTD 3660' TD 3704'

3574

Pre-Drilled Liner

3702

Hole Size	Casing	Cement	Top of CMT
12-1/4"	8-5/8", 24#	350 sx	Surface
7-7/8"	5-1/2", 15.5#	535 sx	Surface
6-1/4"	4", 10.5#	Did not cmt	N/A