RECEIVED

Form 3160-5 (August 2007)

UNITED STATES

FORM APPROVED

DEPARTMENT OF THE INTERIOR 3 0 2012 BUREAU OF LAND MANAGEMENT OMB No 1004-0137 Expires: July 31, 2010 Farmington Field Off & Lease Serial No. SUNDRY NOTICES AND REPORTS ON WELLS

Bureau of Land Managemei. I-149-IND-8473 6 If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals. Navajo Allotted SUBMIT IN TRIPLICATE - Other instructions on page 2 7 If Unit of CA/Agreement, Name and/or No 1. Type of Well Huerfanito Unit X Gas Well 8 Well Name and No Oil Well Other **Huerfanito Unit 82P** 9 API Well No. 2 Name of Operator Burlington Resources Oil & Gas Company LP 30-045-35329 3a Address 3b Phone No (include area code) 10 Field and Pool or Exploratory Area PO Box 4289, Farmington, NM 87499 (505) 326-9700 Blanco MV/Basin Mancos/Basin DK 4 Location of Well (Footage, Sec., T.,R.,M., or Survey Description) 11 Country or Parish, State UNIT E (SWNW), 2600' FNL & 270' FWL, Sec. 25, T27N, R9W San Juan New Mexico 12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Acidize Deepen Production (Start/Resume) Water Shut-Off Reclamation Well Integrity Alter Casing Fracture Treat X Other Casing Report X Subsequent Report New Construction Casing Repair Recomplete Change Plans Plug and Abandon Temporarily Abandon Final Abandonment Notice Convert to Injection Plug Back Water Disposal 13 Describe Proposed or Completed Operation Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones Attach the bond under which the work will be performed or provide the Bond No on file with BLM/BIA Required subsequent reports must be filed within 30 days following completion of the involved operations If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once Testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection) RCVD AUG 17'12 PLEASE SEE ATTACHED. OIL CONS. DIV. DIST. 3 PT will be conducted by Completion Rig. Results & TOC will appear on next report. ACCEPTED FOR RECORD AUG 1 5 2012 an amended Sundry with the Pressure test results for FARMINGTON FIELD OFFICE I hereby certify that the foregoing is true and correct. Name (Printed Typed) DENISE JOURNEY Title REGULATORY TECHNICIAN 7/30/2012 ourne Date Signature ITHIS SPACE FOR FEDERAL OR STATE OFFICE USE Approved by Title Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify Office that the applicant holds legal or equitable title to those rights in the subject lease which would

Title 18 U S.C. Section 1001 and Title 43 U S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

entitle the applicant to conduct operations thereon

HUERFANITO UNIT 82P 30-045-35329 Burlington Resources Blanco MV/Basin Mancos/Basin DK

7/15/12 MIRU AWS 920. ND WH. NU BOPE. <u>PT 9 5/</u>8" casing to <u>600#/30</u> min. Test OK.✓

7/17/12 TIH w/ 8 3/4" bit, tag cmt @ 197' & DO. Drilled ahead w/ 8 3/4" bit to 3,901' – Inter TD reached 7/18/12. Circ. hole. TIH w/ 92 jts. (82 jts., 20#, ST&C & 5 jts., 23#, LT&C) 7", J-55 casing set @ 3,889'.

7/19/12 RU to cmt. Pre-flush w/ 10 bbls FW, 10 bbls GW, & 10 bbls FW. Pumped scavenger, 19 sx (57cf-10bbls=3.02 yld) Prem Lite cement w/ 3% CACL, .25 pps cello-flake, 5 pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Lead w/ 402 sx (856cf-152 bbls=2.13 yld) Prem Lite cement w/ 3% CACL, .25 pps cello-flake, 5 pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Tail w/ 92 sx (127cf-23bbls=1.38 yld) Type III cement w/ 1% CACL, .25 pps cello-flake, & 0.2% FL-52. Drop plug & displaced w/ 156 bbls FW. Bump plug w/ 2005#. Plug down @ 08:52 hrs on 7/19/12. Circ. 55 bbls cmt to surface. RD cmt. WOC. PT 7" casing to 1500#/30 min. @ 19:00 hrs on 7/19/12 TIH w/ 6 ½" bit, tag cmt @ 3,848' & DO. Drilled ahead w/ 6 ½" bit to 6,754' (TD), TD reached 7/22/12.

7/23/12 Circ. hole. TIH w/ 162 jts., 4 ½", 11.6#, L-80, LT&C casing, set @ 6,743′. RU to cmt. Pre-flush w/ 10 bbls CW & 2 bbls FW. Pumped scavenger 9 sx (27cf-5bbls=3.02 yld) Prem Lite cement w/ .25 pps cello-flake, 0.3% CD-32, 6.25 pps LCM-1, & 1% FL-52. Tail w/ 213 sx (422cf-75bbls=1.98 yld) Prem. Lite cement w/ .25 pps cello-flake, 0.3% CD-32, 6.25 pps LCM-1, & 1% FL-52. Drop plug & displaced w/ 105 bbls FW (1st 10 bbls w/ sugar water). Bump plug w/ 1934#. Plug down @ 16:17 hrs on 7/23/12. WOC. RD cmt. ND BOPE. NU WH. RD RR @ 06:00 hrs on 7/24/12. ✓ ✔