Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT

FORM APPROVED
ORM APPROVED OM B No. 1004-0137 Expires: March 31, 200

5. Lease Serial No.

SHINDRY	NOTICES AND RE	PORTS ON WE	IIS	SF 07906	U	
Do not use th	his form for proposals rell. Use Form 3160 - 3 (to drill or to re-	enter an	6. If Indian,	Allottee or Tribe	Name
SUBMIT IN TR	IPLICATE- Other inst	tructions on reve	rse side.	7. If Unit or	CA/Agreement, N	ame and/or No.
1. Type of Well				Northea	st Blanco Unit	
Oil Well Gas Well Other				8. Well Name and No. NEBU 403A		
2. Name of Operator Devon Energ	gy Production Company, L.P.		-	9. API Wel		
3a Address		3b. Phone No. (include area code) 505-632-0244		30-039-27750		
PO Box 6459, Navajo Dam, No. 4. Location of Well (Footage, Sec.,		_L			O. Field and Pool, or Exploratory Area Basin Fruitland Coal	
945' FSL & 1,625' FEL, SW				11. County o	r Parish, State	~ <u></u>
, 10 102 10 1,020 1,22, 0 11	52., 0 0, 0 , 0			Rio Arr	iba, NM	
12. CHECK A	PPROPRIATE BOX(ES) TO	O INDICATE NATUI	RE OF NOTICE, RE	PORT, OR	OTHER DATA	A.
TYPE OF SUBMISSION		TY	PE OF ACTION			
Notice of Intent Subsequent Report Final Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Production (Start Reclamation Recomplete Temporarily Aba	ŕ	Water Shut-C Well Integrit Other Casia	
Attach the Bond under which following completion of the in testing has been completed. F	ectionally or recomplete horizonta the work will be performed or pro- tvolved operations. If the operation inal Abandonment Notices shall be	vide the Bond No. on file in results in a multiple com	with BLM/BIA. Required pletion or recompletion in	subsequent re a new interval	ports shall be filed , a Form 3160-4 sl	l within 30 days nall be filed once
If the proposal is to deepen dir Attach the Bond under which following completion of the in testing has been completed. F determined that the site is read Drilled 12 1/4" hole to 30 CaC1 and 1/4# PSX Flose Drilled 8 3/4" hole to 2,87 Gel, 5# Gilsonite, 1/4# Flo	ectionally or recomplete horizonta the work will be performed or pro- ivolved operations. If the operation inal Abandonment Notices shall be by for final inspection.) 5' on 4/6/05, set 9 jts of 9 5/8". eal. Circulated 10 bbls of cem. 75' on 4/9/05, set 68 jts of 7", Jocele, 1/10% CFR 3, 4/10% H	vide the Bond No. on file in results in a multiple com- pe filed only after all require t, H-40, ST&C, 32.3# cannot to surface. Test can J-55 LT&C, 23# casing	with BLM/BIA. Required pletion or recompletion in ements, including reclamat asing at 295'. Cemente sing to 1500 psi. at 2,850'. Cemented le	subsequent re a new interval ion, have been d w/175 sx (c	ports shall be filed, a Form 3160-4 slacompleted, and the state of the	d within 30 days nall be filed once ne operator has ment w/2% D POZ w/3%
If the proposal is to deepen dir Attach the Bond under which following completion of the in testing has been completed. F determined that the site is read Drilled 12 1/4" hole to 30 CaC1 and 1/4# PSX Flose Drilled 8 3/4" hole to 2,87 Gel, 5# Gilsonite, 1/4# Fle to pit. Tested casing to 19 Drilled 6 1/4" hole to 3,27 from 3,110' to 3,274'. Uti	ectionally or recomplete horizonta the work will be performed or pro- ivolved operations. If the operation inal Abandonment Notices shall be by for final inspection.) 5' on 4/6/05, set 9 jts of 9 5/8". eal. Circulated 10 bbls of cem. 75' on 4/9/05, set 68 jts of 7", Jocele, 1/10% CFR 3, 4/10% H	vide the Bond No. on file in results in a multiple come filed only after all required, H-40, ST&C, 32.3# cannot to surface. Test can J-55 LT&C, 23# casing falad 344 and tail w/75 amed in two stages; 1st surges to remove near	with BLM/BIA. Required pletion or recompletion in ements, including reclamat asing at 295'. Cemente sing to 1500 psi. at 2,850'. Cemented less (16 bbls) STD, 4/10% at 250 psi. stage hole to 9 1/2" frewellbore material. On	subsequent rea new interval ion, have been d w/175 sx (ad w/550 sx 6 Halad 344 om 2,860' to 4/25/05, set	ports shall be filed, a Form 3160-4 slacompleted, and the completed, and the state of the completed, and the state of the	d within 30 days and be filed once the operator has ment w/2% DPOZ w/3% bbls of cement e hole to 9 1/2" 5, J-55 liner at
If the proposal is to deepen dir Attach the Bond under which following completion of the in testing has been completed. F determined that the site is read Drilled 12 1/4" hole to 30 CaC1 and 1/4# PSX Flose Drilled 8 3/4" hole to 2,87 Gel, 5# Gilsonite, 1/4# Fle to pit. Tested casing to 1! Drilled 6 1/4" hole to 3,27 from 3,110' to 3,274'. Uti 3,273' with JGS rotating at 3,247'.	ectionally or recomplete horizonta the work will be performed or provolved operations. If the operation inal Abandonment Notices shall be by for final inspection.) 5' on 4/6/05, set 9 jts of 9 5/8". eal. Circulated 10 bbls of cem 75' on 4/9/05, set 68 jts of 7", Jocele, 1/10% CFR 3, 4/10% H 500 psi. 74' TVD on 4/18/05. Underrestilized natural and air assisted liner hanger at 2,803'. Perfor	vide the Bond No. on file in results in a multiple come filed only after all required, H-40, ST&C, 32.3# cannot to surface. Test can J-55 LT&C, 23# casing falad 344 and tail w/75 amed in two stages; 1st surges to remove near	with BLM/BIA. Required pletion or recompletion in ements, including reclamat asing at 295'. Cemente sing to 1500 psi. at 2,850'. Cemented le sx (16 bbls) STD, 4/10's stage hole to 9 1/2" frewellbore material. On 9" holes, from 2,860' to	subsequent rea new interval ion, have been d w/175 sx (ad w/550 sx 6 Halad 344 om 2,860' to 4/25/05, set	ports shall be filed, a Form 3160-4 slater completed, and the state completed and state completed and state completed and state complete co	d within 30 days and be filed once the operator has ment w/2% DPOZ w/3% bbls of cement e hole to 9 1/2" 5, J-55 liner at
If the proposal is to deepen dir Attach the Bond under which following completion of the in testing has been completed. F determined that the site is read Drilled 12 1/4" hole to 30 CaC1 and 1/4# PSX Flose Drilled 8 3/4" hole to 2,87 Gel, 5# Gilsonite, 1/4# Flot to pit. Tested casing to 19 Drilled 6 1/4" hole to 3,27 from 3,110' to 3,274'. Uti 3,273' with JGS rotating at 3,247'. 14. I hereby certify that the for Name (Printed/Typed)	ectionally or recomplete horizonta the work will be performed or provolved operations. If the operation inal Abandonment Notices shall be by for final inspection.) 5' on 4/6/05, set 9 jts of 9 5/8". eal. Circulated 10 bbls of cem 75' on 4/9/05, set 68 jts of 7", Jocele, 1/10% CFR 3, 4/10% H 500 psi. 74' TVD on 4/18/05. Underrestlized natural and air assisted liner hanger at 2,803'. Performedictions of the company of the	vide the Bond No. on file in results in a multiple come filed only after all require the filed only after the filed o	with BLM/BIA. Required pletion or recompletion in ements, including reclamate asing at 295'. Cemented its 1500 psi. at 2,850'. Cemented its x (16 bbls) STD, 4/10°. stage hole to 9 1/2" frewellbore material. On 9" holes, from 2,860' to	subsequent rea new interval ion, have been d w/175 sx (can d w/550 sx 6 Halad 344 om 2,860' to 4/25/05, set 3,159'. Lan	ports shall be filed, a Form 3160-4 slater multiple completed, and the state of the	within 30 days nall be filed once ne operator has ment w/2% DPOZ w/3% bbls of cement e hole to 9 1/2" 5, J-55 liner at duction tubing
If the proposal is to deepen dir Attach the Bond under which following completion of the in testing has been completed. F determined that the site is read Drilled 12 1/4" hole to 30 CaC1 and 1/4# PSX Flose Drilled 8 3/4" hole to 2,87 Gel, 5# Gilsonite, 1/4# Fle to pit. Tested casing to 1! Drilled 6 1/4" hole to 3,27 from 3,110' to 3,274'. Uti 3,273' with JGS rotating at 3,247'.	ectionally or recomplete horizonta the work will be performed or provolved operations. If the operation inal Abandonment Notices shall be by for final inspection.) 5' on 4/6/05, set 9 jts of 9 5/8". eal. Circulated 10 bbls of cem 75' on 4/9/05, set 68 jts of 7", Jocele, 1/10% CFR 3, 4/10% H 500 psi. 74' TVD on 4/18/05. Underrestlized natural and air assisted liner hanger at 2,803'. Performedictions of the company of the	vide the Bond No. on file in results in a multiple come filed only after all required. H-40, ST&C, 32.3# cannot to surface. Test can J-55 LT&C, 23# casing falad 344 and tail w/75 amed in two stages; 1st surges to remove near rated liner with size 0.4	with BLM/BIA. Required pletion or recompletion in ements, including reclamat asing at 295'. Cemented is 1500 psi. at 2,850'. Cemented is sx (16 bbls) STD, 4/10°. stage hole to 9 1/2" frowellbore material. On 9" holes, from 2,860' to MAY 2005 Senior Operations, Tech.	subsequent rea new interval ion, have been d w/175 sx (can d w/550 sx 6 Halad 344 om 2,860' to 4/25/05, set 3,159'. Lan	ports shall be filed, a Form 3160-4 slater completed, and the state completed and state completed and state completed and state complete co	d within 30 days and be filed once the operator has ment w/2% DPOZ w/3% bbls of cement e hole to 9 1/2" 5, J-55 liner at
If the proposal is to deepen dir Attach the Bond under which following completion of the in testing has been completed. F determined that the site is read Drilled 12 1/4" hole to 30 CaC1 and 1/4# PSX Flose Drilled 8 3/4" hole to 2,87 Gel, 5# Gilsonite, 1/4# Flo to pit. Tested casing to 19 Drilled 6 1/4" hole to 3,27 from 3,110' to 3,274'. Uti 3,273' with JGS rotating at 3,247'. 14. I hereby certify that the for Name (Printed/Typed) Melisa Zimmer	ectionally or recomplete horizonta the work will be performed or provolved operations. If the operation inal Abandonment Notices shall be by for final inspection.) 5' on 4/6/05, set 9 jts of 9 5/8". eal. Circulated 10 bbls of cem 75' on 4/9/05, set 68 jts of 7", Jocele, 1/10% CFR 3, 4/10% H 500 psi. 74' TVD on 4/18/05. Underrea lilized natural and air assisted liner hanger at 2,803'. Performan	vide the Bond No. on file in results in a multiple come filed only after all required. H-40, ST&C, 32.3# cannot to surface. Test can J-55 LT&C, 23# casing falad 344 and tail w/75 amed in two stages; 1st surges to remove near rated liner with size 0.4	with BLM/BIA. Required pletion or recompletion in ements, including reclamat asing at 295'. Cemented is sing to 1500 psi. at 2,850'. Cemented is sx (16 bbls) STD, 4/109 stage hole to 9 1/2" frowellbore material. On 9" holes, from 2,860' to MAY 2005 Senior Operations Tech	subsequent rea new interval ion, have been d w/175 sx (d w/175 sx	ports shall be filed, a Form 3160-4 slater man and the completed, and the state man	d within 30 days hall be filed once he operator has ment w/2% D POZ w/3% bbls of cement e hole to 9 1/2" 5, J-55 liner at duction tubing
If the proposal is to deepen dir Attach the Bond under which following completion of the in testing has been completed. F determined that the site is read Drilled 12 1/4" hole to 30 CaC1 and 1/4# PSX Flose Drilled 8 3/4" hole to 2,87 Gel, 5# Gilsonite, 1/4# Fle to pit. Tested casing to 19 Drilled 6 1/4" hole to 3,27 from 3,110' to 3,274'. Uti 3,273' with JGS rotating at 3,247'. 14. I hereby certify that the for Name (Printed/Typed) Melisa Zimmer Signature	ectionally or recomplete horizonta the work will be performed or provolved operations. If the operation inal Abandonment Notices shall be by for final inspection.) 5' on 4/6/05, set 9 jts of 9 5/8". eal. Circulated 10 bbls of cem 75' on 4/9/05, set 68 jts of 7", Jocele, 1/10% CFR 3, 4/10% H 500 psi. 74' TVD on 4/18/05. Underrea lilized natural and air assisted liner hanger at 2,803'. Performan	vide the Bond No. on file in results in a multiple come filed only after all required. H-40, ST&C, 32.3# cannot to surface. Test can J-55 LT&C, 23# casing falad 344 and tail w/75 amed in two stages; 1st surges to remove near rated liner with size 0.4 Title STATE CALL OR	with BLM/BIA. Required pletion or recompletion in ements, including reclamate asing at 295'. Cemented its sing to 1500 psi. at 2,850'. Cemented its sx (16 bbls) STD, 4/10°. stage hole to 9 1/2" frowellbore material. On 9" holes, from 2,860' to MAY 2005 Senior Operations, Tecl	subsequent rea new interval ion, have been d w/175 sx (c) and w/550 sx (c) Halad 344 om 2,860' to 4/25/05, set 13,159'. Land Land Land Land Land Land Land Land	ports shall be filed, a Form 3160-4 slater man and the completed, and the street man and	within 30 days nall be filed once ne operator has ment w/2% POZ w/3% bbls of cement e hole to 9 1/2" 5, J-55 liner at duction tubing
If the proposal is to deepen dir Attach the Bond under which following completion of the in testing has been completed. F determined that the site is read Drilled 12 1/4" hole to 30 CaC1 and 1/4# PSX Flose Drilled 8 3/4" hole to 2,87 Gel, 5# Gilsonite, 1/4# Flo to pit. Tested casing to 19 Drilled 6 1/4" hole to 3,27 from 3,110' to 3,274'. Uti 3,273' with JGS rotating at 3,247'. 14. I hereby certify that the for Name (Printed/Typed) Melisa Zimmer	ectionally or recomplete horizonta the work will be performed or provolved operations. If the operation inal Abandonment Notices shall be by for final inspection.) 5' on 4/6/05, set 9 jts of 9 5/8". eal. Circulated 10 bbls of cem 75' on 4/9/05, set 68 jts of 7", Jocele, 1/10% CFR 3, 4/10% H 500 psi. 74' TVD on 4/18/05. Underreallized natural and air assisted liner hanger at 2,803'. Performan	vide the Bond No. on file in results in a multiple come filed only after all required. H-40, ST&C, 32.3# cannot to surface. Test can J-55 LT&C, 23# casing falad 344 and tail w/75 amed in two stages; 1st surges to remove near rated liner with size 0.4 Title STATE CALL OR	with BLM/BIA. Required pletion or recompletion in ements, including reclamat asing at 295'. Cemented its 1500 psi. at 2,850'. Cemented its x (16 bbls) STD, 4/10'. stage hole to 9 1/2" frowellbore material. On 9" holes, from 2,860' to MAY 2005 Senior Operations Tech	subsequent rea new interval ion, have been d w/175 sx (c) and w/550 sx (c) Halad 344 om 2,860' to 4/25/05, set 13,159'. Land Land Land Land Land Land Land Land	ports shall be filed, a Form 3160-4 slater man and the completed, and the state man	d within 30 days hall be filed once he operator has ment w/2% D POZ w/3% bbls of cement e hole to 9 1/2" 5, J-55 liner at duction tubing

(Instructions on page 2)