

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
 Sundry Notices and Reports on Wells

2005 JUL 5 PM 2 28

1. Type of Well

Oil Well

RECEIVED

070 FARMINGTON NM

2. Name of Operator

Vulcan Minerals & Energy, c/o NMOCD Aztec District Office

3. Address & Phone No. of Operator

1000 Rio Brazos Road, Aztec, NM 87410 505-334-6178

4. Location of Well, Footage, Sec., T, R, M

100' FSL and 1310' FEL, Section 30, T-31-N, R-16-W

5. **Lease Number**
BIA #14-20-603-734
6. **If Indian, All. or Tribe Name**
Navajo
7. **Unit Agreement Name**
Horseshoe Gallup
8. **Well Name & Number**
HSGU #299
9. **API Well No.**
30-045-25726
10. **Field and Pool**
Horseshoe Gallup
11. **County & State**
San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**Type of Submission**☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment**Type of Action**☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other -☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut off☐ Conversion to Injection**13. Describe Proposed or Completed Operations**


A-Plus Well Service Plugged and Abandoned the above well NMSA 1978, Section 13-1-127, Purchase Agreement: 415210700028; Purchase Document: 05-199-000441.

6/8/05 MOL and RU rig.

6/9/05 Check well pressures: 0# on BH, 0# on casing, 0# on tubing. ND wellhead. NU BOP. TIH with 5.5" casing scraper and A+ workstring to 1106'. TOH and LD scraper. TIH with 5.5" DHS CR and set at 1074'. Circulate casing clean with 26 bbls of water. Pressure test bradenhead to 500#, held OK. Pressure test 5.5" casing to 500#, held OK. Establish rate 1.5 bpm at 650#. Plug #1 with CR at 1074', spot 38 sxs Type III cement (50 cf) inside the 5.5" casing above the CR up to 700' to isolate the Gallup interval. PUH to 221'. Load casing with 6 bbls of water and circulate casing clean. Plug #2 with 27 sxs Type III cement (36 cf) inside the 5.5" casing from 221' to surface, circulate good cement out the casing valve. TOH and LD tubing. Shut in well and WOC. ND BOP. Dig out and cut off wellhead. Found cement down 15' in the 5.5" casing and at the surface in the annulus. Mix 15 sxs cement to fill casing and install P&A marker. RD and MOL.

H. Villanueva, NMOCD was on location.

SIGNATURE


 William F. Clark

Contractor

June 10, 2005

(This space for Federal or State Office use)


ACCEPTED FOR RECORD

APPROVED BY

Title

Date JUL 08 2005

CONDITION OF APPROVAL, if any:

FARMINGTON FIELD OFFICE
 BY 
 NMOCD