1220 S. St. Francis Dr., Santa Fe, NM 87505

Energy Minerals and Natural Resources

Form C-144 June 1, 2004

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 82505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Pit or Below-Grade Tank Registration of Closure
Is pit or below-grade tank covered by a "general plan"? Yes No [

Type of action: Registration of a pit	or below-grade tank (1). Closure of a pit of below-grade	
Operator: WEST LARGO CORPTelephor	ne: (918) 492,3239e-mail achiress: jpgarre	tt@aol.com
Address: 8801 S. Yale, Suite 240, Tulsa, OK 74137-3535	91 11 91 51	
Facility or well name: Crockett 25 #1Y API #: 30-	045-32195 U/L or Qtr/Qtr D (N	NWNW) Sec 25 T 29N R 10W
County: San Juan Latitud	e 36° 42.0685 N Longitude 107° 50.42	90 W NAD: 1927 🔀 1983 🗌
Surface Owner: Federal State Private Indian		
Pit Below-grade tank		
Type: Drilling 🔀 Production 🗌 Disposal 🗌	Volume:bbl Type of fluid:	
Workover ☐ Emergency ☐	Construction material:	
Lined 🗹 Unlined 🗀	Double-walled, with leak detection? Yes If not, explain why not.	
Liner type: Synthetic M Thickness 12_mil Clay Pit Volume 2100- bbl		
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)
high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)
ingli water elevation of ground water.)	100 feet or more	(0 points)
W. 10 - 1	Yes	(20 points)
Wellhead protection area: (Less than 200 feet from a private domestic	No	(0 points)
water source, or less than 1000 feet from all other water sources.)		
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet	(20 points)
	200 feet or more, but less than 1000 feet	(10 points)
	1000 feet or more	(0 points)
	Ranking Score (Total Points)	10
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if your are burying in place) onsite offsite. If offsite, name of facility		
(5) Attach soil sample results and a diagram of sample locations and excavations.		
Additional Comments:		
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit, or an (attached) alternative OCD-approved plan .		
Date: 8/1/2005		
Date: 8/1/2005 Printed Name/Title John P. Garrett, President Signature		
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.		
Approval: Printed Name/Title GAS INSPECTOR, DIST. Signature Demy Tour AUG - 4 2005 Date:		

CROCKETT 25 HIY 990' FNL & 1310' FWL, SECTION 25, T29N, R10W, NMPM SAN JUAN COUNTY, NEW MEXICO GROUND BLEVATION: 5521' DATE: NOVEMBER 7, 2003 PROPERTY LINE FENCE-LINE 6 -0-F2 (5) 25' WIDE X 50' LONG X 7' DEEP 2:1 Slopes Reserve Pit ğ Š 502°W LAYDOWN
15' Wellhead to front Mellhead to back C1 (4) (1) CI EXISTING POADWAY 100 100 CI ACCESS (NO NEW) 8 <u></u> OLD FENCE-LINE C2 3 B' SEPARATOR A-A 5530 5520 5510 B-B' 5530 5520' 5510' C-C 5530 5520' 5510' Note: Contractor should call One-Call for location of any marked or unmarked buried pipelines or cables on well pad and/or access road at least two (2) working days prior to construction

Daily Drilling Report West Largo Corp.

Crockett 25 #1-Y

980' FNL 1310' FWL W/2 Section 25 T29N R9W San Juan County, NM 5521' G.L.

Note:

Fluid in reserve pit was allowed to evaporate before closure.

2/2/05

MIRU Vaughn Oilfield Services, Inc. Remove fence around reserve pit. Cut off pit liner and rolled into pit. Used dozer to push berms and surrounding soil into pit. Leveled surface to existing ground level.