## This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

## NEW MEXICO OIL CONSERVATION DIVISION

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Page 1 Revised June 10, 2003

Well No. <u>1</u> Operator Willaims Exploration and Production Lease Name Indian I Location Of Well: Unit Letter D Twp 28N Rge 03W API # 30-0 300390724600 Sec 27 Name of Reservoir or Pool Type of Prod. Method of Prod. Prod. Medium (Oil or Gas) Flow or Art. Lift) (Tbg. 0r Csg.) Upper 7484317 Fictured CLIA O'L & GAS TUB. Completion Lower FLOW DILAGAS MESAVERDE Completion **Pre-Flow Shut-In Pressure Data** Upper Hour, Date, Shut-In Length of Time Shut-In SI Press. Psig Stabilized? (Yes or No) Completion 90/Am 7-8-05 12 HRS YES 405 Hour, Date, Shut-In Length of Time Shut-In Stabilized? (Yes or No) Lower SI Press. Psig YES. Completion 909Am 7-8-05 712 HRS 490 Flow Test No. 1 Commenced at (hour, date)\* 100/km 7-11-05 Zone producing (Upper or Lower): LOWER Time Lapsed Time Pressure Prod. Zone Remarks (Hour, Date) Since\* Upper Compl. Lower Compl. Temp. STATERO, LOWER ZONE FLOWING 72 HRS 490 100/Am 7-11-05 405 80. STOP Chock Of GRATION. LOWER ZONE 7 FOWING 90 24 Hes 404 115 Lowar Zone Howing 435 160 16 WHR ZONE THOWING 103/2 7-14-05 470 900 UDAR ZOND BUILDING 'roduction rate during test pil: 1/2 BOPD based on 2 Bbls. In 96 Hrs. Grav. GOR GOR ias: 106 Per Day MCFPD; Test thru (Orifice or Meter): Office 106× 4 = 424 TOTAL PUR TEST) Mid-Test Shut-In Pressure Data Hour, Date, Shut-In Length of Time Shut-In SI Press. Psig Stabilized? (Yes or No) Upper Completion Hour, Date, Shut-In Length of Time Shut-In SI Press. Psig Stabilized? (Yes or No) Lower Completion

(Continue on reverse side)

Flow Test No. 2

			TIOW TEST I	10. 4			
Commenced a	at (hour, date)**		one producing (Upper or Lower):				
Time Lapsed Time		Pressure		Prod. Zone	Remarks		
(Hour, Date)	Since**		Lower Compl.	Temp.			
				<del>                                     </del>			
				<del></del>			
							•
'roduction rate				•			
)il:	BOPD based onBbls. In			Hrs	Grav	GOR	
	MCFP	D; Test thru (Orif	ice or Meter):				
emarks:							
hereby certify	that the informati	ion herein contair	ned is true and com	nlete to the hest	of my knowledge		
nereby certify			ica is true and com			. 0	
pproved	AUG -	o Zuun	20	Operator V	Villians E	\$ P.	
	l Conservation D	ivision		1	$\Omega$		
				By -Dom	y ( ament	€ <b>ફ</b> ₽.	
	1:00						
y	Wan	LE INSPECTOR, DIST		Title	TECH.	<u></u>	
•	ocruit Of & GA	ls inspector, dist	. 200				
tle	·····		E-mail Address				
				Date	14-05		
				Date	, 00		

Northwest New Mexico Packer Leakage Test Instructions

A packer leakage test shall be commenced on each multiply mpleted well within seven days after actual completion of the well, and nually thereafter as prescribed by the order authorizing the multiple mpletion. Such tests shall also be commenced on all multiple mpletions within seven days following recompletion and/or chemical fracture treatment, and whenever remedial work has been done on a ll during which the packer or the tubing have been disturbed. Tests ill also be taken at any time that communication is suspected or when uested by the Division.

At least 72 hours prior to the commencement of any packer leakage, the operator shall notify the Division in writing of the exact time the is to be commenced. Offset operators shall also be so notified.

The packer leakage test shall commence when both zones of the dual apletion are shut-in for pressure stabilization. Both zones shall remain t-in until the well-head pressure in each has stabilized, provided vever, that they need not remain shut-in more than seven days.

For Flow Test No. 1, one zone of the dual completion shall be duced at the normal rate of production while the other zone remains t-in. Such test shall be continued for seven days in case of a gas well 24 hours in the case of an oil well. Note: if, on an initial packer age test, a gas well is being flowed to the atmosphere due to the lack pipeline connection the flow period shall be three hours.

Following completion of Flow Test No. 1, the well shall again be in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).