

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

2005 JUL 32 PM 2 01

1. Type of Well
GAS


RECEIVED
070 FARMINGTON NM

5. Lease Number
NMSF-077648
6. If Indian, All. or
Tribe Name

2. Name of Operator
BURLINGTON
RESOURCES OIL & GAS COMPANY

7. Unit Agreement Name

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700



Well Name & Number
Davis 11M
API Well No.
30-045-33129

4. Location of Well, Footage, Sec., T, R, M
1630' FSL, 660' FWL, Sec. 3, T31N, R12W, NMPM

10. Field and Pool
Blanco Mesaverde/Basin Dakota
11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment <input type="checkbox"/> Change of Plans
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion <input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back <input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair <input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing <input type="checkbox"/> Conversion to Injection
	<input checked="" type="checkbox"/> Change of Casing Depth & Cement

13. Describe Proposed or Completed Operations

It is intended to change the intermediate 7" casing depth from 2876' to 4556'.

Therefore the cement will be changed on the 7" casing to lead with 411 sxs Premium Lite cement w/3% calcium chloride, 0.25 pps celloflake, 5 pps LCM-1, 0.4% fluid loss, 0.4% sodium metasilicate (876 cu ft). Tail w/90 sxs Type III cement w/1% calcium chloride, 0.25 pps celloflake, 0.2% fluid loss (124 cu ft).

Alternative 7" two stage: Stage collar set 300' above the top of the Fruitland. first stage: Lead w/118 sxs Premium Lite cement w/3% calcium chloride, .25 pps celloflake, 5 pps LCM-1, 0.4% fluid loss (251 cu ft). Tail w/90 sxs Type III cement w/1% calcium chloride, 0.25 celloflake, 0.2% fluid loss (124 cu ft). Second stage: 293 sxs Premium Lite cement w/3% calcium chloride, .25 pps celloflake, 5 pps LCM-1, 0.4% fluid loss, 0.4% sodium metasilicate (625 cu ft - 50% excess to circulate to surface).

14. I hereby certify that the foregoing is true and correct.

Signed Joni Clark Title Regulatory Specialist Date 7/28/05

(This space for Federal or State Office use)
APPROVED BY Shirley Brunley Title Pet. Eng
CONDITION OF APPROVAL, if any:

Date 8/8/05

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC