Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR

LOKM ALLKOVED
OM B No. 1004-0137
Evnison March 21 200
Expires: March 31, 200

DELAKTMENT OF THE		Expires: March 31, 2007				
BUREAU OF LAND MANAGEMENT				erial No.		
SUNDRY NOTICES AND REP	6. If Indi	an, Allottee or Tribe Name				
Do not use this form for proposals to abandoned well. Use Form 3160 - 3 (A	1 07	an, Another of Thoe Walte				
SUBMIT IN TRIPLICATE- Other instru	7. If Unit	or CA/Agreement, Name and/or No.				
1. Type of Well	Nort	heast Blanco Unit				
Oil Well Gas Well Other	070	FARMINGTO	8. Well 1	lame and No.		
2. Name of Operator Devon Energy Production Company, L.P.				U 233		
3a. Address	3b. Phone No. (includ	No. (include area code)		Vell No. I5-32800		
PO Box 6459, Navajo Dam, NM 87419	505-632-0244		10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				Pinos Frt/Sd Pictured Cliffs		
1,400' FNL & 1' FWL, SW NW, Unit E, Sec. 23-T31N-R7W			11. Coun	ty or Parish, State		
				uan, NM		
12. CHECK APPROPRIATE BOX(ES) TO	INDICATE NATUR	RE OF NOTICE, RE	PORT, (OR OTHER DATA		
TYPE OF SUBMISSION	TY	PE OF ACTION				
Acidize	Deepen	Production (Star				
Notice of Intent Alter Casing	Fracture Treat	Reclamation	/ Kesume)	Well Integrity		
Subsequent Report Casing Repair	New Construction	Recomplete		Other Casing and Cement		
Change Plans Plug and Abandon Temporarily Abandon						
Final Abandonment Notice Convert to Injection Plug Back Water Disposal						
Attach the Bond under which the work will be performed or provided following completion of the involved operations. If the operation in testing has been completed. Final Abandonment Notices shall be find determined that the site is ready for final inspection.) Drilled 12 1/4" hole to 299' on 5/19/05, set 13 jts of 9 5/8" CaC1 and 1/4# PSX Floseal. Circulated 0 bbls of cement Drilled 6 1/4" hole to 3,535' on 7/25/05, set 83 jts 4 1/2", J Gel, 2/10% Veraset, 1/10% Diacel LWL and tail w/75 sx Flocele. Circulated 60 bbls foamed cement to surface. L	esults in a multiple compiled only after all require H-40, ST&C, 32.3# to surface, top of cen 555, LT&C, 11.6# ca (19 bbls) 50/50 POZ.	casing at 299'. Cemenent at surface. Test of sing at 3,530'. Cemenent at 3,530'. Cemenent at 3,530'. Cemenent at 3,530'.	a new inter tion, have b nted w/179 casing to 1	val, a Form 3160-4 shall be filed once een completed, and the operator has 5 sx (36 bbls) "B" cement w/2% 500 psi.		
		16 17 18 19 3m	NO DE	205 26 27 20 20 20 20 20 20 20 20 20 20 20 20 20		
14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)	1	1	Elc	. 97		
Melisa Zimmerman	Title S	enior Operations Tecl	niciae	1.016.8 1		
Signature M.S.3	Date	8-16-03	5			
THIS SPACE FOR F	TATE OFFICE (JSE	ACCEPTED FOR RECOR			
Approved by		itle		Date AUG 2 4 2005		
Conditions of approval, if any, are attached. Approval of this notice d	oes not warrant or					
certify that the applicant holds legal or equitable title to those rights in which would entitle the applicant to conduct operations thereon.	the subject lease	office		FARMINGIUM FIELD OFFICE		

BY COMO Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)