

submitted in lieu of Form 3160-5

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
Sundry Notices and Reports on Wells

2005 SEP 8 9 29

1. Type of Well

WIW

2. Name of Operator

Central Resources, Inc.

3. Address & Phone No. of Operator

1775 Sherman St., Denver, CO 80203-4313

4. Location of Well, Footage, Sec., T, R, M

1980' FSL and 706' FWL, Section 19, T-31-N, R-16-W

5. Lease Number  
BIA #14-20-600-3531  
6. Indian, All. or  
Tribe Name  
Navajo  
7. Unit Agreement Name  
Horseshoe Gallup  
8. Well Name & Number  
HSGU #101  
9. API Well No.  
30-045-10549  
10. Field and Pool  
Horseshoe Gallup  
11. County & State  
San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other - Final Abandonment


☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection



13. Describe Proposed or Completed Operations:

Plug and abandon the above well as follows:

- 7/28/05 MOL. RU pump truck on casing valve. RU 3000# pen recorder on tubing and casing. Pressure up on casing to 1090#, held OK for 30 minutes. Test witnessed by EPA rep. RD pump truck. Shut in well.
- 8/10/05 MOL and RU rig. Well pressures: 0# on BH, 0# on casing, 0# on tubing. ND wellhead. Release packer. NU BOP and companion flange. Hot oil tubing. TOH and LD 54 joints 2.375" tubing. TIH with 5.5" casing scraper and A+ workstring to 1232'. Hot oil casing and tubing clean with 30 bbls of water. TOH and LD scraper. TIH with 5.5" DHS CR and set at 1200'. Sting out of CR. Shut in well.
- 8/11/05 Load casing with 20 bbls of water. Attempt to pressure test casing to 500#, small wellhead leak, bled down 25# in 8 minutes. Plug #1 with CR at 1200', spot 37 sxs Type III cement (49 cf) inside the 5.5" casing above the CR up to 844' to isolate the Gallup interval. TOH and LD all tubing. Perforate 2 bi-wire holes at 151'. Establish circulation out the bradenhead at 1 bpm at 750#. Pump 16 bbls of water, returns oily. Wait 15 minutes. Pump 10 bbls of water, returns clean. Plug #2 with 60 sxs Type III cement (79 cf) pumped down the casing from 151' to surface to circulate good cement out the bradenhead. Shut in well and WOC. ND BOP. Dig out and cut off wellhead. Found cement at surface in both the casing and annulus. Mix 15 sxs cement to fill casing and install P&A marker. RD and MOL.
- V. Jamison, BLM, was on location. L. Lee, Navajo EPA, was on location. Jim Walker, EPA, was on location. Gary Shay, BLM Navajo Nation, was on location.

SIGNATURE

*William F. Clark*  
William F. Clark

Contractor

August 15, 2005

(This space for Federal or State Office use)

APPROVED BY

Title

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

SEP 08 2005

FIELD OFFICE  
NMOCD