District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico

Energy Minerals and Natural Resources

Department
Oil Conservation Division
1220 South St. Francis Dr.

Santa Fe, NM 87505

July 21, 2008

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

Form C-144

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Closed-Loop System, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method
Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method
X Modification to an existing permit
Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system,
below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the
environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: Burlington Resources Oil & Gas Company, LP OGRID#: 14538
Address: PO Box 4289, Farmington, NM 87499
Facility or well name: SAN JUAN 30-6 UNIT 57M
API Number: 30-039-31092 OCD Permit Number:
U/L or Qtr/Qtr: D(NW/NW) Section: 30 Township: 30N Range: 6W County: RIO ARRIBA
Center of Proposed Design: Latitude: 36.78909 °N Longitude: 107.51044 °W NAD: 1927 X 1983
Surface Owner: X Federal State Private Tribal Trust or Indian Allotment
RCVD JAN 9 * 13
notice of intent) Drying Pad Above Ground Steel Tanks Haul-off Bins Other Lined Unlined Liner type: Thickness mil LLDPE HDPE PVD Other Liner Seams: Welded Factory Other
Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: bbl Type of fluid: Tank Construction material: Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other Liner Type: Thickness mil HDPE PVC Other
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution of barbed wire evenly spaced between one and four feet Alternate. Please specify	tion or church)
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)		
Signs: Subsection C of 19.15.17.11 NMAC 12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers X Signed in compliance with 19.15.3.103 NMAC		
Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: X Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consideration pit for Pre-set) Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	leration of app	roval.
Siting Criteria (regarding permitting) 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.		
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes	No
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes	No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	No
(Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	□NA	
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applied to permanent pits) Visual inspection (contification) of the proposed site. A cried photo: Setallite image.	Yes NA	No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	No
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.		
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes	No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes	No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes	□No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	Yes	No
Within a 100-year floodplain - FEMA map	Yes	No

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment ChecklistSubsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design) APIor Permit
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9
Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design) API
Previously Approved Operating and Maintenance Plan API
13
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
Climatological Factors Assessment
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC
Quality Control/Quality Assurance Construction and Installation Plan
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
Nuisance or Hazardous Odors, including H2S, Prevention Plan
Emergency Response Plan
Oil Field Waste Stream Characterization
Monitoring and Inspection Plan Erosion Control Plan
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Closure Fran - based upon the appropriate requirements of subsection C of 19.13.17.3 Notice and 19.13.17.13 Notice
Proposed Closure: 19.15.17.13 NMAC
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.
Type: Drilling Workover Emergency X Cavitation P&A Permanent Pit Below-grade Tank Closed-loop System
Alternative
Proposed Closure Method: Waste Excavation and Removal
Waste Removal (Closed-loop systems only)
On-site Closure Method (only for temporary pits and closed-loop systems)
In-place BurialOn-site Trench
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)
15
Waste Excavation and Removal Closure Plan Checklist (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan.
Please indicate, by a check mark in the box, that the documents are attached.
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC
Dianocal Facility Name and Bermit Number (for liquide drilling fluide and drill auttings)
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19 15 17 13 NMAC
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC

Form C-144 Oil Conservation Division Page 3 of 5

16		
Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Ste Instructions: Please identify the facility or facilities for the disposal of liquids, drilling	eel Tanks or Haul-off Bins Only: (19.15.17.13.D NMAC) g fluids and drill cuttings. Use attachment if more than two	
facilities are required.		
Disposal Facility Name: Envirotech / JFJ Landfarm % IEI	Disposal Facility Permit #: NM-01-0011 / NM-01-0	010B
Disposal Facility Name: Basin Disposal Facility	Disposal Facility Permit #: NM-01-005	<u></u>
Will any of the proposed closed-loop system operations and associated active Yes (If yes, please provide the information No	ities occur on or in areas that will nbe used for future	service and
Required for impacted areas which will not be used for future service and operations Soil Backfill and Cover Design Specification - based upon the appropriate requirements of Subset Site Reclamation Plan - based upon the appropriate requirements of Su	oriate requirements of Subsection H of 19.15.17.13 Notion I of 19.15.17.13 NMAC	MAC
1		
Siting Criteria (Regarding on-site closure methods only: 19.15.17.10 NMA Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recertain siting criteria may require administrative approval from the appropriate district office of office for consideration of approval. Justifications and/or demonstrations of equivalency are received.	ecommendations of acceptable source material are provided below; r may be considered an exception which must be submitted to the Sa	Requests regarding changes to unta Fe Environmental Bureau
Ground water is less than 50 feet below the bottom of the buried waste.		Yes No
- NM Office of the State Engineer - iWATERS database search; USGS: Data ob	tained from nearby wells	∐N/A
Ground water is between 50 and 100 feet below the bottom of the buried wa - NM Office of the State Engineer - iWATERS database search; USGS; Data obt		Yes No
- NW Office of the state Engineer - TWATERS database search; 0505, Data out	amed from nearby wells	∐N/A
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obt	ained from nearby wells	∐Yes ∐No ∏N/A
· · · · · · · · · · · · · · · · · · ·	,	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other signif (measured from the ordinary high-water mark).	icant watercourse or takebed, sinkhole, or playa take	∐Yes ∐No
- Topographic map; Visual inspection (certification) of the proposed site		
Within 300 feet from a permanent residence, school, hospital, institution, or church in - Visual inspection (certification) of the proposed site; Aerial photo; satellite image	· ·	Yes No
		Yes No
Within 500 horizontal feet of a private, domestic fresh water well or spring that less th purposes, or within 1000 horizontal fee of any other fresh water well or spring, in exist. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification)	stence at the time of the initial application.	
Within incorporated municipal boundaries or within a defined municipal fresh water w pursuant to NMSA 1978. Section 3-27-3, as amended.	·	Yes No
 Written confirmation or verification from the municipality; Written approval ob Within 500 feet of a wetland 	tained from the municipality	∏yes ∏No
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual ins	pection (certification) of the proposed site	
Within the area overlying a subsurface mine Written confirantion or verification or map from the NM EMNRD-Mining and	Mineral Division	∐Yes ∐No
Within an unstable area.		Yes No
 Engineering measures incorporated into the design; NM Bureau of Geology & N Topographic map 	Aineral Resources; USGS; NM Geological Society;	
Within a 100-year floodplain FEMA map		Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each by a check mark in the box, that the documents are attached.	h of the following items must bee attached to the clos	sure plan. Please indicate,
Siting Criteria Compliance Demonstrations - based upon the appropr	iate requirements of 19 15 17 10 NMAC	
Proof of Surface Owner Notice - based upon the appropriate requirem	•	
Construction/Design Plan of Burial Trench (if applicable) based upor		
Construction/Design Plan of Temporary Pit (for in place burial of a d		
X Protocols and Procedures - based upon the appropriate requirements		
Confirmation Sampling Plan (if applicable) - based upon the appropr	iate requirements of Subsection F of 19.15.17.13 NM	AC
X Waste Material Sampling Plan - based upon the appropriate requirem	ents of Subsection F of 19.15.17.13 NMAC	
X Disposal Facility Name and Permit Number (for liquids, drilling fluid	~	s cannot be achieved)
Soil Cover Design - based upon the appropriate requirements of Subs		
Re-vegetation Plan - based upon the appropriate requirements of Sub Site Reclamation Plan - based upon the appropriate requirements of S		
in the recommendation is an a passed upon the appropriate requirements of the	ASSESSED OF LANDITHIS INTINO	

Form C-144 Oil Conservation Division Page 4 of 5

19
Operator Application Certification:
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.
Name (Print): Title: Regulatory Technician
Signature. La
e-mail address: jamie.l.goodwin@conocophillips.com
20 OCD Assessment Manufaction (including about a plan) OCD Assessment Manufaction (including about a plan) OCD Assessment Manufaction (including about a plan)
OCD Approval: Permit Application (including closure plan) OCD Conditions (see attachment)
OCD Representative Signature: Approval Date:
Ols Clark
Title: OCD Permit Number:
Clause Depart (required within 60 days of clause and stime): 0.1 to 1.1 to 2.1
Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure
report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an
approved closure plan has been obtained and the closure activities have been completed.
Closure Completion Date:
22 Closure Method:
Waste Excavation and Removal On-site Closure Method Alternative Closure Method Waste Removal (Closed-loop systems only)
If different from approved plan, please explain.
The state of the s
23
Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: Instructions: Please identify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities
were utilized.
Disposal Facility Name: Disposal Facility Permit Number:
Disposal Facility Name: Disposal Facility Permit Number:
Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and opeartions?
Yes (If yes, please demonstrate compliane to the items below)
Required for impacted areas which will not be used for future service and operations:
Site Reclamation (Photo Documentation)
Soil Backfilling and Cover Installation
Re-vegetation Application Rates and Seeding Technique
24
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in
the box, that the documents are attached.
Proof of Closure Notice (surface owner and division)
Proof of Deed Notice (required for on-site closure)
Plot Plan (for on-site closures and temporary pits)
Confirmation Sampling Analytical Results (if applicable)
Waste Material Sampling Analytical Results (if applicable)
Disposal Facility Name and Permit Number
Soil Backfilling and Cover Installation
Re-vegetation Application Rates and Seeding Technique
Site Reclamation (Photo Documentation)
On-site Closure Location: Latitude: Longitude: NAD 1927 1983
25
Operator Closure Certification:
I hereby certify that the information and attachments submitted with this closure report is ture, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.
то можно сотраво тап на прупошно можно годин ототь ит сопштото вресующ и то пруготой споле с рай.
Name (Print): Title:
Signature: Date:
Signature: Date:
e-mail address: Telephone:

Burlington Resources Oil & Gas Company, LP Cavitation Pit for Closed-Loop Locations

Design:

Burlington Resources Oil & Gas Company, LP will use a cavitation pit plan when the surface casing will be pre-set on closed-loop locations. The drill cuttings will be stockpiled on the surface.

Operations and Maintenance:

The cavitation pit will be operated and maintained as follows:

- 1. Only Fresh water and air will be used in the drilling of the surface casing.
- 2. The Cement used will be: Neat Cement with no additives.
- 3. All of the fluids will be removed within 48hrs after drilling.
- 4. A representative five point composite sample will be taken of the drill cuttings, after the setting of the surface casing is complete, using sampling tools and all samples will be tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the testing criteria is not met, all contents will be dug and hauled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

5. The NMOCD will be notified via email of the test results of the cavitation surface as follows:

Components	Tests Method	Limit (mg/Kg)	Results
Benzene	EPA SW-846 8021B or 8260B	0.2	
BTEX	EPA SW-846 8021B or 8260B	50	
TPH	EPA SW-846 418.1	2500	
GRO/DRO	EPA SW-846 8015M	500	
Chlorides	EPA 300.1	500	

Closure Plan:

- 1. The NMOCD will be notified of the sample results and the intent to start the closure process 3-7 days prior to the drill cuttings being transported, moved, or distributed on location.
- In the event the criteria are not met, all solids and liquids will be removed and disposed of at Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B).
- 3. Testing results will be submitted with the Closure Report of the well locations Closed-Loop Permit on Form C-144.

Burlington Resources is aware that approval of this plan does not relieve Burlington Resources of liability should operations result in pollution of surface water, ground water, or the environment. Nor does approval relieve ConocoPhillips of its responsibility to comply with any other applicable governmental authority's rules and regulations.