Form 3160-5 (August 2007)	UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT				APPROVED lo. 1004-0137 : July 31, 2010	
SUNDRY NOTICES AND REPORTS ON WELLS JAN				16 Allottee or Trib	pe Name	
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals minator				eld Office RC	VD JAN 22 '13	
SUBMIT IN TRIPLICATE – Other instructions on page 2. Bureau OT Lat				Unit of CA/Agreement		
1. Type of Well	Gas Well Other	CONFIDENTIA	(f) 8. W	ell Name and No.	DIST. 3	
2. Name of Operator Encana Oil & Gas (USA) Inc.				rook H26 2307 02H PI Well No. 043-21133	······································	
3a. Address		Field and Pool or Explo	ratory Area			
370 17th Street, Suite 1700 Denver, CO 80202	720-876-3941		rook Gallup			
4. Location of Well ( <i>Footage, Sec., T.,R.,M., or Survey Description</i> ) SHL: 2227 FNL and 357 FEL Sec 26, T23N, R7W BHL: 1880' FNL and 330' FWL Sec 26, T23N, R7W				11. Country or Parish, State Sandoval, NM		
12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA						
TYPE OF SUBMISSION TYPE OF ACT						
Notice of Intent		Deepen	=	n (Start/Resume)	Water Shut-Off	
	Alter Casing	Fracture Treat	Reclamatio		Well Integrity	
Subsequent Report	Change Plans	Plug and Abandon		ly Abandon		
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disp		approximate duration thereof. If	
Attach the Bond under which following completion of the	ectionally or recomplete horizonta h the work will be performed or p involved operations. If the operat Final Abandonment Notices must ady for final inspection.)	rovide the Bond No. on file with ion results in a multiple comple	BLM/BIA. Requir tion or recompletion	red subsequent reports r n in a new interval, a Fo	nust be filed within 30 days rm 3160-4 must be filed once	
Utlilized synthetic oil-based mi	ud system from intermediate ca	asing point 5672' to TD of late	eral.			
Kicked off lateral at 4539' MD production liner 1/10/13.	on 12/27/12. Landed lateral at	5878' on 1/5/13. Length of I	ateral 3762'. TD of	f <u>9640'MD/5255'TVD</u>	reached 1/9/13. Set	
Hole diameter: <u>6 1/8"</u> product Float shoe at 5672'MD and flo	ion string diameter, <u>4 1/2"</u> prod at collar at 5626'MD. Producti	luction string weight and grad on <u>liner se</u> t from <u>5469</u> 'MD <u>to</u>	le: <u>11.6# SB80</u> LT <u>9637'</u> MD.	FC. Depth of 6 1/8" ho	ble from 5792'MD to 9640'MD.	
	ng packers for isolation of prod 10) 7297' (11) 7029'  (12) 6767'			(2) 9175' (3) 8945' (4	) 8722' (5) 8456' (6) 8233'	
Rig Released 1/11/13.				ACCOPTED FOR RECORD		
				AL	N 1 7 2013	
				FARMINGT BY	ON FIELD OFFICE Lam Tambekoy	
14. I hereby certify that the foregoin Name (Printed/Typed)	ing is true and correct.					
Robynn Haden Title Engineering Te				st		
Signature #	up Hade	- Date //	14/13		·	
THIS SPACE FOR FEDERAL OR STATE OFFICE USE						
Approved by	· · · · · · · · · · · · · · · · · · ·					
	attached. Approval of this notice do itable title to those rights in the subj rations thereon.			Date		
	itle 43 U.S.C. Section 1212, make in or representations as to any matter w		and willfully to mak	ke to any department or a	gency of the United States any false,	
(Instructions on page 2) NWOCD re-						

· . .

-

.