District I 1625 N. French Dr., Hobbs, NM 88240

District II 1301 W. Grand Ave., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

> Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 July 21, 2008

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

,043 <sup>1</sup>
<b>\</b> -

District IV

	Pit, Closed-Loop System, Below-Grade Tank, or			
Prop	Proposed Alternative Method Permit or Closure Plan Application			
Type of action:	Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method  X Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method			
	Modification to an existing permit  Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system, below-grade tank, or proposed alternative method			

Instructions: Please submit one application (Form C-144) per individual pit, closed-in Please be advised that approval of this request does not relieve the operator of liability should operation environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable.	is result in pollution of surface water, ground water or the
Operator: Burlington Resources Oil & Gas Company, LP	OGRID#: <u>14538</u>
Address: PO Box 4289, Farmington, NM 87499	
Facility or well name: SAN JUAN 27-4 UNIT 32B	
API Number: 30-039-30930 OCD Permit Num	mber:
U/L or Qtr/Qtr: F(SE/NW) Section: 23 Township: 27N Range:	4W County: Rio Arriba
Center of Proposed Design: Latitude: 36.559308 °N Longitude:	<b>107.222301 °W</b> NAD: 1927 <b>X</b> 1983
Surface Owner: X Federal State Private Tribal Trust or Inc	dian Allotment
X   Pit: Subsection F or G of 19.15.17.11 NMAC     Temporary:	
Closed-loop System: Subsection H of 19.15.17.11 NMAC  Type of Operation: P&A Drilling a new well Workover or Drilling (Applies notice of intent)  Drying Pad Above Ground Steel Tanks Haul-off Bins Other  Lined Unlined Liner type: Thickness mil LLDPE  Liner Seams: Welded Factory Other	s to activities which require prior approval of a permit or  HDPE PVD Other
Below-grade tank: Subsection I of 19.15.17.11 NMAC  Volume: bbl Type of fluid:  Tank Construction material:  Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and a Visible sidewalls and liner Visible sidewalls only Other  Liner Type: Thickness mil HDPE PVC Other	automatic overflow shut-off
5  Alternative Method:  Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Envi	ironmental Bureau office for consideration of approval.

Form C-144

Oil Conservation Division

Page 1 of 5

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks)  Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution of the light, four strands of barbed wire evenly spaced between one and four feet  Alternate. Please specify  Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)  Screen Netting Other  Monthly inspections (If netting or screening is not physically feasible)	ution or church)
Signs: Subsection C of 19.15.17.11 NMAC  12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers  X Signed in compliance with 19.15.3.103 NMAC	·
Administrative Approvals and Exceptions:  Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.  Please check a box if one or more of the following is requested, if not leave blank:  X Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consideration pit for Pre-set)  Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	deration of approval.
Siting Criteria (regarding permitting) 19.15.17.10 NMAC  Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.  Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank.	Yes No
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).</li> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  (Applies to temporary, emergency, or cavitation pits and below-grade tanks)  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  (Applied to permanent pits)	Yes No NA Yes No NA
<ul> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> <li>Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.</li> </ul>	Yes No
<ul> <li>NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.</li> <li>Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended</li> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> <li>Within 500 feet of a wetland.</li> <li>US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site</li> <li>Within the area overlying a subsurface mine.</li> <li>Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division</li> <li>Within an unstable area.</li> </ul>	☐Yes         ☐No           ☐Yes         ☐No           ☐Yes         ☐No           ☐Yes         ☐No
<ul> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> <li>Within a 100-year floodplain</li> <li>FEMA map</li> </ul>	Yes No

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment ChecklistSubsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.				
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC				
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9				
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC				
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC				
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC				
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of				
19.15.17.9 NMAC and 19.15.17.13 NMAC				
Previously Approved Design (attach copy of design)  APIor Permit				
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.  Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9				
Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC				
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC				
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC				
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC				
Previously Approved Design (attach copy of design)  API				
Previously Approved Operating and Maintenance Plan API				
13				
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC				
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.				
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC				
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Climatological Factors Assessment				
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC				
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC				
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC				
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC				
Quality Control/Quality Assurance Construction and Installation Plan				
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC				
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Nuisance or Hazardous Odors, including H2S, Prevention Plan				
Emergency Response Plan				
Oil Field Waste Stream Characterization				
Monitoring and Inspection Plan				
Erosion Control Plan				
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC				
14				
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.				
Type: Drilling Workover Emergency X Cavitation P&A Permanent Pit Below-grade Tank Closed-loop System  Alternative				
Proposed Closure Method: Waste Excavation and Removal				
Waste Removal (Closed-loop systems only)				
On-site Closure Method (only for temporary pits and closed-loop systems)				
In-place Burial On-site Trench				
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)				
Waste Everystian and Remayal Clasure Plan Checklist (10.15.17.12.NMAC) Justine Factor of the fellowing to several and the seve				
Waste Excavation and Removal Closure Plan Checklist (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan.  Please indicate, by a check mark in the box, that the documents are attached.				
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC				
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC				
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)				
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC				
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC				
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC				

16				
Waste Removal Closure For Closed-loop Systems That Utilize Above Ground St Instructions: Please identify the facility or facilities for the disposal of liquids, drilling facilities are required.				
Disposal Facility Name: Envirotech / JFJ Landfarm % IEI	Disposal Facility Permit #: NM-01-0011 / NM-01-0	010B		
Disposal Facility Name: Basin Disposal Facility	Disposal Facility Permit #: NM-01-005			
Will any of the proposed closed-loop system operations and associated activ  Yes (If yes, please provide the information No	rities occur on or in areas that will nbe used for future	service and		
Required for impacted areas which will not be used for future service and operations:  Soil Backfill and Cover Design Specification - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC				
17 Siting Criteria (Regarding on-site closure methods only: 19.15.17.10 NMA Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. R certain siting criteria may require administrative approval from the appropriate district office o office for consideration of approval. Justifications and/or demonstrations of equivalency are re-	ecommendations of acceptable source material are provided below. r may be considered an exception which must be submitted to the Sa			
Ground water is less than 50 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS: Data ob	tained from nearby wells	Yes No		
Ground water is between 50 and 100 feet below the bottom of the buried wa	ste	Yes No		
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained the state of the State Engineer - iWATERS database search; USGS; Data obtained the state of the state of the State Engineer - iWATERS database search; USGS; Data obtained the state of		□N/A		
Ground water is more than 100 feet below the bottom of the buried waste.		☐Yes ☐No		
- NM Office of the State Engineer - iWATERS database search; USGS; Data obt	tained from nearby wells	□N/A		
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other signi (measured from the ordinary high-water mark).	ficant watercourse or lakebed, sinkhole, or playa lake	Yes No		
- Topographic map; Visual inspection (certification) of the proposed site				
Within 300 feet from a permanent residence, school, hospital, institution, or church in Visual inspection (certification) of the proposed site; Aerial photo; satellite image	**	Yes No		
		Yes No		
Within 500 horizontal feet of a private, domestic fresh water well or spring that less th purposes, or within 1000 horizontal fee of any other fresh water well or spring, in exi - NM Office of the State Engineer - iWATERS database; Visual inspection (certi-	stence at the time of the initial application.			
Within incorporated municipal boundaries or within a defined municipal fresh water w pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval ob	·	Yes No		
Within 500 feet of a wetland	named from the muticipanty	Пyes ПNo		
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual ins	spection (certification) of the proposed site			
Within the area overlying a subsurface mine.		Yes No		
- Written confirmation or verification or map from the NM EMNRD-Mining and	Mineral Division			
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & N Topographic map	Mineral Resources; USGS; NM Geological Society;	∐Yes ∐No		
Within a 100-year floodplain FEMA map		Yes No		
18				
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each by a check mark in the box, that the documents are attached.	h of the following items must bee attached to the clos	sure plan. Please indicate,		
Siting Criteria Compliance Demonstrations - based upon the appropr	iate requirements of 19.15.17.10 NMAC			
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC				
Construction/Design Plan of Burial Trench (if applicable) based upor	•• •			
Construction/Design Plan of Temporary Pit (for in place burial of a d		of 19.15.17.11 NMAC		
X Protocols and Procedures - based upon the appropriate requirements				
Confirmation Sampling Plan (if applicable) - based upon the appropr		AC		
X Waste Material Sampling Plan - based upon the appropriate requirem		a connect he calciumed		
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)  Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC				
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC				
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC				

Form C-144 Oil Conservation Division Page 4 of 5

19  Operator Application Certification:  I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.
Name (Print): Title:
Signature: Date:
e-mail address: Telephone:
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)  OCD Representative Signature: Approval Date: 2/0/2013  Title: OM Phance Office OCD Permit Number:
21
Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed.  Closure Completion Date:  6/25/2011
22
Closure Method:  Waste Excavation and Removal On-site Closure Method X Alternative Closure Method Waste Removal (Closed-loop systems only)  If different from approved plan, please explain.
23
Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only:  Instructions: Please identify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities were utilized.
Disposal Facility Name: Disposal Facility Permit Number:
Disposal Facility Name: Disposal Facility Permit Number:
Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations?
Yes (If yes, please demonstrate compliane to the items below)
Required for impacted areas which will not be used for future service and operations:  Site Reclamation (Photo Documentation)
Soil Backfilling and Cover Installation
Re-vegetation Application Rates and Seeding Technique
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice (surface owner and division)  Proof of Deed Notice (required for on-site closure)  Plot Plan (for on-site closures and temporary pits)  Confirmation Sampling Analytical Results (if applicable)  Waste Material Sampling Analytical Results (if applicable)  Disposal Facility Name and Permit Number  Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique  Site Reclamation (Photo Documentation)  On-site Closure Location: Latitude: Longitude: NAD 1927 1983
25
Operator Closure Certification:
I hereby certify that the information and attachments submitted with this closure report is ture, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.
Name (Print): Jamie Goodwin Title: Regulatory Technician
Signature: (2001) Date: 13/13
e-mail address: / jamie.l.goodwin@conocophillips.com Telephone: 505-326-9784

# Burlington Resources Oil & Gas Company, LP Cavitation Pit for Closed-Loop Locations

#### Design:

Burlington Resources Oil & Gas Company, LP will use a cavitation pit plan when the surface casing will be pre-set on closed-loop locations. The drill cuttings will be stockpiled on the surface.

#### **Operations and Maintenance:**

The cavitation pit will be operated and maintained as follows:

- 1. Only Fresh water and air will be used in the drilling of the surface casing.
- 2. The Cement used will be: Neat Cement with no additives.
- 3. All of the fluids will be removed within 48hrs after drilling.
- 4. A representative five point composite sample will be taken of the drill cuttings, after the setting of the surface casing is complete, using sampling tools and all samples will be tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the testing criteria is not met, all contents will be dug and hauled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

The NMOCD will be notified via email of the test results of the cavitation surface as follows:

Components	Tests Method	Limit (mg/Kg)	Results
Benzene	EPA SW-846 8021B or 8260B	0.2	ND
BTEX	EPA SW-846 8021B or 8260B	50	50.6
TPH	EPA SW-846 418.1	2500	55.0
GRO/DRO	EPA SW-846 8015M	500	ND
Chlorides	EPA 300.1	500	30

#### Closure Plan:

- 1. The NMOCD will be notified of the sample results and the intent to start the closure process 3-7 days prior to the drill cuttings being transported, moved, or distributed on location.
- 2. In the event the criteria are not met, all solids and liquids will be removed and disposed of at Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B).
- 3. Testing results will be submitted with the Closure Report of the well locations Closed-Loop Permit on Form C-144.

Burlington Resources is aware that approval of this plan does not relieve Burlington Resources of liability should operations result in pollution of surface water, ground water, or the environment. Nor does approval relieve ConocoPhillips of its responsibility to comply with any other applicable governmental authority's rules and regulations.



## **EPA METHOD 8015 Modified** Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	ConocoPhillips	Project #:	96052-1706
Sample ID:	Pre-Set Cuttings	Date Reported:	06-27-11
Laboratory Number:	58652	Sampled:	06-24-11
Chain of Custody No:	9542	Date Received:	06-24-11
Sample Matrix:	Soil	Date Extracted:	06-27-11
Preservative:	Cool	Date Analyzed:	06-27-11
Condition:	Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	, ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid

Waste, SW-846, USEPA, December 1996.

Comments:

San Juan 27-4 Unit 32B



## EPA Method 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

## **Quality Assurance Report**

Client:	QA/QC	Project #:	N/A
Sample ID:	06-27-11 QA/QC	Date Reported:	06-27-11
Laboratory Number:	58650	Date Sampled:	N/A
Sample Matrix:	Methylene Chloride	Date Received:	,N/A
Preservative:	N/A	Date Analyzed:	06-27-11
Condition:	N/A	Analysis Requested:	TPH

	FCal Date (	(I-CaliRF	C-CaliRF1+19	Difference	Accept Range
Gasoline Range C5 - C10	06/27/11	9.996E+02	1.000E+03	0.04%	0 - 15%
Diesel Range C10 - C28	06/27/11	9.996E+02	1.000E±03	0.04%	0 - 15%

Blank Conc. (mg/L - mg/Kg)	- Concentration	Detection Limit
Gasoline Range C5 - C10	2.6	0.2
Diesel Range C10 - C28	1.2	0.1

Duplicate/Conc. (mg/Kg)	√ Sample :	Duplicate*	% Difference	Range
Gasoline Range C5 - C10	120	123	2.3%	0 - 30%
Diesel Range C10 - C28	6.4	7.2	12.0%	0 - 30%

Spike Conc. (mg/Kg)	Sample	Spike Added	· Spike Result	% Recovery	Accept. Range 1/2
Gasoline Range C5 - C10	120	250	367	99.2%	75 - 125%
Diesel Range C10 - C28	6.4	250	259	101%	<b>75 - 125%</b>

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid

Waste,

SW-846, USEPA, December 1996.

Comments:

QA/QC for Samples 58645-58653

Analyst



#### **EPA METHOD 8021** AROMATIC VOLATILE ORGANICS

1.2

0.9

÷		,			
Client:	ConocoPhillips		Project#:		96052-1706
Sample ID:	Pre-Set Cuttings		Date Reported:	•	06-27-11
Laboratory Number:	58652		Date Sampled:		06-24-11
Chain of Custody:	9542		Date Received:		06-24-11
Sample Matrix:	Soil		Date Analyzed:		06-27-11
Preservative:	Cool		Date Extracted:		06-27-11
Condition:	Intact		Analysis Requested:		BTEX
			Dilution:		10
				Det.	-
		Concentration		Limit	
Parameter		(ug/Kg)		(ug/Kg)	
**. * .			-	_	
Benzene		ND	, <del>-</del>	0.9	
Toluene	•	15.3		1.0	•
Ethylbenzene	•	'nĎ		1.0	

24.2

11.1

50.6

ND - Parameter not detected at the stated detection limit.

p,m-Xylene

**Total BTEX** 

o-Xylene

Surrogate: F	Recov	eries: Parameter	Percent Re	covery
-		Fluorobenzene	86.0	%
		1,4-difluorobenzene	93.2	%
		Bromochlorobenzene	103	%
	: -	^ · · · · · · · · · · · · · · · · · · ·	•	
References:	سود	Method 5030B, Purge-and-Trap, Test Method 5030B, Purge-And-Trap, Purge-And-Trap, Test Method 5030B, Purge-And-Trap, Purg	ods for Evaluating Solid Waste, SW-846,	USEPA,
	•	Method 8021B; Aromatic Volatile Organics, USEPA, December 1996.	Test Methods for Evaluating Solid Waste	, SW-846,
Comments	<b>s:</b>	San Juan 27-4 Unit 32B		



#### **EPA METHOD 8021** AROMATIC VOLATILE ORGANICS

Client	N/A		Project#:		N/A
Sample ID:	0627BBLK QA/QC		Date Reported:		06-27-11
Laboratory Number:	58650		Date Sampled:		N/A
Sample Matrix:	Soil		Date Received:		N/A
Preservative:	N/A ,		Date Analyzed:		06-27-11
Condition:	N/A		Analysis:		BTEX
			Dilution:		10
Calibration and	L-Cal RF		% Diff	E. 443 (2.45) M.12 (2.25)	Detect
Detection Limits (ug/L)		Accept Ran	ge 0 - 15%	Conc.	Limit
Benzene	3.2067E+006	3.2132E+006	0.2%	ND	0.1
Toluene	3.3237E+006	3.3304E+006	0.2%	ND	0.1
Ethylbenzene	3.1004E+006	- 3.1066E+006	0.2%	ŅD	0.1
p,m-Xylene	8.1195E+008	8.1358E+006	0.2%	ND	0.1
o-Xylene	2.7146E+006	2.7200E+006	0.2%	ND	0.1

Duplicate Conc. (ug/Kg)	Sample Sample	Duplicate	% %Diff	, Accept Range	Detect. Limit
Benzene	204	215.	5.2%	0 - 30%	0.9
Toluene	9,000	8,970	0.3%	0 - 30%	1.0
Ethylbenzene	1,490	1,490	0.1%	0 - 30%	1.0
p,m-Xylene	13,000	12,900	0.8%	0 - 30%	1.2
o-Xylene	3,490	3,420	2.0%	0 - 30%	0.9

Spike Conc. (ug/Kg)	Sample Am	ount Spiked Sp	iked Sample: %	. Recovery	Accept Range	Ŋ
Benzene	204	500	745	106%	39 - 150	٠,
Toluene	9,000	500	9,530	100%	46 - 148	
Ethylbenzene	1,490	500	2,060	104%	32 - 160	
p,m-Xylene	13,000	1000	13,600	97.1%	46 - 148	
o-Xylene	3,490	500	4,050	102%	46 - 148	

ND - Parameter not detected at the stated detection limit.

Dilution: Spike and spiked sample concentration represent a dilution proportional to sample dilution.

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments:

A/QC for Samples 58645-58653



## **EPA METHOD 418.1** TOTAL PETROLEUM HYDROCARBONS

Project #: Client: ConocoPhillips 96052-1706 **Pre-Set Cuttings** Date Reported: Sample ID: 06/27/11 58652 Date Sampled: 06/24/11 Laboratory Number: 9542 Date Received: 06/24/11 Chain of Custody No: Sample Matrix: Soil Date Extracted: 06/27/11 Date Analyzed: 06/27/11 Preservative: Cool TPH-418.1 Condition: Intact Analysis Needed:

•	*	-	Det.
	a	Concentration	Limit
Parameter	ii.	(mg/kg)	(mg/kg)

**Total Petroleum Hydrocarbons** 

55.0

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

San Juan 27-4 Unit 32B

Review

5796 US Highway 64, Farmington, NM 87401

Ph (505) 632-0615 Fr (800) 362-1879 Fx (505) 632-1865 lab@envirotech-inc.com envirotech-inc.com



# **EPA METHOD 418.1** TOTAL PETROLEUM HYDROCARBONS **QUALITY ASSURANCE REPORT**

Client:		
Sample ID	);	

QA/QC

Project #:

N/A

QA/QC

Date Reported:

06/27/11

Laboratory Number:

06-27-TPH.QA/QC 58652

Date Sampled:

N/A

Sample Matrix:

Freon-113

Date Analyzed:

06/27/11 06/27/11

Preservative: Condition:

N/A N/A Date Extracted: Analysis Needed:

**TPH** 

Calibration
-------------

l-Cal Date C-Cal Date 06/14/11 06/27/11

1,760

1,670

5.1%

+/- 10%

Blank Conc. (mg/Kg)

Concentration

**Detection Limit** 

TPH

15.5

5.0

Duplicate Co	onc: (mg/Kg)	
TPH	. ريش	

55.0

Duplicate 57.8

5.1%

% Difference Accept. Range +/- 30%

Spike Conc. (mg/Kg) TPH.

Sample: Spike Added Spike Result, % Recovery. Accept Range 55.0

2,000

1,830

89.1%

80 - 120%

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

QA/QC for Samples 58635-58636, 58652



#### Chloride

Client: Sample ID: ConocoPhillips Pre-Set Cuttings Project #:

96052-1706

Lab ID#:

58652

Date Reported: Date Sampled:

06/27/11 06/24/11

Sample Matrix:

Soil Cool Date Received:

06/24/11

Preservative: Condition:

Intact

Date Analyzed: Chain of Custody: 06/27/11 9542

**Parameter** 

Concentration (mg/Kg)

Total Chloride

Reference:

U.S.E.P.A., 4500B, "Methods for Chemical Analysis of Water and Wastes", 1983. Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments:

San Juan 27-4 Unit 32B

Review

5796 US Highway 64, Farmington, NM 87401

Ph (505) 632-0615 Fr (800) 362-1879 Fx (505) 632-1865

lab@envirotech-inc.com envirotech-inc.com

The SAN JUAN 27-4 UNIT 32B was approved for a Closed Loop permit # 6546 on 1/05/2011. Due to COPC change in plans to Air Pre Set. Pre Set application permit # 8510 was submitted and approved on 6/24/2011. According to Cavitation Pit for a Closed Loop Locations Closure Plan #1 - (The NMOCD will be notified of the sample results and the intent to start the closure process 3-7 days prior to the drill cutting being transported, moved or distributed on location). COPC is notifying the NMOCD after the fact. Pre Set was conducted on 6/25/2011 and Environmental Samples are attached to this closure report. In the future COPC will comply with closure procedure #1 via: e-mail of move on date, environmental test samples and will be followed by the Pre Set closure report.

Jamie Goodwin ∕ConocoPhillips