District I State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Energy Minerals and Natural Reso District II Department 1301 W. Grand Ave., Artesia, NM 88210 Oil Conservation Division District III 1220 South St. Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.
Pit Closed-Loon System Below-	Grade Tank, or
Proposed Alternative Method Permit or	Closure Plan Application
Proposed Alternative Method Permit or Type of action: X Permit of a pit, closed-loop system, below- Closure of a pit, closed-loop system, below-	grade tank, or proposed alternative method
Closure of a pit, closed-loop system, below	-grade tank, or proposed alternative method
Modification to an existing permit	
Closure plan only submitted for an existing below-grade tank, or proposed alternative r	g permitted or non-permitted pit, closed-loop system, nethod
Instructions: Please submit one application (Form C-144) per individual pit, clo	sed-loop system, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should ope	
environment. Nor does approval relieve the operator of its responsibility to comply with any other ap	plicable governmental authority's rules, regulations or ordinances.
1 Operator: ConocoPhillips Company	OGRID#: 217817
Address: PO Box 4289, Farmington, NM 87499	
Facility or well name: SAN JUAN 28-7 UNIT 238N	
API Number: 30-039-31/50 OCD Permit	t Number:
U/L or Qtr/Qtr: D(NW/NW) Section: 29 Township: 28N Range	
Center of Proposed Design: Latitude: 36.637695 °N Longitude	
	r Indian Allotment
2 Pit: Subsection F or G of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation P&A Lined Unlined Liner type: Thickness mil LLDI String-Reinforced Liner Seams: Welded Factory Other Volume:	RCVD OCT 17'12 OIL CONS. DIV. PE PVC Other DIST. 3 bbl Dimensions L x W x D
3 X Closed-loop System: Subsection H of 19.15.17.11 NMAC Type of Operation: P&A X Drilling a new well Workover or Drilling (Approximation of the section of the sectin of the section of the section of the section	oplies to activities which require prior approval of a permit or
X Drying Pad X Above Ground Steel Tanks Haul-off Bins Other X Lined Unlined Liner type: Thickness 20 mil X LLDP Liner Seams: X Welded X Factory Other	E HDPE PVD Other
4 Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: bbl Type of fluid: Tank Construction material: Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift a Visible sidewalls and liner Visible sidewalls only Other Liner Type: Thickness mil HDPE PVC Other	
5 Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe	Environmental Bureau office for consideration of approval.

· ·

.

7

7 Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other		
8 Signs: Subsection C of 19.15.17.11 NMAC 12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers X Signed in compliance with 19.15.3.103 NMAC		
 9 Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. 	deration of app	roval.
10		
Siting Criteria (regarding permitting) 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.		
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes	No
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes	No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	No
(Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	□na	
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applied to permanent pits) Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes	No
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	No
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.		
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes	No
 Written communication of vermeation from the municipality, written approval obtained from the municipality Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 		No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes	No
 Written commutation of vertication of map from the NM EMNKD - Mining and Mineral Division Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological 		No
Society; Topographic map Within a 100-year floodplain - FEMA map		No

n en	
Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment ChecklistSubsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9	
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API or Permit	
12 Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17. Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC	1.9
X Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
X Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	
X Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15. NMAC and 19.15.17.13 NMAC	17.9
Previously Approved Design (attach copy of design) API	
Previously Approved Operating and Maintenance Plan API	
13	
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.	
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC	
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Climatological Factors Assessment	
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC	
 Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC 	
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC	
Quality Control/Quality Assurance Construction and Installation Plan	
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
Nuisance or Hazardous Odors, including H2S, Prevention Plan	
Emergency Response Plan	
Oil Field Waste Stream Characterization	
Monitoring and Inspection Plan	
 Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC 	
Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank X Closed-loop System	
Proposed Closure Method: • Waste Excavation and Removal	
X Waste Removal (Closed-loop systems only)	
On-site Closure Method (only for temporary pits and closed-loop systems)	
In-place Burial On-site Trench	
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)	
15 Waste Excavation and Removal Closure Plan Checklist (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closu	re nlan
Please indicate, by a check mark in the box, that the documents are attached.	prun
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC	
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC	
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)	
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC	
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC	

16 <u>Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only</u> :(19.15.17.13.D NMAC) Instructions: Please identify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings. Use attachment if more than two facilities are required.	,	
Disposal Facility Name: Envirotech / JFJ Landfarm % IEl Disposal Facility Permit #: NM-01-0011 / NM-01-0	0010B	
Disposal Facility Name: Basin Disposal Facility Disposal Facility Permit #: NM-01-005		
Will any of the proposed closed-loop system operations and associated activities occur on or in areas that will nbe used for future Yes (If yes, please provide the information No	e service and	
Required for impacted areas which will not be used for future service and operations: Soil Backfill and Cover Design Specification - based upon the appropriate requirements of Subsection H of 19.15.17.13 N Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC	IMAC	
17 <u>Siting Criteria (Regarding on-site closure methods only:</u> 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the S office for consideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.		
Ground water is less than 50 feet below the bottom of the buried waste.	Yes No	
- NM Office of the State Engineer - iWATERS database search; USGS: Data obtained from nearby wells	N/A	
Ground water is between 50 and 100 feet below the bottom of the buried waste	Yes No	
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells		
Ground water is more than 100 feet below the bottom of the buried waste.	Yes No	
- NM Office of the State Engineer - iWATERS database search; USGS: Data obtained from nearby wells	N/A	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	Yes No	
- Topographic map: Visual inspection (certification) of the proposed site		
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; satellite image	Yes No	
	Yes No	
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes. or within 1000 horizontal fee of any other fresh water well or spring, in existence at the time of the initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site		
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.	Yes No	
- Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 fost of a watland		
Within 500 feet of a wetland - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site		
Within the area overlying a subsurface mine.	Yes No	
- Written confiramtion or verification or map from the NM EMNRD-Mining and Mineral Division Within an unstable area.		
 Final an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources: USGS: NM Geological Society; Topographic map 	Yes No	
Within a 100-year floodplain.	Yes No	
- FEMA map		
¹⁸ <u>On-Site Closure Plan Checklist:</u> (19.15.17.13 NMAC) Instructions: Each of the following items must bee attached to the clo by a check mark in the box, that the documents are attached.	osure plan. Please indicate,	
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC		
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC		
Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC		
Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.11 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC		
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC		

Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC

Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)

Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC

Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC

Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC

•	
19 Operator Application	n Certification
	nformation submitted with this application is true, accurate and complete to the best of my knowledge and belief.
Name (Print):	Jamie Goodwin Title: Regulatory Technician
Signature: /	
e-mail address:	jamie.l.goodwin@conocophillips.comTelephone:505-326-9784
0	
20 OCD Approval:	Permit Application (including closure plan) A Closure Plan (only) OCD Conditions (see attachment)
OCD Representative	Signature: Jon All All Approval Date: 2/7/20(3
\sim	
Title: CoM	Pliance V Ottize () OCD Permit Number:
21	
Closure Report (requ	uired within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC
•	are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure
	submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an as been obtained and the closure activities have been completed.
approved closure plan n	
	Closure Completion Date:
22	
Closure Method:	
Waste Excavatio	on and Removal On-site Closure Method Alternative Closure Method Waste Removal (Closed-loop systems only)
	approved plan, please explain.
23	
	ling Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only:
	ntify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities
were utilized.	Diseased Fasility Demuit Number
Disposal Facility Nat	
Disposal Facility Nat	
	system operations and associated activities performed on or in areas that will not be used for future service and opeartions?
Yes (If yes, plea	se demonstrate complilane to the items below)
	d areas which will not be used for future service and operations:
	a (Photo Documentation)
-	and Cover Installation
Re-vegetation A	pplication Rates and Seeding Technique
24	
	ttachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in
the box, that the doc	
	re Notice (surface owner and division)
	Notice (required for on-site closure)
Plot Plan (for o	on-site closures and temporary pits)
Confirmation S	Sampling Analytical Results (if applicable)
Waste Materia	I Sampling Analytical Results (if applicable)
	ity Name and Permit Number
	g and Cover Installation
	Application Rates and Seeding Technique
	on (Photo Documentation)
On-site Closur	e Location: Latitude: Longitude: NAD 1927 1983
25	
Operator Closure Co	ertification:
	information and attachments submitted with this closure report is ture, accurate and complete to the best of my knowledge and belief. I also certify that
	hall applicable closure requirements and conditions specified in the approved closure plan.
Name (Print):	Title:
Signature	Date
Signature.	
e-mail address:	Telephone:
Signature:	Date: Telephone:

ConocoPhillips Company

Closed Loop Design:

The closed loop design will not incorporate a temporary pit or below grade tank. The plan will utilize an above grade tank suitable for holding the cuttings and fluids generated during drilling operations. The volume of the tank shall be of a sufficient volume to maintain an adequate free board for periodic removal and disposal of cuttings and fluids.

ConocoPhillips Company may incorporate the use of a 20 mil, string reinforced, LLDPE liner with factory welded seams to line the drying pad in order to minimize the volume of fluids to be disposed of. The drying pad will be designed to prevent contamination of fresh water, protect public health and the environment, and have sumps to facilitate the collection of liquids derived from drilling cuttings, as specified per subsection H of 19.15.17.11. The cuttings pad will be constructed above grade and containment will be through the use of earthen berms of sufficient height to contain the cuttings and prevent run-off of surface water or fluids. The drying pad area will replace the area of the drill site previously designated for the reserve pit. It will be signed in compliance with 19.15.3.103.NMAC. Frac tanks will be utilized on site for fresh water storage.

Closed Loop Operations and Maintenance:

The closed loop system will be operated and maintained for solids and liquid containment to prevent ground water contamination as follows:

- Any free liquids will be recovered and reused or disposed of at the Basin Disposal Facility (Permit # NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). Reuse may include the relocating of liquids to be used in other permitted drilling operations.
- Drill solids will be recovered from location and hauled to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) periodically as required to maintain a safe free board in the cuttings tank. No onsite trench burial of cuttings will occur.
- 3. In the event a drying pad is utilized, the cuttings will be picked up and transported to Basin Disposal Facility (Permit #NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). The liner will be disposed of at the San Juan County Landfill located on CR 3100. The drying pad will be closed within 6 months from the date that the drilling rig is released. Berms constructed from native materials will be bladed on site to the location's contour.
- 4. Any drilling materials or trash will be stored and disposed of appropriately.
- 5. The NMOCD will be notified within 48 hours of the discovery of compromised integrity of the closed loop containment. Any required repairs will commence immediately.

Closed Loop Closure Plan:

 Upon completion of the drilling operations, all solids and liquids will be removed and disposed of to Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit # NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). Equipment shall also be removed from location. In the event a drying pad is utilized, the solids contained on the pad shall remain on site to allow sufficient drying and will then be transported to Envirotech (Permit # NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) within 6 months from the date that the drilling rig is released. 2. After the drying pad is removed the surface below will be visually inspected for any contamination. If contamination is discovered a five point composite sample will be taken of the drying pad area using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e., Dig and haul.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

- 3. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 4. Notification will be sent to OCD when the reclaimed area is seeded.
- 5. COP shall seed the disturbed areas the first growing season after the operator closes the drying pad. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Туре	Variety or Cultivator	PLS/A
Western wheatgrass	Arriba	3.0
Indian ricegrass	Paloma or Rimrock	3.0
Slender wheatgrass	San Luis	2.0
Crested wheatgrass	Hy-crest	3.0
Bottlebrush Squirreltail	Unknown	2.0
Four-wing Saltbrush	Delar	.25

Species shall be planted in pounds of pure live seed per acre: Present Pure Live Seed (PLS) = Purity X Germination/100 Two lots of seed can be compared on the basis of PLS as follows: Source No. One (poor quality) Source No. two (better quality) Purity 50 percent 80 percent Purity Germination 40 percent Germination 63 percent Percent PLS 20 percent Percent PLS 50 percent 5 lb. bulk seed required to make 2 lb. bulk seed required to make 1 lb. PLS 1 lb. PLS