District II

State of New Mexico Energy Minerals and Natural Resources

Department

Oil Conservation Division 1220 South St. Francis Dr. For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

District III

1301 W. Grand Ave., Artesia, NM 88210

District IV	Rd., Aztec, NM 87410 is Dr., Santa Fe, NM 87505	Santa	a Fe, NM 87505	En	•	u office and	ions submit to the Santa Fe provide a copy to the fice.
		Pit, Closed-Loop osed Alternative M				lication	1
10U78	Type of action: X Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method Modification to an existing permit						
	Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system, below-grade tank, or proposed alternative method						ed-loop system,
Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.							
	rlington Resources Oi Box 4289, Farmingto			OG	RID#: <u>1453</u>	8	
	Facility or well name: GE-ELE-GU-LITH-E 2E						
API Number:		30-045- 35438	OCD Per	mit Number:			
U/L or Qtr/Qtr Center of Prop Surface Owne	oosed Design: Latitude	· -	26N Ran °N Longitu ate X Tribal Trus	.ide: 10'	7.727011	SAN JUZ	
2 Pit: Sub Temporary: Permanen	oscetion F or G of 19.15.17 Drilling Wor t Emergency C					1	RCVD OCT 4'12 OIL CONS. DIV. DIST. 3

miles					
String-Reinforced					
Liner Seams: Welded Factory Other Volume: bbl Dimensions L x W x D					
Liner Seams: Welded Factory Other Volume: bbl Dimensions L x W x D					
3					
X Closed-loop System: Subsection H of 19.15.17.11 NMAC					
Type of Operation: P&A X Drilling a new well Workover or Drilling (Applies to activities which require prior approval of a permit or					
notice of intent)					
X Drying Pad X Above Ground Steel Tanks Haul-off Bins Other					
Liner Seams: X Welded X Factory Other					
4					
Below-grade tank: Subsection Lof 19.15.17.11 NMAC					
Volume: bbl Type of fluid:					
Tank Construction material:					
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off					
Visible sidewalls and liner Visible sidewalls only Other					
Liner Type: Thickness mil HDPE PVC Other					
s					

Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify					
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)					
Signs: Subsection C of 19.15.17.11 NMAC 12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers X Signed in compliance with 19.15.3.103 NMAC					
Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for cons (Fencing/BGT Liner) Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	ideration of ap	proval.			
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.					
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes	No			
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes	No			
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	No			
(Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	□NA				
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applied to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes NA	No			
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Ycs	No			
 NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site. Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended Written confirmation or verification from the municipality; Written approval obtained from the municipality 	Yes	□No			
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within the area overlying a subsurface mine.	☐Yes ☐Yes	□No			
- Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes	□No			
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map					
Within a 100-year floodplain - FEMA map	Yes	□No .			

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC				
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC				
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9				
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC				
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC				
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC				
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of				
19.15.17.9 NMAC and 19.15.17.13 NMAC				
Previously Approved Design (attach copy of design) API or Permit				
12				
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.				
Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9				
Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC				
N Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC				
Note				
X Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9				
NMAC and 19.15.17.13 NMAC				
Previously Approved Design (attach copy of design) API				
Previously Approved Operating and Maintenance Plan API				
13				
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC				
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.				
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC				
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC				
Climatological Factors Assessment				
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC				
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC				
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC				
Quality Control/Quality Assurance Construction and Installation Plan				
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC				
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC				
Nuisance or Hazardous Odors, including H2S, Prevention Plan				
Emergency Response Plan				
Oil Field Waste Stream Characterization				
☐ Monitoring and Inspection Plan ☐ Erosion Control Plan				
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC				
Proposed Closure: 19.15.17.13 NMAC				
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.				
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank X Closed-loop System				
Alternative Proposed Clasura Method: Weste Frequestion and Pomousi				
Proposed Closure Method: Waste Excavation and Removal X Waste Removal (Closed-loop systems only)				
On-site Closure Method (only for temporary pits and closed-loop systems)				
In-place Burial On-site Trench				
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)				
15				
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan.				
Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC				
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC				
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)				
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC				
Re-vegetation Plan - based upon the appropriate requirements of Subsection 1 of 19.15.17.13 NMAC				
The regulation than caused apon the appropriate regulations of supervision of the supervi				

Form C-144 Oil Conservation Division Page 3 of 5

Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Instructions: Please identify the facility or facilities for the disposal of liquids, dr.						
facilities are required.	uing juids and arm cutings. Ose andenment y more man two	,				
Disposal Facility Name: Envirotech / JFJ Landfarm % IEI	Disposal Facility Permit #: NM-01-0011 / NM-01-0	010B				
Disposal Facility Name: Basin Disposal Facility	Disposal Facility Permit #: NM-01-005					
Will any of the proposed closed-loop system operations and associated act Yes (If yes, please provide the information No	•	service and				
Required for impacted areas which will not be used for future service and operation. Soil Backfill and Cover Design Specification - based upon the approximation.	ropriate requirements of Subsection H of 19.15.17.13 NM	AC				
Re-vegetation Plan - based upon the appropriate requirements of Su Site Reclamation Plan - based upon the appropriate requirements of						
Site rectamation Fran - based apon the appropriate requirements of	Subsection G of 17.13.17.13 Market					
17 Siting Criteria (Regarding on-site closure methods only: 19.15.17.10 N	IMAC					
Instructions: Each siting criteria requires a demonstration of compliance in the closure	plan. Recommendations of acceptable source material are provided					
certain siting criteria may require administrative approval from the appropriate district office for consideration of approval. Justifications and/or demonstrations of equivalence		o the Santa Fe Environmental Bureau				
Ground water is less than 50 feet below the bottom of the buried waste.		Yes No				
- NM Office of the State Engineer - iWATERS database search; USGS: Data	a obtained from nearby wells	N/A				
Ground water is between 50 and 100 feet below the bottom of the buried v	vaste	Yes No				
- NM Office of the State Engineer - iWATERS database search; USGS; Data		□N/A □				
Ground water is more than 100 feet below the bottom of the buried waste.		Yes No				
- NM Office of the State Engineer - iWATERS database search; USGS; Data	obtained from nearby wells	□N/A				
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other sig	gnificant watercourse or lakebed, sinkhole, or playa lake	☐Yes ☐No				
(measured from the ordinary high-water mark).						
- Topographic map; Visual inspection (certification) of the proposed site						
Within 300 feet from a permanent residence, school, hospital, institution, or churel - Visual inspection (certification) of the proposed site; Aerial photo; satellite in	**	Yes No				
, , , , , , , , , , , , , , , , , , , ,		Yes No				
• • • • • • • • • • • • • • • • • • • •	Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering					
 purposes, or within 1000 horizontal fee of any other fresh water well or spring, in NM Office of the State Engineer - iWATERS database; Visual inspection (or 	• •					
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted Yes No						
 pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval 	obtained from the municipality					
Within 500 feet of a wetland	• •	Yes No				
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual	inspection (certification) of the proposed site					
Within the area overlying a subsurface mine. - Written confirantion or verification or map from the NM EMNRD-Mining a	nd Mineral Division	Yes No				
Within an unstable area.		Yes No				
- Engineering measures incorporated into the design; NM Bureau of Geology &	& Mineral Resources; USGS; NM Geological Society;					
Topographic map Within a 100-year floodplain.		Yes No				
- FEMA map						
18						
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: E by a check mark in the box, that the documents are attached.	Cach of the following items must bee attached to the close	ure plan. Please indicate,				
Siting Criteria Compliance Demonstrations - based upon the appropriate Compliance Demonstration - based upon the compliance - based upon the	priate requirements of 19.15.17.10 NMAC					
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC						
Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC						
Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.11 NMAC						
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC						
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC						
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)						
Soil Cover Design - based upon the appropriate requirements of Subsection II of 19.15.17.13 NMAC						
Re-vegetation Plan - based upon the appropriate requirements of Subsection Lof 19.15.17.13 NMAC						
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC						

Form C-144 Oil Conservation Division Page 4 of 5

19 Operator Application Contifications				•
Operator Application Certification: I hereby certify that the information submitted with	this application is true accura	ate and complete to the be	est of my knowledge and belief	
	ios dwin	Title:	Regulatory, Technician	
Signature:	TOOdur	Date:	0/2/12	
· (conocophillips.com	Telephone:	505-326-9784	<u> </u>
c-man address.	лоносоргиира.сон	Telephone.	303-320-7764	
20 OCD Approval: Permit Application (incl	usling thousandon)	Closure Plan (only)	OCD Conditions (see attachi	
<i>/</i> (\	111	Mostife Flan (only)		10 C
OCD Representative Signature:	nall D. Kl	lls	Approval Date:	0/01/2012
Title: Compliance	Offices	OCD Perm	it Number:	
21	· · · ·			
Closure Report (required within 60 days of a Instructions: Operators are required to obtain an a report is required to be submitted to the division win approved closure plan has been obtained and the cl	pproved closure plan prior to thin 60 days of the completion	o implementing any closu n of the closure activities. mpleted.	re activities and submitting the closur Please do not complete this section	-
		Closure	Completion Date:	
22				
Closure Method:	lá sa gras Araba	Duke at all a	utalis I Diversity is 1701.	
	-	Alternative Closure	Method Waste Removal (Close	ed-toop systems only)
If different from approved plan, please expla	,m,		·	
23	E	70 A 1127 A 1 C	Lou lin A H L cont of	
Closure Report Regarding Waste Removal Closu Instructions: Please identify the facility or facilities were utilized.				
Disposal Facility Name:		Disposal Facility	Permit Number:	
Disposal Facility Name:		Disposal Facility	Permit Number:	
Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations?				
Yes (If yes, please demonstrate complilane t	o the items below)	No		
Required for impacted areas which will not be u	sed for future service and ope	erations:		
Site Reclamation (Photo Documentation) Soil Backfilling and Cover Installation				
Re-vegetation Application Rates and Seedin	g Technique			
	5 recumide			
24 Closure Report Attachment Checklist: In	structions: Each of the follo	owing items must be atta	ched to the closure report. Please inc	licate, by a check mark in
the box, that the documents are attached.		J	•	
Proof of Closure Notice (surface owner	′			
Proof of Deed Notice (required for on-si	*			
Plot Plan (for on-site closures and tempo				
Confirmation Sampling Analytical Resu	` '''			
Waste Material Sampling Analytical Re			,	
Disposal Facility Name and Permit Nun	.ber			
Soil Backfilling and Cover Installation Re-vegetation Application Rates and Se	edina Tachnique			
Site Reclamation (Photo Documentation				
On-site Closure Location: Latitude:	,	Longitude:	NAD 🗍 19	27 🗍 1983
Silver State				
25				
Operator Closure Certification: I hereby certify that the information and attachment		•		dge and belief. I also certify that
the closure complies with all applicable closure req Name (Print):	uirements and conditions spe	ecified in the approved cl Title:	osure plan.	
				
Signature:		Date:		
e-mail address:		Telephone:		

Burlington Resources Oil & Gas Company, LP

Closed Loop Design:

The closed loop design will not incorporate a temporary pit or below grade tank. The plan will utilize an above grade tank suitable for holding the cuttings and fluids generated during drilling operations. The volume of the tank shall be of a sufficient volume to maintain an adequate free board for periodic removal and disposal of cuttings and fluids.

Burlington Resources Oil & Gas Company, LP may incorporate the use of a 20 mil, string reinforced, LLDPE liner with factory welded seams to line the drying pad in order to minimize the volume of fluids to be disposed of. The drying pad will be designed to prevent contamination of fresh water, protect public health and the environment, and have sumps to facilitate the collection of liquids derived from drilling cuttings, as specified per subsection H of 19.15.17.11. The cuttings pad will be constructed above grade and containment will be through the use of earthen berms of sufficient height to contain the cuttings and prevent run-off of surface water or fluids. The drying pad area will replace the area of the drill site previously designated for the reserve pit. It will be signed in compliance with 19.15.3.103.NMAC. Frac tanks will be utilized on site for fresh water storage.

Closed Loop Operations and Maintenance:

The closed loop system will be operated and maintained for solids and liquid containment to prevent ground water contamination as follows:

- 1. Any free liquids will be recovered and reused or disposed of at the Basin Disposal Facility (Permit # NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). Reuse may include the relocating of liquids to be used in other permitted drilling operations.
- 2. Drill solids will be recovered from location and hauled to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) periodically as required to maintain a safe free board in the cuttings tank. No onsite trench burial of cuttings will occur.
- 3. In the event a drying pad is utilized, the cuttings will be picked up and transported to Basin Disposal Facility (Permit #NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). The liner will be disposed of at the San Juan County Landfill located on CR 3100. The drying pad will be closed within 6 months from the date that the drilling rig is released. Berms constructed from native materials will be bladed on site to the location's contour.
- 4. Any drilling materials or trash will be stored and disposed of appropriately.
- 5. The NMOCD will be notified within 48 hours of the discovery of compromised integrity of the closed loop containment. Any required repairs will commence immediately.

Closed Loop Closure Plan:

1. Upon completion of the drilling operations, all solids and liquids will be removed and disposed of to Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B). Equipment shall also be removed from location. In the event a drying pad is utilized, the solids contained on the pad shall remain on site to allow sufficient drying and will then be transported to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B) within 6 months from the date that the drilling rig is released.

2. After the drying pad is removed the surface below will be visually inspected for any contamination. If contamination is discovered a five point composite sample will be taken of the drying pad area using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e., Dig and haul.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

- 3. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 4. Notification will be sent to OCD when the reclaimed area is seeded.
- 5. BR shall seed the disturbed areas the first growing season after the operator closes the drying pad. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Туре	Variety or Cultivator	PLS/A
Western wheatgrass	Arriba	3.0
Indian ricegrass	Paloma or Rimrock	3.0
Slender wheatgrass	San Luis	2.0
Crested wheatgrass	Hy-crest	3.0
Bottlebrush Squirreltail	Unknown	2.0
Four-wing Saltbrush	Delar	.25

Species shall be planted in pounds of pure live seed per acre: Present Pure Live Seed (PLS) = Purity X Germination/100 Two lots of seed can be compared on the basis of PLS as follows:

Source No. One (poor quality)
Purity
50 percent
Percent PLS
20 percent
Source No. two (better quality)
Purity
80 percent
Germination
63 percent
Percent PLS
50 percent

5 lb. bulk seed required to make 2 lb. bulk seed required to make

1 lb. PLS 1 lb. PLS