District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Ave., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV

State of New Mexico Energy Minerals and Natural Resources

Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 July 21, 2008

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

1220 S. St. Fran	cis Dr., Santa Fe, NM 87505	appropriate NMOCD District Office.
		Pit, Closed-Loop System, Below-Grade Tank, or
$^{\prime}\sigma$	<u>Prop</u>	osed Alternative Method Permit or Closure Plan Application
1020	Type of action:	X Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method
		Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method
		Modification to an existing permit

Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request

below-grade tank, or proposed alternative method

Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system,

Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the

perator: ConocoPhillips Company	OGRID#: 217817
ddress: PO Box 4289, Farmington, NM 87499	
acility or well name: PUBCO FEDERAL GAS COM IN	
API Number: 30-045- 35448	OCD Permit Number:
/L or Qtr/Qtr: G(SW/NE) Section: 14 Township: 30N	Range: 11W County: SAN JUAN
enter of Proposed Design: Latitude: 36.812693 °N	Longitude: 107.957281 °W NAD: 1927 X 1983
urface Owner: X Federal State Private Tr	ribal Trust or Indian Allotment
Pit: Subsection F or G of 19:15.17.11 NMAC  Temporary: Drilling Workover	RCVD MAR 4
Permanent Emergency Cavitation P&A	OIL CONS. D DIST. 3
Lined Unlined Liner type: Thickness mil	LLDPE HDPE PVC Other
String-Reinforced .	
Liner Seams: Welded Factory Other	Volume:bbl Dimensions Lx Wx D
X.   Closed-loop System: Subsection H of 19.15.17.11 NMAC   Type of Operation: P&A   X Drilling a new well   Workover on otice of int     X Drying Pad   X Above Ground Steel Tanks   Haul-off Bins     X Lined   Unlined Liner type: Thickness   20 mil     Liner Seams:   X Welded   X Factory   Other	r Drilling (Applies to activities which require prior approval of a permit or ent)  Other  XLLDPE HDPE PVD Other
	er, 6-inch lift and automatic overflow shut-off
Liner Type: ThicknessmilHDPEPVC	Other
Alternative Method:	
	the Santa Fe Environmental Bureau office for consideration of approval.

Form C-144

Oil Conservation Division

Page 1 of 5

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks)  Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)  Four foot height, four strands of barbed wire evenly spaced between one and four feet  Alternate. Please specify  Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)  Screen Netting Other  Monthly inspections (If netting or screening is not physically feasible)			
Signs: Subsection C of 19.15.17.11 NMAC  12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers  X Signed in compliance with 19.15.3.103 NMAC			
Administrative Approvals and Exceptions:  Justifications and/or demonstrations of equivalency are required. Please refer to 19:15.17 NMAC for guidance.  Please check a box if one or more of the following is requested, if not leave blank:  Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consi  (Fencing/BGT Liner)  Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	deration of ap	proval.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.			
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS, Data obtained from nearby wells	Yes	□No	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	Yes	∏No	
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	□No	
(Applies to temporary, emergency, or cavitation pits and below-grade tanks)  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	L]NA		
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  (Applied to permanent pits)  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐Yes ☐NA	∏No.	
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	No	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes	□No	
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes	□No	
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes	□No	
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map			
Within a 100-year floodplain	Yes	No	

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.				
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC				
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9				
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC				
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC				
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC				
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of				
19:15:17.9 NMAC and 19:15:17:13 NMAC				
Previously Approved Design (attach copy of design) API or Permit				
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mork in the box, that the documents are attached.  Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9  Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC				
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC				
X Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC				
X Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9  NMAC and 19.15.17.13 NMAC				
Previously Approved Design (attach copy of design)  API				
Previously Approved Operating and Maintenance Plan API				
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.				
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC				
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC				
Climatological Factors Assessment				
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17,11 NMAC				
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC				
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC				
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15:17.11 NMAC				
Quality Control/Quality Assurance Construction and Installation Plan  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC				
Preeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC				
Nuisance or Hazardous Odors, including H2S, Prevention Plan				
Emergency Response Plan				
Oil Field Waste Stream Characterization				
Monitoring and Inspection Plan				
Erosion Control Plan				
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC				
14				
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.				
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank X Closed-loop System  Alternative				
Proposed Closure Method: Waste Excavation and Removal				
X Waste Removal (Closed-loop systems only)				
On-site Closure Method (only for temporary pits and closed-loop systems)				
In-place Burial On-site Trench				
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)				
15				
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.				
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC				
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC				
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)				
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC				
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC				
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC				

Form C-144 Oil Conservation Division Page 3 of 5

16 Waste Removal Closure For Closed-loop Systems That Utilize Above Groun	d Steel Tanks or Haul-off Bins On	ly: (19.15.17,13.D NMAC)		
Instructions: Please identify the facility or facilities for the disposal of liquids, di facilities are required.	illing fluids and drill cultings. Use	allächment if more than two		
Disposal Facility Name: Envirotech / JFJ Landfamt % IEI	Disposal Facility Permit #:	NM-01-0011 / NM-01-00	010B	
Disposal Facility Name: Basin Disposal Facility	Disposal Facility Permit #:	NM-01-005		
Will any of the proposed closed-loop system operations and associated ac  Yes (If yes, please provide the information No	tivities occur on or in areas that n	vill not be used for future:	service and	
Required for impacted areas which will not be used for future service and operations:  Soil Backfill and Cover Design Specification - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC				
it Siting Criteria (Regarding on-site closure methods only: 19.15,17.10 to Instructions: Each stiling criteria requires a demonstration of compilance in the closure certain siting criteria may require administrative approval from the appropriate district office for consideration of approval. Justifications and/or demonstrations of equivalent	e plan: Recommendations of acceptable coffice or may be considered an excep	tion which must be submitted to		
Ground water is less than 50 feet below the bottom of the buried waste.			Yes No	
- NM Office of the State Engineer - iWATERS database search; USGS: Dat	ta obtained from nearby wells	[	∐N/A	
Ground water is between 50 and 100 feet below the bottom of the buried	waste		Yes No	
- NM Office of the State Engineer - iWATERS database search; USGS; Dat	a obtained from nearby wells		N/A	
Ground water is more than 100 feet below the bottom of the buried waste			Yes No	
- NM Office of the State Engineer - iWATERS database search; USGS; Dat	a obtained from nearby wells		N/A	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other s (measured from the ordinary high-water mark).	ignificant watercourse or lakebed, si	nkhole, or playa laké	∏Yes ∏No	
- Topographic map; Visual inspection (certification) of the proposed site				
Within 300 feet from a permanent residence, school, hospital, institution, or chure - Visual inspection (certification) of the proposed site; Aerial photo; satellite	· ·	pplication.	∐Yes ∐No	
			Yes No.	
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal fee of any other fresh water well or spring, in existence at the time of the initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site				
Within incorporated municipal boundaries or within a defined municipal fresh was pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approve		ipal ordinance adopted	Yes No	
Within 500 feet of a wetland  - US Fish and Wildlife Wetland Identification map; Topographic map; Visus		posed site	Yes No	
Within the area overlying a subsurface mine.	n mekeenen (eerimennen) ää ine kie	posid sito	Yes No	
- Written confirmation or verification or map from the NM EMNRD-Mining	and Mineral Division			
Within an unstable area.	\$ 100 mg	~ · · · · · · ·	Yes No	
Engineering measures incorporated into the design; NM Bureau of Geology Topographic map	& Mineral Resources; USGS; NM	Cicological Society;		
Within a 100-year floodplain FEMA map		:	Yes No	
18 On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: by a check mark in the box, that the documents are attached.	Each of the following items mu	st bee attached to the clos	ure plan. Please indicate,	
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC				
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC				
Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC				
Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19,15,17.11 NMAC				
Protocols and Procedures - based upon the appropriate requirement	·	on Faf 19 15 17 13 NMAA	~	
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC  Wasta Material Sampling Plan, based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC				
Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)				
Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC				
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC				

19 Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate	and complete to the best of my knowledge and belief.
Name (Print): / Jamie Goodwin	Title: Regulatory, Technician
Signature: 10 mm ( 9000104	Date: 1/10// 1/23
e-mail address: / jamie L'goodwin@conocophilips.com	Telephone: 505-326-9784
20	
OCD Approval: Permit Application (including closure plan)	Notice Plan (only) OCD Conditions (see attachment)
OCD Representative Signature:	M Approval Date: 3/05/2013
Carolina	7-10-0
Title: Oraylance Ottore	OCD Permit Number:
21	
Closure Report (required within 60 days of closure completion): Subsection	of K of 19.15.17.13 NMAC
Instructions: Operators are required to obtain an approved closure plan prior to in	plementing any closure activities and submitting the closure report. The closure
report is required to be submitted to the division within 60 days of the completion of approved closure plan has been obtained and the closure activities have been comp	
, , , , , , , , , , , , , , , , , , ,	Closure Completion Date:
	Closure Completion Dates
Classes Matheda	
Closure Method:  Waste Excavation and Removal On-site Closure Method	Alternative Closure Method Waste Removal (Closed-loop systems only)
If different from approved plan, please explain.	Alternative Closure Method Waste Removal (Closed-loop systems only)
If different from approved plant, please explain.	
23	
Closure Report Regarding Waste Removal Closure For Closed-loop Systems Ti Instructions: Please identify the facility or facilities for where the liquids, drilling	hat Utilize Above Ground Steel Tanks or Haul-off Bins Only; fluids and drill cuttings were disposed. Use attachment if more than two facilities
were utilized.	James and arm estings resembles est indennetally more multipleatures
Disposal Facility Name:	Disposal Facility Permit Number:
Disposal Facility Name:	Disposal Facility Permit Number:
Were the closed-loop system operations and associated activities performed on o	·
Yes (If yes, please demonstrate compliane to the items below)	
Required for impacted areas which will not be used for future service and opera  Site Reclamation (Photo Documentation)	tions:
Soil Backfilling and Cover Installation	
Re-vegetation Application Rates and Seeding Technique	
24	
	ng items must be attached to the closure report. Please indicate, by a check mark in
the box, that the documents are attached.	
Proof of Closure Notice (surface owner and division)	·
Proof of Deed Notice (required for on-site closure)	
Plot Plan (for on-site closures and temporary pits)	
Confirmation Sampling Analytical Results (if applicable)	
Waste Material Sampling Analytical Results (if applicable)	
Disposal Facility Name and Permit Number	
Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique	
Site Reclamation (Photo Documentation)	
On-site Closure Location: Latitude:	Longitude: NAD 1927 1983
25	
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure re	port is live, accurate and complete to the best of my knowledge and belief. I also certify that
the closure complies with all applicable closure requirements and conditions specif	fied in the approved closure plan.
Name (Print):	Title:
Signatura	Dieto
Signature:	Date:
a mail address:	Talanhana

## ConocoPhillips Company

## Closed Loop Design:

The closed loop design will not incorporate a temporary pit or below grade tank. The plan will utilize an above grade tank suitable for holding the cuttings and fluids generated during drilling operations. The volume of the tank shall be of a sufficient volume to maintain an adequate free board for periodic removal and disposal of cuttings and fluids.

ConocoPhillips Company may incorporate the use of a 20 mil, string reinforced, LLDPE liner with factory welded seams to line the drying pad in order to minimize the volume of fluids to be disposed of. The drying pad will be designed to prevent contamination of fresh water, protect public health and the environment, and have sumps to facilitate the collection of liquids derived from drilling cuttings, as specified per subsection H of 19.15.17.11. The cuttings pad will be constructed above grade and containment will be through the use of earthen berms of sufficient height to contain the cuttings and prevent run-off of surface water or fluids. The drying pad area will replace the area of the drill site previously designated for the reserve pit. It will be signed in compliance with 19.15.3.103.NMAC. Frac tanks will be utilized on site for fresh water storage.

## **Closed Loop Operations and Maintenance:**

The closed foop system will be operated and maintained for solids and liquid containment to prevent ground water contamination as follows:

- Any free liquids will be recovered and reused or disposed of at the Basin Disposal Facility (Permit # NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). Reuse may include the relocating of liquids to be used in other permitted drilling operations.
- 2. Drill solids will be recovered from location and hauled to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) periodically as required to maintain a safe free board in the cuttings tank. No onsite trench burial of cuttings will occur.
- 3. In the event a drying pad is utilized, the cuttings will be picked up and transported to Basin Disposal Facility (Permit #NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). The liner will be disposed of at the San Juan County Landfill located on CR 3100. The drying pad will be closed within 6 months from the date that the drilling rig is released. Berms constructed from native materials will be bladed on site to the location's contour.
- 4. Any drilling materials or trash will be stored and disposed of appropriately.
- 5. The NMOCD will be notified within 48 hours of the discovery of compromised integrity of the closed loop containment. Any required repairs will commence immediately.

## **Closed Loop Closure Plan:**

1. Upon completion of the drilling operations, all solids and liquids will be removed and disposed of to Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B). Equipment shall also be removed from location. In the event a drying pad is utilized, the solids contained on the pad shall remain on site to allow sufficient drying and will then be transported to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B) within 6 months from the date that the drilling rig is released.

2. After the drying pad is removed the surface below will be visually inspected for any contamination. If contamination is discovered a five point composite sample will be taken of the drying pad area using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e., Dig and haul.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

- 3. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 4. Notification will be sent to OCD when the reclaimed area is seeded.
- 5. COP shall seed the disturbed areas the first growing season after the operator closes the drying pad. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Туре	Variety or Cultivator	PLS/A
Western wheatgrass	Arriba	3.0
Indian ricegrass	Paloma or Rimrock	3.0
Slender wheatgrass	San Luis	2.0
Crested wheatgrass	Hy-crest	3.0
Bottlebrush Squirreltail	Unknown	2.0
Four-wing Saltbrush	Delar	.25

Species shall be planted in pounds of pure live seed per acre: Present Pure Live Seed (PLS) = Purity X Germination/100 Two lots of seed can be compared on the basis of PLS as follows:

Source No. One (poor quality)

Purity

Source No. two (better quality)

Source No. two (better quality)

Purity

Source No. two (better quality)

Source No. two (better quality)

Purity

Source No. two (better quality)

Source No. two (better quality)

Purity

Source No. two (better quality)

Source No. two (better quality)

Purity

Source No. two (better quality)

Purity

Source No. two (better quality)

Source No. two (better quality)

Purity

Source No. two (better quality)

Source No. two (better quality)

Purity

Source No. two (better quality)

Source No. two (better quality)

Purity

Source No. two (better quality)

Purity

Source No. two (better quality)

Source No. two (better quality)

Purity

Source No. two (better quality)

Source No. two (better quality)

5 lb. bulk seed required to make 2 lb. bulk seed required to make

1 lb. PLS 1 lb. PLS