RECEIVED

Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR

MAR 04 201

FORM APPROVED OM B No. 1004-0137 Expires: March 31, 2007

· F	BUREAU OF LAND MAI	NAGEMENT	COMO: O	4	2 1 1 2 1		
			(Webirston	5. Lease S Field Officino-		. •	
SUNDRY NOTICES AND REPORTS ON WELLES ION Field C Do not use this form for proposals to drill or Proferance Mana					3/6/VIf-Indian, Allottee or Tribe Name		
abandoned we	ell. Use Form 3160 - 3	(APD) for su	ch proposals.	I	ijo Allotted		
SUBMIT IN TRIPLICATE- Other instructions on reverse side.					it or CA/Agreeme	ent, Name and/or No.	
1. Type of Well					NA NA		
					8. Well Name and No. John #1		
2. Name of Operator Coleman Oil & Gas, Inc.					9. API Well No.		
3a Address .3b. Phone No. (include area code) P.O. Drawer 3337, Farmington NM 87499 505-327-0356				<u> </u>	30-045-30692 10. Field and Pool, or Exploratory Area		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					WAW Fruitland Sand - Pictured Cliffs 11. County or Parish, State San Juan, New Mexico		
1980' FNL, 660' FEL H, Section 25, T26N, R12W Latitude 36.461111°, Longitude 108.056389°							
12. CHECK AI	PPROPRIATE BOX(ES) TO	O INDICATE 1	NATURE OF NO	ПСЕ, REPORT,	OR OTHER D	DATA	
TYPE OF SUBMISSION			TYPE OF AC	ΠΟΝ			
✓ Notice of Intent	Acidize Alter Casing	Deepen Fracture Tre	F 1	action (Start/Resume)	art/Resume) Water Shut-Off Well Integrity		
Subsequent Report	Casing Repair	New Constr		mplete	Other		
Final Abandonment Notice	Final Abandonment Notice Change Plans Plug and Abandon Temporarily Abandon Convert to Injection Plug Back Water Disposal						
determined that the site is ready PRESSURE TESTED PR LOAD PRODUCTION C COMMUNICATION INT AFTER REVIEWING CI	ODUCTION AND SURFAC ASING AND SURFACE CA FOODUCTION CASING EMENT BOND LOG DATE	TE CASING AND SING ANNULU S. SHUT DOWN D OCTOBER 15	NULUS. PRESSUI S. PRESSURE IN AND PRESSURE 5, 2001, IT WOULT	RE TEST-FAILED. ICREASED TO 100 WENT ON VACU	IT TOOK 120 PSI AND FEL JUM. S RECOMMEN	GALLONS TO LL OFF WITH NO	
PREFORM BRADEN HE PROCEDURE.	EAD SQUEEZE PRIOR TO	FILLING 4 1/2"	CASING WITH O	CEMENT. SEE TH	IE ATTACHEI	REVISED	
	· · · · · · · · · · · · · · · · · · ·		•			CVD MAR 6 13 IL CONS. DIV.	
						DTST. 3	
SPUD WELL SEPTEMB RELEASED ROTARY TO	ER 21, 2001 OOLS SEPTEMBER 25, 200	01	·				
14. I hereby certify that the fore Name (Printed/Typed)	going is true and correct	. 1		· 	,		
MICHAEL T. H	ANSON	*,	Title OPERATIO	NS ENGINEER	. *		
Signature Muhay	1. Hans	•	Date 3/	1/2013	,		
	THIS SPACE FOR	FEDERAL	OR STATE C	FFICE USE			
Approved by Original Signed: Stephen Mason Title					Date MAR () 5 2013		
Conditions of approval, if any, are certify that the applicant holds lega which would entitle the applicant to	attached. Approval of this notice of the control of this notice of the control of		t or		·		
Title 18 U.S.C. Section 1001 and Titl States any false, fictitious or fraudu	e 43 U.S.C. Section 1212, make i	t a crime for any p	person knowingly an within its jurisdictio	d willfully to make to	any department	or agency of the United	

(Instructions on page 2)

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this

form and the number of copies to be submitted, particularly with regard to local area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13 - Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or

present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well and date well site conditioned for final inspection looking to approval of the abandonment.

NOTICE

The Privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c) and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

This information is being collected to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT

Public reporting burden for this form is estimated to average 25 minutes per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer, (WO-630), Mail Stop 401 LS, 1849 C St., N.W., Washington D.C. 20240

(Form 3160-5, page 2)



Coleman Oil & Gas, Inc.

Plug and Abandon WAW Fruitland Sand – Pictured Cliffs Formation

Thursday, February 28, 2013

Well:

John #1

Field:

WAW Fruitland Sand-PC

Location:

1980' FNL & 660' FEL (SENE)

Elevation:

6130 RKB

Sec 25, T26N, R12W, NMPM

6125' GL

San Juan County, New Mexico

Lease:

NO-G-0006-1391

By:

Michael T. Hanson

Revised Procedure:

(Note: This procedure will be adjusted on site based upon actual

conditions)

Plug and Abandon

- 1. MIRU and POOH with rods & tubing, tag up with tubing prior to pulling. Lay down rods and tubing. Make sure perforations are not covered with sand.
- 2. Establish rate down Production and Surface Casing Annulus. Fill Production and Surface Casing Annulus with Cement.
- 3. Load and Pressure Test VIA Braden Head Valve Production and Surface Casing Annulus to 650 psig. Record volume and pressure drop if any over a 30 minute period. If Production and Surface Casing Annulus holds pressure proceed to next step.
- 4. Rig up cementers and bullhead cement into WAW Fruitland Sand (PC) perforations. Fill casing with cement. Pressure up and displace cement into PC formation.
- 5. Tag cement to make sure cement is above 80 Feet GL. If required top off with cement.
- 6. Cut off wellhead below Braden Head and top off with cement per regulations.
- 7. Install four inch dry hole marker as per regulations.